MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COUNTER, BINARY, DIGITAL, KEY CODE NZC

This amendment forms a part of MIL-M-28787/319A(EC), dated 16 December 1982, and is approved for use within the Space and Naval Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions G1-G5, G10-G13, G18-G21, Min columns: Delete "-10" (five places) and substitute "0" (five places).

PAGE 5

TABLE I, Test conditions G6, G14, G15, G22, Min columns: Delete "-10" (five places) and substitute "0" (five places).

TABLE I, Test conditions G7, G8, G9, G16, G17, G23, Min columns: Delete "-0.1" (fifteen places) and substitute "0" (fifteen places).

PAGE 8

4.4.2, delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through X shall be performed in any order with the following exceptions. Test conditions A, B, C, D and E are stress tests and will be performed only at 25°C ±5°C. If test conditions A, B, C, D, or E are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E where applicable, followed by the remaining tests in the sequence."

4.5.1, fifth line: Delete "B, E," and substitute "F".

4.5.1, sixth line: Delete "P" and substitute "N".

4.5.3, delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests F through L and N through X shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements of table I. Following the return of the module to 25°C, electrical tests F through L, and N through X shall be performed in the order specified in 4.4.2 using the 25°C ±5°C ambient end-of-life requirements of table I."

PAGE 24

TABLE IX: Delete and substitute new table IX as printed on page 2 of this amendment.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:43Z
Check the source to verify that this is the current version before use.

TABLE IX. Input current (low-level) test.

Test condition	Parameter	Connect			Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	Min	Max		
G1	1A Input current, low level	Open	2	Open	0	-430	µA	10
G2	1B "	"	22	"	"	"	"	"
G3	1C "	"	3	"	"	"	"	"
G4	1D "	"	23	"	"	"	"	"
G5	1ENP̄ "	"	4	"	"	"	"	"
G6	1ENT̄ "	"	7	"	"	-870	"	"
G7	1LOAD "	"	27	"	"	-1.3	mA	"
G8	U/D̄ "	"	20	"	"	-1.8	"	"
G9	1CK "	"	21	"	"	-1.3	"	"
G10	2A "	"	30	"	"	-430	µA	"
G11	2B "	"	29	"	"	"	"	"
G12	2C "	"	9	"	"	"	"	"
G13	2D "	"	8	"	"	"	"	"
G14	2ENP̄ "	"	28	"	"	-870	"	"
G15	2ENT̄ "	"	32	"	"	-870	"	"
G16	2LOAD "	"	12	"	"	-1.3	mA	"
G17	2,3CK "	"	11	"	"	-2.6	mA	"
G18	3A "	"	16	"	"	-430	µA	"
G19	3B "	"	36	"	"	"	"	"
G20	3C "	"	15	"	"	"	"	"
G21	3D "	"	35	"	"	"	"	"
G22	3ENT̄ "	"	17	"	"	-870	"	"
G23	3LOAD "	"	37	"	"	-1.3	mA	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:43Z
Check the source to verify that this is the current version before use.

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5963-N675)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:43Z
Check the source to verify that this is the current version before use.