INCH-POUND

MIL-M-28787/319A
AMENDMENT 2
16 December 1992
SUPERSEDING
AMENDMENT 1
14 February 1986

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COUNTER, BINARY, DIGITAL, KEY CODE NZC

This amendment forms a part of Military Specification MIL-M-28787/319A(EC), dated 16 September 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

*TABLE I, Test conditions B1-B15, Test type column: Delete "X" and substitute "S".

*TABLE I, Test conditions B1-B15, Min columns: Delete "-15" (five places) and substitute "0" (five places).

TABLE I, Test conditions G1-G5, G10-G13, G18-G21, Min columns: Delete "-10" (five places) and substitute "0" (five places).

PAGE 5

TABLE I, Test conditions G6, G14, G15, G22, Min columns: Delete "-10" (five places) and substitute "0" (five places).

TABLE I, Test conditions G7, G8, G9, G16, G17, G23, Min columns: Delete "-0.1" (fifteen places) and substitute "0" (fifteen places).

PAGE 7

*TABLE I, Test conditions W1-W12, Max columns: Delete "600" (five places) and substitute "700" (five places).

*TABLE I, Test condition X, Unit column: Delete "F" and substitute "μF".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:43Z
Check the source to verify that this is the current version before use.

PAGE 8

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through X shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and E are stress tests and shall be performed only at 25 ± 5°C ambient. If test conditions A, B, C, D, or E are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, and E, where applicable, followed by the remaining tests in the sequence."

*4.5.1: Delete third sentence and substitute the following:

"When electrical testing is called for at the end of each temperature stabilization period, test conditions F through L and N through X shall be performed in the order specified in 4.4.2 using the initial limits for applicable operating temperature."

4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests F through L and N through X shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests F through L and N through X shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 14

*TABLE IV, Test conditions B1 through B15, Min column: Delete "-15" (one place) and substitute "0" (one place).

PAGES 24 AND 24a

TABLE IX: Delete and substitute new table IX as printed on pages 4 and 5 of this amendment.

PAGE 68

*TABLE XXIII, Test conditions W1 through W12, Max column: Delete "600" (one place) and substitute "700" (one place).

*TABLE XXIV, Test condition X, Unit column: Delete "F" and substitute "μF".

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:43Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0272)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:43Z
Check the source to verify that this is the current version before use.

TABLE IX. Input current (low-level) test.

Test cond	Parameter	Connect A to pin	Connect B to pin	Connect C to pin	Initial limits 25°C ± 5°C ambient Min	Initial limits 25°C ± 5°C ambient Max	Unit	Test fig
G1	1A Input current, low level	Open	2	Open	0	-430	µA	10
G2	1B		22					
G3	1C		3					
G4	1D		23					
G5	1$\overline{\text{ENP}}$		4		0	-430		
G6	1$\overline{\text{ENT}}$		7		0	-870	µA	
G7	1LOAD		27		0	-1.3	mA	
G8	U/$\overline{\text{D}}$		20		0	-1.8		
G9	1CK		21		0	-1.3	mA	
G10	2A		30		0	-430	µA	
G11	2B		29					
G12	2C		9					
G13	2D		8		0	-430		
G14	2$\overline{\text{ENP}}$		28		0	-870		
G15	2$\overline{\text{ENT}}$		32		0	-870	µA	
G16	2LOAD		12		0	-1.3	mA	
G17	2,3CK		11		0	-2.6	mA	
G18	3A		16		0	-430	µA	
G19	3B		36					
G20	3C Input current, low level	Open	15	Open	0	-430	µA	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:43Z
Check the source to verify that this is the current version before use.

TABLE IX. Input current (low-level) test - Continued.

Test cond	Parameter	Connect			Initial limits 25°C ± 5°C ambient		Unit	Test fig
		A to pin	B to pin	C to pin	Min	Max		
G21	3D Input current, low level	Open	35	Open	0	-430	µA	10
G22	3ENT	|	17	|	0	-870	µA	10
G23	3LOAD Input current, low level	Open	37	Open	0	-1.3	mA	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:43Z
Check the source to verify that this is the current version before use.