INCH-POUND

MIL-M-28787/328(SH)
AMENDMENT 2
29 March 1991
SUPERSEDING
AMENDMENT 1
14 September 1984

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

INTERFACE, MICROPROCESSOR, KEY CODE NGK

This amendment forms a part of Military Specification MIL-M-28787/328(EC), dated 22 August 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense

PAGE 4

* TABLE I, Test conditions D1-D38, Min columns Delete "0" (five places) and substitute "-10" (five places).

* TABLE I, Test conditions D1-D38, Max columns Delete "-10" (five places) and substitute "0" (five places)

TABLE I, Test conditions K1-K8, Max columns Delete "210" (five places) and substitute "260" (five places).

TABLE I, Test conditions K9-K16, Max columns· Delete "400" (five places) and substitute "550" (five places).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:47Z
Check the source to verify that this is the current version before use.

PAGE 6

* 4 4.2. Delete and substitute the following

"4 4.2 Order of testing Test conditions A through R shall be performed in any order with the following exceptions. Test conditions A, B, and C are stress tests and shall be performed only at 25 ± 5°C If test conditions A, B, or C are part of a sequence of tests, the order of testing shall be as follows A, B, and C where applicable, followed by the remaining tests in the sequence "

* 4 5.1 Delete third sentence and substitute the following

"When electrical testing is called for at the end of each temperature stabilization period, test conditions D through Q shall be performed in the order specified in 4 4 2 using the initial limits for applicable operating temperature "

* 4 5 3 Delete and substitute the following

"4 5 3 Life test The life test shall be conducted in accordance with MIL-M-28787 The module shall be operated as shown on figure 2 Following the life test and while still at the maximum class temperature, electrical tests D through Q shall be performed in the order specified in 4 4 2 using the operating temperature end-of-life requirements in table I Following the return of the module to 25 ± 5°C, electrical tests D through M and Q shall be performed in the order specified in 4 4 2 using the 25 ± 5°C ambient end-of-life requirements in table I "

PAGES 16, 17, AND 18

* TABLE V, Test conditions D1 through D38, Min column Delete "0" (three places) and substitute "-10" (three places)

* TABLE V, Test conditions D1 through D38, Max column: Delete "-10" (three places) and substitute "0" (three places)

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:47Z
Check the source to verify that this is the current version before use.

PAGE 40

TABLE XIV. Test conditions K1 through K8, Max column: Delete "210" (one place) and substitute "260" (one place)

TABLE XIV, Test conditions K9 through K16, Max column Delete "400" (one place) and substitute "550" (one place)

NOTE The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment

Preparing activity:
Navy - SH

(Project 5963-N815)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:47Z
Check the source to verify that this is the current version before use.