MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

OSCILLATOR, CRYSTAL, DIGITAL, KEY CODE YBS

This specification is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document establishes the requirements and test procedures for the acquisition of an electronic crystal oscillator module.

1.2 Classification. This specification covers two classes of modules:

Class I and class II as specified in MIL-STD-1389.

2. APPLICABLE DOCUMENTS

2.1 Government specifications and standards. Unless otherwise specified, the following specifications and standards, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-28787	-	Modules, Standard Electronic, General Specification for.

STANDARDS

MILITARY

MIL-STD-1389	-	Design Requirements for Standard Electronic Modules.
MIL-STD-1665	-	Test Equipment for the Standard Electronic Modules Program.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 General requirements. The module shall comply with the requirements of MIL-M-28787 except as modified herein.

3.2 Correlation requirements. Before any production modules are tested, all testers and test equipment shall be correlated in accordance with MIL-M-28787.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Electronic Systems Command, ATTN: ELEX 8111, Department of the Navy, Washington, DC 20363, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:49Z
Check the source to verify that this is the current version before use.

3.3 Failure rate requirements. All modules acquired to this specification shall have a predicted failure rate no greater than 0.210 failures per million operating hours for class I or 0.214 failures per million operating hours for class II, when predicted in accordance with MIL-STD-1389. When a class II module is used in a class I environment, failure rate for class I shall be used for reliability prediction (see 6.3).

3.4 Performance requirements. The module shall conform to the electrical requirements specified in table I. Class I modules shall conform to the electrical requirements of class I only, and class II modules shall conform to the electrical requirements of class I and class II (see 6.3).

3.5 Module configuration requirements. The module configuration requirements shall be in accordance with MIL-STD-1389 and as specified herein.

3.5.1 Key code. The module key code shall be YBS.

3.5.2 Size. The module size shall be 1A.

3.5.3 Weight. The module shall have a maximum weight of 35 grams.

3.5.4 Contact pins. The module shall have 40 contact pins positioned A1 through A40. Contact pins A1 through A20 are required whereas contact pins A21 through A40 are optional.

3.5.5 Fin position. The module shall have an insertion and extraction and heat dissipation fin on increment A.

3.5.6 Depth. The module shall have no additional depth requirements.

3.5.7 Holddown holes. The module shall have no additional requirements for location or quantity of holddown holes.

3.5.8 Marking. Marking shall be as specified in MIL-STD-1389, and the module shall be marked with the military part number M28787/331-1 for class I and M28787/331-2 for class II, except no marking shall interfere with heat dissipation from the fin (for example, affixing a label which may be a heat barrier).

3.6 Circuit pin configuration. The function diagram and pin assignments shall conform to figure 1.

3.7 Acceptance test. All production modules shall be tested in accordance with footnotes 1 and 2 of table I.

3.8 End-of-life limits. Modules which have been plugged into an operating system, or exceed 2 years from date of manufacture and are to be tested, shall be capable of conforming to the 25°C end-of-life limits of table I (see 6.2).

* 3.9 Power supply voltage. The module shall be capable of conforming to the requirements of table I for a power supply voltage (V_{CC}) of 5.00 ±0.25 V dc.

4. QUALITY ASSURANCE PROVISIONS


4.1 Quality assurance. The quality assurance provisions of MIL-M-28787 shall apply.

4.2 Acceptance tests. Acceptance tests of all modules shall be in accordance with procedures and equipment specified in MIL-M-28787.

4.3 Test equipment. Test equipment specified on figures and in tables with a type designator shall be as specified in MIL-STD-1665. Other equipment and components shall be as specified on the figures. All resistors shall be metal film and all capacitors shall be ceramic unless otherwise specified.

4.4 Test procedures. The module shall be tested as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:49Z
Check the source to verify that this is the current version before use.



NOTE: Pins 2, 3, 4, 5, 6, 7, 8, and 11 through 40 are not used.

FIGURE 1. YBS module function diagram, crystal oscillator.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:49Z
Check the source to verify that this is the current version before use.

*TABLE I. Module electrical requirements.

Test condition	Parameter	Ref test table	Test type 1/-3/	25°C ±5°C 4/		Class I 4/				Class II 4/				Unit
						0°C ±5°C		60°C ±5°C		-55°C ±5°C		85°C ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
A	V_{CC} stress check	II	S	22.04	22.40	22.04	22.40	22.04	22.40	22.04	22.40	22.04	22.40	MHz
B1, B2	Isolation	III	S	10	∞	10	∞	10	∞	10	∞	10	∞	MΩ
C	Power supply current	IV	X	1	20	1	20	1	20	1	20	1	20	mA
D1, D2	Frequency check	V	X	22.221889	22.222555	22.220778	22.223666	22.220778	22.223666	22.219667	22.224777	22.219667	22.224777	MHz
E	Output voltage, high level	VI	X	2.40	4.75	2.40	4.75	2.40	4.75	2.40	4.75	2.40	4.75	V
F	Output voltage, low level	VI	X	0.00	0.65	0.00	0.65	0.00	0.65	0.00	0.65	0.00	0.65	V
G	Transition time (t_{TLH}), C_L = 130 pF	VI	X	1	8	1	8	1	8	1	10	1	10	ns
H	Transition time (t_{THL}), C_L = 130 pF	VI	X	1	5	1	5	1	5	1	6	1	6	ns
J	Pulse width (PW)	VI	X	15.75	29.25	15.75	29.25	15.75	29.25	15.75	29.25	15.75	29.25	ns
K	Power supply transient amplitude	VII	Q	0	400	0	400	0	400	0	400	0	400	mV
L	Power supply filter capacitance	VIII	S	1.6	3.0	1.6	3.0	1.6	3.0	1.6	3.0	1.6	3.0	µF

1/ "X" parameters shall be 100 percent tested during module acceptance tests.
2/ "S" parameters shall be sample acceptance tested (1 percent or two modules from each inspection lot, whichever is greater) at 25°C.
3/ "Q" parameters shall be tested during qualification testing only.
4/ Unless otherwise specified, limits are for initial and end-of-life.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.

4.4.1 Alternate test methods. Alternate test methods may be employed if approved by the Standard Electronic Modules Program Quality Assurance Activity and they conform to the requirement of MIL-M-28787.

4.4.2 Order of testing. Test conditions A through L shall be performed in any order with the following exceptions. If test conditions A or B are part of a sequence of tests, the order of testing shall be as follows: A, B where applicable, followed by the remaining tests in the sequence.

4.5 Qualification testing. Initial qualification tests and periodic-check tests shall be performed in accordance with the test plan specified in MIL-M-28787 with the following modifications or additions.

4.5.1 Operating temperature test. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through L in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ±5°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions C through L shall be performed in the order specified in 4.4.2 using the initial limits for applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2.

4.5.1.1 Component temperature test. The component temperature test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 3.

4.5.2 Vibration tests. The vibration tests shall be conducted in accordance with MIL-M-28787. During the vibration tests, the module shall be operated in the test circuit shown on figure 4. Following the vibration tests, the electrical tests of table I which are marked with an "X" in the test type column, and test condition L, shall be performed using the initial limits at 25°C ±5°C ambient.

4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests C through L shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements of table I. Following the return of the module to 25°C, electrical tests C through L shall be performed in the order specified in 4.4.2 using the 25°C ±5°C ambient end-of-life requirements of table I.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-28787.

6. NOTES

6.1 Definitions. Definitions are as specified in MIL-STD-1331.

6.2 End-of-life. When any individual module circuit parameter fails to conform to the end-of-life requirements of table I, the module is considered to have completed its useful life (see 3.8).

6.3 Substitutability. Class II modules are substitutable for class I modules. When class II modules are used in a class I environment, the failure rate for class I shall be used for reliability prediction (see 3.3 and 3.4).

* 6.4 Module description. The following electrical parameters reflect the 0°C to 60°C and -55°C to 85°C end-of-life limits from table I.

	Class I	Class II	Unit
Power supply	5 ±5%	5 ±5%	V dc
Power dissipation (outputs not loaded)	105 max	105 max	mW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.

	Class I	Class II	Unit
Frequency	22.220778 min, 22.223666 max	22.219667 min, 22.224777 max	MHz
Pulse width	15.75 min, 29.25 max	15.75 min, 29.25 max	ns
Output voltage			
Low level (I_{OL} = 16 mA)	0 min, 0.65 max	0 min, 0.65 max	V
High level (I_{OH} = -0.4 mA)	2.4 min, 4.75 max	2.4 min, 4.75 max	V
Output drive current			
Low level (V_{OL} = 400 mV)	16 max	16 max	mA
High level (V_{OH} = 2.4 V)	-0.4 max	-0.4 max	mA


6.5 Module function. This module contains a 22.222222 MHz square wave oscillator.

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N535)


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.



NOTE. R1 = 328Ω ±1%, 1/4 W.

FIGURE 2. Operating temperature and life test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.



NOTE: R1 = 328Ω ±1%, 1/4 W.

FIGURE 3. Component temperature test circuit.

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:49Z
Check the source to verify that this is the current version before use.




FIGURE 4. Vibration test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.

*TABLE II. V_{CC} stress check test.

Test condition	Parameter	Initial limits 25°C ±5°C ambient		Unit	Test figure
		Min	Max		
A	V_{CC} stress check	22.04	22.40	MHz	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.





*FIGURE 5. V_{CC} stress check test circuit for table II.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:49Z
Check the source to verify that this is the current version before use.

TABLE III. Isolation test.

Test condition	Parameter	Connect		Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	Min	Max		
B1	Isolation, used to unused pins	1, 9, 10	All other pins	10	∞	MΩ	6
B2	Isolation, frame to module pins	All pins	Frame	10	∞	MΩ	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.



WARNING:

When using a megohm bridge, high voltage may be present at any of the output binding posts. Always set the megohm bridge function switch to "discharge" before connecting or disconnecting the test leads.

NOTE: For test condition B2, penetrate the anodized finish on the module frame with a sharply pointed probe connected to the negative terminal.


FIGURE 6. Isolation test circuit for table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.

*TABLE IV. Power supply current test.

Test condition	Parameter	Initial limits 25°C ±5°C ambient		Unit	Test figure
		Min	Max		
C	Power supply current	1	20	mA	7

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:49Z
Check the source to verify that this is the current version before use.



CAUTION:

Do not isolate the chassis
of item XO1 from earth ground.


FIGURE 7. Power supply current test circuit for table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.

*TABLE V. Frequency check test.

Test condition	Parameter	Connect	Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	Min	Max		
D1	Frequency check	9	22.221889	22.222555	MHz	8
D2	Frequency check	9	22.221889	22.222555	MHz	8


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.



NOTES:
1. For test condition D1, V_{CC} = 4.75 V.
2. For test condition D2, V_{CC} = 5.25 V.
3. Load output with a load as shown on figure 9.

FIGURE 8. Frequency check test circuit for table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.



NOTES:
1. CR1 = 1N4150, or equivalent.
2. C_L = 130 ±5 pF (including probe and parasitic capacitance).
3. R1 = 6.04 kΩ ±1%, 1/8 W.
4. R2 = Select value for current flow of 16 mA ±1% out of point L with point L held at 0.4 V.


* FIGURE 9. YBS logic load circuit.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:49Z
Check the source to verify that this is the current version before use.

*TABLE VI. Output voltage (high-level and low-level), transition time (t_{TLH} and t_{THL}), and pulse width (PW) test.

Test condition		Parameter	Initial limits 25°C ±5°C ambient		Unit	Test figure
			Min	Max		
E	Q	Output voltage, high level	2.40	4.75	V	10,11
F	Q	Output voltage, low level	0.00	0.65	V	"
G	Q	Transition time (t_{TLH}), C_L = 130 pF	1	8	ns	"
H	Q	Transition time (t_{THL}), C_L = 130 pF	1	5	ns	"
J	Q	Pulse width (PW)	15.75	29.25	ns	"


Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:49Z
Check the source to verify that this is the current version before use.



NOTE: Load output with a load as shown on figure 9.

FIGURE 10. Output voltage (high-level and low-level), transition time (t_{TLH} and t_{THL}), and pulse width (PW) test circuit for table VI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.



* FIGURE 11. Output voltage (high-level and low-level), transition time (t_{TLH} and t_{THL}), and pulse width (PW) test circuit waveform for table VI.

Source: https://assist.dla.mil Downloaded: 202610-20T17:49Z
Check the source to verify that this is the current version before use.

TABLE VII. Power supply transient amplitude test.

Test condition	Parameter	Initial limits 25°C ±5°C ambient		Unit	Test figure
		Min	Max		
K	Power supply transient amplitude	0	400	mV	12,13

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:49Z
Check the source to verify that this is the current version before use.





FIGURE 12. Power supply transient amplitude test circuit for table VII.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:49Z
Check the source to verify that this is the current version before use.




* FIGURE 13. Power supply transient amplitude test circuit waveforms for table VII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.

*TABLE VIII. Power supply filter capacitance test.

Test condition	Parameter	Initial limits 25°C ±5°C ambient		Unit	Test figure
		Min	Max		
L	Power supply filter capacitance	1.6	3.0	µF	14

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.



NOTE: Item C01 setup:
Frequency = 1 kHz.
V_{pk} = 0.3 V maximum.

* FIGURE 14. Power supply filter capacitance test circuit for table VIII.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Naval Electronic Systems Command
Washington, DC 20363

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20363
ATTN: ELEX 8111

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-28787/331A(EC	MODULES, STANDARD ELECTRONIC, OSCILLATOR, CRYSTAL, DIGITAL, KEY CODE YBS

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.