INCH-POUND

MIL-M-28787/332
AMENDMENT 1
31 December 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DECODER, DIGITAL, KEY CODE MFP

This amendment forms a part of Military Specification MIL-M-28787/332(EC), dated 21 July 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.4: Delete and substitute the following:

"3.4 Performance requirements. The module shall conform to the electrical requirements specified in table I. Class I modules shall conform to the electrical requirements of class I only, and class II modules shall conform to the electrical requirements of class I and class II (see 6.3)."

3.9: Add a new paragraph as follows:

"3.9 Power supply voltage. The module shall be capable of conforming to the requirements in table I for a power supply voltage of 5.0 ± 0.5 Vdc, except that the limits for output short circuit current apply only for a power supply voltage of 5.5 Vdc ± 1 percent."

PAGE 4

TABLE I, Test condition A2, Isolation, Initial, Test type column: Delete "X" and substitute "S".

TABLE I, Test condition A2, Isolation, End-of-life, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions A3-A9, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions F1-F6, Test type column: Delete "X" and substitute "S".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.

4.4 2 Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through X shall be performed in any order with the following exceptions. Test conditions A, C, F, and G are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, C, F, or G are part of a sequence of tests, the order of testing shall be as follows: A, C, F, and G where applicable, followed by the remaining tests in the sequence."

4.5.1: Delete and substitute the following:

"4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through X in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions B, D, E, H through S, and W shall be performed in the order specified in 4.4.2 using the initial limits for applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2."

4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests B, D, E, H through S, and W shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests B, D, E, H through S, and W shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

Custodians:
Army - ER
Navy - SH
Air Force - 95

Review activities:
Army - AT
Navy - AS, MC
Air Force - 17, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0255)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:49Z
Check the source to verify that this is the current version before use.