MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

CONVERTER, S/D, KEY CODE JWP

This specification is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document establishes the requirements and test procedures for the acquisition of an electronic S/D converter module.

1.2 Classification. This specification covers two classes of modules.

Class I and class II as specified in MIL-STD-1389.

2. APPLICABLE DOCUMENTS

2.1 Government specifications and standards. Unless otherwise specified, the following specifications and standards, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-28787 - Modules, Standard Electronic, General Specification for.

STANDARDS

MILITARY

MIL-STD-1389 - Design Requirements for Standard Electronic Modules.

MIL-STD-1665 - Test Equipment for the Standard Electronic Modules Program.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 General requirements. The module shall comply with the requirements of MIL-M-28787 except as modified herein.

3.2 Correlation requirements. Before any production modules are tested, all testers and test equipment shall be correlated in accordance with MIL-M-28787.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Electronic Systems Command, ATTN: ELEX 8111, Department of the Navy, Washington, DC 20363, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.

3.3 Failure rate requirements. All modules acquired to this specification shall have a predicted failure rate no greater than 1.06 failures per million operating hours for class I or 5.36 failures per million operating hours for class II, when predicted in accordance with MIL-STD-1389. When a class II module is used in a class I environment, failure rate for class I shall be used for reliability prediction (see 6.3).

3.4 Performance requirements. The module shall conform to the electrical requirements specified in table I. Class I modules shall conform to the electrical requirements of class I only, and class II modules shall conform to the electrical requirements of class I and class II (see 6.3).

3.5 Module configuration requirements. The module configuration requirements shall be in accordance with MIL-STD-1389 and as specified herein.

3.5.1 Key code. The module key code shall be JWP.

* 3.5.2 Size. The module size shall be 1A, format A.

3.5.3 Weight. The module shall have a maximum weight of 50 grams.

3.5.4 Contact pins. The module shall have 40 contact pins positioned A1 through A40.

3.5.5 Fin position. The module shall have an insertion and extraction and heat dissipation fin on increment A.

3.5.6 Depth. The module shall have no additional depth requirements.

3.5.7 Holddown holes. The module shall have no additional requirements for location or quantity of holddown holes.

3.5.8 Marking. Marking shall be as specified in MIL-STD-1389, and the module shall be marked with the military part number M28787/337-1 for class I and M28787/337-2 for class II, except no marking shall interfere with heat dissipation from the fin (for example, affixing a label which may be a heat barrier).

3.6 Circuit pin configuration. The function diagram and pin assignments shall conform to figure 1.

3.7 Acceptance tests. All production modules shall be tested in accordance with footnotes 1 and 2 of table I.

3.8 End-of-life limits. Modules which have been plugged into an operating system, or exceed 2 years from date of manufacture and are to be tested, shall be capable of conforming to the 25°C end-of-life limits of table I (see 6.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance. The quality assurance provisions of MIL-M-28787 shall apply.


4.2 Acceptance tests. Acceptance tests of all modules shall be in accordance with procedures and equipment specified in MIL-M-28787.

4.3 Test equipment. Test equipment specified on figures and in tables with a type designator shall be as specified in MIL-STD-1665. Other equipment and components shall be as specified on the figures. All resistors shall be metal film and all capacitors shall be ceramic unless otherwise specified.

4.4 Test procedures. The module shall be tested as specified in table I.

4.4.1 Alternate test methods. Alternate test methods may be employed if approved by the Standard Electronic Modules Program Quality Assurance Activity and they conform to the requirements of MIL-M-28787.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.



NOTE: Pins 2, 4, 17, 21, 23, 25, 38, and 40 are not used.

FIGURE 1. JWP module function diagram, S/D converter.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.

* TABLE I. Module electrical requirements.

Test condition	Parameter	Ref test table	Test type 1/-3/	25°C ±5°C 4/		Class I 4/				Class II 4/				Unit
						0°C ±5°C		60°C ±5°C		-55°C ±5°C		85°C ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
A1,A2	Continuity	II	X	0	1	0	1	0	1	0	1	0	1	Ω
B1-B9	Isolation													
	Initial	III	X	10	∞	10	∞	10	∞	10	∞	10	∞	MΩ
	End-of-life	III	X	1	∞	1	∞	1	∞	1	∞	1	∞	MΩ
C	Insulation resistance													
	Initial	III	Q	10	∞	10	∞	10	∞	10	∞	10	∞	MΩ
	End-of-life	III	Q	1	∞	1	∞	1	∞	1	∞	1	∞	MΩ
D	Common mode voltage	IV	Q	◄---------- Survival ---------►										
E1-E6	Power supply sequencing	V	Q	◄---------- Survival ---------►										
F1	Power supply current	VI	X	0.1	30.0	0.1	30.0	0.1	30.0	0.1	30.0	0.1	30.0	mA
F2	Power supply current	VI	X	-0.01	30.00	-0.01	30.00	-0.01	30.00	-0.01	30.00	-0.01	30.00	mA
F3	Power supply current	VI	X	0.1	130.0	0.1	130.0	0.1	130.0	0.1	130.0	0.1	130.0	mA
G1	Power supply capacitance	VII	X	1.82	3.38	1.82	3.38	1.82	3.38	1.82	3.38	1.82	3.38	µF
G2	Power supply capacitance	VII	X	1.96	3.64	1.96	3.64	1.96	3.64	1.96	3.64	1.96	3.64	µF
H1-H17	Static angular accuracy (60 Hz), V_{normal}													
	Initial	VIII	X	-4	4	-4	4	-4	4	-4	4	-4	4	LSB
	End-of-life	VIII	X	-5	5	-5	5	-5	5	-5	5	-5	5	LSB
J1-J17	Static angular accuracy (60 Hz), V_{low}													
	Initial	IX	S	-4	4	-4	4	-4	4	-4	4	-4	4	LSB
	End-of-life	IX	S	-5	5	-5	5	-5	5	-5	5	-5	5	LSB
K1-K17	Static angular accuracy (60 Hz), V_{high}													
	Initial	X	S	-4	4	-4	4	-4	4	-4	4	-4	4	LSB
	End-of-life	X	S	-5	5	-5	5	-5	5	-5	5	-5	5	LSB

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

* TABLE I. Module electrical requirements - Continued.

Test condition	Parameter	Ref test table	Test type 1/-3/	25°C ±5°C 4/		Class I 4/				Class II 4/				Unit
						0°C ±5°C		60°C ±5°C		-55°C ±5°C		85°C ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
L1-L17	Static angular accuracy (400 Hz), V_{normal}													
	Initial	XI	X	-4	4	-4	4	-4	4	-4	4	-4	4	LSB
	End-of-life	XI	X	-5	5	-5	5	-5	5	-5	5	-5	5	LSB
M1-M17	Static angular accuracy (400 Hz), V_{low}													
	Initial	XII	S	-4	4	-4	4	-4	4	-4	4	-4	4	LSB
	End-of-life	XII	S	-5	5	-5	5	-5	5	-5	5	-5	5	LSB
N1-N17	Static angular accuracy (400 Hz), V_{high}													
	Initial	XIII	S	-4	4	-4	4	-4	4	-4	4	-4	4	LSB
	End-of-life	XIII	S	-5	5	-5	5	-5	5	-5	5	-5	5	LSB
P1,P2	Sensitivity check	XIV	S	0.010	0.033	0.010	0.033	0.010	0.033	0.010	0.033	0.010	0.033	Degree
Q1-Q14	Digital output voltage (V_{OH})	XV	X	2.4	5.1	2.4	5.1	2.4	5.1	2.4	5.1	2.4	5.1	V
R1-R14	Digital output voltage (V_{OL})	XVI	X	0	400	0	400	0	400	0	400	0	400	mV
S1-S3	Digital input breakdown current	XVII	S	0	40	0	40	0	40	0	40	0	40	µA
T1-T3	Digital input current	XVIII	S	-1.6	0.0	-1.6	0.0	-1.6	-0.0	-1.6	0.0	-1.6	0.0	mA
U1-U16	Three-state leakage current, high level	XIX	X	-1	20	-1	20	-1	20	-1	20	-1	20	µA
V1-V16	Three-state leakage current, low level	XX	X	-20	1	-20	1	-20	1	-20	1	-20	1	µA
W	Delay time	XXI	Q	0	3	0	3	0	3	0	3	0	3	µs
X1,X2	Delay time	XXI	Q	0	150	0	150	0	150	0	150	0	150	ns
Y1-Y4	Tracking rate check	XXII	Q	2	6	2	6	2	6	2	6	2	6	rps

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:52Z
Check the source to verify that this is the current version before use.

* TABLE I. Module electrical requirements - Continued.

Test condition	Parameter	Ref test table	Test type 1/-3/	25°C ±5°C 4/		Class I 4/				Class II 4/				Unit
						0°C ±5°C		60°C ±5°C		-55°C ±5°C		85°C ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
Z	Settling time (60 Hz)	XXIII	Q	0.0	1.5	0.0	1.5	0.0	1.5	0.0	1.5	0.0	1.5	s
AA	Noise sensitivity	XXIV	Q	-1	1	-1	1	-1	1	-1	1	-1	1	LSB
BB1	Converter busy, direct (V_H)	XXV	X	2.4	5.1	2.4	5.1	2.4	5.1	2.4	5.1	2.4	5.1	V
BB2	Converter busy, direct (V_L)	XXV	X	0	400	0	400	0	400	0	400	0	400	mV
BB3	Converter busy, direct (P_W)	XXV	X	0.5	3.5	0.5	3.5	0.5	3.5	0.5	3.5	0.5	3.5	µs
BB4	Converter busy, 3-state (V_H)	XXV	X	2.4	5.1	2.4	5.1	2.4	5.1	2.4	5.1	2.4	5.1	V
BB5	Converter busy, 3-state (V_L)	XXV	X	0	400	0	400	0	400	0	400	0	400	mV
BB6	Converter busy, 3-state (P_W)	XXV	X	0.5	3.5	0.5	3.5	0.5	3.5	0.5	3.5	0.5	3.5	µs
CC1-CC3	Power supply ripple rejection	XXVI	Q	-1	1	-1	1	-1	1	-1	1	-1	1	LSB
DD	Continuous conversion	XXVII	Q	◄---------- See table XXVII ---------- ►										
EE1, EE2	Power supply transient amplitude	XXVIII	Q	0	700	0	700	0	700	0	700	0	700	mV pk
FF	Stress	XXIX	Q	◄---------- See table XXIX ---------- ►										

1/ "X" parameters shall be 100 percent tested during module acceptance test.

2/ "S" parameters shall be sample acceptance tested (1 percent or two modules from each inspection lot, whichever is greater) at 25°C.

3/ "Q" parameters shall be tested during qualification testing only.

4/ Unless otherwise specified, limits are for initial and end-of-life.

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:52Z
Check the source to verify that this is the current version before use.

4.4.2 Order of testing. Test conditions A through EE shall be performed in any order with the following exceptions. If test conditions A, B, C, D, E, or FF are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, FF where applicable, followed by the remaining tests in the sequence. If at any time during quality assurance inspection testing, test conditions A, B, C, D, E, or FF are performed, they shall be followed by performance of all tests in table I which are marked with an "X" in the test type column.

4.5 Qualification testing. Initial qualification tests and periodic-check tests shall be performed in accordance with the test plan specified in MIL-M-28787 with the following modifications or additions.

4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through FF in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ±5°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions F through V and BB shall be performed in the order specified in 4.4.2 using the initial limits for applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2.

4.5.1.1 Component temperature test. The component temperature test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2.

4.5.2 Vibration tests. The vibration tests shall be conducted in accordance with MIL-M-28787. During the vibration tests, the module shall be operated in the test circuit shown on figure 3. Following the vibration tests, the electrical tests of table I which are marked with an "X" in the test type column shall be performed using the initial limits at 25°C ±5°C ambient.

4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests F through V shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements of table I. Following the return of the module to 25°C, electrical tests A, B, and F through EE shall be performed in the order specified in 4.4.2 using the 25°C ±5°C ambient end-of-life requirements of table I.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-28787.

6. NOTES

6.1 Definitions. Definitions are as specified in MIL-STD-1331.

6.2 End-of-life. When any individual module circuit parameter fails to conform to the end-of-life requirements of table I, the module is considered to have completed its useful life (see 3.8).

6.3 Substitutability. Class II modules are substitutable for class I modules. When class II modules are used in a class I environment, the failure rate for class I shall be used for reliability prediction (see 3.3 and 3.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

* 6.4 Module description. The following electrical parameters reflect the 0°C to 60°C and -55°C to 85°C end-of-life limits from table I.

	Class I	Class II	
Power dissipation	1.9 max	1.9 max	W
Input voltage			
Low level	0 min, 400 max	0 min, 400 max	mV
High level	2.4 min, 5.1 max	2.4 min, 5.1 max	V
Input current			
Low level (V_{IL} = 400 mV)	0.0 min, 1.6 max	0.0 min, 1.6 max	mA
High level (V_{IH} = 2.4V)	0 min, 40 max	0 min, 40 max	µA
Output drive current			
Three state low level (V_{OL} = 400 mV)	12	12	mA
Three state high level (V_{OH} = 2.4V)	400	400	µA
Direct output low level (V_{OL} = 400 mV)	1.2	1.2	mA
Direct output high level (V_{OH} = 2.4V)	40	40	µA
Synchro input voltage	90 ±10%	90 ±10%	V rms L-L
Frequency	47 min, 440 max	47 min, 440 max	Hz
Input reference voltage	115 ±10%	115 ±10%	V rms L-L
Frequency	47 min, 440 max	47 min, 440 max	Hz

6.5 Module function. The JWP module contains a complete type II servoloop, tracking, synchro to digital converter.


6.5.1 Input to output relationship. The JWP module accepts a 3 line, 90V line to line synchro signal and converts the angle data contained into a 14 BIT three-state digital signal. The reference is a 115V line to line signal. The module outputs a converter busy (CB) and a $\overline{\text{BITE}}$ signal which are available either directly or through the three-state buffer. The three-state buffer is controlled by 2 enable lines. $\overline{\text{ENABLE 2}}$ controls BITS 7 through 14 and $\overline{\text{ENABLE 1}}$ controls BITS 1 through 6, converter busy and $\overline{\text{BITE}}$. An $\overline{\text{INHIBIT}}$ line freezes the data in the transparent latch for easy data transfer. The converter is not inhibited and continues to track the input.

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N648)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. Scott-T transformer = M28787/185-1 (Key Code STT).
2. Loads 1 through 18 are as shown on figure 4.
3. Item G07 setup:
   115 V rms ±10% at 400 Hz ±10%.

* FIGURE 2. Operating temperature, component temperature and life test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.





FIGURE 3. Vibration test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. CR1 = 1N4150 or equivalent.
2. C_L = 150 pF ±20% including fixture and probe capacitance.
3. R1 = 60 kΩ ±1%, 1/10 watt for load 1 and 2.
   = 6.25 kΩ ±1%, 1/10 watt for loads 3-18.
4. For loads 1 and 2, select R2 for a current flow of 1.2 mA ±5% out of point L with point L held at 400 mV.
5. For loads 3-18, select R2 for a current flow of 12 mA ±5% out of point L with point L held at 400 mV.

* FIGURE 4. JWP logic load circuit.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T17:52Z
Check the source to verify that this is the currentversion before use.


TABLE II. Continuity test.


Test condition	Parameter	Connect		Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	Min	Max		
A1	Continuity, frame	11	Frame	0	1	Ω	5
A2	Continuity	10	30	0	1	Ω	5

TABLE III. Isolation and insulation resistance test.

Test condition	Parameter	Connect		Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	Min	Max		
B1	Isolation, used to unused	1,3,5,6,7,8,9, 10,11,12,13,14, 15,16,18,19,20, 22,24,26,27,28, 29,30,31,32,33, 34,35,36,37,39	2,4,17,21,23, 25,38,40	10	∞	MΩ	6
B2	Isolation, unused to unused	2	4,17,21,23, 25,38,40	"	"	"	"
B3	"	4	17,21,23,25, 38,40	"	"	"	"
B4	"	17	21,23,25,38, 40	"	"	"	"
B5	"	21	23,25,38,40	"	"	"	"
B6	"	23	25,38,40	"	"	"	"
B7	"	25	38,40	"	"	"	"
B8	"	38	40	"	"	"	"
B9	Isolation, frame	38	11	"	"	"	"
C	Insulation resistance	18,19,22,24,39	All other pins	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.






NOTE: For test condition A1, penetrate the anodized finish of the module frame with a sharply pointed probe connected to the negative terminal.


* FIGURE 5. Continuity test circuit for table II.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.



WARNING

High voltage may be present at the output binding posts of item R06. Always set the function switch to discharge before connecting or disconnecting test loads.



NOTE: Item R06 setup:
100 ±10 V dc for test conditions B1-B9.
300 ±30 V dc for test condition C.

FIGURE 6. Isolation and insulation resistance test circuit for table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.


TABLE IV. Common mode voltage test.

Test condition	Parameter	Initial limits 25°C ±5°C ambient		Unit	Test figure
		Min	Max		
D	Common mode voltage	Survival		---	7

TABLE V. Power supply sequencing test.

Test condition	Parameter	Switch closing order			Initial limits 25°C ±5°C ambient		Unit	Test figure
		1	2	3	Min	Max		
E1	Power supply sequencing	S4	S5	S6	Survival		---	8
E2	"	S5	S6	S4	(see note 8 on figure 8)		"	"
E3	"	S6	S4	S5	"		"	"
E4	"	S6	S5	S4	"		"	"
E5	"	S5	S4	S6	"		"	"
E6	"	S4	S6	S5	"		"	"


Source: https://assist.dla.mil -- Downloaded: 2025-10-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. Item G07 setup:
   106 V rms ±1% at 400 Hz ±10%.
2. The module shall pass this test if it passes the remaining tests in the sequence of tests.

FIGURE 7. Common mode voltage test circuit for table IV.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. S1-S3 = SPDT switch.
2. S4-S6 = SPST switch.
3. Synchro standard shall be either item F03 or ILC Data Device Corporation model SR-460 or equivalent. Set the output at 90 V rms position.
4. Item G07 setup:
   126.5 V rms ±1% at 400 Hz ±10%.
5. Set switches S1-S3 to position 1.
6. Switches S4-S6 shall be closed in the order specified in table V.
7. Loads 1 through 18 are as shown on figure 4.
8. The module shall pass if it passes the remaining tests.

FIGURE 8. Power supply sequencing test circuit for table V.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T17:52Z
Check the source to verify that this is the current version before use.


TABLE VI. Power supply current test.

Test condition	Parameter		Initial limits 25°C ±5°C ambient		Unit	Test figure
			Min	Max		
F1	15V	Power supply current	0.1	30.0	mA	9
F2	-15V	"	-0.01	30.00	"	"
F3	5V	"	0.1	130.0	"	"

TABLE VII. Power supply capacitance test.

Test condition	Parameter		Connect		Initial limits 25°C ±5°C ambient		Unit	Test figure
			A to pin	B to pin	Min	Max		
G1	5V	Power supply capacitance	1	10	1.82	3.38	µF	10
G2	15V	Power supply capacitance	3	10	1.96	3.64	µF	10


Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.



NOTE: Since the ammeters are not used simultaneously, only one is required.

FIGURE 9. Power supply current test circuit for table VI.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.



NOTE: Item C03 setup:
Frequency = 1 kHz ±10%.
V_{pk} = 300 mV maximum.

FIGURE 10. Power supply capacitance test circuit for table VII.

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE VIII. Static angular accuracy (60 Hz) test.

Test condition	Parameter	Angle input	Output pin states														Initial limits 25°C ±5°C ambient		Unit	Test figure
			16	35	15	34	14	13	12	9	8	7	27	6	5	31	Min	Max		
H1	Static angular accuracy (60 Hz), V_{normal}	000.00	L	L	L	L	L	L	L	L	L	L	L	L	L	L	-4	4	LSB	11
H2	"	015.00	L	L	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
H3	"	030.00	L	L	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
H4	"	045.00	L	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
H5	"	060.00	L	L	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
H6	"	075.00	L	L	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
H7	"	090.00	L	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
H8	"	105.00	L	H	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
H9	"	120.00	L	H	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
H10	"	135.00	L	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
H11	"	150.00	L	H	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
H12	"	165.00	L	H	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
H13	"	180.00	H	L	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
H14	"	225.00	H	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
H15	"	270.00	H	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
H16	"	315.00	H	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
H17	"	359.98	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE IX. Static angular accuracy (60 Hz) tests.

Test condition	Parameter	Angle input	Output pin states															Initial limits 25°C ±5°C ambient		Unit	Test figure
			16	35	15	34	14	13	12	9	8	7	27	6	5	31		Min	Max		
J1	Static angular accuracy (60 Hz), V_{low}	000.00	L	L	L	L	L	L	L	L	L	L	L	L	L	L		-4	4	LSB	11
J2	"	015.00	L	L	L	L	H	L	H	L	H	L	H	L	H	H		"	"	"	"
J3	"	030.00	L	L	L	H	L	H	L	H	L	H	L	H	L	H		"	"	"	"
J4	"	045.00	L	L	H	L	L	L	L	L	L	L	L	L	L	L		"	"	"	"
J5	"	060.00	L	L	H	L	H	L	H	L	H	L	H	L	H	H		"	"	"	"
J6	"	075.00	L	L	H	H	L	H	L	H	L	H	L	H	L	H		"	"	"	"
J7	"	090.00	L	H	L	L	L	L	L	L	L	L	L	L	L	L		"	"	"	"
J8	"	105.00	L	H	L	L	H	L	H	L	H	L	H	L	H	H		"	"	"	"
J9	"	120.00	L	H	L	H	L	H	L	H	L	H	L	H	L	H		"	"	"	"
J10	"	135.00	L	H	H	L	L	L	L	L	L	L	L	L	L	L		"	"	"	"
J11	"	150.00	L	H	H	L	H	L	H	L	H	L	H	L	H	H		"	"	"	"
J12	"	165.00	L	H	H	H	L	H	L	H	L	H	L	H	L	H		"	"	"	"
J13	"	180.00	H	L	L	L	L	L	L	L	L	L	L	L	L	L		"	"	"	"
J14	"	225.00	H	L	H	L	L	L	L	L	L	L	L	L	L	L		"	"	"	"
J15	"	270.00	H	H	L	L	L	L	L	L	L	L	L	L	L	L		"	"	"	"
J16	"	315.00	H	H	H	L	L	L	L	L	L	L	L	L	L	L		"	"	"	"
J17	"	359.98	H	H	H	H	H	H	H	H	H	H	H	H	H	H		"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE X. Static angular accuracy (60 Hz) test.

Test condition	Parameter	Angle input	Output pin states														Initial limits 25°C ±5°C ambient		Unit	Test figure
			16	35	15	34	14	13	12	9	8	7	27	6	5	31	Min	Max		
K1	Static angular accuracy (60 Hz), V_{high}	000.00	L	L	L	L	L	L	L	L	L	L	L	L	L	L	-4	4	LSB	11
K2	"	015.00	L	L	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
K3	"	030.00	L	L	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
K4	"	045.00	L	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
K5	"	060.00	L	L	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
K6	"	075.00	L	L	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
K7	"	090.00	L	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
K8	"	105.00	L	H	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
K9	"	120.00	L	H	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
K10	"	135.00	L	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
K11	"	150.00	L	H	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
K12	"	165.00	L	H	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
K13	"	180.00	H	L	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
K14	"	225.00	H	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
K15	"	270.00	H	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
K16	"	315.00	H	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
K17	"	359.98	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE XI. Static angular accuracy (400 Hz) test.

Test condition	Parameter	Angle input	Output pin states														Initial limits 25°C ±5°C ambient		Unit	Test figure
			16	35	15	34	14	13	12	9	8	7	27	6	5	31	Min	Max		
L1	Static angular accuracy (400 Hz), V_{normal}	000.00	L	L	L	L	L	L	L	L	L	L	L	L	L	L	-4	4	LSB	11
L2	"	015.00	L	L	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
L3	"	030.00	L	L	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
L4	"	045.00	L	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
L5	"	060.00	L	L	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
L6	"	075.00	L	L	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
L7	"	090.00	L	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
L8	"	105.00	L	H	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
L9	"	120.00	L	H	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
L10	"	135.00	L	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
L11	"	150.00	L	H	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
L12	"	165.00	L	H	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
L13	"	180.00	H	L	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
L14	"	225.00	H	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
L15	"	270.00	H	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
L16	"	315.00	H	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
L17	"	359.98	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE XII. Static angular accuracy (400 Hz) test.

Test condition	Parameter	Angle input	Output pin states														Initial limits 25°C ±5°C ambient		Unit	Test figure
			16	35	15	34	14	13	12	9	8	7	27	6	5	31	Min	Max		
M1	Static angular accuracy (400 Hz), V_{low}	000.00	L	L	L	L	L	L	L	L	L	L	L	L	L	L	-4	4	LSB	11
M2	"	015.00	L	L	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
M3	"	030.00	L	L	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
M4	"	045.00	L	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
M5	"	060.00	L	L	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
M6	"	075.00	L	L	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
M7	"	090.00	L	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
M8	"	105.00	L	H	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
M9	"	120.00	L	H	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
M10	"	135.00	L	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
M11	"	150.00	L	H	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
M12	"	165.00	L	H	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
M13	"	180.00	H	L	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
M14	"	225.00	H	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
M15	"	270.00	H	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
M16	"	315.00	H	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
M17	"	359.98	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE XIII. Static angular accuracy (400 Hz) test.


Test condition	Parameter	Angle input	Output pin states														Initial limits 25°C ±5°C ambient		Unit	Test figure
			16	35	15	34	14	13	12	9	8	7	27	6	5	31	Min	Max		
N1	Static angular accuracy (400 Hz), V_{high}	000.00	L	L	L	L	L	L	L	L	L	L	L	L	L	L	-4	4	LSB	11
N2	"	015.00	L	L	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
N3	"	030.00	L	L	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
N4	"	045.00	L	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
N5	"	060.00	L	L	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
N6	"	075.00	L	L	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
N7	"	090.00	L	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
N8	"	105.00	L	H	L	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
N9	"	120.00	L	H	L	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
N10	"	135.00	L	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
N11	"	150.00	L	H	H	L	H	L	H	L	H	L	H	L	H	H	"	"	"	"
N12	"	165.00	L	H	H	H	L	H	L	H	L	H	L	H	L	H	"	"	"	"
N13	"	180.00	H	L	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
N14	"	225.00	H	L	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
N15	"	270.00	H	H	L	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
N16	"	315.00	H	H	H	L	L	L	L	L	L	L	L	L	L	L	"	"	"	"
N17	"	359.98	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE XIV. Sensitivity check test.

Test condition	Parameter	Angle input	Output pin states														Initial limits 25°C ±5°C ambient		Unit	Test figure
			16	35	15	34	14	13	12	9	8	7	27	6	5	31	Min	Max		
P1	Sensitivity check	45.00	L	L	H	L	L	L	L	L	L	L	L	L	L	L	0.010	0.033	Degree	11
P2	Sensitivity check	45.00	L	L	H	L	L	L	L	L	L	L	L	L	L	L	0.010	0.033	Degree	11

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.



* FIGURE 11. Static angular accuracy (60 Hz and 400 Hz) and sensitivity check test circuit for tables VIII through XIV.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.

NOTES:
1. S1 = S2 = S3 = SPDT switch.
2. S1 shall be in position 1 and S2 and S3 in position 2.
3. Synchro standard is ILC Data Device Corporation model SR-460 or equivalent.
4. The synchro standard controls shall be set to output a 90 V rms L-L synchro signal.
5. For test conditions H1-H17, set synchro standard to operate at 60 Hz and adjust item G07 for 60 Hz ±10%, 115 V rms ±1%. Use item M02 to adjust voltage.
6. Set the synchro standard to the angle specified in the test table and monitor the module outputs. These outputs shall be as specified in the test table.
7. For test conditions J1-J17, adjust item G07 to 103.5 V rms ±1% and repeat note 6.
8. For test conditions K1-K17, adjust item G07 to 126.5 V rms ±1% and repeat note 6.
9. For test conditions L1-L17, set synchro standard to operate at 400 Hz and adjust item G07 for 400 Hz ±10%, 115 V rms ±1%. Repeat note 6.
10. For test conditions M1-M17, adjust item G07 to 103.5 V rms ±1% and repeat note 6.
11. For test conditions N1-N17, adjust item G07 to 126.5 V rms ±1% and repeat note 6.
12. For test condition P1, set synchro standard for 400 Hz and adjust item G07 for 115 V rms ±1% at 400 Hz ±1%.
13. Adjust synchro standard to obtain the module output angle specified in table XIV. Increase the synchro standard setting until the module digital output increases +1 LSB. Record the synchro standard setting. Again increase the synchro standard setting until the module digital output increases an additional +1 LSB. Record the synchro standard setting. The difference of the two setting shall meet the limits of table XIV, test condition P1.
14. For test condition P2, set synchro standard for 60 Hz and adjust item G07 for 115 V rms ±1% at 60 Hz ±1%.
15. Adjust synchro standard to obtain the module output angle specified in table XIV. Decrease the synchro standard setting until the module digital output decreases by -1 LSB. Record the synchro standard setting. Again decrease the synchro standard setting until the module digital output decreases an additional -1 LSB. Record the synchro standard setting. The difference of the two settings shall meet the limits of table XIV, test condition P2.
16. Loads 1 through 18 are as shown on figure 4.

* FIGURE 11. Static angular accuracy (60 Hz and 400 Hz) and sensitivity check test circuit for tables VIII through XIV - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the currentersion before use.

TABLE XV. Digital output voltage (V_{OH}) test.


Test condition	Parameter	Input angle	Connect	Initial limits 25°C ±5°C ambient		Unit	Test figure
			A to pin	Min	Max		
Q1	BIT 1 Digital output voltage (V_{OH})	359.98°	16	2.4	5.1	V	12
Q2	BIT 2 "	"	35	"	"	"	"
Q3	BIT 3 "	"	15	"	"	"	"
Q4	BIT 4 "	"	34	"	"	"	"
Q5	BIT 5 "	"	14	"	"	"	"
Q6	BIT 6 "	"	13	"	"	"	"
Q7	BIT 7 "	"	12	"	"	"	"
Q8	BIT 8 "	"	9	"	"	"	"
Q9	BIT 9 "	"	8	"	"	"	"
Q10	BIT 10 "	"	7	"	"	"	"
Q11	BIT 11 "	"	27	"	"	"	"
Q12	BIT 12 "	"	6	"	"	"	"
Q13	BIT 13 "	"	5	"	"	"	"
Q14	BIT 14 "	"	31	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE XVI. Digital output voltage (V_{OL}) test.

Test condition	Parameter	Input angle	Connect A to pin	Initial limits 25°C ±5°C ambient Min	Initial limits 25°C ±5°C ambient Max	Unit	Test figure
R1	BIT 1 Digital output voltage (V_{OL})	000.00°	16	0	400	mV	12
R2	BIT 2 "	"	35	"	"	"	"
R3	BIT 3 "	"	15	"	"	"	"
R4	BIT 4 "	"	34	"	"	"	"
R5	BIT 5 "	"	14	"	"	"	"
R6	BIT 6 "	"	13	"	"	"	"
R7	BIT 7 "	"	12	"	"	"	"
R8	BIT 8 "	"	9	"	"	"	"
R9	BIT 9 "	"	8	"	"	"	"
R10	BIT 10 "	"	7	"	"	"	"
R11	BIT 11 "	"	27	"	"	"	"
R12	BIT 12 "	"	6	"	"	"	"
R13	BIT 13 "	"	5	"	"	"	"
R14	BIT 14 "	"	31	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. S1 = S2 = S3 = SPDT switch.
2. S1 shall be in position 1 and S2 and S3 shall be in position 2.
3. Synchro standard is ILC Data Device Corporation, model SR-460 or equivalent. The output shall be 90 V rms L-L position.
4. Item G07 setup: 115 V rms ±10% at 400 Hz ±10%.
5. It may be necessary to slightly adjust the synchro standard setting to obtain the desired output state.
6. Loads 1 through 18 are as shown on figure 4.

* FIGURE 12. Digital output voltage (V_{OH} and V_{OL}) test circuit for tables XV and XVI.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE XVII. Digital input breakdown current test.

Test condition	Parameter		Connect			Initial limits 25°C ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	Min	Max		
S1	$\overline{\text{ENABLE 1}}$	Digital input breakdown current	Open	33	32,37	0	40	µA	13
S2	$\overline{\text{ENABLE 2}}$	"	Open	32	33,37	0	40	µA	13
S3	$\overline{\text{INHIBIT}}$	"	Open	37	32,33	0	40	µA	13

* TABLE XVIII. Digital input current test.

Test condition	Parameter		Connect			Initial limits 25°C ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	Min	Max		
T1	$\overline{\text{ENABLE 1}}$	Digital input current	Open	33	32,37	-1.6	0.0	mA	13
T2	$\overline{\text{ENABLE 2}}$	"	Open	32	33,37	-1.6	0.0	mA	13
T3	$\overline{\text{INHIBIT}}$	"	Open	37	32,33	-1.6	0.0	mA	13

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T17:52Z
Check the source to verify that this is the current version before use.

* TABLE XIX. Three-state leakage current (high-level) test.


Test condition	Parameter	Connect			Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	Min	Max		
U1	BIT1 Three-state leakage current, high level	32,33	16	37	-1	20	uA	13
U2	BIT2 "	"	35	"	"	"	"	"
U3	BIT3 "	"	15	"	"	"	"	"
U4	BIT4 "	"	34	"	"	"	"	"
U5	BIT5 "	"	14	"	"	"	"	"
U6	BIT6 "	"	13	"	"	"	"	"
U7	BIT7 "	"	12	"	"	"	"	"
U8	BIT8 "	"	9	"	"	"	"	"
U9	BIT9 "	"	8	"	"	"	"	"
U10	BIT10 "	"	7	"	"	"	"	"
U11	BIT11 "	"	27	"	"	"	"	"
U12	BIT12 "	"	6	"	"	"	"	"
U13	BIT13 "	"	5	"	"	"	"	"
U14	BIT14 "	"	31	"	"	"	"	"
U15	CB "	"	28	"	"	"	"	"
U16	$\overline{\text{BITE}}$ "	"	26	"	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:52Z
Check the source to verify that this is the current version before use.

* TABLE XX. Three-state leakage current (low-level) test.

Test condition	Parameter	Connect			Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	Min	Max		
V1	BIT1 Three-state leakage current, low level	32,33	16	37	-20	1	µA	13
V2	BIT2 "	"	35	"	"	"	"	"
V3	BIT3 "	"	15	"	"	"	"	"
V4	BIT4 "	"	34	"	"	"	"	"
V5	BIT5 "	"	14	"	"	"	"	"
V6	BIT6 "	"	13	"	"	"	"	"
V7	BIT7 "	"	12	"	"	"	"	"
V8	BIT8 "	"	9	"	"	"	"	"
V9	BIT9 "	"	8	"	"	"	"	"
V10	BIT10 "	"	7	"	"	"	"	"
V11	BIT11 "	"	27	"	"	"	"	"
V12	BIT12 "	"	6	"	"	"	"	"
V13	BIT13 "	"	5	"	"	"	"	"
V14	BIT14 "	"	31	"	"	"	"	"
V15	CB "	"	28	"	"	"	"	"
V16	$\overline{\text{BITE}}$ "	"	26	"	"	"	"	"



NOTES:
1. R1 = 420 ±1%, 1/8 W.
2. Adjust item P07-4 voltages as follows:
   5.5 V ±1% for test conditions S1-S3.
   400 mV ±1% for test conditions T1-T3 and V1-V16.
   2.7 V ±1% for test conditions U1-U16.

* FIGURE 13. Digital input breakdown current, digital input current, and three-state leakage current (high-level and low-level) test circuit for tables XVII through XX.

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:52Z
Check the source to verify that this is the current version before use.


TABLE XXI. Delay time ($\overline{\text{INHIBIT}}$, $\overline{\text{ENABLE 2}}$ and $\overline{\text{ENABLE 1}}$) test.

Test condition	Parameter	Connect					Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	E to pin	Min	Max		
W	Delay time, $\overline{\text{INHIBIT}}$	Open	32,33	37	37	31	0	3	µs	14,15
X1	Delay time, $\overline{\text{ENABLE 2}}$	37	Open	32	32	31	"	150	ns	14,16
X2	Delay time, $\overline{\text{ENABLE 1}}$	37	Open	33	33	13	"	150	ns	14,16

TABLE XXII. Tracking rate check test.

Test condition	Parameter	Connect			Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	Min	Max		
Y1	Tracking rate check, 60 Hz, count up	37,D	32,33	36	72	216	kHz	18
Y2	Tracking rate check, 60 Hz, count down	37	32,33,D	"	"	"	"	"
Y3	Tracking rate check, 400 Hz, count down	37	32,33,D	"	"	"	"	"
Y4	Tracking rate check, 400 Hz, count up	37,D	32,33	"	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T17:52Z
Check the source to verify that this is the current version before use.




* FIGURE 14. Delay time (INHIBIT, ENABLE 2 and ENABLE 1) test circuit for table XXI.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.

NOTES:
1. R1 = R3 = 1 kΩ ±5%, 1/10 W.
2. R2 = 100Ω ±5%, 1/10 W.
3. Q1 = 2N2222A or equivalent.
4. U1 = SN5470 or 54LS70 or equivalent.
5. Synchro standard is ILC Data Device Corporation model SR-460 or equivalent. The output shall be set to 90 V rms L-L position.
6. Set item G07 to 115 V rms ±10% at 400 Hz ±10%.
7. Procedure for test condition W:
   a. Connect the circuit as specified in table XXI.
   b. Adjust item G10 to 3.5 V ±10% at 100 KHz ±10%.
   c. Set item J05 to external trigger and adjust the pulse width and amplitude as specified on figure 15. Then, using item D07 with channel A at pin 31 and channel B connected to pin 37, use the delay of item J05 to aline the waveforms as specified on figure 15.
   d. Slowly adjust the delay of item J05 so that the negative going edge of the waveform on pin 37 lags the negative edge of the waveform on pin 31. Continue to increase the delay between the waveforms until the LSB stops switching. Slowly backoff the delay until the switching point is again discernable. Measure this delay time (t_D) as shown on figure 15. The delay time shall meet the limits in table XXI.
8. For test condition X, set the synchro standard to "LOCAL" control and the angle to 45 degrees. Set item J05 to "NORMAL" and adjust to obtain the waveforms specified on figure 16. Connect the circuit as specified in table XXI and measure the time delay (t_{ED}) as specified on figure 16. The delay shall meet the limits in table XXI.
9. Loads 1 and 3-18 shall be as shown on figure 4.
10. The trigger circuit consisting of Q1, U1, R1-R3 is a suggested driver circuit. Alternatives are acceptable.

* FIGURE 14. Delay time ($\overline{\text{INHIBIT}}$, $\overline{\text{ENABLE 1}}$, and $\overline{\text{ENABLE 2}}$) test circuit for table XXI - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. PW = 20.0 ±0.2 µs.
2. $t_{TLH} = t_{THL} < 20$ ns.
3. The center waveforms show LSB (pin 31) in inhibited state for reference only.

* FIGURE 15. Delay time ($\overline{\text{INHIBIT}}$) test circuit waveforms for table XXI.


Source: https://assist.dla.mil -- Downloaded: 202640-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. Item J05 setup:
   PW = 250 ±2 µs.
   PRP = 500 ±5 µs.
   $t_{TLH} = t_{THL} \leq 20$ ns.
2. The enable delay time (t_{ED}) shall meet the limits as specified in table XXI.
3. Either output pulse is possible dependent upon state of the module.

* FIGURE 16. Delay time ($\overline{\text{ENABLE 2}}$ and $\overline{\text{ENABLE 1}}$) test circuit waveforms for table XXI.


Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. U1=U5 = 74LS168 or equivalent.
2. U6=U7 = U10 = U11 = 74LS30 or equivalent.
3. U8 = U12 = 74LS04 or equivalent.
4. U9 = 74LS00 or equivalent.
5. Connector = Amphenol 17-20500-1 or equivalent.

* FIGURE 17. Synchro controller.

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:52Z
Check the source to verify that this is the current version before use.



* FIGURE 18. Tracking rate check test circuit for table XXII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

NOTES:
1. Item G07 setup:
   115 V rms L-L ±10% at 60 Hz ±1% for test conditions Y1 and Y2.
   115 V rms L-L ±10% at 400 Hz ±1% for test conditions Y3 and Y4.
2. Adjust item G10 as follows:
   PRR = 36 kHz ±10%.
   PW = 6 µs ±10%.
   PA = 3.5 V ±10%.
   $t_{TLH} = t_{THL} \leq 100$ ns.
3. Synchro standard is ILC Data Device Corporation model SR-460 or equivalent. Set the output at 90 V rms L-L ±1% at 400 Hz ±10%.
4. Verify that pin 36 ($\overline{BITE}$) is in the high level state ($\leq$2.4 V). Increase the frequency of G10 until pin 36 output voltage level goes to the low level state (400 mV). This frequency as measured by item T01 shall meet the limits of table XXII.
5. The table I limits for test conditions Y1-Y4 shall be calculated as follows:

   $$\text{TABLE I limits} = \frac{\text{Table XXII limits}}{36 \text{ kHz}}$$

6. This test verifies a $\overline{BITE}$ low level output voltage (V_{OL}) of 400 mV maximum.
7. Loads 1 through 18 are as shown on figure 4.

* FIGURE 18. Tracking rate check test circuit for table XXII. - Continued.

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE XXIII. Settling time (60 Hz) test.

Test condition	Parameter	Connect			Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	Min	Max		
Z	Settling time (60 Hz)	37	32,33	31	0.0	1.5	s	19,20

TABLE XXIV. Noise sensitivity test.


Test condition	Parameter	Initial limits 25°C ±5°C ambient		Unit	Test figure
		Min	Max		
AA	Noise sensitivity	1/	1/	---	21

1/ See note 6 of figure 21.

TABLE XXV. Converter busy test.

Test condition	Parameter		Connect	Initial limits 25°C ±5°C ambient		Unit	Test figure
			A to pin	Min	Max		
BB1	Direct (V_H)	Converter busy	29	2.4	5.1	V	22,23
BB2	Direct (V_L)	"	29	0	400	mV	"
BB3	Direct (P_W)	"	29	0.5	3.5	µs	"
BB4	3-state (V_H)	"	28	2.4	5.1	V	"
BB5	3-state (V_L)	"	28	0	400	mV	"
BB6	3-state (P_W)	"	28	0.5	3.5	µs	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.




* FIGURE 19. Settling time (60 Hz) test circuit for table XXIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

NOTES:
1. Item G10-1 setup:
   PA = 3.5 V ±10%.
   PW = 27 µs ±10%.
   PRR = 18 kHz ±10%.
   $t_{TLH} = t_{THL} \leq 100$ ns.
2. Item G10-2 setup:
   PA = 3.5 V ±10%.
   PW = 2 µs ±10%.
   Frequency = manual trigger.
   $t_{TLH} = t_{THL} \leq 100$ ns.
3. Synchro standard is ILC Data Device Corporation model SR-460 or equivalent.
4. Item G07 setup:
   115 V rms L-L ±10% at 60 Hz ±1%.
5. Set the synchro controller reset on high and the S time to low.
6. Press the manual trigger button on item G10-2 and allow a full cycle. Verify that the angle displayed on the synchro standard is 000.00 degrees.
7. Set the synchro controller reset to low and the S time to high.
8. Press the manual trigger button on G10-2 and measure the settling time as shown on figure 20. Verify that the angle displayed on the synchro standard is 179.29 degrees.
9. Loads 1 through 18 are as shown on figure 4.

* FIGURE 19. Settling time (60 Hz) test circuit for table XXIII - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.



NOTE: Output may settle in the high or low level.

* FIGURE 20. Setting time (60 Hz) test circuit waveforms for table XXIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.




* FIGURE 21. Noise sensitivity test circuit for table XXIV.

Source: https://assist.dla.mil -- Downloaded: 20260-20T17:52Z
Check the source to verify that this is the current version before use.

NOTES:
1. S1-S3 = SPDT switch.
2. Synchro standard is ILC Data Device Corporation model SR-460 or equivalent. The output voltage shall be 90 V rms L-L. The angle shall be set to 45.000.
3. Item G07 setup:
   115 V rms ±10% at 60 Hz ±10%.
4. Item K03 setup:
   5 Hz to 20 kHz.
   1 V rms ±10%.
5. Set switch S1 to position 1, S2 and S3 to positive 2.
6. Monitor BIT 14 (LSB). The module passes this test if the output remains stable and does not toggle.

* FIGURE 21. Noise sensitivity test circuit for table XXIV - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.



* FIGURE 22. Converter busy test circuit for table XXV.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.

NOTES:
1. S1-S3 = SPDT switch.
2. Synchro standard shall be item F03 or ILC Data Device Corporation model SR-460 or equivalent. The output voltage shall be 90 V rms L-L position.
3. Item G07 setup:
   115 V rms ±10% at 400 Hz ±10%.
4. S1 shall be in position 1, S2 and S3 in position 2.
5. Loads 1 through 18 are as shown on figure 4.
6. Measure the converter busy pulse parameters as shown on figure 23.

* FIGURE 22. Converter busy test circuit for table XXV - Continued.

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:52Z
Check the source to verify that this is the current version before use.




FIGURE 23. Converter busy test circuit waveforms for table XXV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE XXVI. Power supply ripple rejection test.


Test condition	Parameter	Connect		Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	Min	Max		
CC1	5V Power supply ripple rejection	1	Open	1/	1/	---	24
CC2	15V "	3	Open	"	"	"	"
CC3	-15V "	Open	20	"	"	"	"

1/ See note 7 of figure 24.

TABLE XXVII. Continuous conversion test.

Test condition	Parameter	Initial limits 25°C ±5°C ambient		Unit	Test figure
		Min	Max		
DD	Continuous conversion	See figure 25 note 6		---	25

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.




* FIGURE 24. Power supply ripple rejection test circuit for table XXVI.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.

NOTES:
1. R1-R3 = 100Ω ±5%, 1/8 W.
2. C1 = C2 = 20 µF ±20%, 20 V dc.
3. S1-S3 = SPDT switch. Set S1 to position 1 and S2 and S3 to position 2.
4. Synchro standard is ILC Data Device Corporation model SR-460 or equivalent. The output voltage shall be 90 V rms L-L position. The angle shall be set to 45.00.
5. Item G07 setup.
   115 V rms ±10% at 60 Hz ±10%.
6. Item G10 setup: 1 kHz ±1% at:
   500 mV rms ±1% for test condition CC1.
   1 V rms ±1% for test conditions CC@ and CC3.
7. Monitor item D07. The module shall pass the test if the output does not toggle.

* FIGURE 24. Power supply ripple rejection test circuit for table XXVI - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.



* FIGURE 25. Continuous conversion test circuit for table XXVII.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.

NOTES:
1. Item G10 setup:
   PA = 3.5 V ±10%.
   PRR = 18 kHz ±10%.
2. Item J05 setup:
   PA = 3.5 V ±10%.
   PW = 166.7 µs ±10%.
   PRR = 3 kHz ±10%.
   $t_{TLH} = t_{THL} \leq 100$ ns.
3. Item G07 setup:
   115 V rms ±10% at 60 Hz ±10%.
4. Synchro standard is ILC Data Device Corporation model SR-460 or equivalent. The output voltage shall be 90 V rms L-L position.
5. Loads 1 through 18 are as shown on figure 4.
6. Monitor pin 29 (CB). The module passes the continuous conversion test if the converter busy pulses continue when item J05 is in the low level state.

* FIGURE 25. Continuous conversion test circuit for table XXVII - Continued.

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:52Z
Check the source to verify that this is the currenversion before use.


TABLE XXVIII. Power supply transient amplitude test.

Test condition	Parameter	Connect	Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	Min	Max		
EE1	Power supply transient amplitude (Vp_{pk})	1	0	700	mV pk	26,27
EE2	Power supply transient amplitude (V_{Npk})	1	0	700	mV pk	26,27

TABLE XXIX. Stress test.

Test condition	Parameter		Initial limits 25°C ±5°C ambient		Unit	Test figure
			Min	Max		
FF	Stress	Following this test the module shall conform to the requirements of all test conditions in table I marked test type X.	---	---	---	28


Source: https://assist.dla.mil -- [illegible]
Check the source to verify that this



NOTES:
1. Synchro standard is ILC Data Device Corporation model SR-460 or equivalent. Set to 90 V rms L-L position.
2. Item G07 setup:
   115 V rms ±10% at 400 Hz ±10%.

* FIGURE 26. Power supply transient amplitude test circuit for table XXVIII.


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:52Z
Check the source to verify that this is the current version before use.



NOTES:
1. V_{Ppk} = is the most positive peak.
2. V_{Npk} = is the most negative peak.
3. Trigger item D07 from channel A.

* FIGURE 27. Power supply transient amplitude test circuit waveforms for table XXVIII.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the currentersion before use.



NOTES:
1. R1-R3 = V275 LA15A varistor.
2. S1 = DPST switch.
3. Set switch S1 to the closed position for a period of 10 to 30 seconds then operate switch S1 to the open position.
4. Item G07 setup.
   115 V rms ±10% at 400 Hz ±10%.
5. This test shall not exceed 1 minute.

* FIGURE 28. Stress test circuit for table XXIX.

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.

ISTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in bmitting comments and suggestions for improvements All users of military standardization documents are invited to provide ggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and ailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was o rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the oblems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an knowledgement will be mailed to you within 30 days to let you know that your comments were received and are being nsidered.

OTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of ecification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

EPARTMENT OF THE NAVY

aval Electronic Systems Command
ashington, DC 20363

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

FICIAL BUSINESS
NALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20363
ATTN: ELEX 8111

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-28787/33A(EC)	MODULES, STANDARD ELECT. CERAMIC

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* ____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.