INCH-POUND

MIL-M-28787/337A(SH)
AMENDMENT 1
24 August 1990

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

CONVERTER, S/D, KEY CODE JWP

This amendment forms a part of Military Specification MIL-M-28787/337A(SH), dated 6 May 1985, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense

PAGE 4

TABLE I, Test condition G1, Min column (5 places) Delete "1.82" (5 places) and substitute "1 05"

TABLE I, Test condition G1, Max column (5 places) Delete "3 38" (5 places) and substitute "1 95"

TABLE I, Test condition G2, Min column (5 places) Delete "1 96" (5 places) and substitute "0 43"

TABLE I, Test condition G2, Max column (5 places) Delete "3 64" (5 places) and substitute "0 80"

PAGE 5

TABLE I, Test conditions Y1-Y4, Min column Delete "2" (5 places) and substitute "3" (5 places)

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202610-20T17:52Z
Check the source to verify that this is the current version before use.

PAGE 6

TABLE I. Delete and substitute new table I as printed on page 3 of this amendment.

PAGE 18

TABLE VII, Test condition G1, Min column Delete "1 82" (1 place) and substitute "1 05" (1 place)

TABLE VII, Test condition G1, Max column Delete "3 38" (1 place) and substitute "1 95" (1 place)

TABLE VII, Test condition G2, Min column Delete "1 96" (1 place) and substitute "0 43" (1 place)

TABLE VII, Test condition G2, Max column Delete "3 64" (1 place) and substitute "0 80" (1 place)

PAGE 37

TABLE XXII, Test conditions Y1 through Y4, Min column Delete "72" (4 places) and substitute "108" (4 places)

Preparing activity
Navy - SH

(Project 5963-N827)

Agent NW

Source: https://assist.dla.mil -- Downloaded: 202640-20T17:52Z
Check the source to verify that this is the current version before use.

TABLE I Module electrical requirements - Continued.

Test condition	Parameter	Ref test table	Test type 1/-3/	25 ± 5°C 4/		Class I 4/				Class II 4/				Unit
						0 ± 5°C		60 ± 5°C		-55 ± 5°C		85 ± 5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
Z	Settling time (60Hz)	XXIII	Q	0 0	1 5	0 0	1 5	0 0	1 5	0 0	1 5	0 0	1 5	s
AA	Noise sensitivity	XXIV	Q	◄----------See table XXIV----------►										
BB1	Converter busy, direct (V_H)	XXV	X	2 4	5 1	2 4	5 1	2 4	5 1	2 4	5 1	2 4	5 1	V
BB2	Converter busy, direct (V_L)	XXV	X	0	400	0	400	0	400	0	400	0	400	mV
BB3	Converter busy, direct (P_W)	XXV	X	0 5	3 5	0 5	3 5	0 5	3 5	0.5	3 5	0 5	3 5	µs
BB4	Converter busy, 3-state (V_H)	XXV	X	2 4	5 1	2 4	5 1	2 4	5 1	2 4	5 1	2 4	5 1	V
BB5	Converter busy, 3-state (V_L)	XXV	X	0	400	0	400	0	400	0	400	0	400	mV
BB6	Converter busy, 3-state (P_W)	XXV	X	0 5	3 5	0 5	3 5	0 5	3 5	0 5	3 5	0 5	3.5	µs
CC1-CC3	Power supply ripple rejection	XXVI	Q	◄----------See table XXVI----------										
DD	Continuous conversion	XXVII	Q	◄----------See table XXVII----------										
EE1, EE2	Power supply transient amplitude	XXVIII	Q	0	700	0	700	0	700	0	700	0	700	mV pk
FF	Stress	XXIX	Q	◄----------See table XXIX----------										

1/ "X" parameters shall be 100 percent tested during module acceptance test
2/ "S" parameters shall be sample acceptance tested (1 percent or two modules from each inspection lot, whichever is greater) at 25°C.
3/ "Q" parameters shall be tested during qualification testing only
4/ Unless otherwise specified, limits are for initial and end-of-life

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:52Z
Check the source to verify that this is the current version before use.