INCH-POUND

MIL-M-28787/338
AMENDMENT 2
30 July 1993
SUPERSEDING
AMENDMENT 1
22 August 1986

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

ENCODER, PRIORITY, KEY CODE NTA

This amendment forms a part of Military Specification MIL-M-28787/338(EC), dated 4 February 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 7

TABLE I, Test conditions AA1-AA14, Max columns: Delete "15" (five places) and substitute "20" (five places).

PAGE 8

*4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through AA shall be performed in any order with the following exceptions. Test conditions A, C, D, E, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, C, D, E, or F are part of a sequence of tests, the order of testing shall be as follows: A, C, D, E, and F where applicable, followed by the remaining tests in the sequence."

PAGE 9

6.4, Input current, low level: Delete "G3" and substitute "$\overline{G3}$".

PAGE 37

*TABLE XIII, Test figure column: Delete "14" and substitute "14,15".

PAGE 38

*TABLE XIV, Test figure column: Delete "14" and substitute "14,15".

PAGE 59

FIGURE 18, ITEM P07-1: Delete "4.5" and substitute "5".

PAGE 69

FIGURE 20, ITEM P07-1: Delete "4.5" and substitute "5".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:53Z
Check the source to verify that this is the current version before use.

PAGE 72

TABLE XX, Test condition W3, C to pin column: Delete "23,32" and substitute "22,32".

TABLE XX, Test condition X6, A to pin column: Delete "24 and 34".

PAGE 75

FIGURE 24, OUTPUT PULSE AT POINT B WITH B CONNECTED: Delete "90%PA" and substitute "2.0 ± 0.1 V".

FIGURE 24, OUTPUT PULSE AT POINT B WITH B CONNECTED: Delete "10%PA" and substitute "0.8 ± 0.1 V".

FIGURE 24, OUTPUT PULSE AT POINT C WITH C CONNECTED: Delete "90%PA" and substitute "2.0 ± 0.1 V".

FIGURE 24, OUTPUT PULSE AT POINT C WITH C CONNECTED: Delete "10%PA" and substitute "0.8 ± 0.1 V".

PAGE 78

FIGURE 26, OUTPUT PULSE AT POINT A: Delete "90%PA" and substitute "2.0 ± 0.1 V".

FIGURE 26, OUTPUT PULSE AT POINT A: Delete "10%PA" and substitute "0.8 ± 0.1 V".

PAGE 80

TABLE XXIII, Test conditions AA1-AA14, Max column: Delete "15" (fourteen places) and substitute "20" (fourteen places).

PAGE 81

TABLE XXIII, Test condition AA25, B to pin column: Delete "37" and substitute "31".

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - NW
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0279)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:53Z
Check the source to verify that this is the current version before use.