MIL-E-29406(MC)
AMENDMENT 2
26 July 1984
SUPERSEDING
AMENDMENT 1
9 May 1984

MILITARY SPECIFICATION

EXTINGUISHER, FIRE, DRY, CHEMICAL AND AQUEOUS FILM FORMING FOAM: SELF-CONTAINED

This amendment forms a part of Military Specification MIL-E-29406(MC), dated 6 September 1983, and is approved for use by the U.S. Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of the Defense.

PAGE 2

*2.1.1: Under "SPECIFICATIONS MILITARY", delete "MIL-E-52798- Enamel, Alkyd, Camouflage" and add "MIL-C-46168 - Coating, Aliphatic Polyurethane, Chemical Agent Resistant".

PAGE 5

3.3.2, line 5: Delete "250" and substitute "275".

PAGE 6

3.3.3, line 1: Delete "250" and substitute "275".

PAGE 11

*3.8: Delete in entirety and substitute the following:

"3.8 Treatment and paintings. The portion of the fire extinguisher normally painted shall be cleaned, treated, primed and finish coated in accordance with MIL-TD-704, Type "F" for ferrous metals and Type "G" for nonferrous metals and fiberglass. Parts and components may be primed with alkyd based primer which has been allowed to cure for a minimum of 14 days and then cleaned and primed as per MIL-T-704, Type "F" or "G" as applicable, either prior to or at final assembly painting. The finish coat color shall be forest green, in accordance with MIL-C-46168."

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 202640-20T22:56Z
Check the source to verify that this is the current version before use.

PAGE 14

*4.7.4: Delete in entirety and substitute the following:

"4.7.4 Cycling and rupture test. A sample of both the dry chemical tank and the AFFF tank, selected from the tank manufacturers production run, which is used for fabricating the fire extinguisher, shall be charged from atmospheric pressure to the tank's 250 psi operating pressure and then vented back to atmospheric pressure for 10,000 cycles. At the end of 10,000 cycles, the tank shall be pressure tested and shall not rupture below 250 percent of the tank's design operating pressure. Both agent tanks shall be so tested."

PAGE 15

4.7.5.6, line 15: Delete "4" and substitute "5".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity
NAVY - MC
Project No. 4210-N194

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:56Z
Check the source to verify that this is the currentversion before use.