MILITARY SPECIFICATION

RADIO SET: AN/PRC-104(V)

This amendment forms a part of Military Specification MIL-R-29418(MC), dated 26 March 1985, and is approved for use within the Marine Corps, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.3.1: Delete in entirety and substitute the following:

"3.3.1 Major components. The following components and ancillary items are part of, or used with, the Radio Set, AN/PRC-104, and shall be supplied by the contractor:.

Item	Quantity
Radio Set	1 each
Alice pack	1 each
Antenna, Whip AT-217A/PRC; spring section antenna AB-129/PR	1 each
~~Handset, H-250/U~~	~~1 each~~
Telegraph Key KY-872/PRC-104	1 each
Battery Case Assembly CY-7541/PRC-104 - for Silver Zinc batteries, or CY-7875/PRC-104 - for Lithium or Ni-Cad batteries (Quantity, type and batteries to be furnished will be specified in bid request and contract (see 6.2.1))	1 each
Antenna Base, Adapter AB-1241/PRC-104 for AS-2259/GR	1 each
Radio Frequency Cable Assembly CG-3815/U	1 each
Battery Charge Cable, CX-13032/PRC-104 - for Silver Zinc batteries, or Cable assembly, Charger external power, P/N 79A5029A0050 - for Lithium or Ni-Cad batteries (Type of cable assembly to be furnished will be specified in bid request or contract (see 6.2.1))	1 each
Bench Test Power Cable, CX-13030/PRC-104	1 each
Battery Extension Cable, XC-13031/PRC-104	1 each
Transit Case CY-7542/PRC-104 - for Silver Zinc batteries, or Transit Case CY-8291/PRC-104(V) - for Lithium or Ni-CAD batteries (Type of Transit Case to be furnished will be specified in bid request or contract (see 6.2.1))	1 each"

AMSC N/A FSC 5820

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:01Z
Check the source to verify that this is the current version before use.

PAGE 7

3.6.1.6: Delete in entirety and substitute the following:

"3.6.1.6 Battery case assembly.

"3.6.1.6.1 CY-7541/PRC-104. The battery case CY-7541/PRC-104 shall be in accordance with Drawing No. 755002A0850.

"3.6.1.6.2 CY-7875/PRC-104. The battery case CY-7875/PRC-104 shall be in accordance with Drawing No. 79A5029A0000. The battery case assembly shall consist of a container for two batteries and shall contain the necessary circuitry for using either a single battery, or two batteries of the same type in parallel, to power the radio set. The battery case assembly shall interface with the radio set and two of either Battery, Storage, Sealed, Nickel-Cadmium BB-590/U or Battery, Primary, Lithium Organic BA-5590/U. The circuitry shall provide for the charging of the rechargeable batteries, shall prevent this discharge of one battery into the other when two batteries are used in parallel, shall provide temperature control to prevent damage to the batteries when charged at extremely low temperatures, and shall protect the batteries from discharge should the charger connector develop a short. The circuitry shall be capable of using a battery charging source to recharge the battery or batteries in the battery case assembly while the battery case assembly is attached to, and providing power for, the radio set. The circuitry shall be capable of transferring power from a battery charger to the radio set without batteries in the case."

PAGE 13

3.3.6, line 1: After "radio set", add "and the battery case assembly shall".

PAGE 16

3.6.1.5.4, line 3: Delete "variable" and substitute "voltage".

PAGE 22

3.6.4.1, line 15: Delete "power factor (PF)" and substitute "picofarad (pF)".

PAGE 23

3.7.1, line 1: After "radio set", add "and the battery case assembly".

PAGE 24

3.7.1(h), line 1: After "Radio Set", add "Battery Case Assembly".

PAGE 27

Table III, Test 8: Add "3.3.1.6".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:01Z
Check the source to verify that this is the current version before use.

PAGE 33

4.8.1.7: Delete in entirety and substitute the following:

"4.8.1.7 Leakage (immersion). The radio set and the battery case with simulated battery shall be tested in accordance with test method 512.2, Procedure 1 or MIL-STD-810."

PAGE 34

4.8.9, line 1: After "radio set", add "and the battery case assembly".

PAGE 40

6.2.1: Add the following:

"(f) Battery case assembly requirements (see 3.3.1).

(g) Battery charge cable requirements (see 3.3.1).

(h) Transit case requirements (see 3.3.1)."

Preparing activity:
Navy - MC
Project No. 5820-N842

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:01Z
Check the source to verify that this is the current version before use.