MIL-B-28635C
22 September 1985
SUPERSEDING
MIL-B-28635B(YD)
6 April 1979

MILITARY SPECIFICATION

BOOKSHELF FOR BUNK BED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for component materials and their assembly into bookshelves.

1.2 Classification. The bookshelves shall be of the following types, as specified (see 6.2).

Type I - Bookshelf for round tube bunk bed (see figures 1 and 2).
Type II - Bookshelf for square tube bunk bed (see figure 3).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7105

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

MMM-A-130 - Adhesive, Contact.
PPP-B-636 - Boxes, Shipping, Fiberboard.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-15228 - Bed, Bunk, Steel, Round Tube, Single and Double-Deck (Convertible).
MIL-B-28644 - Bed, Bunk, Steel, Square Tube, with End Panels, Single and Double-Deck.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

MIL-STD-147 - Palletized Unit Loads.
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of.

(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as Department of Defense adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)

A208.1 - Mat-Formed Wood Particleboard.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A366 - Steel Sheet, Carbon, Cold-Rolled, Commercial Quality, Specification for.

D3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

LD 3 - High-Pressure Decorative Laminates.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish a bookshelf of the type specified for first article inspection and approval (see 4.2.1 and 6.4).

3.2 Materials. Materials shall be as specified herein and in applicable specifications and standards, and other referenced documents. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects which adversely affect performance or serviceability of the finished product.

3.2.1 Particleboard. Particleboard shall be 3/4 inch thick, and in accordance with ANSI A208.1, type 1, grade 1-M-3.

3.2.2 Decorative laminated plastic sheets. Decorative laminated plastic sheets shall be 0.032-inch thick and in accordance with NEMA LD 3. Pattern, color and finish shall be as specified (see 6.2).

3.2.3 Plastic edge molding. Plastic edge molding shall be tee-style, extruded of ethyl cellulose, polypropylene, or cellulose acetate butyrate. The tongue of the tee shall be formed with barbs to hold securely in the slot of panel edge. Face shall be convex and smooth, without grooves or other detailing. Edge molding shall match the wood grain of the decorative laminated plastic sheet or be a solid color which blends with the woodgrain color, as specified (see 6.2). When solid color laminated plastic sheets are used, the edge molding shall be the same color or a lighter shade of the same color.

3.2.4 Bracket fasteners. Hardware for securing the two brackets to the type I bookshelf shall consist of cap screws with button heads and hexagon socket openings, capped tee-nuts, and washers. The capped tee-nuts shall be pronged to prevent turning during assembly. Hardware dimensions shall be as shown on figure 2 and finish shall be cadmium plating for corrosion resistance.

3.2.5 Particleboard mechanical fasteners. The particleboard back and bottom of the type I bookshelf shall be secured to the sides with helically wound coils of carbon steel wire. The wire insert shall be of double coarse thread type with matching screw.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

3.2.6 Sheet steel. Sheet steel for the type I brackets, and the shelf and channel of the type II bookshelf shall conform to ASTM A366. Sheets of 16-gauge and lighter shall have a stretcher-leveled standard of flatness.

3.2.7 Adhesive. Adhesive for bonding the decorative laminated plastic sheet to particleboard shall conform to MMM-A-130.

3.3 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.4 Design and construction. The bookshelves shall be constructed as specified herein and as shown on figures 1 through 3 for the type specified. Allowable tolerances shall be as shown on figures 1 through 3 and as specified herein. Materials shall be in accordance with 3.2 and as otherwise specified herein.

3.4.1 Brackets.

3.4.1.1 Type I brackets. Each type I bookshelf shall have two brackets of 10-gauge steel. The brackets shall be formed and punched as shown on figures 1 and 2. Sharp edges shall be eased and burrs shall be removed. When finished as specified in 3.6, the brackets shall fit snugly over the headboard corner posts.

3.4.1.1.1 Type I bracket assembly. The plastic surrounding the opening for the capped tee-nuts shall be punched as necessary at the proper locations for insertion of the three prongs of the capped tee-nuts. The two brackets and shelf shall be assembled with a washer being placed between the cap screw head and bracket, and two washers placed between the bracket and shelf side as shown on figure 2. The two washers are used as spacers and may be removed as necessary for adjustment if there is any variation in distance between the corner posts. When the type I bookshelf is completely assembled it shall be capable of being installed or removed without the use of tools.

3.4.1.2 Type II brackets. Each type II bookshelf shall have a channel bracket of 10-gauge steel spot welded to the underside of the shelf at the front. Sharp edges shall be eased and burrs shall be removed. When finished as specified in 3.6, the bracket shall fit snugly over the uppermost crossmember of the headboard.

3.4.2 Panels.

3.4.2.1 Type I panels. The type I bookshelf shall be constructed of particleboard panels. The panels consisting of the bottom, back, and two sides shall be covered on both sides with decorative laminated plastic sheets. The exposed edges shall be covered with plastic edge moldings in accordance with 3.5. Laminated plastic sheets shall be bonded to the particleboard core as specified in 3.4.3. The finished laminated plastic surfaces shall not contain cracks, scratches, dents, or chipped edges. Slots in the shelf bottom for the exit of electrical cords and for use in cleaning shall be of the size and location shown on figure 1. Exposed particleboard

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

edges created by the slots shall be stained to closely match the adjoining plastic surfacing. The back, bottom and side of each end of the bookshelf shall be secured with four wire inserts and matching screws at the locations shown on figure 2. The back shall be fastened to the bottom with three wire inserts and matching screws; one centered between the ends, and one near each end of the bottom between the opening and the bookshelf side. The screws which fasten the sides and back to the shelf bottom shall be installed prior to bonding the laminated plastic sheets to the particleboard to provide a smooth surface without holes in the plastic surface. Joining of exterior surfaces of the panels shall fit flush.

3.4.2.2 Type II panels. The type II bookshelf shall be constructed of particleboard back and end panels, and a bottom panel of 16-gauge sheet steel. The particleboard panels shall be covered on both sides with decorative laminated plastic sheets, and the exposed edges covered with plastic edge moldings in accordance with 3.5. Laminated plastic sheets shall be bonded to the particleboard core as specified in 3.4.3. The finished laminated plastic surfaces shall not contain cracks, scratches, dents, or chipped edges. Slots in the bottom panel for the exit of electrical cords and for use in cleaning shall be of the size and location shown on figure 3. The bottom panel shall be finished as specified in 3.6. Assembly of the type II bookshelf shall be as shown on figure 3. When the type II bookshelf is completely assembled it shall be capable of being installed or removed without the use of tools.

3.4.3 Bonding. Laminated plastic sheets shall be bonded to the particleboard core with a solvent based contact adhesive as specified in 3.2.7. The bonding procedure shall be in accordance with NEMA LD 3.

3.5 Installation of the plastic edge molding. The molding shall cover particleboard panel edges with a tolerance of plus 0-inch and minus 1/64-inch on each side. Molding for each exposed panel edge shall be one continuous piece, without splicing; except that one butt joint centered at the bottom is permitted for each side panel molding. Both ends of each length of molding shall be secured with brads driven through the molding tongue. Brads for securing the bottom and the back panel edge moldings shall be driven from the least exposed surfaces: that is, from the underside of the bottom and the outside of the back respectively. Brads for securing side panel molding shall be driven from the exterior sides. Brads shall be set, and holes filled completely with a nonshrinking, pigmented filler material to closely match the plastic surfacing. The molding shall fit tightly and securely, without gaps or crevices.

3.6 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.7 Identification marking. Identification shall be permanently and legibly marked directly on the underside of the shelf or on a corrosion-resisting metal plate securely attached to the underside of the shelf at the source of manufacturer. Identification shall include the manufacturer's model number, name and trademark to be readily identifiable to the manufacturer.

3.8 Workmanship.

3.8.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.8.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.8.3 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Spot welds shall be a minimum of 0.016-inch diameter when measured at the fused nugget or 0.8 times the square root of the material thickness, whichever is greater. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one bookshelf when a first article is required (see 3.1 and 6.2). This inspection shall include the examination of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4 and the packaging inspection of 4.5. This inspection shall be performed on the samples selected in accordance with 4.3.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of product shall be one bookshelf. All bookshelves offered for delivery at one time shall be considered a lot for the purpose of inspection. The inspection level shall be level II and the Acceptable Quality Level shall be 2.5 percent defective. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separated from new lots, and shall be clearly identified as reinspected lots.

4.4 Examination. Each bookshelf selected shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirement shall constitute one defect.

4.5 Packaging inspection. The preservation, packing, palletization and marking shall be inspected to verify conformance with section 5.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each bookshelf shall be preserved method III in accordance with MIL-P-116 in a close-fitting fiberboard box conforming to PPP-B-636, class weather-resistant. Bookshelves shall be shipped completely assembled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

The contents shall be cushioned, blocked and braced to prevent movement. The fiberboard box shall be closed in accordance with method V as specified in the appendix to the box specification.

5.1.2 Level C. Material shall be packaged in accordance with ASTM D3951. Bookshelves shall be shipped completely assembled.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Levels A and B. Packing shall be in accordance with MIL-STD-794 for the applicable level specified. Containers shall be selected from table I for the appropriate level. Only closed containers shall be used.

5.2.2 Level C. Material shall be packed in accordance with ASTM D3951.

5.3 Palletization. Material shall be palletized in accordance with MIL-STD-147 when the following criteria are met:

a. Load to consist of four or more unskidded containers; and,
b. Load shall utilize a minimum of 80 percent of the pallet base.

5.4 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The bookshelves are for use with military standard bunk beds for enlisted personnel conforming to Military Specification MIL-B-15228 or MIL-B-28644. One bookshelf is required per bed. The type I bookshelf slips directly over the headboard corner posts and rests on the upper cross tube. The steel channel bracket of the type II bookshelf slips directly over the uppermost crossmember of the headboard and the ends rest against the headboard corner posts.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Whether type I or type II is required (see 1.2).
c. Issue of document required if other than as specified (see 2.1.1).
d. When a first article is required (see 3.1, 4.2.1 and 6.4).
e. Pattern, color and finish of decorative laminated plastic sheets required (see 3.2.2).
f. Whether the edge molding is to be wood grain color or a solid color (see 3.2.3).
g. Color of the finish coat (see 3.6).
h. Level of preservation and level of packing required (see 5.1 and 5.2).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of DoD Federal Acquisition Regulations (FAR) Supplement 27.410-6, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DoD FAR 27.410-6 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one complete bookshelf. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Navy - YD
Air Force - 99

Preparing Activity:

Navy - YD

(Project 7105-N249)

Review Activity:

Air Force - 84

User Activity:

Army - GL

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.




FIGURE 1. Type I bookshelf - details.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.





FIGURE 2. Type I bookshelf - sections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.



NOTES:

1. DIMENSIONS ARE INCHES. DIMENSIONS DO NOT INCLUDE "T" MOLDING.
2. APPLY PLASTIC LAMINATE & "T" MOLDING TO ENDS AND BACK AS SHOWN (BOTH SIDES).
3. ASSEMBLE & GLUE ENDS AND BACK PANEL.
4. LOCATE SHELF ASSEMBLY AS SHOWN. DRILL AND FASTEN WITH NO.10 PAN HEAD SCREWS.

FIGURE 3. Type II bookshelf.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-28635C	BOOKSHELF FOR BUNK BED

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil/quicksearch/ 2010-10-20T13:29Z
Check the source to verify that this is the current version before use.