|INCH-POUND|

MIL-L-28627C
31 August 1988
SUPERSEDING
MIL-L-28627B(YD)
8 August 1983

MILITARY SPECIFICATION

LOADER, SKID STEER, FOUR-WHEEL HYDROSTATIC OR MECHANICAL DRIVE, 10 CUBIC FOOT HEAPED CAPACITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a commercial, hydraulically operated, skid steer loader of 10 cubic foot heaped capacity, gasoline or diesel-engine-driven, pneumatic-tired, four-wheel hydrostatic or mechanical drive.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standard. The following specifications and standard form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

|Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.|

AMSC N/A FSC 3805

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-20T13:27Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-V-173 - Varnish, Moisture-and-Fungus-Resistant (For Treatment of Communications, Electronics, and Associated Equipment).
MIL-T-3351 - Tractor, Full Tracked, Low-Speed; Tractor Wheeled, Agricultural; and Tractor Wheeled, Industrial, and Their Attachments, Packaging of.

STANDARD

MILITARY

MS51335 - Pintle Assembly, Towing, 18,000 Pounds Capacity, Manual Release.

(Unless otherwise indicated, copies of the federal and military specifications, standards, and handbooks are available form the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government document. The following other Government documents drawing and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF LABOR (DoL)
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The loader shall be gasoline or diesel-engine-driven, pneumatic-tired, four-wheel hydrostatic or mechanical drive, equipped with a hydraulically operated front bucket with the capability of being converted for backhoe, angle push plate dozer, or an angle sweeper operation. Differential skid steering shall be accomplished by either hydrostatic motors, clutches, or brakes.

3.2 Standard commercial product. The loader shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the loader being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.3 First article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to first article inspection (see 4.2.1 and 6.4).

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.5 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.6 Design and construction. The loader shall be designed as a complete self-contained, self-powered, wheeled unit for the specific function of bucket loading and handling small aggregate or sandy materials. Components of the loader shall be of such size, material, and strength that the maximum unit stress imposed through normal operation shall be not greater than 65 percent of the yield strength of the material. The bucket and support arms shall be powered by a centrally controlled hydraulic system.

3.6.1 Bucket construction. The bucket shall be of welded steel construction and designed for heavy duty small aggregate and sandy materials handling. Extra wear-resistant protection shall be provided for the bottom of the bucket. Cutting edge(s) shall be replaceable. The bucket shall have a scooping width greater than the maximum dimensions from outside-to-outside of the carrier tires. The bucket shall be capable of being operated as a scoop or a scraper by means of hydraulic cylinders controlled by the operator.

3.6.1.1 Bucket mounting. The bucket shall be mounted on arms extending beyond the front of the loader. The arms shall be designed with sufficient strength to perform the intended operation without any permanent distortion. The arms shall be pivoted from a location clear of the operator's position, to provide vertical travel without interference with the operator's movement or vision while operating the loader. The height to the bucket hinge pin, with the arms in the fully extended position, shall be not less than 108 inches. The complete cycle of bucket operations shall be controlled by means of double action hydraulic cylinders. Weight of the maximum bucket load shall be counter-balanced by proper proportional weight distribution of the loader over the four wheels or the use of removable counterweights as supplied on the contractor's regular standard commercial units of the same size, and the loader shall remain in a substantially level position under rated capacity bucket operation. The bucket shall be capable of sufficient tilt back at ground level to satisfactorily retain its load. The bucket shall thereafter

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

continue to tilt back as it raises until the cutting edge and spill guard are in a substantially horizontal plane, and shall thereafter remain sufficiently horizontal to retain the load to top of travel. Tilt back of the bucket to maintain the horizontal plane may be accomplished by operating the bucket controls.

3.6.2 Hydraulic system. The hydraulic system shall include a pump, hydraulic cylinders, reservoir, pressure relief valve, and all necessary controls, hoses, piping, filters, and fittings required to perform the intended operations. Hydraulic components shall be equipped with hydraulic circuit filtration conforming to SAE J931. When operating under full load, the temperature of hydraulic oil shall be not greater than 225 degrees Fahrenheit (°F). A hydraulic oil cooler may be installed to assist the cooling, if required.

3.6.3 Controls. All controls, except backhoe controls, shall be mounted in the operator's station. The operator shall be able to completely control all intended bucket and travel operations with clear view without leaving his seat.

3.6.4 Power train. The loader shall be equipped with either a hydrostatic or mechanical four-wheel drive and shall also serve for steering purposes.

3.6.5 Lights. When specified (see 6.2), a complete lighting system, including at least two forward and two rearward directed sealed beam units and taillights, shall be furnished. Independent controls shall be provided for forward and rearward directed lights. Forward directed lights shall provide adequate illumination to flood the work area and to permit safe travel at night. Light fixtures shall be recessed or otherwise adequately protected.

3.6.6 Brake systems. Systems to satisfy emergency service and parking brake requirements shall be provided.

3.6.7 Engine. The loader shall be powered by a gasoline or diesel engine having horsepower, torque, and speed characteristics to meet satisfactorily all vehicular performance requirements specified herein. The engine shall be furnished complete with not less than the following accessories:

a. An instrument panel complete with a lubricating oil pressure indicator or gage, a cooling liquid temperature indicator (when liquid cooled engine is furnished), and an ammeter, voltmeter or charging indicator.
b. A fuel level gage or indicator or dipstick.
c. An hour meter, mounted within the operator's or engine compartment.
d. A fuel tank with sufficient capacity for 4 hours of normal operation.

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T13:27Z
Check the source to verify that this is the currentversion before use.

e. An electric cranking system.
f. Battery charging generator or alternator.
g. An engine speed governor.
h. A dry type air cleaner with condition indicator.
i. For diesel engines, cold weather starting system of either electric glow plug(s), or ether. When an ether starting system is furnished, it shall be of the measured shot type with ether storage capacity of not less than 12 fluid ounces. The cold weather starting system shall permit starting of the diesel engine in temperatures down to -10°F.

3.6.7.1 Instrument and control location. Except for the hour meter, all panel instruments and all controls shall be located so as to be visible and accessible to the operator in his normal position.

3.6.7.2 Engine exhaust. The engine exhaust shall be terminated in a location clear of the operator's station, with means to prevent rain or water spray from entering the exhaust pipe.

3.6.8 Tires, rims, and wheels. Tires, rims, and wheels shall conform to the recommendations of the TRA applicable to the type of operation and load. The tires shall be of the tube or tubeless type.

3.6.9 Pintle assembly. When specified (see 6.2), loader shall be provided with a pintle assembly conforming to MS51335 or similar commercial pintle assembly.

3.6.10 Cab. When specified (see 6.2), the loader shall be provided with a metal operator's cab, equipped with heater, defroster, and windshield wiper. The cab design shall provide for visibility in accordance with 3.7.1.

3.6.11 Attachments. The loader shall be designed for the attachment of an angle push plate dozer, a front mounted backhoe, and an angle sweeper. The attachments shall be operated through the loader hydraulic system as required. Attachments shall be furnished as specified (see 6.2).

3.6.11.1 Backhoe. The backhoe unit shall be designed for front chassis mounting, hydraulically operated and controlled on an operator's forward station. It shall be complete with necessary hydraulic cylinders for swing, lift, digging, and dipper stick operation. Individually controlled hydraulic outriggers, a 24-inch trenching bucket of not less than 2.6 cubic feet heaped capacity, with cutting edge and replaceable teeth; an operator's seat; and operating controls shall be provided. The backhoe unit shall have the following characteristics:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

a. Swing: Not less than 168 degrees.
b. Side reach: Not less than 114 inches.
c. Front reach: Not less than 140 inches.
d. Maximum dump height: Not less than 53 inches.
e. Digging depth: Not less than 94 inches.
f. Transport height: Not more than 105 inches.
g. Ground clearance: Not less than 5 inches.

Provisions shall be made for coupling of the backhoe hydraulic system to the loader system by means of quick-disconnect fittings. Terminal connection fittings shall be protected by captive type dust caps on both systems, or a provision shall be made for reconnecting of hoses. Removable counterweights or ballast containers, when necessary, shall be furnished to replace the backhoe when the backhoe is removed.

3.6.11.2 Angle push plate dozer. Push plate dozer shall be heavy-duty steel blade, with replaceable cutting tip, capable of being angled not less than 15 degrees to the right and left for collecting the surface loose material to be deposited in windrow on the side. Hydraulic control mechanism shall provide the dozer with lowering, raising, floating, holding, and tilting operations. Overall width and height shall be of the manufacturer's standard for the plate dozer, capable of performing satisfactorily under full load without deformation.

3.6.11.3 Sweeper. Sweeper shall be constructed with a rotating brush of wear-resistant polypropylene material capable of being angled not less than 15 degrees to the right and left to sweep not less than 0.50 inch thick loose material from a hard surface, and to deposit the material on the side in one swath. A metal cover shall be provided to reduce the hazard of flying debris and dust. Sweeper shall be not less than 24 inches in diameter and shall be long enough to cover the front width of loader.

3.7 Safety. All rotating or reciprocating parts that are of such nature or so located as to become a hazard to operating personnel shall be properly protected. Platforms and steps shall have antiskid surfaces. Ladders, steps, and handholds shall be provided for easy access to the operator's position. The loader shall comply with OSHA regulations in effect at time of manufacture. The loader shall be provided with not less than the following safety equipment:

a. Horn.
b. Seat belt for operator's seat.
c. Rollover protective structure.

3.7.1 Operator's visibility. The loader shall be so designed that the operator in his normal operating position can observe the bucket in all of its intended operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

3.8 Performance. The loader shall meet the performance requirements as shown in table I. For definition of terms used herein, SAE J732 shall apply.

3.8.1 Operating load. The loader, with the bucket loaded with the operating load specified in table I and conforming to SAE J818, shall meet the following requirements:

a. The bucket shall be capable of being raised and lowered through all operating positions with no excessive spillage.
b. With the loaded bucket in the carry position, the loader shall be capable of transporting the load at the speeds and turning radius specified in table I.

3.8.2 Bucket capacity. The bucket size shall be nominally heaped in accordance with SAE J742 and table I. The loader shall have sufficient power to crowd the bucket into a stockpile with sufficient force to fill the bucket to its rated capacity in one pass and to retain same with the natural fall of the material handled is reduced no more than 10 percent throughout the elevating range of the loader, and while in carry position.

TABLE I. Performance characteristics.

Characteristics	Requirements
Heaped capacity of bucket	Not less than 10 cubic feet
Operating load capacity, full turn (based on 2,700 pounds per cubic yard material)	Not less than 1,000 pounds
Clear turning radius with bucket	Not greater than 78 inches
Forward and reverse speeds under full load	Not less than 4 miles per hour

3.9 Toolbox. A toolbox shall be provided to carry the tools and accessories required to operate the loader. Toolbox shall be constructed of sheet steel, shall have a hinged lid which shall open not less than 90 degrees, and shall be equipped with a latching device of a type that shall keep the lid closed. The toolbox shall be securely fastened to the loader in a protected, but easily accessible location.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

3.10 Identification plate. The contracting officer will furnish to the Government inspector the required identification plates. The contractor will be required to stamp the necessary data in the blank spaces thereon and securely affix said plates in a conspicuous place on each unit, assembly or subassembly, and parts as directed by the Government inspector. Nonferrous screws, rivets, or bolts of not less than 0.125 inch in diameter shall be used to affix the plates. Nomenclature shall be "LOADER, SKID STEER, 4 BY 4, HYDROSTATIC OR MECHANICAL DRIVE, 10 CU FT CAPACITY."

3.11 Instruction plates. The loader shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment. Plates shall be securely affixed to the equipment with nonferrous screws or bolts of not less than 0.125 inch diameter.

3.12 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high-pressure lubricating equipment, 1,000 pound-force per square inch (psi) or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location. The unit shall be lubricated prior to delivery with type of lubricant specified in the operator's manual and grade of lubricant recommended for ambient temperature at the delivery point. The unit shall be conspicuously tagged to identify the lubricants and their temperature range.

3.13 Cleaning, treatment, and painting. Portions of the loader normally painted shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.14 Fungus resistance. When specified (see 6.2), electrical components and circuit elements, including terminal and circuit connections, shall be coated with varnish conforming to MIL-V-173, except that:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

a. Components and elements inherently inert to fungi or in hermetically sealed enclosures need not be coated.
b. Current-carrying contact surfaces, such as relay contact points, shall not be coated.

3.15 System of measurement. The dimensions used in this specification are not intended to preclude the use of the metric system of measurement in the fabrication and production of the material, individual parts, and the finished product, provided form, fit, and function requirements are satisfied.

3.16 Workmanship.

3.16.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.16.2 Bolted connections. Boltholes shall be punched or drilled within manufacturer's design tolerances and shall have the burrs removed. Washers or lockwashers shall be provided and all bolts, nuts, and screws shall be tight.

3.16.3 Riveted connections. Rivet holes shall be punched or drilled within manufacturer's design tolerances and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.16.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.16.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one loader when a first article is required (see 3.3 and 6.2). This inspection shall include the examination of 4.3, the tests of 4.4, and, when specified, the preproduction pack inspection of 4.5 (see 4.5 and 6.2). The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the test of 4.4.8, and the packaging inspection of 4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

4.3 Examination. Each loader shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests. When a first article is required, the first article shall be subjected to the tests specified in 4.4.1 through 4.4.5, and when equipped with attachments, to 4.4.6. Production units shall be tested as specified in 4.4.8. Failure to pass any phase of the tests shall be cause for rejection.

4.4.1 Stockpile loading test. A stockpile of loose soil, equal in volume to 10 times the capacity of the bucket, shall be loaded and transported a distance of not less than 100 feet over uneven terrain. This operation shall not require more than 11 round trips per hour and leave the pickup area relatively clean. This operation shall be repeated for 4 consecutive hours.

4.4.2 Rollback. With the bucket employed as a scoop at ground level and crowded into the stockpile, the bucket shall be capable of being tilted back sufficiently to retain the rated load specified in SAE J732 and J742.

4.4.3 Travel speed and turning radius tests. The loader shall travel over a ground surface for 1 continuous hour using each of the forward and reverse speeds indicated in table I. Random figure-8 turns shall be made using the shortest possible turning radius to determine conformance to table I.

4.4.4 Operating load test. The bucket shall be loaded to the operating load capacity specified in table I and raised and lowered through all operating positions. With the bucket in carry position, the loader shall travel over a level paved surface for 1 continuous hour at low forward and reverse speeds to determine conformance to 3.8.1. The loader shall make right and left turns, minimum radius circles, and figure-8 turns. At no time shall there be excessive spillage.

4.4.5 Tipping load. The loader at standard operating weight, equipped as specified herein, shall be placed in a stationary position on a hard level surface. The bucket shall be tilted back and positioned at the maximum forward position in the raising cycle. The bucket shall be loaded until the rear wheels clear the surface to determine the tipping load. The operating load upper limit shall be calculated to determine conformance to 3.8.1.

4.4.6 Attachments. Attachments, when furnished, shall be assembled, adjusted, and hydraulically operated to determine ease of installation and adequacy of design for the intended service and conformance to the requirements of this specification. Failure to function or any permanent deformation under load shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:27Z
Check the source to verify that this is the current version before use.

4.4.7 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and may be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.4.8 Production unit operation test. Each loader produced in fulfillment of a Government contract shall be completely assembled, adjusted, lubricated, or otherwise serviced for operation. The engine shall be started and subjected to a warmup period as recommended by the manufacturer. The loader shall be given a run-in test and all controls operated a sufficient number of times to ascertain that the components and mechanisms actuated by the controls operated promptly, fully, and without restriction or malfunction. Failure to pass any phase of this test shall be cause for rejection.

4.5 Inspection of packaging. The sampling and inspection of the preservation, packing, and container marking shall be in accordance with the requirements of MIL-T-3351. The inspection shall consist of the quality conformance inspection; and, when specified (see 6.2), a preproduction pack shall be furnished for examination and test within the time frame required (see 6.2).

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-T-3351, Type II (unboxed/mobile) with the level of preservation and the level of packing as specified (see 6.2).

6. NOTES

6.1 Intended use. The loader covered by this specification is a multi-purpose vehicle which, with the various attachments, can be used at construction sites for excavating, loading, and sweeping operations.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When first article and inspection sample is required (see 3.3 and 4.2.1).
c. When lighting system is required (see 3.6.5).
d. When a pintle assembly is required (see 3.6.9).
e. When a cab is required (see 3.6.10).
f. Attachments to be furnished (see 3.6.11).
g. Means for lubrication, if other than as specified (see 3.12).
h. Color of finish coat (see 3.13).
i. When treatment for fungus resistance is required (see 3.14).
j. When a preproduction pack inspection is required (see 4.2.1).
k. Time frame required for preproduction pack inspection (see 4.5).
l. Level of preservation and level of packing required (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of DOD Federal Acquisition Regulations (FAR) Supplement 27.410-6, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DOD FAR 27.410-6 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item(s) should be a first production item, or it may be a standard production item from the contractor's current inventory as specified in 4.1.2. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Subject term (key word) listing.

Skid-steer loader
Hydraulically operated front bucket

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Navy - YD
Air Force - 99

Review Activities:
Air Force - 84
DLA - CS

Preparing activity:
Navy - YD

(Project 3805-0131)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-L-28627C	LOADER, SKID STEER, FOUR-WHEEL HYDROSTATIC OR MECHANICAL DRIVE, 10 CUBIC FOOT HEAPED CAPACITY

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:27Z
Check the source to verify that this is the currenversion before use.