MILITARY SPECIFICATION

TAMPER, VIBRATING TYPE, GED

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a manually controlled, vibrating plate type tamper, powered by a gasoline engine.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-P-664	-	Primer Coating, Synthetic, Rust Inhibiting, Lacquer-Resisting.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-E-10062	-	Engines: Preparation for Shipment and Storage.
MIL-T-22085	-	Tapes, Adhesive, Preservation, and Sealing.
MIL-P-46093	-	Primer Coating, Synthetic (for Brake Drums).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF LABOR (DoL)
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as Department of Defense adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D1557 - Moisture-Density Relations of Soils, Using 10-lb Rammer and 18-in Drop, Tests for.
D2487 - Classification of Soils for Engineering Purposes.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

CONSTRUCTION INDUSTRY MANUFACTURERS ASSOCIATION (CIMA)

Light Equipment Manufacturers Bureau (LEMB)
LEMB Standard No. 2 - Uniform Method for Rating Vibratory Plates, (Hand-Guided, Walk-Behind).

(Application for copies should be addressed to the Construction Industry Manufacturers Association, 111 East Wisconsin Avenue, Milwaukee, WI 53202.).

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The tamper shall consist essentially of a powerplant, power train, vibrating mechanism, base plate, handle, wheels or a transportation cart, and a sprinkler system.

3.1.1 Standard commercial product. The tamper shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the tamper being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

* 3.2 Dimensions and weight. Tamper shall conform to the dimensions and weight specified in table 1. Terms used in table 1 are defined in accordance with LEMB Standard No. 2 (see 6.5).

TABLE 1. Dimensions and weight.

	Minimum	Maximum
Base plate:		
Overall width	19 in	21 in
Overall length	20 in	25 in
Effective area	198 sq in	280 sq in
Operating weight	150 lb	230 lb

3.3 First article. When specified (see 6.2), the contractor shall furnish a tamper for first article inspection and approval (see 4.2.1 and 6.4).

* 3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

* 3.5 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.6 Ease of maintenance. Design of the tamper shall permit ready accessibility to all parts for maintenance and repair in the field by use of conventional general-purpose tools associated with tampers. Replacement and adjustment of component parts and accessories shall be accomplished with minimum disturbance to other elements of the tamper. Accessibility to lubricating oil fill openings, fluid checking devices, and drainplugs shall be provided without the need of removing or adjusting accessories and parts.

3.7 Safety. All rotating or reciprocating parts, and all parts subject to high operational temperatures, that are of such nature or are so located as to be or become a hazard to the operating or attending personnel, shall be substantially guarded or insulated to the extent necessary to eliminate the hazard. The tamper shall comply with applicable DoL, OSHA regulations in effect at time of manufacture.

3.8 Performance. When operating at maximum frequency and as specified herein, the tamper shall withstand the strains imposed upon it without receiving any damage or deformation. Tamper shall be capable of compacting hot and cold mixed asphalt concrete. Not more than three passes (see 6.5), with the tamper shall be required to compact the asphalt concrete. Surface of the compacted asphalt shall be smooth, without any evidence of washboard, rills, dips, depressions, and projections. Tamper shall compact both fine and coarse grained soils as classified in accordance with ASTM D2487. Maximum density, as determined by ASTM D1557, shall be not less than 90 percent for both soils. Not more than six passes with the tamper shall be required to compact the fine grained soil. Tamper shall travel at a maximum forward speed of not less than 50 feet per minute without any assistance from the operator except directional control. The tamper in general, and the engine and vibrating mechanism in particular, shall be designed or protected against the harmful effects of dust, water, and temperature.

3.9 Powerplant. Tamper shall be powered by a four-stroke cycle, air cooled, gasoline engine. The corrected maximum brake horsepower of the engine shall be not less than 4. The engine furnished shall produce the required performance on unleaded or low-lead content gasoline and shall not exceed 0.5 gram per gallon. Unless otherwise specified (see 6.2), regular grade (92 octane class) gasoline shall be used. Engine shall be equipped with a governor, set to limit engine speed to the maximum operating speed recommended by the engine manufacturer, but speed shall not exceed 3,600 revolutions per minute (rpm). The engine shall be furnished complete with the following:

a. A fuel tank with a capacity of not less than 1/2 gallon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

b. A suitable serviceable dry type or oil bath type intake air cleaner.
c. Manual speed control and choke.
d. A recoil starter.
e. Stop control.
f. An exhaust muffler.

3.10 Power train. Power train shall consist of a V-belt and pulley arrangement. The engine's drive shaft shall be furnished with a centrifugal type clutch equipped with heavy-duty ball bearings, and a drive pulley(s). The vibrating mechanism's eccentric rotor shaft shall be fitted with a pulley(s). V-belt(s) shall transfer power from the engine to the vibrating mechanism. A mechanical method shall be provided for adjusting belt tension without removing any components.

3.11 Vibrating mechanism. The vibrating mechanism's eccentric rotor shall rotate at a maximum speed of not less than 5,000 rpm, and shall produce vibrations at a maximum frequency of not less than 5,000 vibrations per minute. Operating at the manufacturer's recommended maximum continuous frequency, the centrifugal force generated by the eccentric rotor shall be not less than 2,000 pounds (lb). The following formula shall be used to compute the minimum centrifugal force:

$$CF = 0.0000284Wrn^2$$

Where W - weight of eccentric revolving body in lb;
r - mean radius in inches;
n - number of rpm.

The contractor shall prepare the above data, verifying the accuracy of the values used and the centrifugal force computed. The eccentric rotor shaft shall be mounted on heavy-duty ball or roller bearings.

3.12 Base plate. Base plate shall be cast nodular iron, cast alloy steel, or fabricated of steel plate having a minimum thickness of not less than 3/16 inch. To withstand the stresses imposed, and to prevent permanent deformation or damage to itself, the plate shall be braced and reinforced wherever necessary. All fabricated sections of the base plate shall be joined by using one of the arc-welding processes. Hereinafter that part of the base plate that is in contact with the material being compacted shall be considered the underside. The underside of the plate shall have a smooth surface. Holes, pits, cavities, mill scale, welding slag, spatter, beads, and any type of depression or projection shall not be permitted on the underside of the base plate.

3.13 Sprinkler system. Tamper shall be equipped with a gravity feed type sprinkler system. The sprinker system system shall wet the full width of the base plate and shall prevent asphalt sticking to the underside of the base plate. The sprinkler system shall include a storage tank, plug valve, feeder hose, and distributor hose or pipe. Storage tank capacity shall be not less than 1 gallon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

3.14 Transportability. Tamper shall be furnished with a maneuvering handle, lifting handles, and two transportation wheels or a two-wheeled transportation cart. The maneuvering handle shall serve as a control handle and as a transportation handle. As a control handle, it shall allow the operator to control travel speed and direction of travel. As a transportation handle, it shall allow the operator to push or pull the tamper, balance it, and control its direction of travel. Not less than two lifting handles shall be provided. When two lifting handles are furnished, they shall be located on the tamper in positions that shall assure the tamper will remain in a relatively horizontal plane while being lifted. Transporation wheels shall be equipped with ball, roller, or sleeve type bearings. Tires shall be pneumatic or semipneumatic. Tire size shall be not less than 3.50 by 10 for pneumatic or 2.75 by 10 for semipneumatic. When a transportation cart is furnished, the frame shall be constructed of tubular steel with members joined by using one of the arc-welding processes.

* 3.15 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. All parts requiring lubrication shall be lubricated as specified in section 5. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.16 Radio noise suppressors. When specified (see 6.2), tamper shall be equipped with radio noise suppressors conforming to SAE J552. Electromagnetic radiation from the tamper shall not exceed the limits recommended by SAE J551.

* 3.17 Plates.

* 3.17.1 Identification plate. An identification plate will be furnished by the contracting officer for each tamper. The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix a plate to each tamper in a conspicuous place with brass screws or bolts not less than 1/8 inch in diameter. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

* 3.17.2 Instruction plates. The tamper shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment, and shall be securely affixed thereto with nonferrous screws or bolts of not less than 1/8-inch diameter.

3.18 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.19 Workmanship.

3.19.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.19.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.19.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.19.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.19.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

* 4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one tamper when a first article is required (see 3.3 and 6.2). This inspection shall include the examination of 4.3 and the tests of 4.4.1 through 4.4.3. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

* 4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4.4, and the packaging inspection of 4.5.

4.3 Examination. Each tamper shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests.

* 4.4.1 Performance test. Before testing, the contractor shall prepare a maintenance schedule. Unless otherwise specified in the maintenance schedule, the tamper shall operate as specified herein without maintenance. Tamper shall be operated continuously at full rated engine speed for a period of 4 hours. At the conclusion of the 4-hour test, the tamper shall be checked for lubrication and any signs of damage or deformation. Oil or grease shall be replaced as required. Tamper shall be operated for an accumulated period of 8 hours over a duration of not more than 2 days. Tests 4.4.2 and 4.4.3 may be performed at the same time. Travel speed shall be checked with a tachometer and the vibration frequency with a vibratory type tachometer. Every 4 hours

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

the tamper shall be examined for excessive wear, overheating, and any signs of damage or deformation. Throughout the test, tamper shall be observed to ascertain compliance with:

a. Safety requirements of 3.7.
b. Ease of maintenance and lubrication requirements of 3.6 and 3.15 respectively.
c. V-belt adjustment requirement of 3.10.
d. Base plate requirements of 3.12.

4.4.2 Compaction test. The tamper shall compact both fine and coarse grained soils. Two test areas shall be prepared, each being not less than 3 feet by 20 feet. A single layer of soil at optimum moisture shall be spread over each test area. Thickness of the fine grained soil shall be not less than 6 inches and not greater than 8 inches. Thickness of the coarse grained soil shall be not less than 8 inches and not greater than 10 inches. Tamper shall make not more than six passes over the fine grained soil and shall be tested to ascertain compliance with the density requirements as specified in 3.8.

4.4.3 Transportability test. The transportation wheels or cart shall be installed on the tamper. Tamper shall be maneuvered over loose ground in such a manner as to simulate transporting on a construction site for not less than 30 minutes. Two men utilizing the lifting handles shall lift the tamper from the ground to a height of not less than 30 inches. Tamper shall be observed to determine conformance to the requirements of 3.8 and 3.14.

4.4.4 Operational test. Each tamper shall be completely assembled, properly adjusted, and serviced for operation. Engine shall be started and subjected to a warmup period as recommended by the manufactuer. Tamper shall be operated for not less than 1 hour. The engine shall be stopped and started as many times as necessary to determine ease of operation, effectiveness, and responsiveness, and that the engine and vibrating mechanism actuated by the speed control and centrifugal clutch operate promptly, without restriction, or malfunction. Travel speed shall be determined to verify conformance to 3.8. Water tank shall be filled with water and the sprinkler system operated to verify compliance with 3.13. Bearings and shafts shall be tactually examined for excessive heating or abnormal operation insofar as is practicable and possible. Failure to meet the requirements of section 3 and any evidence of damage or deformation shall be cause for rejection.

4.5 Packaging inspection. The preservation, packing, and marking of the item shall be inspected to verify conformance to the requirements of section 5.

* 5. PACKAGING

5.1 Preservation. Preservation shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

5.1.1.1 Methods of preservation. Cleaning processes, drying procedures, preservatives, and methods of preservation specified in the following paragraphs are listed in MIL-P-116 and shall conform to the requirements of MIL-P-116 and any applicable specifications.

5.1.1.2 Disassembly. Disassembly shall be the minimum necessary to protect parts subject to damage or loss, and to accomplish reduction in cube. Removed bolts, nuts, pins, screws, and washers shall be reinstalled in mating parts and secured to prevent their loss.

5.1.1.3 Cleaning and drying. Prior to the application of preservative compounds or paint, surfaces shall be cleaned by process C-1 and dried by any applicable procedure of MIL-P-116.

5.1.1.4 Unit protection. The complete tamper shall be preserved method IIa. Openings in the equipment shall not be sealed, so that desiccated air may circulate.

5.1.1.5 Unprotected surfaces. Unprotected exterior metal surfaces requiring the application of a contact preservative in accordance with MIL-P-116 and not specifically provided for herein shall be preserved as follows:

5.1.1.5.1 Unfinished (not machined) surfaces. Unfinished exterior metal surfaces shall be coated with type P-1 preservative.

5.1.1.5.2 Machined surfaces. Exposed machined surfaces shall be coated with type P-6 or P-11 preservative and wrapped or covered, as applicable, with barrier material conforming to MIL-B-121, type I, grade A, class 2. The material shall be secured in place with waterproof tape.

5.1.1.6 Engines. Engines, engine components, and accessories shall be preserved in accordance with the level A requirements of MIL-E-10062, type II, submethod IIa.

5.1.1.7 Clutches. All unpainted surfaces of the clutches shall be coated with a thin film of primer conforming to TT-P-664. The clutches shall be completely disengaged.

5.1.1.8 Drivebelts and pulleys. Drivebelts shall be removed or released from tension. Removed belts shall be preserved method IC-1 or IC-3. Unpainted surfaces shall be coated with primer conforming to TT-P-664 or MIL-P-46093. A weatherproof tag shall be attached in a conspicuous location indicating: "Belts have been (removed or released from tension.) (Install or tension) prior to operation." Markings shall be applied to the tags with a waterproof material.

5.1.1.9 Metallic sprinkler systems. Interior surfaces of metallic sprinkler systems, including tanks, piping, and valves shall be coated with type P-21 preservative. Excess preservative shall be drained and the drains left open.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

5.1.1.10 Lubrication. Lubricate all grease fittings with type P-11 preservative. Wheel bearings should be lubricated with a compound specified by the manufacturer. Lubricate control mechanisms, linkage, hinges, fasteners, and all pivot points with P-10.

5.1.1.11 Technical publications. Technical publications for each piece of equipment shall be preserved method IC-1 or IC-3.

5.1.1.12 Consolidation. Dissasembled items and technical publications for each tamper shall be consolidated in containers conforming to PPP-B-636, class weather-resistant. Contents shall be cushioned, blocked, and braced to prevent movement in accordance with MIL-STD-1186.

5.1.2 Level B. Level of preservation shall be the same as level A with the following exceptions:

5.1.2.1 Unit protection. The complete tamper shall be preserved method I. Openings in the equipment shall be sealed with tape conforming to MIL-T-22085, type II.

5.1.2.2 Engines. Engines, engine components, and accessories shall be preserved in accordance with the level A requirements of MIL-E-10062, type II, method I.

5.1.3 Level C. The equipment shall be preserved in accordance with the contractor's standard practice in a manner to prevent deterioration and damage.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Each complete tamper shall be packed in a close-fitting box conforming to PPP-B-601, overseas type; or PPP-B-621, class 2. The contents shall be blocked, braced, and secured to prevent movement inside the container.

5.2.2 Level B. Each complete tamper shall be packed as specified for level A, except that the boxes shall conform to PPP-B-601, domestic type; or PPP-B-621, class 1.

5.2.3 Level C. The equipment shall be prepared for shipment in a manner which will insure arrival at destination in a satisfactory condition. Preparation for delivery shall comply with applicable carrier rules and regulations.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The tamper is intended for use in compacting fine and coarse grained soil and finishing hot and cold mixed asphalt in areas inaccessible by large self-propelled compacting equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Specifications and standards (see 2.1.1).
c. When a first article tamper is required for inspection and approval (see 3.3, 4.2.1, and 6.4).
d. When regular grade gasoline shall not be used (see 3.9).
e. When lubrication shall be other than the manufacturers standard practice (see 3.15).
f. When radio noise suppressors are required (see 3.16).
g. Color of finish coat shall be as specified (see 3.18).
h. Level of preservation and level of packing required (see 5.1 and 5.2).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 Contract Data Requirements List (CDRL) and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required (see 3.3. and 6.2), the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one complete tamper. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Definitions.

6.5.1 Pass. Manuevering the tamper in one direction, over the material being compacted, is defined as one pass. Maneuvering the tamper over the original path a second time in the same or opposite direction is defined as two passes.

6.5.2 Plate.

6.5.2.1 Width. The plate width is the overall projected dimension, not necessarily in contact with the soil, latitudinal to the control handle.

6.5.2.2 Length. The plate length is the overall projected dimension, not necessarily in contact with the soil, longitudinal to the control handle.

6.5.2.3 Effective area. Effective area is that portion of the plate that is in actual contact with the soil, exclusive of bends and radii.

6.5.3 Operating weight. Operating weight is the total weight of a standard machine serviced and ready for compacting soil. The total weight is determined without optional accessories and with the water tank empty.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Navy - YD

Preparing activity:

Navy - YD

(Project 3895-N217)
Project No. 3895-N217

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer (04M2)
Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-28623B(YD)	TAMPER, VIBRATING TYPE, GED

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:27Z
Check the source to verify that this is the current version before use.