MILITARY SPECIFICATION

# BOOTH, SPRAYING, PAINT, FLOOR TYPE (WITH TOP EXHAUST SYSTEM)

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

## 1. SCOPE

1.1 Scope - This specification covers the requirements for floor type (with top exhaust system) paint spraying booths (herein referenced spray booth).

1.2 Classification - Spray booths shall be of the following types as specified (see 6.2):

Type I - Walk-in, Open front, 6 ft. 8 in. long
Type II - Drive-in, Totally enclosed, 26 ft. 4 in. long
Type III - Drive-in, Totally enclosed, 27 ft. long

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-C-650 Crates, Wood, Open and Covered

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-C-104 | Crates, Wood, Lumber and Plywood Sheathed, Nailed and Bolted |
| MIL-P-116 | Preservation, Methods of |
| MIL-T-704 | Treatment and Painting of Material |
| MIL-D-1000 | Drawings, Engineering, and Associated Lists |
| MIL-C-3774 | Crates, Wood, Open 12,000 and 16,000 Pound Capacity |
| MIL-H-15424 | Hand Tools, Packaging of |
| MIL-F-16082 | Fans, Ventilating, Propeller, Electric Spray Booth Exhaust |
| MIL-E-16298 | Electric Machines Having Rotating Parts and Associated Repair Parts, Packaging of |
| MIL-E-17555 | Electronic and Electrical Equipment, Accessories and Repair Parts, Packaging and Packing of |

STANDARDS

Military

| | |
|---|---|
| MIL-STD-129 | Marking for Shipment and Storage |
| MIL-STD-130 | Identification Marking of U.S. Military Property |
| MIL-STD-143 | Standards and Specifications, Order of Precedence for the Selection of |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

STANDARDS

Military (Continued)

| | |
|---|---|
| MIL-STD-461 | Electromagnetic Interference Characteristics Requirements for Equipment |
| MIL-STD-889 | Dissimilar Metals |
| MIL-STD-1186 | Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, With Appropriate Test Methods |

PUBLICATIONS

National Bureau of Standards

| | |
|---|---|
| Handbook H-28 | Screw-Thread Standards for Federal Services |

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Fire Protection Association (NFPA)

STD. No. 70 - National Electric Code

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, Mass. 02110.)

Occupational Safety and Health Administration (OSHA) Standards

(Application for copies should be addressed to the Occupational Safety and Health Administration (OSHA), Gateway Building, 3535 Market St., Philadelphia, Pa. 19104)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

American Trucking Associations, Inc.

National Motor Freight Classification Rules

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Freight Classification Committee

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Freight Classification Committee, 202 Union Station, 516 W. Jackson Boulevard, Chicago, Illinois 60606.)

## 3. REQUIREMENTS

3.1 First article - The spray booths furnished under this specification shall be a product which has been inspected and passed the first article inspection specified herein (see 4.3).

3.2 Selection of specifications and standards - Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Materials - Materials shall conform to the applicable specifications and shall be as specified herein. Materials which are not covered by applicable specifications shall be of the best quality and entirely suitable for the purpose intended.

3.3.1 Metals - All metal parts shall be of corrosion-resistant material or treated in a manner to render them adequately resistant to corrosion by fuels, oils, salt spray, water, paint, thinners, or atmospheric conditions.

3.3.1.1 Dissimilar metals - Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.2.2 Fungus proof materials - Materials that are nutrients for fungi shall not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

3.4 Design and construction - The spray booths shall be designed and constructed in such a manner as to provide a substantially rigid enclosure with provisions for complete removal of paint vapors, from the spray area, through a top outlet exhaust duct. It shall be a filter-type, floor mounted booth, with adequate safety devices to afford maximum protection to the painters. All design, construction, components and safety devices shall conform to OSHA rules and regulations, paragraph 1910.107, Part II of OSHA Standards.

3.4.1 Safety devices - Safety devices shall be incorporated to adequately protect the painters from all hazards incident to operation. The spray booths shall be equipped with suitable grounding devices for static discharge. Electrical wiring and associated electrical components shall conform to and be installed in accordance with National Fire Protection Association (NFPA) Standard No. 70.

3.4.2 Fastening devices - All screws, pins, bolts, and similar parts shall be installed with means of preventing loss of proper torque. All such parts, when subject to removal or adjustment, shall not be swaged, peened, staked, or otherwise permanently deformed. Screw threads shall be in accordance with applicable requirements of Handbook H-28.

3.5 Maintainability - All working parts and components shall be designed to afford maximum operational performance with minimum maintenance. Adjustment shall be readily accomplished by operating personnel without special training, and without the need of special tools. All parts subject to wear, breakage, or loss of adjustment shall be readily accessible for adjustment, repair or replacement. Filters subject to loss of efficiency shall be easily removed for replacement.

3.6 Performance - The spray booths shall meet the performance requirements specified in Section 4 when subjected to the applicable tests.

3.7 Details of components - The spray booths shall include, but not be limited to, the following components:

| | |
|---|---|
| Cabinet | (3.7.1) |
| Paint filters | (3.7.2) |
| Lighting fixtures | (3.7.3) |
| Filter replacement indicator | (3.7.4) |
| Exhaust fan | (3.7.5) |
| Exhaust duct | (3.7.6) |
| Switches | (3.7.7) |
| Electrical wiring and components | (3.7.8) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

3.7.1 Cabinet - Cabinet panels shall be fabricated from 18 gage (0.0478) sheet steel. Panels and joints shall be reinforced to make the cabinet self-supporting. Panel edges shall be rolled or reinforced, and the corners shall be mitered. All fasteners and fittings necessary for assembly shall be furnished. The cabinet for Type I shall be a floor mounted type with three walls and a top bolted together. The cabinet for Types II and III shall be a floor mounted type with four walls and a top bolted together, a pair of doors for a front entrance, and a single door at the side (rear) for a service entrance. Types II and III shall also be provided with air filtration for removal of dust and dirt from air brought into the closed cabinet. The interior of the assembled booths shall be smooth, all flanges shall be on the exterior of the cabinet. Light windows shall be provided in cabinet wall and ceiling panels to provide sufficient openings for lighting fixtures. An adequate quantity of lighting windows shall be provided to sufficiently illuminate the working area of the cabinet (see 3.7.3). A frame assembly for securing paint filters shall be located within the cabinet before the exhaust fan positioned to provide maximum working area. The frame assembly shall facilitate removal of used paint filters and installation of new paint filters.

3.7.1.1 Front cabinet doors (Types II and III) - The front of the cabinet shall be equipped with one pair of doors hinged at top and bottom. Each door shall be approximately 4'6" wide by 9' high, and equipped with eight air filters. The air filters shall be easily removed for replacement of used filters. Snap-in grid devices with positive locking capability shall be necessary to secure the air filters to the filter cells. The doors' movement when closing shall be restricted, from entering the cabinet, by door stops provided at the top and bottom of the door (opening) entrance in the cabinet. The doors shall also be provided with positive, heavy duty, adjustable, spring loaded latches to prevent the doors from becoming ajar during painting operations.

3.7.1.2 Side cabinet door (Types II and III) - A side cabinet door (service door) shall be provided for personnel access into the cabinet. The service door, approximately 2'6" wide and 6'9" high, shall be positioned on either side of the cabinet at the rear, before the paint filter frame assembly. Door stops shall be provided to prevent the door from entering the cabinet.

3.7.1.3 Front cabinet panels (Types II and III) - Each front cabinet side panel shall be equipped with two replaceable air filters. The air filters shall be secured by snap-in grids (see 3.7.1.1).



Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:38Z
Check the source to verify that this is the currentversion before use.

3.7.1.4 Panel and door air filters (Types II and III) - Individual air filter cells 20" x 20" x 2" thick shall be utilized for door and wall panel air ventilation units. Eight are required for each door unit and two for each front panel unit. Each filter, fabricated of spun glass (or other suitable material), shall provide efficient filtering of dust and dirt, be non-fire supporting, and be secured as indicated in paragraph 3.7.1.1.

3.7.1.5 Cabinet light windows - Window units shall be wire glass, securely held in place and sealed with a suitable gasketing material. Brackets shall be incorporated with the light windows, on the exterior of the cabinet, for attaching light fixtures.

3.7.2 Paint filters - Paint filters, of a suitable material shall be arranged to assure uniform air circulation and filtration in the spray booth. The paint filter shall effectively remove paint from air passing through it, offer low resistance to air flow, be easily removed for replacement, and be UL approved.

3.7.3 Lighting fixtures - The work area of the spray booths shall be illuminated by light fixtures mounted outside of the spray booth. The light fixtures shall be ruggedly constructed, provide high lighting efficiency, and incorporate as applicable requirements specified in the following paragraphs.

3.7.3.1 Lighting fixtures (Type I) - Type I spray booths shall be illuminated by three fluorescent, totally enclosed, explosion proof, vapor-tight units. One top mounted unit shall provide overhead lighting and two side mounted units (one each side) shall provide side lighting. The units shall be for use with three 48" 40-watt fluorescent tube lamps and operated on 110 volt, 60 cycle, single phase alternating current.

3.7.3.2 Lighting fixtures (Types II and III) - Types II and III spray booths shall be illuminated by ten fluorescent, totally enclosed, explosive proof, vapor-tight units. Six top mounted units shall provide overhead lighting and four side mounted units (two each side) shall provide side lighting. Each unit shall be for use with three 48" 40-watt fluorescent tube lamps and operated on 110 volt, 60 cycle, single phase alternating current.

3.7.4 Exhaust filter replacement indicator - For Type I spray booths, a visual detecting device outside the spray booth, which measures the difference in static pressure between the upstream and downstream sides of the paint filters and indicates restriction of air passage through the filters due to excessive paint and dirt accumulation, shall be provided. For Types II and III spray booths, the detecting



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

device shall include both a visual indicator outside the spray booth and a connection to a dirty filter safety shut down system which will automatically turn off the compressed air supply to the spray guns when paint and dirt accumulation in the paint filters reaches a pre-set load point (set-point is to be adjustable for fire and health code requirements and for particular spray paint operations). The devices shall operate on 110 volt, 60 cycle, single phase alternating current.

3.7.5 Exhaust fan - The exhaust fan shall supply maximum free air delivery per horsepower used. Power for the fan shall be supplied by an electric motor (see 3.7.5.3). The fan shall be a single ring mount type, belt-driven, aero type high capacity ventilating unit and incorporate, as applicable, requirements specified in the following paragraphs.

3.7.5.1 Exhaust fan (Type I) - Unless otherwise specified herein, the exhaust fan shall meet the requirements of MIL-F-16082. The fan and pipe size shall be 24 inches in diameter. The fan shall be six bladed and have the capacity of free air delivery of 5,950 cubic fee of air per minute (CFM) at 1,422 revolutions per minute (rpm) motor speed. At a resistance equivalent to 1/4 inch water gage the fan shall have the capability of 4,600 CFM air delivery.

3.7.5.2 Exhaust fan (Types II and III) - Unless otherwise specified herein, the exhaust fan shall meet the requirements of MIL-F-16082. The fan and pipe size shall be 34 inches in diameter. The fan shall be eight bladed and have the capacity of free air delivery of 15, 350 cubic feet of air per minute (CFM) at 1,010 revolutions per minute (rpm) motor speed. At a resistance equivalent to 1/4 inch water gage the fan shall have the capability of 13,500 CFM air delivery.

3.7.5.3 Motor - Unless otherwise specified herein the motor shall be explosion proof and meet the requirements of MIL-F-16082. The motor shall be .5 horsepower (HP) for Type 1, and 2.0 (HP) for Types II and III, of the 440/220 volt as specified (see 6.2), 60-cycle, 3 phase alternating current (ac) type. The motor shall be mounted outside the exhaust duct on a base, and shall be adjustable for belt tension.

3.7.5.4 Motor starter - The motor starter control shall be magnetic with thermal overload protection of the size and capacity suitable for the required service. The motor starter control shall be totally enclosed and explosion proof.

3.7.5.5 Belt and pulley - A "V" belt and pulley shall be encased in a dust-proof, vapor-tight housing meeting the requirements of MIL-F-16082. The belt and pulley shall be adjustable for belt tension and alignment.



Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:38Z
Check the source to verify that this is the current version before use.

3.7.6 Exhaust duct - When specified (see 6.2) exhaust duct shall be furnished in increments of 48 inches long, 24 inch diameter for Type I and 34 inch diameter for Types II and III, plain, straight, 20-gage (0.0392), galvanized metal sections. The sections shall have a lock seam and one end reduced for easy installation. An exhaust duct fan connecting ring shall be furnished. One length of exhaust duct shall include a cleanout door and non-motorized automatic damper.

3.7.7 Switches -

3.7.7.1 Light switch - An on-off completely enclosed explosion-proof motor switch shall be mounted outside the spray booth readily accessible to the painter.

3.7.7.2 Motor switch - An on-off completely enclosed explosion-proof motor switch shall be mounted outside the spray booth readily accessible to the operator.

3.7.8 Electrical wiring and components - All wiring shall be color coded and shall conform to the requirements of NFPA Standard No. 70. Switches for lights and fan motor shall be mounted and pre-wired.

3.8 Part numbering of interchangeable parts - All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The item identification and part number requirements of MIL-D-1000 shall govern the manufacturer's part numbers and changes thereto.

3.9 Dimensions - The dimensions of the spray booths shall be as specified in Table I.

TABLE I. Spray booth dimensions and weight

| Type | Width (inside) | Height (inside) | Depth (working) | Depth (overall) | Weight (lbs) |
|---|---|---|---|---|---|
| I | 5' | 7' | 4' | 6'8" | 1,000 |
| II | 14' | 9'4" | 22' | 26'4" | 6,000 |
| III | 8' | 9'6" | 23' | 27' | 3,500 |



Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

3.10 Weight - The weight of the spray booths (complete with components) shall not exceed that specified in Table I.

3.11 Color and finish - Unless otherwise specified (see 6.2), all metal surfaces of the spray booths which are normally painted shall be treated and painted in accordance with Type A of MIL-T-704.

3.12 Identification of product -

3.12.1 Identification plate - A corrosion-resistant metal nameplate shall be permanently attached to the spray booth. The identification marking shall be in accordance with MIL-STD-130, and contain the following information:

Booth, Spraying, Paint, Floor Type (With Top Exhaust System)

Type (Insert I, II, or III)

Contract or Order Number

Manufacturer's Name or Trademark

U.S.

3.13 Workmanship - Workmanship shall be of the quality necessary to produce complete units of good appearance, with safe and efficient operating characteristics as is customarily found in high grade commercial quality items of a similar nature.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Governement reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections - The inspection of the spray booths shall be classified as follows:

(a) First article inspection (4.3)

(b) Quality conformance inspection (4.4)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

4.3 First article inspection - First article inspection shall consist of all the inspections of the specification.

4.3.1 Sampling for first article inspection - Unless otherwise specified, as soon as practicable after award of a contract or order, the contractor shall furnish one spray booth(s) of the type or types specified on the contract or order (one each if more than one type) for inspection to determine conformance with this specification. The unit submitted by the contractor shall be fabricated from the same type or kind of material, produced by the same methods, and shall be fully representative of the planned production unit in all details and respects. The sample shall be identified with the manufacturer's part number, contract number, Type (I, II, or III) and shall be inspected as specified herein and in accordance with the contract or order (see 6.2).

4.4 Quality conformance inspection - Each spray booth on the contract or order shall be subject to examination (4.6.1). Any spray booth failing to pass the examination shall be rejected.

4.5 Test conditions - Unless otherwise specified, tests shall be conducted at an ambient temperature of 77° ± 18°F and at an ambient barometric pressure of 28 to 32 inches of mercury.

4.6 Inspection methods -

4.6.1 Examination - The spray booths shall be examined for design, dimensions, weight, construction, materials, components, electrical equipment, and workmanship to determine compliance with the requirements of this specification.

4.6.1.1 The spray booths shall be examined to ascertain that the preparation for delivery conforms to this specification.

4.6.2 Operational test - The specified power source shall be supplied to the components of the spray booth. The light switch and motor switch shall be energized (put in the ON position), and the fan and lights operated for 30 minutes. The light fixtures and conduit connections, fan propeller, duct, motor, controls, and accessories shall be inspected. Air movement through the paint filters shall be restricted to cause air delivered for Type I spray booth to drop below 4,600 CFM, and for Types II and III spray booths to drop below 13,500 CFM. As soon as the air delivered drops, the Filter Replacement Indicator shall be checked. When the air delivered drops below the values specified, the indicator shall indicate that filters need replacing. Also, for Types II and III, when the air delivered drops below the values specified, compressed air to the guns shall automatically be shut-off. During the test there shall be no vibration, overheating, loosening of parts, or malfunction.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

4.6.3 Capacity test - The spray booth fan shall be subjected to and pass capacity tests in accordance with MIL-F-16082. The capacity for Type I shall be free air delivery of 5,950 CFM at 1,422 rpm motor speed. The fan shall deliver 4,600 CFM at a resistance equivalent to 1/4 inch water gage. The capacity for Types II and III shall be free air delivery of 15,350 CFM at 1,010 rpm motor speed. The fan shall deliver 13,500 CFM at a resistance equivalent to 1/4 inch water gage.

4.6.4 Electromagnetic interference tests - The spray booths shall be subject to and pass the electromagnetic test specified in MIL-STD-461, Class IIB.

## 5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging - Preservation and packaging shall be level A or level C (see 6.2).

5.1.1 Level A -

5.1.1.1 Disassembly - In order to reduce the size of the shipping container and to provide additional protection, the parts of the spray booth unit which can easily be reassembled shall be dismantled. Mating parts shall be identically marked for identification.

5.1.1.2 Preservation application - All unpainted ferrous critical, operating, or highly finished metal surfaces shall be coated with type P-9 preservative oil in accordance with MIL-P-116. All other unpainted ferrous metal surfaces including threaded areas shall be coated with type P-2 preservative compound in accordance with MIL-P-116.

5.1.1.3 Electrical equipment - Motors, starters, and electrical controls shall be preserved and packaged in accordance with the applicable level A requirements of MIL-E-17555 and MIL-P-16298, as applicable.

5.1.1.4 Lubrication - Grease pressure points shall be lubricated with type P-11 grease in accordance with MIL-P-116.

5.1.1.5 Technical publications - Technical publications shall be preserved by method IC-1, in accordance with MIL-P-116.

5.1.1.6 Repair parts and tools - Repair parts and tools shall be preserved and packaged in accordance with level A requirements of MIL-E-17555, MIL-P-16298, MIL-H-15424, and MIL-P-116 for parts not specifically covered in aforementioned specifications.



Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the currentversion before use.

5.1.2 Level C - The complete equipment shall be preserved and packaged in accordance with the supplier's standard practice.

5.2 Packing - Packing shall be level A, level B, or level C (see 6.2).

5.2.1 Level A - The complete equipment shall be packed in a crate conforming to MIL-C-104, Type I, Class 2, Style A or PPP-C-650, Type 5, Style B, covered. Contents shall be cushioned, anchored, braced, and blocked in accordance with MIL-STD-1186.

5.2.2 Level B - The complete equipment shall be packed in a crate conforming to MIL-C-3774, Type 1 or PPP-C-650, Type 5, Style B, open. Contents shall be shrouded in accordance with the Appendix to the applicable crate specification. The contents shall be blocked and braced to prevent movement and damage during shipment.

5.2.3 Level C - The complete equipment shall be packed in a manner which will insure arrival at destination in satisfactory condition and be acceptable to the carrier at lowest rates. Containers and packing shall comply with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking - In addition to any special marking required by the contract or order, packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use - The spray booths covered by this specification are intended for use in maintenance shops for the purpose of confining, directing, and exhausting dust, fumes, and overspray when spraying items with paints or preservatives. Types II and III also provide a dust and dirt free atmosphere, and a drive-in capability to accommodate small vehicles.

6.2 Information for the contracting officer - Contracts or orders should specify the following:

(a) Title, number, and date of this specification.

(b) Type (see 1.2).

(c) Required wiring for motor and magnetic starter (whether 440 or 220 volts operation) (see 3.7.5.3).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

(d) Required quantity of exhaust duct (see 3.7.6).

(e) Color and finish if other than specified (see 3.12).

(f) Selection of applicable levels of preservation, packaging, and packing required (see 5.1 and 5.2).

(g) Special marking, if required (see 5.3).

(h) Items of data required (see 6.3).

(i) Engineering change procedure in accordance with NAVAIR INST 4275.3A. The Naval Air Systems Command, Department of the Navy, Washington, D.C. 20360 (Attn: AIR-534), will be responsible for review of class I changes under the contract. The Commanding Officer, Naval Air Engineering Center, Lakehurst, N.J. 08733 (Attn: GSED) will be responsible for approval of class II changes.

6.2.1 Contracts or orders should specify the following provisions for first article inspection.

6.2.1.1 Whether first article inspection is required - When a contractor is in continuous production of the spray booths from contract to contract, consideration should be given to waive the first article inspections. If first article inspection is required, indicate:

(a) Where the first article inspection is to be conducted (at the contractor's plant or Government or commerical laboratory).

(b) That the approval of first article samples or the waiving of the first article inspection shall not relieve the contractor of his obligation to fulfill all other requirements of the specification and contract.

6.3 Data - For the information of the Contractors and Contracting Officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in.Section 2 of this specification, or (c) referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List), which shall be attached to and made part of the contract or order. NAVAIR Form 4200/25 (Drawings, Lists, and Specifications Required) shall be attached where applicable.



Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

6.3.1 Installation drawing or instruction - The installation drawing or instruction shall include the following information:

(a) Complete assembly instructions, including wiring schematic and bolt down information.

(b) Minimum size of area for installation and maintenance.

6.3.2 Instruction manual - The instruction manual shall completely describe the operation of the unit and include a description of the operation of each individual system. The instruction manual shall completely describe each maintenance operation.

Preparing activity:
Navy - AS
(Project number 4940-N327)

☆U.S. GOVERNMENT PRINTING OFFICE: 1975-603-131/1454



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-B- 81993 (AS) Booth, Spraying, Paint, Floor Type (with top exhaust system)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO.

DATE

DD FORM 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 20260410-26T04:38Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Lakehurst, NJ 08733

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DOD 316

U.S.MAIL

Engineering Specifications and Standards Department (Code 9312)
Naval Air Engineering Center
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.