MIL-C-82086B
9 September 1980
SUPERSEDING
MIL-C-82086A
14 September 1973

MILITARY SPECIFICATION

COMPRESSOR UNITS: DIESEL-ENGINE-DRIVEN (COMMERCIAL TYPE)

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers commercial, skid-mounted and wheelmounted, diesel-engine-driven, air compressors.

1.2 Classification. The air compressors shall be of the following classes and sizes as specified (see 6.2):

Class A - Skid-mounted.
Class B - Wheel-mounted.

Size 125 - 125 cubic feet per minute (cfm) at 100 pounds per square inch gage (psig).
Size 250 - 250 cfm at 100 psig.
Size 365 - 365 cfm at 100 psig.
Size 600 - 600 cfm at 100 psig.
Size 750 - 750 cfm at 100 psig.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

WW-C-633 - Couplings, Hose, (Half), Pneumatic, Universal Type.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-V-173 - Varnish, Moisture-and-Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment).
MIL-P-514 - Plates, Identification, Instruction and Marking, Blank.
MIL-C-3600 - Compressors, Rotary, Power-Driven; and Compressors, Reciprocating Power-Driven; Air and Gas (Except Oxygen and Refrigerant), Packaging of.
MIL-C-83286 - Coating Urethane, Aliphatic Isocyanate, For Aerospace Applications.

STANDARDS

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MS51336 - Lunette-Coupler, Drawbar, Ring.

(Copies of specifications, standards, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section VIII - Pressure Vessels.
Power Test Code, PTC-9 - Displacement Compressors, Vacuum Pumps and Blowers.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Title 40, CFR, Part 204 Subpart B - Noise Emission Standards for Construction Equipment.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC.

T&RA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Description. The compressor unit shall consist of a diesel engine, air compressor, receiver, air pressure regulating system, lubricating and cooling systems, safety controls, steel housing, and the piping, instruments, gages, and other accessories specified herein all assembled and mounted on either a skid base or a wheel mounted undercarriage.

3.2 First article. When specified (see 6.2), the contractor shall furnish one complete compressor for first article inspection and approval (see 4.2.1 and 6.6).

3.3 Standard commercial product. Each compressor unit of the same classification shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification, but which are a part of the manufacturer's standard commercial product, shall be included in the unit being furnished. Standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

* 3.3.1 Federal Motor Vehicle Safety Standards. When specified (see 6.2), wheeled undercarriages and furnished accessories shall comply with all applicable Federal Motor Vehicle Safety Standards (FMVSS) in effect on the date of manufacture.

* 3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification specifically specified.

* 3.5 Identical items. All compressor units of the same classification, furnished under any specific contract, shall be physically and mechanically identical. This requirement includes parts, assemblies, components, and accessories. No deviations will be acceptable without written approval of the contracting officer.

3.6 Performance. The compressor unit shall be capable of compressing and delivering not less than the nominal volume of free air applicable to the compressor size specified at a receiver pressure of 100 psig under the following atmospheric conditions:

(a) 14.696 pounds per square inch absolute (sea level).
(b) 60° Fahrenheit (F).
(c) Zero humidity.

Under the conditions specified, the air discharge temperature shall not exceed 250°F. The compressor shall be capable of operating satisfactorily when tilted 15° longitudinally or transversely from a level position.

3.6.1 Regulation. Regulation of compressor output shall be accomplished by a stepless, pneumatic control system. The system shall be adjustable within limits established by the manufacturer and shall be set to automatically maintain a nominal discharge pressure of 100 psig when the compressor is operating at full rated capacity. The system shall also provide for automatic regulation of compressor output from zero to 100 percent of rated capacity. Primary regulation shall be effected by the proportional and automatic reduction of engine speed within the range of full-rated-capacity speed to a speed not less than the engine manufacturer's recommended idle speed. Supplemental control may be accomplished by the proportional and automatic actuation of a compressor inlet unloader valve.

3.6.2 Environmental conditions. The compressor shall be capable of starting and operating under the following atmospheric conditions:

(a) Plus 120°F to -25°F at sea level (29.92 inches of mercury).
(b) Plus 102°F to -25°F at an elevation of 5,000 feet (24.89 inches of mercury).

3.6.3 Safety shutdown. The compressor shall be equipped with a safety shutdown system designed to automatically stop the engine under any of the following conditions:

(a) Compressor discharge air temperature in excess of safe limit established by the manufacturer but in no case exceeding 250°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

(b) Engine cooling water temperature in excess of predetermined safe limit.
(c) Engine lubricating oil pressure below minimum predetermined safe limit.

When specified (see 6.2), the engine shall also be equipped with an overspeed trip to automatically stop the engine in the event the engine speed exceeds the lesser of either the maximum speed recommended by the engine manufacturer or the maximum speed recommended for the compressor. The overspeed trip shall operate independently from the regular speed control system and shall require manual reset.

* 3.6.4 Sound level. The exterior sound level produced by the compressor unit shall not exceed the noise limits established by the EPA in effect on the date of manufacture.

3.7 Engine. The compressor unit shall be driven by a liquid- or air-cooled diesel engine of a size and type used or recommended for use by the compressor manufacturer on standard commercial compressor units. The engine, at full-rated compressor output shall have an intermittent horsepower (hp) rating sufficient to properly and adequately operate the compressor and all connected auxiliaries at the speed required to develop rated compressor capacity under the atmospheric conditions specified in 3.6. Instruments and gages specified in 3.7.1 shall be of the type recommended by the manufacturer. All engine accessories supplied commercially as standard equipment shall be furnished. The engine shall be equipped with an electrical starting system rated either at 12 or 24 volts in accordance with the standard voltage for the engine being furnished. The diesel engine shall be capable of starting within 5 minutes and shall be ready for full-load operation within 15 minutes under any of the environmental conditions specified in 3.6.2. The fuel tank shall be sized for continuous operation at rated compressor output of at least 5 hours for sizes 125 and 250 and 8 hours for size 365 and over. The diesel engine shall start in any temperature above -20°F. Starting aids may be either electric glow plug or ether primer. When an ether priming system is required, it shall be the measured shot type, with storage capacity of not less than 12 fluid ounces. An enbloc design engine compressor unit is not excluded from this specification.

3.7.1 Instruments and controls. The following engine instruments and controls, as a minimum, shall be furnished:

(a) Control, starter button.
(b) Control, shutoff.
(c) Control, manual engine warm-up.
(d) Gage, lubricating oil pressure.
(e) Gage, engine water temperature.
(f) Ammeter or battery charging indicator.
(g) Safety controls (see 3.6.3).
(h) Priming aid controls (see 3.8).
(i) Hour meter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

All instruments shall be mounted on a panel or panels located near the operating controls and shall be visible to the operator. The instrument panel(s) shall be furnished with illumination for night operation. The engine hour meter shall have a totalizing mechanism capable of registering not less than 9,999.9 hours of engine operating time.

* 3.8 Storage battery(s). The manufacturer's standard commercial storage battery(s) normally furnished to make a complete electrical system shall be furnished dry charged and moisture sealed. Electrolyte shall not be furnished. When specified (see 6.2), a wet charged battery(s) shall be furnished. The wet charged battery(s) shall be filled with electrolyte and fully charged. Electrolyte shall have a specific gravity of 1.265±0.010 at 80°F.

* 3.9 Air cleaners. Air cleaners shall be of the two-stage dry-type design wherein the first stage provides centrifugal separation and the second stage provides impingement filtration with use of a suitable filter medium. When handling dust concentrations of 0.025 grams per cubic foot, the air cleaners shall be capable of operating not less than 8 hours without exceeding an air restriction which could adversely affect the rated output of the compressor. When located outside the compressor housing, air intake shall be fitted with a rain cap and screen. Connections of components associated with the air cleaner installation shall be water- and gas-tight. The cleaner shall have an indicator that shows when the cartridge is ready for replacement.

* 3.10 Compressor. Unless otherwise specified (see 6.2), the compressor shall be either rotary screw or reciprocating type.

* 3.11 Receiver. The air receiver shall be designed, constructed, and stamped for a pressure of not less than 150 psig, in accordance with the ASME Boiler and Pressure Vessel Code, Section VIII - Pressure Vessels. The receiver shall be equipped with a pressure gage and drain valve and shall be protected against excessive pressure by the manufacturer's standard relief valve. The receiver discharge system shall include a manual blowdown valve and an automatic blowdown valve designed to blow the complete air system down to atmospheric pressure when the engine stops. When a pressure in excess of 10 psig must be maintained in the receiver to insure adequate circulation of compressor oil or elimination of carryover, the air discharge piping shall include a minimum pressure valve or device set to maintain a predetermined minimum back-pressure on the compressor oil system.

* 3.12 Manifold and service outlets. The air receiver discharge line shall be equipped with an air service manifold having individually controlled service outlets with standard universal type pneumatic hose couplings. The air service manifolds of each size of compressor shall be fitted with not less than the number and sizes of outlets specified in table I. All 3/4-inch outlets shall be equipped with the manufacturer's standard lever-type air cocks. When specified (see 6.2), lever-handle, plug-type air cocks and couplings conforming to WW-C-633, type II or III shall be provided. When specified (see 6.2), the compressor unit shall be equipped with a check valve installed in the air line between the receiver and the manifold outlets to prevent reverse flow of air into the receiver during blowdown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

TABLE I. Service outlets.

Compressor size	No. of 3/4" outlets	No. of 1-1/2" outlets w/globe valve
125	2	-
250	4	1
365	4	1
600	4	2
750	4	2

* 3.13 Housing. A suitable housing shall be provided to enclose the engine, compressor, and instrument panel(s). Steel housing and steel panels shall be not less than 0.0598 inch (U. S. revised standard gage No. 16) thick. Supporting members and braces shall be furnished as required. The housing shall be sufficiently rigid to support a 300-pound load applied to any single one-square-foot area on the top of the housing. The housing shall include hinged access openings to the engine, compressor, and instrument panel(s). Access panel(s) shall be equipped with devices to hold the panel(s) in an open position and clamps or latches to retain the panel(s) in the closed position.

3.14 Mounting.

3.14.1 Class A. The compressor shall be mounted on a welded structural steel skid base. The skid base shall include two longitudinal structural steel skids and a base plate or steel cross members to support the compressor. When the compressor is supported on steel cross members, open areas between the skids shall be enclosed by a sheet steel splash pan not less than 0.0598 inch (U. S. revised standard gage No. 16) thick. Both ends of each skid runner shall be shaped to facilitate skidding and shall be provided with holes or attachments for inserting towing slings. The clearance between the ground and the lowest part of the compressor unit shall be not less than 4 inches. The skid-mounted compressor, serviced for operation, shall be capable of being pulled in S curves over dry level ground at speeds up to 5 miles per hour (mph) without damage to or deformation of the skid base or compressor unit.

* 3.14.2 Class B. The complete compressor unit shall be securely mounted on a wheel mounted undercarriage equipped with parking brakes. Size 125 shall be of the two-wheel type with towing tongue, wheeled landing leg, and drawbar lunette-coupler. Sizes 365, 600, and 750 shall be of the four-wheel type with drawbar, drawbar lunette-coupler, and automotive type steering or tandem axle, as specified (see 6.2). Size 250 shall be of the two-wheel or four-wheel type, as specified (see 6.2). Drawbar couplers shall conform to MS51336. All units shall be equipped with springs having components with a rated capacity at least equal to the loads imposed on each member, measured at the ground, with compressor loaded to capacity. When suspension capacity is rated at spring pads, unsprung weight shall be deducted. Two safety chains shall be furnished on each unit. The units shall be designed for towing over graded gravel roads at speeds up to 20 mph. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

trailer loaded to rated gross vehicle weight. Tires shall not drag on fenders when making turns. Unless a particular type and size is specified in the contract (see 6.2), tires shall be standard passenger car tires having a ply rating and size recommended in the T&RA Yearbook for the gross weight of the unit. The parking brake shall be capable of holding the unit in a stationary position on a 15 percent grade.

3.15 Lubrication. The equipment shall be serviced with grease and oils of types and grades recommended by the manufacturer. Lubrication fittings shall conform to SAE J534 and shall be located in accessible protected positions. A bright red circle shall be painted around each lubricating point. The equipment shall be designed to operate efficiently and satisfactorily when lubricating equipment, 1,000 pounds per square inch and higher, will damage grease seals or other parts, a suitable warning plate shall be affixed to the unit in a conspicuous location. The equipment shall be tagged indicate the temperature range and grades of lubricants used.

* 3.16 Cleaning, treatment, and painting. Unless otherwise specified (see 6.2), surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.16.1 Air Force compressor. When specified for Air Force use (see 6.2), compressors shall be cleaned, treated, and painted in accordance with MIL-C-83286.

3.17 Slinging eyes and tiedown eyes. When specified for class B (see 6.2), the units shall be equipped with slinging eyes, tiedown eyes, or both, as indicated in the contract. The slinging eyes and tiedown eyes shall conform to the requirements of MIL-STD-209 applicable to type III equipment. Unless multipurpose eyes for both slinging and tiedown are furnished, tiedown eyes shall be clearly marked to indicate the attachment is intended only for tie-down to the transportation medium and not for slinging.

* 3.18 Fungus resistance. When specified (see 6.2), electrical connections, including terminal and circuit connections, components, and circuit elements shall be coated with varnish conforming to MIL-V-173 except that:

(a) Components and elements inherently inert to fungi or hermetically sealed need not be treated.
(b) Components and elements whose operation will be adversely affected by the application of varnish shall not be treated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.19 Identification marking. Unless otherwise specified (see 6.2), the compressor units shall be marked for identification in accordance with manufacturer's standard practice. When specified (see 6.2), the marking shall be applied to the units on a plate conforming to MIL-P-514. Plates shall be furnished by the contractor unless procurement documents indicate the plates will be Government-furnished. Contractor-furnished plates shall be an aluminum or copper-base alloy plate conforming to type I, style 1, composition A or C of MIL-P-514. The contractor shall apply the information required to the plates, whether contractor- or Government-furnished, using a method of application specified in MIL-P-514. Plates shall be attached to the equipment by bolts, screws, or rivets in a conspicuous location affording protection against damage or disfigurement during normal use of the equipment.

3.20 Instruction plates. The equipment shall be provided with instruction plates describing special or important procedures for operating and servicing equipment or warnings of hazardous procedures. The plates shall be durable and legible throughout the life of the equipment. The plates shall be conspicuously located. Brass screws, bolts, or rivets not less than 1/8 inch in diameter shall be used to affix the plates to the equipment.

* 3.21 Workmanship.

* 3.21.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

* 3.21.2 Bolted connections. All bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided. All nuts, bolts, and screws shall be tight.

* 3.21.3 Riveted connections. All rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall completely fill the hole. Rivet heads shall be of a uniform shape and shall be concentric with the rivet. Rivet head shall make full contact with the intended surface. The rivets shall be so fabricated as to develop a joint strength not less than the design value.

* 3.21.4 Welding. Surfaces to be welded shall be free from foreign matter which would be injurious to the weld. Welding procedures shall be in accordance with a nationally recognized code. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit imposed stresses without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

* 3.21.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:39Z
Check the source to verify that this is the currentversion before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.2.1).
(b) Quality conformance inspection (see 4.2.2).
(c) Packaging inspection (see 4.5).

4.2.1 First article inspection. First article inspection shall be performed on one complete compressor unit when first article sample is required (see 3.2 and 6.6). This inspection shall include the examination of 4.3 and the tests of 4.4.1, 4.4.2, 4.4.4, and when applicable 4.4.5.

4.2.2. Quality conformance inspection. Each compressor unit furnished under a contract shall be examined in accordance with 4.3 and tested in accordance with 4.4.3.

4.3 Examination. Each compressor shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirement or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection. For the receiver, the compressor manufacturer shall have responsibility for verifying that the receiver has been inspected in accordance with the ASME Code. Official ASME Code symbols will be accepted as evidence of compliance.

4.4 Tests. Prior to the tests specified herein which require the compressor(s) be operated, the unit(s) shall be serviced with oils and greases recommended by the manufacturer for use in the ambient temperature at the test location. Batteries used for test purposes shall be supplied by the manufacturer in lieu of the batteries to be shipped with the unit.

4.4.1 Performance test. The compressor shall be tested to determine capacity and power consumption in accordance with the rules, procedures, and instrumentation specified in the ASME PTC-9. The duration of the test shall be sufficient to record all data required under Report of Test of PTC-9, but in no case shall the test duration be less than one hour. Test results shall be corrected to the atmospheric conditions specified in 3.6. Prior to the actual performance test, preliminary tests shall be run, as required, to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

verify that the compressor and associated system are in suitable condition, that speed controls have been properly adjusted, and that gages and instruments are functioning properly. Following the successful completion of the performance test, the compressor shall be operated for a period of not less than 30 minutes in each of the 4 tilted positions specified in 3.6. Inability of the compressor to meet the performance requirements of this specificaton or to operate satisfactorily in any of the 4 titled positions shall be cause for rejection.

4.4.2 Functional test. The compressor shall be operated continuously for a period of not less than 8 hours during which time a log shall be maintained of the capacity, discharge pressure, operating speed, and temperature of compressed air at the receiver discharge outlet. For a 1-hour period during the test, the air discharge valve shall be alternately opened and closed so as to operate the compressor through the complete loading cycle (from zero to full rated capacity to zero capacity) not less than once every 5 minutes. The compressor shall operate at zero capacity for not more than 1 minute between cycles. Cycling operation shall be observed to determine if, when the air discharge valve is closed, the engine speed reduces from full- rated-capacity speed to a speed within the idling range recommended by the engine manufacturer. Failure of the compressor to meet the performance requirements of 3.6, 3.6.1, and 3.7, or malfunction or failure of any parts, components, or controls shall be cause for rejection.

4.4.3 Operational test. Each compressor, excluding first article samples, shall be tested for a period of not less than 60 minutes to verify satisfactory operation of the compressor and all controls. During the test all necessary adjustments in controls shall be made as required to insure that performance requirements relating to compressor output and regulation and engine speeds will be met.

4.4.4 Mobility test.

4.4.4.1 Class A. The skid-mounted compressor shall be pulled over level dry ground at speeds up to 5 mph in a series of S curves for a linear distance of 300 feet. Evidence of deformation or structural failure shall be cause for rejection of the skid design.

4.4.4.2 Class B. The wheel-mounted compressor shall be towed over graded gravel roads for a distance of not less than 25 miles at speeds up to 20 mph. When graded gravel roads are not readily available for mobility tests, paved highways in a condition similar to gravel roads will be acceptable for test purposes subject to the approval of the contracting officer or his authorized representative. After successful completion of the road test, the compressor shall be towed on off-road cross-country terrain for 10 miles at average speeds of approximately 5 mph. Off-road terrain is defined as open fields, ungraded roadways, and generally uneven terrain normally encountered at construction sites where compressors are used. During the mobility test, the unit shall be checked for steering capability and the parking brake shall be operated to verify that the brake will hold the unit on a 15 percent grade.

* 4.5 Packaging inspection. The preservation, packing, and marking of the compressors shall be inspected to the requirements of section 4 of MIL-C-3600. When specified (see 6.2), a preproduction pack inspection shall be performed in accordance with MIL-C-3600.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation, packing, and marking. The compressors shall be preserved, packed, and marked in accordance with MIL-C-3600. Preservation shall be level A, B, or commercial and packing shall be level A, B, or commercial as specified (see 6.2).

6. NOTES

6.1 Intended use. The air compressors are intended as portable sources of compressed air. Each compressor is a self-contained unit readily movable and suitable for field service at construction sites.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of the specification.
(b) Class and size of unit required (see 1.2).
(c) When a first article is required (see 3.2).
(d) When wheeled undercarriages shall comply with FMVSS (see 3.3.1).
(e) When an engine overspeed device is required (see 3.6.3).
(f) When a wet charged battery shall be furnished (see 3.8).
(g) Type of compressor if different (see 3.10).
(h) When lever-handle, plug-type airlocks and couplings conforming to WW-C-633 are required (see 3.12).
(i) When a check valve in discharge air line is required (see 3.12).
(j) Size and type of tires required for the class B units if particular tires are required; whether size 250, class B units shall be two-wheel or four-wheel; whether sizes 365, 600, and 750 shall be equipped with automotive type steering or tandem-axle (see 3.14.2).
(k) Color required (see 3.16).
(l) If, for Air Force acquisitions, cleaning, treatment, and painting shall conform to MIL-C-83286 (see 3.16.1).
(m) When slinging eyes and tiedown devices are required for class B units (see 3.17).
(n) When fungus treatment is required (see 3.18).
(o) When the marking for identification is different (see 3.19).
(p) When the marking shall conform to MIL-P-514 (see 3.19).
(q) When a preproduction pack inspection is required (see 4.5).
(r) Level of preservation and level of packing required (see 5.1).

* 6.3 Definitive specification part number. The specification part number is a definitive part number which corresponds to the classes and sizes of compressors covered by this specification and defines the requirements of the options presented under this specification. The specification number, and the class and size code number are combined to form the definitive specification part number.

* 6.3.1 Cataloging data. For cataloging purposes, part numbers for the compressors are assigned as follows:

M82086 XX
Specification part number
Class and size code number (see 6.3.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

* 6.3.2 Class and size. The class and size of the compressor are identified by a two-digit number (see table II).

TABLE II. Code number to class and size.

Size	Class A	Class B
125	01	06
250	02	07
365	03	08
600	04	09
750	05	10

6.4 Contract data requirements. When this specification is used in a acquisition which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquistion Regulation (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.5 Standard lubricants. When requested by the manufacturer, the contracting officer should obtain through established channels, a list of standard military lubricants applicable to the equipment covered herein. This information is contained in the Department of Defense Section of the Federal Supply Catalog, 9100-IL.

6.6 First article. When a first article is required, it shall be tested and approved under the approriate provisions of paragraph 7-104.55 of the DAR. The first article should be a first production unit or it may be a standard production unit from the contractor's current inventory as specified in 4.2.1.

* 6.7 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Navy - YD
Air Force - 99

Preparing activity:

Navy - YD

Project No. 4310-0146

Review activity:

Navy - MC
Army - ME

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

4310-0146

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-C-82086B COMPRESSOR UNITS: DIESEL-ENGINE-DRIVEN (COMMERCIAL TYPE)

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

FOLD

Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DoD-316

U.S. MAIL

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE: 1980—603-121/4145 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.