INCH-POUND

MIL-F-71127 (AR)
26 May 1992

MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M775 WITH PYROTECHNIC SIGNATURE CARTRIDGE

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the manufacture of metal parts and pyrotechnic signature cartridges for one type of point detonating practice fuze designated as Fuze, Point Detonating, Practice, M775, for use on Cartridge, 81MM, Practice, Short Range, M880.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of the document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (see 6.5)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12953291 - Fuze, PD, Practice M775
12598354 - Packing and Marking of Box, Fiberboard, Fuze, Practice M751
12598356 - Packing and Marking of Wood Box for Fuze, Practice M751

(Copies of other Government documents, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY OF TESTING AND MATERIAL (ASTM)

ASTM-A370 - Mechanical Testing of Steel Products

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

(Application for copies of ASTM publication should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with the applicable drawings and specifications.

3.2 Fuze assemblies and parts.

3.2.1 Fuze parts & sub-assemblies. The fuze assemblies shall comply with all requirements specified on dwg. 12953291 and associated drawings and with all requirements specified in applicable specifications and standards.

3.2.2 Fuze loading assembly. The fuze loading assembly shall comply with all requirements on dwg. 12944180 and associated drawings and with all requirements specified in the applicable specifications and standards.

3.3 Functioning. Optional fuze settings shall be available for manual adjustment to simulate the M734 Multi-option fuze. However, the practice fuze shall detonate only on impact regardless of the setting.

3.4 Jolt and jumble. The fuze assembly shall be subjected to and must meet the requirements of the Jolt Test specified in MIL-STD-331, Test A1 with the exception that the fuze shall not be disassembled and inspected after the Jolt Test. After completion of the Jolt Test, the same fuze shall be subjected to and must meet the requirements of the Jumble Test specified in MIL-STD-331, test A2.

3.5 Transportation vibration. The fuze assembly shall comply with the requirements of MIL-STD-331, test B1, at ambient temperature only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3.6 Ballistic test. Loaded fuzes from the Transportation Vibration Test, when ballistically fired, shall provide both a visible and audible signature at a minimum range of 1500 meters from the observer. Only a visible or only an audible signature only upon impact is not sufficient to meet this requirement. Visual and audio enhancement equipment shall not be used for this assessment. Visible is defined as flash or smoke or both flash and smoke.

3.7 1.5 Meter drop test. The fuze assembly shall comply with the requirements of MIL-STD-331, test A4, 3.1.1.

3.8 Spring embrittlement. None of the springs used in the fabrication of the fuze shall break when extended to the point of minimum permanent deformation.

3.9 Fuze sleeve and chamber operation. When the fuze functions, the chamber base shall blow-out and the sleeve shall remain intact.

3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive at both the forward and rear section joint and at the rear section joint after it is properly assembled to an M775 fuze body.

3.11 First article. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor are specified in the contract and 4.3 herein. (see 6.2)

3.12 Statistical process control (SPC). This specification requires the use of SPC (see 4.1.3.1).

3.13 Kitting. This specification requires the use of kitting (see 4.1.3.2 and 6.7).

3.14 Fuze sleeve tensile strength. Stock to be used in the manufacture of the fuze sleeves shall be subjected to a tensile strength test and shall provide a minimum yield strength of ninety thousand (90,000) pounds per square inch (psi) at 0.2% offset and 10% minimum elongation.

3.15 Chamber hydrostatic test. After final machining, the chamber shall fail in the grooved base when subjected to a hydrostatic pressure of no greater than 5000 psi or less than 1000 psi.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3.16 Workmanship. All parts and assemblies shall be free from burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, porosity, warpage, burn marks, checks, blisters, excess flash, corrosion products and any other foreign matter. Any cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material. The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. The requirements of MIL-A-48078 form a part of the quality assurance provisions of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.1.3 Special provisions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.1.3.1 Use of SPC. While it is desirable (optional) to use SPC as an inspection procedure on all parts, components, subassemblies, assemblies and complete rounds, it is mandatory that it be used on the following parts as indicated in their individual classification of characteristics paragraphs:

a.	Pin, setback	dwg. 12944164
b.	Slider	dwg. 9343999
c.	Striker	dwg. 9343995

4.1.3.2 Use of kitting. As with SPC, it is desirable (optional) to use kitting on all parts, it is mandatory to use kitting on the following parts to assure that they are not missing (their presence in the fuze is accounted for):

a.	Slider	dwg. 9343999
b.	Spring, slider	dwg. 9343994
c.	Rivet	dwg. MS9403
d.	Pin, setback	dwg. 12944164
e.	Spring, setback pin	dwg. 9342992

4.2 Classification of inspection. The following types of inspections shall be conducted on this item:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following (see Table I for details):

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity(EA)
Body, Fuze	12944162	10
Ogive, Rear Section	12944196	10
Ogive, Simulated M734 Forward Section	9387054	10
Ogive, M775 Final Assembly	12944198	20
Shell, Shotgun, Primed, 20 Gauge	9344010	10
Cartridge, Spotting, 20 Gauge Assembly	12944177	10
Wad	9341592	10
Spring, Setback Pin	9343992	10
Spring, Striker	9343993	10
Spring, Slider	9343994	10
Spring, Ball	9344006	10
Pin, Packing Clip	9344001	10
Clip, Packing	9344004	10
Packing Clip Assembly	9344005	10
Chamber	12944178	10
Pin, Setback	12944164	10
Slider	9343999	10
Striker, Marking	9344007	10
Striker	9343995	10
Rivet	12929047	10
Packing Preformed AMS 3303 O-Ring	12929048	10
Metal Parts Assembly Fuze M775	12944172	20
Loading, Assembly, Fuze M775	12944180	35
Sleeve	12944179	10
Fuze Body Assembly	9387100	20
Fuze, PD, Practice M775	12953291	181

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 2 OF 6	DRAWING NUMBER
	Fuze, Point Detonating, Practice M775		See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Body, fuze (Dwg. 9343991) Examination for defects	10 ea	3.2	4.4.2.1
	Ogive, Rear Section (Dwg. 12944196) Examination for defects	10 ea	3.2	4.4.2.2
	Ogive, Simulated M734 Forward Section (Dwg. 9387054) Examination for defects	10 ea	3.2	4.4.2.3
	Ogive, M775 Final Assembly (Dwg. 12944198) Examination for defects	10 ea	3.2	4.4.2.4
	Ogive component part separation test	10 ea	3.2	4.5.13.1

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Fuze, Point Detonating, Practice M775	2 OF 6	See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Shell, Shotgun, Primed 20 Gauge (Dwg. 9344010)			
	Examination for defects	10 ea	3.2	4.4.2.5
	Wad (Dwg. 9341592)			
	Examination for defects	10 ea	3.2	4.4.2.6
	Cartridge, Spotting 20 Gauge Assembly (Dwg. 12944177)			
	Examination for defects	10 ea	3.2	4.4.2.7

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Fuze, Point Detonating, Practice M775	3 OF 6	See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Spring, Setback Pin			
	(Dwg. 9343992)			
	Examination for defects	10 ea	3.2	4.4.2.8
	Spring embrittlement test	10 ea (a)	3.8	4.5.3
	Spring, Striker			
	(Dwg. 9343993)			
	Examination for defects	10 ea	3.2	4.4.2.9
	Spring embrittlement test	10 ea (a)	3.8	4.5.3
	Spring, Slider			
	(Dwg. 9343994)			
	Examination for defects	10 ea	3.2	4.4.2.10
	Spring embrittlement test	10 ea (a)	3.8	4.5.3

NOTES:

(a) Only 10 springs are required if non-destructive examination if followed by destructive tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I. Fir article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Fuze, Point Detonating, Practice M775	4 OF 6	See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Chamber, Fuze (Dwg. 12944178)			
	Examination for defects	10 ea (a)	3.2	4.4.2.15
	Chamber hydrostatic test	10 ea (a)	3.15	Test/4.5.15
	Pin, Setback (Dwg. 12944164)			
	Examination for defects	10 ea	3.2	4.4.1.16
	Slider (Dwg. 9343999)			
	Examination for defects	10 ea	3.2	4.4.2.17
	Striker (Dwg. 9343995)			
	Examination for defects	10 ea	3.2	4.4.2.18
	Striker Marking (Dwg. 9344007)			
	Examination for defects	10 ea	3.2	4.4.2.19

NOTES:

(a) Only 10 each are required if non-destructive examination is followed by the destructive test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Fuze, Point Detonating, Practice M775	5 OF 6	See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Rivet			
	(Dwg. 12929047)			
	Examination for defects	10 ea	3.2	4.4.2.20
	Packing Preformed AMS 3303 O-ring			
	(Dwg. 12929048)			
	Examination for defects	10 ea	3.2	4.4.2.21
	Sleeve			
	(Dwg. 12944179)			
	Examination for defects	10 ea	3.2	4.4.2.23
	Sleeve strength	(See	3.14	Test/4.5.14
	Metal Parts Assembly, Fuze M775			
	(Dwg. 12944172)			
	Examination for defects	20 ea (a)	3.2	4.4.2.22
	Striker pushout test	20 ea (a)	3.2	Test/4.5.10
	Setback stake pushout test	20 ea (a)	3.2	Test/4.5.11
	Packing clip			
	Assembly retention test	20 ea (a)	3.2	Test/4.5.12

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I. F. t article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 6 OF 6	DRAWING NUMBER
	Fuze, Point Detonating, Practice M775		See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Loading Assy, Fuze M775 (Dwg. 12944180)			
	Examination for defects	10 ea	3.2	4.4.2.25
	Fuze chamber operation test	25 ea	3.9	Test/4.5.16
	Fuze Body Assembly (Dwg. 9387100)			
	Examination for defects	10 ea	3.2	4.4.2.23
	Combined welded and mechanical joint test	10 ea	3.2	Test/4.5.13.2
	Fuze, PD, Practice, M775 (Dwg. 12953291)			
	Examination for defects	10 ea	3.2	4.4.2.25
	Jolt and jumble test	15 ea	3.4	Test/4.5.4
	Transportation vibration test	96 ea	3.5	Test/4.5.6
	1.5 meter drop test	15 ea	3.7	Test/4.5.5
	Ballistic test	80 ea(b,c)	3.6	Test/4.5.7
	Fuze sleeve and chamber operation test	50 ea	3.9	Test/4.5.16

NOTES: (a) Only 20 each are required if non-destructive examination is followed by the destructive test.

(b) These fuzes are to be from the Transportation Vibration Test.

(c) All rounds that are subjected to ballistic firing and did function on impact shall be disassembled and examined to determine if proper fuze-chamber operation occurred. If any functioned fuze is found to have its chamber intact or its sleeve ruptured, it is considered to be defective in operation. One or more defective operating fuzes shall be cause for cartridge lot rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of M775 fuzes shall contain:

a. Primed 20 gauge shells of one lot interfix number from one manufacturer.

b. Springs (for each type independently) of one lot interfix number from one manufacturer.

c. Metal or plastic parts from one interfix number from one manufacturer.

d. No more than thirty thousand or no less than five thousand fuzes per inspection lot.

e. Minimum inspection lot size of all components shall be 5000.

f. Fuze chambers from one lot from one manufacturer.

g. Fuze sleeves from one lot from one manufacturer.

h. Pyrotechnic composition from one lot from one manufacturer.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels cited in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE II. Attributes sampling inspection.

LOT SIZE	INSPECTION LEVELS					
	I	II	III	IV	V	VI
5001 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150001 to 500000	1250	500	200	125	50	13
500001 and over	1250	50	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks indicate one hundred percent inspection. If sample size exceeds size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical provess control, tool control, other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.7). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality conformance provision(s) herein. In case of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

c. For examination under SPC, the following shall be used:

(1) Quality conformance inspection utilizing SPC. The contractor may choose to utilize SPC on any or all parts; however, its use is mandatory on those parts specified in 4.1.3.1. Prior to first article inspections and tests, the contractor shall submit an SPC implementation plan for approval by the Government. The plan shall provide as a minimum, information regarding the following:

(a) Procedures including organizational/personnel responsibilities to be followed to demonstrate that the process is controlled.

(b) Procedures including organizational/personnel responsibilities to be followed after process is in control.

(c) Procedures including organizational/personnel responsibilities to be followed if the process goes out of control and what must be done to demonstrate that the problem has been corrected and the process is back in control.

(2) Acceptance criteria under SPC. Parts that are being manufactured under SPC do not have to undergo acceptance inspection in accordance with a specific sampling plan. Under SPC, acceptance shall be based on the following criteria:

(a) The process is in control (all points on the control chart are within the control limits).

(b) Both C_p and C_{pk} are equal to or greater than 1.33 where:

$C_p = (USL - LSL)/6\bar{R}/d_2$

C_{pk} = The smaller of the two values C_{pu} or C_{pl}

$C_{pu} = (USL - \bar{\bar{X}})/3\bar{R}/d_2)$

$C_{pl} = (\bar{\bar{X}} - LSL)/3\bar{R}/d_2)$

USL = Upper Specification Limit

LSL = Lower Specification Limit

R = Range = $x_{max} - x_{min}$ of the group of n being inspected

$\bar{R}$ = The Average Range of k groups that were inspected $(R_1 = R_2 = \ldots R_k)/k$

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

$\bar{\bar{X}}$ = The Grand Mean of k groups that were inspected = $(X_1 + X_2 = X_k)/k$
Where $n_1 = n_2 \ldots n_k$

X = The individual measurements

$\bar{X}$ = The mean of the individual measurements

d = A common conversion factor which can be found in any statistics test. Common values are shown below on Table I.

TABLE I

Sample Size	Factor
2	1.128
3	1.693
4	2.059
5	2.326
6	2.534

It should be noted that until the SPC acceptance criteria above have been met by the process, acceptance of materiel will be in accordance with 4.4.2.a above. Further, when the process goes out of control (i.e., one or more points are outside of the control limits or 1 or more points are outside of the specification limits), acceptance will go back to the requirements of 4.4.2.a. until the contractor has demonstrated that the process is back in control and the requirements for SPC as stated in this paragraph above have been met. Any point outside of the specification limits is cause for rejection of all material since the last inspection that was found acceptable for that particular examination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Body, Fuze (cont)	2 OF 3	12944162
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major (a)				
117	Length from datum of flange to striker spring counterbore	III	3.2	Gage
118	Length from datum of flange to aft stop counterbore	III	3.2	Gage
119	Depth of setback pin hole	III	3.2	Gage
120	Depth of groove forward of flange	III	3.2	Gage
121	Width of groove forward of flange	III	3.2	Gage
122	Body diameter at leading edge of groove	III	3.2	Gage
123	Major diameter - external thread	III	3.2	Gage
124	Pitch diameter - external thread	III	3.2	Gage
125	Outside diameter of flange	III	3.2	Gage
126	Depth of rear cavity from flange	III	3.2	Gage
127	Inside diameter at forward end of rear cavity	III	3.2	Gage
128	Length of mounting boss	III	3.2	Gage
129	Width between packing clip slots	III	3.2	Gage
130	Lubricant missing or improperly applied	III	3.2	Visual

NOTES:

(continued) Any defects found in any of the 10 each die cavity samples shall be cause for rejection of all bodies produced from that particular die cavity lot. All other features and dimensions shall be examined/inspected per the criteria provided in this classification of characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Body, Fuze (cont)	3 OF 3	12944162
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201	Location of packing clip pin hole	V	3.2	Gage
202	Diameter of packing clip pin hole	V	3.2	Gage
203	Diameter of packing clip pin counterbore	V	3.2	Gage
204	Flange to nose length	V	3.2	Gage
205	External thread length	V	3.2	Gage
206	Exhaust ports not clear of flash	V	3.2	Visual
207	Poor Workmanship	V	3.16	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Ogive, Rear Section	1 OF 1	12944196
			NEXT HIGHER ASSEMBLY: 12944198

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of forward O.D.	(a)	3.2	Gage
102	Forward outside diameter	(a)	3.2	Gage
103	Energy director missing or deformed	(a)	3.2	Visual
Minor				
201	Letters improperly molded and filled	(a)	3.2	Visual
202	Aft outside diameter	(a)	3.2	Gage
203	Wall thickness at base	(a)	3.2	Gage
204	Wall thickness above base	(a)	3.2	Gage
205	Poor workmanship	V	3.16	Visual

NOTES:

(a) 20 samples from each mold cavity shall be examined for this feature or dimension. The sample of 20 shall include the first two parts from the beginning of each production run and the last two parts from the end of each production run. The remaining samples (at least sixteen) shall be randomly selected during the production run. Any defects found in any of the 20 samples from each die cavity shall be cause for rejection of all ogive rear sections produced from that particular die cavity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Ogive, Simulated, M734 Forward Section	1 OF 1	9387054
			NEXT HIGHER ASSEMBLY: 12944198

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	I.D. forward hole	(a)	3.2	Gage
102	I.D. aft counterbore	(a)	3.2	Gage
103	Depth aft counterbore	(a)	3.2	Gage
104	Overall length	(a)	3.2	Gage
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:

(a) 20 samples from each mold cavity shall be examined for this feature or dimension. The sample of 20 shall include the first two parts from the beginning of each production run and the last two parts from the end of the run. The remaining samples of (at least sixteen) shall be randomly selected during the production run. Any defects found in any of the 20 samples from each die cavity shall be cause for rejection of all ogive rear sections produced from that particular die cavity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Ogive, M775 Final Assembly (while assembling and after assembly)	1 OF 1	12944198
			NEXT HIGHER ASSEMBLY: 12953291

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	True position of forward section to aft section	III	3.2	Gage
102	Ogive component part separation test	(a)	3.2	Test/4.5.13.1
Minor				
201	Overall length	V	3.2	Gage
202	Poor workmanship	V	3.16	Visual

NOTES:

(a) One ogive shall be subjected to this test at one half hour intervals during the welding operation. If separation occurs, the one half hour production represented by the sample shall be rejected.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Shell, Shotgun, Primed 20 Gauge	1 OF 1	9344010
			NEXT HIGHER ASSEMBLY: 12944177

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Primer not inserted properly into shell	III	3.2	Visual
102	Check test for deterioration of primer (when applicable)	III	3.2	Test/4.5.2
103	Shell improperly assembled	III	3.2	Visual
104	Improper material	(a)	3.2	
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:
(a) Certification by the contractor is required for compliance of all materials to applicable specifications and for compliance with the above listed inspections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Wad	1 OF 1	9341592
			NEXT HIGHER ASSEMBLY: 9341590

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of wad	III	3.2	Gage
102	Improper material	(a)	3.2	
103	Thickness of wad	III	3.2	Gage
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:

(a) Certification by the contractor is required for compliance of all materials to applicable specifications and for compliance with the above listed inspections.

Source: https://assist.dla.mil -- 25 Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Cartridge, Spotting 20 Gauge Assembly	1 OF 1	12944177
			NEXT HIGHER ASSEMBLY 12944180

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
A	Pyrotechnic composition leaking or outside shell	100%	3.2	Visual
B	Pyrotechnic composition	(a)	3.2	4.5.8
Major				
101	Total length of cartridge, max.	III	3.2	Gage
102	Primer improperly sealed	III	3.2	Visual
103	Outside diameter of cartridge forward of flange, max.	III	3.2	Gage
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:

(a) Three cartridges shall be randomly selected, opened, mixed together, and analyzed for composition.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Spring, Setback Pin	1 OF 1	9343992
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter	III	3.2	Gage
102	Compressed length over max at max load	(a)	3.2	Gage
103	Compressed length under min at min load	(a)	3.2	Gage
104	Free length	III	3.2	Gage
105	Spring embrittlement test	(b)	3.2	Test/4.5.3
Minor				
201	Protective finish missing or incomplete	V	3.2	Visual
202	Poor workmanship	V	3.16	Visual

NOTES:

(a) Compress to height of .40 max. for 24 hours min. prior to checking load requirements.

(b) Ten (10) samples are required for this test. Accept 0/Reject 1.

Source: https://assist.dla.mil - 27 - Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.9	Spring, Striker	SHEET 1 OF 1	9343993
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter	III	3.2	Gage
102	Compressed length over max at max load	III (a)	3.2	Gage
103	Compressed length under min at min load	III (a)	3.2	Gage
104	Free length	III	3.2	Gage
105	Spring embrittlement test	(b)	3.2	Test/4.5.3
Minor				
201	Protective finish missing or incomplete	V	3.2	Visual
202	Poor workmanship	V	3.16	Visual

NOTES:

(a) Compress to height of .40 max. for 24 hours min. prior to checking load requirements.

(b) Ten (10) samples are required for this test. Accept 0/Reject 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Spring, Slider	1 OF 1	9343994
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter	III	3.2	Gage
102	Compressed length over max at max load	III (a)	3.2	Gage
103	Compressed length under min at min load	III (a)	3.2	Gage
104	Free length	III	3.2	Gage
105	Spring embrittlement test	(b)	3.2	Test/4.5.3
Minor				
201	Protective finish missing or incomplete	V	3.2	Visual
202	Poor workmanship	V	3.16	Visual

NOTES:

(a) Compress to height of .27 max. for 24 hrs min. prior to checking load requirements.

(b) Ten (10) samples are required for this test. Accept 0/Reject 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Spring, Ball			9344006
				NEXT HIGHER ASSEMBLY
				12944172
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter	III	3.2	Gage
102	Compressed length over max at max load	III (a)	3.2	Gage
103	Compressed length under min at min load	III (a)	3.2	Gage
104	Free length	III	3.2	Gage
105	Spring embrittlement test	(b)	3.2	Test/4.5.3
Minor				
201	Protective finish missing or incomplete	V	3.2	Visual
202	Poor workmanship	V	3.16	Visual

NOTES:

(a) Compress to height of .25 max. for 24 hours min. prior to checking load requirements.

(b) Ten (10) samples are required for this test. Accept 0/Reject 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.12	Pin, Packing Clip	SHEET 1 OF 1	9344001
			NEXT HIGHER ASSEMBLY: 9344005

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Wire diameter	III	3.2	Gage
102	Point diameter over max.	III	3.2	Gage
Minor				
201	Overall length	V	3.2	Gage
202	Poor workmanship	V	3.16	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.13	Clip, Packing	SHEET 1 OF 1	9344004
			NEXT HIGHER ASSEMBLY 9344005

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width between inside flats at basic length	III	3.2	Gage
102	Thickness of material	III	3.2	Gage
103	Depth of emboss for pin	III	3.2	Gage
104	Width of clip at flats	III	3.2	Gage
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Packing Clip Assembly	1 OF 1	9344005
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of pin to inside radius	III	3.2	Gage
102	Packing clip pull test	III	3.2	Test/4.5.9
Minor				
201	Protective coating missing or incomplete	V	3.2	Visual
202	Poor workmanship	V	3.16	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Chamber, Fuze	1 OF 1	12944178
			NEXT HIGHER ASSEMBLY: 12944180

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
A	Chamber hydrostatic test	10 ea (a)	3.15	Test/4.5.15
Major				
101	Overall length	III	3.2	Gage
102	Inside diameter of cavity	III	3.2	Gage
103	Major diameter of thread	III	3.2	Gage
104	Pitch diameter of thread	III	3.2	Gage
105	Effective thread under min. length	III	3.2	Gage
106	Wall thickness at bottom (in groove)	100%	3.2	Gage
Minor				
201	Chamfer missing from outside diameter at cup opening	V	3.2	Visual
202	Outside diameter	V	3.2	Gage
203	Poor workmanship	V	3.16	Visual

NOTES:

(a) If any unit does not fall within the test pressure tolerance, the chanber lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Pin, Setback	1 OF 1	12944164
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of pin	(a)	3.2	Gage
102	Outside diameter of pin	III	3.2	Gage
103	Straightness of pin	III	3.2	Gage
Minor				
201	Chamfer or radius both ends missing	V	3.2	Visual
202	Poor workmanship	V	3.16	Visual

NOTES:
(a) SPC is required. See 3.12 and 4.4.2.c.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1	DRAWING NUMBER
4.4.2.17	Slider			9343999
				NEXT HIGHER ASSEMBLY
				12944172
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of slider	(a)	3.2	Gage
102	Shank diameter	III	3.2	Gage
103	Head diameter	III	3.2	Gage
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:

(a) SPC is required. See 3.12 and 4.4.2.c.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.18	Striker	1 OF 2	9343995
			NEXT HIGHER ASSEMBLY: 9344007

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
A	Length from aft end to forward surface of aft flange	(a)	3.2	Gage
Major				
101	Aft shank diameter	III	3.2	Gage
102	Length to aft flange rear shoulder	(a)	3.2	Gage
103	Aft flange outside diameter	III	3.2	Gage
104	Length between aft end and stop shoulder	(a)	3.2	Gage
105	Forward flange outside diameter	III	3.2	Gage
106	True position of head outside diameter to aft shank outside diameter	III	3.2	Gage
107	Head outside diameter	III	3.2	Gage
108	True position of aft flange outside diameter to aft shank outside diameter	III	3.2	Gage
109	True position of aft shank diameter to forward flange outside diameter	III	3.2	Gage
110	Diameter of center column	III	3.2	Gage

NOTES:
(a) SPC is required. See 3.12 and 4.4.2.c.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-71127 (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2	DRAWING NUMBER
4.4.2.18	Striker (cont)			9343995
				NEXT HIGHER ASSEMBLY
				9344007
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201	Length from rear face to forward face of forward flange	V	3.2	Gage
202	Length of center column	V	3.2	Gage
203	Overall length	V	3.2	Gage
204	Protective finish missing or incomplete	V	3.2	Visual
205	Poor workmanship	V	3.16	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Striker, Marking	1 OF 1	9344007
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special A	Location of red stripe	100%	3.2	Gage
Major	None defined			
Minor 202	Poor workmanship	V	3.16	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Rivet	1 OF 1	12929047
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of head	III	3.2	Gage
102	Thickness of head	III	3.2	Gage
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Packing Preformed AMS 3303 O-Ring	1 OF 1	12929048
			NEXT HIGHER ASSEMBLY: 12944172

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Improper durometer	III	3.2	Gage
102	Inside diameter	III	3.2	Gage
103	Thickness (excluding parting seam)	III	3.2	Gage
Minor				
201	Parting seam height over max from outside surface	V	3.2	Gage
202	Poor workmanship	V	3.16	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2	DRAWING NUMBER
4.4.2.22	Fuze, Body Sub-Assembly			12944172
				NEXT HIGHER ASSEMBLY
				12944180
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Distance from aft end of striker to forward wall of signature charge cavity	100%	3.2	Gage (a)
2	Test rod passes under the end of striker when inserted into ball hole	100%	3.2	Gage (a)
Special				
A	Test rod passes through setback pin hole stake	100%	3.2	Manual/Gage
B	Test rod passes through ball hole stake	100%	3.2	Manual/Gage
C	Packing clip assembly missing	100%	3.2	Visual
D	Setback stake pushout test	(b)	3.2	Test/4.5.11

NOTES:

(a) Automatic gaging required. The gage must automatically inspect all fuzes and mark each acceptable fuze before that fuze is removed from the gage assembly. Rejected fuzes shall not be marked by the automated gage and shall be removed from the lot and disassembled, destroyed or otherwise controlled to preclude becoming subsequently mixed with acceptable fuzes. See MIL-A-48078 for specific provisions concerning system reliability for critical inspections and critical defect material handling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.22	Fuze, Body Sub-Assembly (cont'd)	2 OF 2	12944172
			NEXT HIGHER ASSEMBLY: 12944180

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major				
101	Improper assembly of components	III	3.2	Visual/Manual
102	Seals missing or not adhering	III	3.2	Visual
103	Packing clip assembly retention test	III	3.2	Test/4.5.12
104	Striker not free to move	100%	3.2	Manual
Minor				
201	Fuze body marking missing or unidentifiable	V	3.2	Visual
202	Poor workmanship	V	3.14	Visual

NOTES:

(b) Of every one thousand fuzes produced, two randomly selected fuzes shall be subjected to this test. If a fuze fails this test, the previous one thousand fuzes since the last test shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.23	Sleeve, Fuze		12944179
			NEXT HIGHER ASSEMBLY
			12944180

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special A	Sleeve strength	See note a	3.14	Test/4.5.14
Major				
101	Outside diameter	III	3.2	Gage
102	Inside diameter	III	3.2	Gage
103	Total length	III	3.2	Gage
104	True position of inside diameter to outside diameter	III	3.2	Gage
Minor				
201	Protective finish missing or incomplete	V	3.2	Visual
202	Poor workmanship	V	3.16	Visual

NOTES:

a. Any test sample that was drawn from a particular length of stock that is not capable of holding the required load shall be deemed a reject. The entire length of stock from which the rejected test sample came shall also be discarded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.24	Loading, Assembly, Fuze M775	SHEET 1 OF 1	12944180
			NEXT HIGHER ASSEMBLY 12953291

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length from aft end of chamber to fuze mounting flange max.	III	3.2	Gage
102	Chamber improperly torqued to fuze	IV	3.2	Gage
103	Length from aft end of mounting flange to forward face of striker	III	3.2	Gage
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-71127 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Fuze, PD, Practice M775	1 OF 1	12953291

NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
A	Red marking is showing on fuze striker	100%	3.2	Visual
B	Automatic gage acceptance stamp missing	100%	3.2	Visual
C	Fuze sleeve and chamber operation test	25 units	3.9	Test/4.5.16
Major				
101	Jolt and jumble test	15 units	3.4	Test/4.5.4
102	Transportation vibration test	96 units (c)	3.5	Test/4.5.6
103	1.5 Meter drop test	15 units	3.7	Test/4.5.5
104	Ballistic test	80 (a) units (b)	3.6	Test/4.5.7
105	Combined welded and mechanical joint test	II	3.2	Test/4.5.13.2
Minor				
201	Ogive does not rotate at max. torque	V	3.2	Gage
202	Embossed letters do not align with notch on fuze body	V	3.2	Visual
203	Poor workmanship	V	3.16	Visual

NOTES:

(a) For the first article and the first production lot, these units are to be from the transportation vibration test. For the remaining fuze lots, the fuzes for ballistic test shall have no transportation vibration conditioning. (b) All rounds that are subjected to ballistic firing and did function on impact, shall be disassembled and examined to determine if proper fuze-chamber operation occurred. If any functioned fuze is found to its chamber intact or its sleeve ruptured it is considered to be defective in operation and shall be cause for fuze lot rejection. (c) This test shall be performed on the first article and on the first production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.3 Testing - See 4.5

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections specified herein is identified in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.4 herein.

4.5 Methods of inspection.

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examinations of inspections and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspection. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.1.2 Determination of safe fuze condition.

4.5.1.2.1 External fuze examination. Before removal of the ogive, the red band on the striker which indicates an armed fuze must not be visible. Similarly, loose powder from the spotting cartridge must not be visible. If either or both of these conditions are found, the fuze shall be considered unsafe to handle.

4.5.1.2.2 Internal fuze examination. After the completion of a test to determine if the fuze is in the safe condition, remove the chamber, the ogive and the four (4) foil seals. Examine for the following:

a. The set back pin must extend over the head of the slider.

b. No ball shall have been released into the firing position under the striker nor shall the striker extent into the spotting cartridge cavity or strike the cartridge itself.

4.5.1.2.3 Damaged fuze. A broken fuze shall be considered safe to dispose of providing that the spotting cartridge is still intact and the striker half of the fuze can no longer come in contact with the spotting cartridge.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.5.2 Check test for deterioration of primers. If the total time between the original acceptance of any primed cartridge lot (20 gage shot gun shell) and the assembly of that lot into fuzes exceeds two years, or, the time between the previous check test of the primed cartridge lot and the assembly of that lot into fuzes exceed two years, the primed cartridge lot shall be subjected to and must satisfactorily pass the functioning and output tests as performed by the original primed cartridge manufacturer. This test shall be performed immediately before the primed cartridges are loaded with the signature mix and subsequently assembled into fuzes. This test shall be performed by the contractor (or a qualified laboratory) on primed cartridges selected by the Government Inspector, without cost to the original primed cartridge manufacturer. The test shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., which occurred while the primed cartridges were under the jurisdiction of either the primed cartridge manufacturer or the fuze prime or subcontractor. This is a destructive test. Primers subjected to this test shall not be returned to the inspection lot.

4.5.3 Spring embrittlement. The spring shall be stretched along its longitudinal axis until the spring no longer returns to its original position. When the spring no longer returns to its original length or profile, it shall be considered permanently deformed. Any spring that breaks prior to this point shall be classed defective. One defective spring shall constitute cause for rejection of that particular spring inspection lot. This is a destructive test. Springs subjected to this test shall not be returned to the inspection lot.

4.5.4 Jolt and jumble. Fifteen loaded fuze assemblies, with the packing clip assembly removed, shall be subjected to the Jolt Test specified in MIL-STD-331, test A1 with the exception that the fuze shall not be disassembled and inspected after the Jolt Test. After completion of the Jolt Test, the same fuze shall be subjected to and withstand the Jumble Test specified in MIL-STD-331, test A2. Any fuze assembly that fails the requirement in 3.4 shall be classed defective. One defective fuze shall constitute cause for rejection of that particular fuze inspection lot. This is a destructive test. Fuzes subjected to this test or their components shall be destroyed following appropriate safety procedures and after a decision on acceptance/rejected of the lot has been made by the government.

4.5.5 1.5 Meter drop test. A random sample of fifteen (15) loaded fuzes shall be selected and subjected to the test as specified in MIL-STD-331, test A4 with the following conditions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

a. The fuze assembly, with packing clip removed, shall be assembled to an M880 81MM practice round (the Government shall supply the M880 practice rounds for the contractor's use) and dropped, at ambient temperature, base down followed by the same fifteen (15) rounds dropped nose down.

b. All fuzes shall be safe to fire after being subjected to this test. Any fuze that is not safe to fire for any reason shall be classed defective. One defective fuze shall constitute rejection of that particular fuze inspection lot. This is a destructive test. Fuzes subjected to this test shall not be returned to the inspection lot.

4.5.6 Transportation vibration test. For first article and for the first production lot, the Government will perform this test at a Government proving ground. Ninety-six (96) loaded fuzes with the packing clip assemblies in place shall be subjected to the Transportation Vibration Test, as specified in MIL-STD-331, Test B1, at ambient temperature. After this test has been performed, sixteen (16) fuzes shall be disassembled and inspected for damage and spotting cartridge leakage. Any fuze that is found to be armed or not safe shall be classed defective. One or more defects shall constitute cause for rejection of that particular fuze inspection lot. The remaining eighty (80) fuzes, from the transportation vibration test, shall be subjected to the Ballistic Test in 4.5.7 herein.

4.5.7 Ballistic test. This test shall be performed by the Government at a Government proving ground in accordance with the applicable USA TECOM Acceptance Test Procedure.

Eighty (80) fuzes from the Transportation Vibration Test shall be subjected to this test for first article and for lot acceptance for the first production lot. For the remaining fuze lots, the fuzes for the ballistic test shall have no transportation vibration conditioning. All fuzes shall be fired from a complete M252 81mm mortar that includes an M3A1 baseplate. The fuze carrier shall be an M880, 81mm practice round. All rounds shall be fired onto a flat, nongrassy earthen surface that is not marshy or frozen. A video camera with a shutter speed of 120 frames per second minimum shall be positioned to cover the round impact area.

Muzzle velocity data is required via radar.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

The following firing schedule shall be used:

a. Forty (40) rounds at charge "0" at a gun elevation of forty-five (45) degrees.

b. Forty (40) rounds at charge "3" at a gun elevation of forty-five (45) degrees.

Twenty fuzed rounds each of the the above phases shall be preconditioned for 24 hours to 0 degrees F prior to firing and the remaining 20 fuzed rounds shall be preconditioned to +110 deg F prior to firing. All rounds shall not be out of the conditioning unit for more than two minutes prior to firing.

The following acceptance/rejection criteria applies:

For the charge "0" and charge "3" firings, two or more duds (total duds for both hot and cold groups combined) constitutes cause for lot rejection. All duds shall be recovered (if possible) for further examination.

A dud is defined as an unobservable signature upon ground impact of the round. Observable is defined as both visual and audible.

4.5.8 Chemical composition. A chemical composition analysis for the ingredients of the SW592 and an analysis for the mixture percent ratio by weight of SW592 to diatomaceous earth shall be performed by the contractor. One copy of each analysis shall be furnished in accordance with 6.6.

4.5.9 Packing clip pin pull test. Each packing clip to be tested shall be restrained in an appropriate fixture. Apply a pulling force of 10±2 pounds 90 degrees to the pin on the weld side of the assembly. If the pin begins to separate from the packing clip or separates completely, the assembly shall be classed defective.

4.5.10 Striker pushout test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply an axial load of 40±5 pounds through the signature cartridge cavity to the base end of the striker. The fuze must be partially/disassembled for this test as the slider must be removed. Any striker that is pushed out or moves if the stake deforms constitutes cause for rejection of this particular first article test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.5.11 Setback pin stake pushout test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply an axial load of 40+5 pounds on the forward edge of the setback pin. The fuze must be partially disassembled for this test as the forward end of the setback pin must be exposed and the packing clop assembly must be removed. Any stake that breaks or deforms shall constitute cause for rejection of the first article sample or rejection of the previous one thousand fuzes prior to this test on a continuous production line operation.

4.5.12 Packing clip assembly retention test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply an axial pull of 2+.5 pounds to the packing clop perpendicular to the fuze assembly in such a manner as to try to pull the packing clip assembly out of the fuze. Any packing clip assembly that pulls out of the fuze fails this test.

4.5.13 Ogive component part separation test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply an axial pulling force of not less than the minimum force required by the drawing to the joint connecting the forward and rear sections of the ogive assembly. The ogive shall not separate at the weld joint when the minimum force is applied for a minimum of two seconds. Any separation of the two component parts or any failure of any section of the weld joint shall be cause for that ogive assembly to be classified defective.

4.5.13.2 Ogive combined welded and mechanical joint test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply an axial pulling force of 50 + 5 pounds on the ogive at both the forward and rear section joint. The ogive shall not separate at the weld joint or at the mechanical joint at the fuze body when the minimum force is applied for a minimum of two seconds. Any ogive that separates or becomes disassembled from the fuze shall be classed defective.

4.5.14. Tensile strength test.

4.5.14.1 Distributor purchase. When the stock is purchased from a distributor, a section of each length of stock to be used in the manufacture of the Fuze Sleeve shall be tensile tested in accordance with ASTM A-370, Supplement I or II (whichever applies to the stock to be used). The tensile tester pull rate shall be .05 inch per minute. Any sample that does not meet the requirement of paragraph 3.14 above shall be classed defective and that length of material from which it came shall not be used for the manufacture of the sleeves.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.5.14.2 Direct steel mill purchase. When the stock is purchased directly from a steel mill, it is required that a certificate of conformance, to include actual test data (in accordance with ASTM A-370, Supplement I or II, whichever applies to the type of stock purchased) indicating that the steel is in accordance with 3.14, be submitted to the Government. Further, two one foot samples from two different lengths of the stock purchased shall be submitted to the Government for physical configuration audit purposes (See 6.6).

4.5.15 Chamber hydrostatic test. After final machining, 10 chambers from each cartridge lot shall be hydrostatically tested using Government approved equipment. In performing this test, the pressure shall be applied at a rate not to exceed 1000 psi per second until the chamber bursts. If the chamber fails at greater than 5000 psi or less than 1000 psi it is considered to be defective. Any defective found by this test shall be cause for chamber lot rejection. All test samples subjected to this test shall not be returned to the lot.

All test data shall be recorded as variables data and send to the Government (See 6.6).

NOTES:

a. When under pressure, the test fixture shall not restrict the chamber in any direction with the exception of the threaded end of the chamber where the hydrostatic tester is to be attached.

b. The hydrostatic test equipment shall be calibrated prior to the start of each day's operation and at intervals of not over 4 hours of continuous operation after a lay-off of three hours or more. If it has been found that the equipment is out of calibration in such a direction that the indicated pressure was actually lower than required, the groups from which the chamber samples came shall be retested. Another sample from each of the affected groups shall be drawn and tested as above.

4.5.16 Fuze sleeve and chamber operation test. Fifty fuzes for first article and 25 fuzes for lot acceptance tests shall be statically functioned with full-up pyrotechnic charges. After functioning, the fuzes shall then be examined for proper operation. Proper operation is defined as the sleeve is intact and the chamber has blown out. Any fuze exhibiting any other mode shall be classed defective. One or more defective fuzes shall be cause for fuze lot rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Unit packing.

5.1.1 Level A. Not applicable.

5.1.2 Level B. Same as Level C.

5.1.3 Level C. Unit packing for fuzes shall be in accordance with requirements of drawing 12598354.

5.2 Packing.

5.2.1 Level A. Not applicable.

5.2.2 Level B. Same as Level C.

5.2.3 Level C. Packing for fuzes shall be in accordance with the requirements of drawing 12598356.

5.3 Marking. Marking of the fiberboard and wood boxes shall comply with drawing 12598354 and drawing 12598356 respectively.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The fuze covered by this specification is intended for use in Cartridge, 81MM, Practice M880.

6.2 Acquisition requirements.

a. See MIL-A-48078.

b. Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (See 2.1).

c. Provisions for submission of first article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

6.3 Consideration of data requirements. The following data requirements should be considered when this specification is applied to the contract:

Reference Paragraph	DID Number	DID Title
4.5.8	DI-NDTI-80809A	Inspection & Test Report
4.5.14	"	"
4.5.15	"	"

The above DIDs were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DIDs are cited in the DD Form 1423.

6.4 Submission of inspection equipment designs for approval. See 6.2 of MIL-A-48078. Submit inspection equipment designs, as required to Commander, AMCCOM, ATTN: SMCAR-QAT-I, Picatinny Arsenal, NJ 07806-5000.

6.5 Drawings. Drawings listed in section 2 of this specification under the headings U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings repared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal or U.S. Army Armament Research and Development Command (ARRADCOM) drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Submission of test data. One copy of proving ground ballistic acceptance test data (i.e, firing record) one copy of the chemical composition analysis, steel mill Certificate of Conformance, and chamber hydrostatic test data shall be forwarded to the following: Commander, U.S. Army Armament Research, Development and Engineering Center (ARDEC), ATTN: SMCAR-QAT-B, SMCAR-FSS-DM and SMCAR-AEF-F, Picatinny Arsenal, NJ 07806-5000.

6.7 Submission of alternative inspection provisions. Proposed alternative inspection provisions should be submitted by the contractor to the procuring contracting officer for evaluation and approval by the technical activity responsible for preparation of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

6.8 Data cards. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167 and DIMISC 80043.

6.9 Kitting. Kitting is defined as an orderly process of maintaining control of components and subassemblies that are to be installed into the final fuze assembly to assure that all required parts have been assembled into the M775 fuze.

6.10 Marshy ground. Marshy ground is defined as an earthen surface that contains standing water or free flowing (fluid) mud or a combination of both.

6.11 Frozen ground. Frozen ground is defined as earthen ground within which water has frozen creating a hard surface.

6.12 Subject term (key word) listing.

Conformance
Dud
Hydrostatic
Inspection
Kitting
Practice
Multioption

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A769)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-F-71127 (AR)	26 MAY 1992

3. DOCUMENT TITLE
FUZE, POINT DETONATING, PRACTICE, M775 WITH PYROTECHNIC SIGNATURE CARTRIDGE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
Paul Tremblay	(1) Commercial 201-724-6671	(2) AUTOVON DSN-880-6671
c. ADDRESS (Include Zip Code) Commander: U.S. Army ARDEC ATTN: SMCAR-BAC-S Picatinny Arsenal, New Jersey 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.