MIL-P-82032A
30 August 1982
SUPERSEDING
MIL-P-82032(DOCKS)
21 December 1964

MILITARY SPECIFICATION

PANTRY UNIT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a compact, self-contained pantry unit consisting essentially of heating, refrigeration, and washing facilities.

* 1.2 Classification. The pantry units shall be of the following types, classes, styles, and sizes, as specified (see 6.2):

Type I - With microwave oven(s).
Type II - Without microwave oven(s).

Class A - With built-in automatic coffee maker.
Class B - Without built-in automatic coffee maker.

Style 1 - Nonrecessed unit (free standing).
Style 2 - Recessed unit.

Size 1 - 20 inches deep, 80 inches high, width as required.
Size 2 - 30 inches deep, 80 inches high, width as required.
Size 3 - 32 inches deep, 80 inches high, width as required.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

S-O-001425 - Ovens, Microwave, Electric.
W-C-596 - Connector, Electrical, Power.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-K-43875 - Kitchen Equipment, Including Unit Assemblies, Repair Parts and Tools, Preparation for Delivery of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)

A40.6 - Backflow Prevention in Plumbing Systems.

(Application for copies should be addresssed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate; Sheet and Strip.
A480 - General Requirements for Flat-Rolled Stainless and Heat-Resisting Steel Plate, Sheet and Strip.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19102.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

MG-1 - Motors and Generators.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037.)

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

No. 70 - National Electrical Code.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

NATIONAL SANITATION FOUNDATION (NSF)

No. 2 - Food Service Equipment.
No. C-2 - Basic Criteria for Special Equipment and/or devices.
No. 4 - Commercial Cooking and Hot Food Storage Equipment.
No. 7 - Food Service Refrigerators and Storage Freezers.
No. 12 - Automatic Ice Making Equipment
Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, P. O. Box 1468, Ann Arbor, MI 48106.)

UNDERWRITERS' LABORATORIES, INC. (UL)

UL 471 - Commercial Refrigerators and Freezers.
UL 1030 - Heating Elements, Sheathed.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

* 3. REQUIREMENTS

3.1 Description. The pantry unit shall be compact, self-contained, and have complete facilities for making, storing, and dispensing ice, and facilities for refrigeration washing and cooking. The unit shall be equipped with ice-making machine, refrigerator, hot plates, sink, work counter, cabinets, microwave oven(s), and coffee maker when required, and all controls and accessories necessary for food preparation, storage, and service. Soap-, towel-, and cup-dispensers, garbage disposal, and a waste container shall be provided.

* 3.2 First action. When specified (see 6.2), the contractor shall furnish a pantry unit of the type, class, style, and size as required for first article inspection and approval (see 4.2.1 and 6.4).

* 3.3 Standards compliance. Pantry units shall meet the requirements of the following sanitary standards:

ANSI A40.6
NSF No. 2, C-2, 4, 7, 12.
UL 471

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

* 3.3.1 Certification. Prior to approval of the first article, if one is submitted, or prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the pantry unit he proposes to supply under this specification meets the requirements of ANSI A40.6, NSF No. 2, C-2, 4, 7, 12, and UL 471.

* 3.3.1.1 ANSI certification. Acceptable evidence of meeting the requirements of ANSI A40.6 shall be a statement from the manufacturer certifying that the pantry unit meets the applicable requirements of ANSI A40.6.

* 3.3.1.2 NSF certification. Acceptable evidence of meeting the requirements of NSF No. 2, C-2, 4, 7, and 12 shall be the NSF Seal on the finished pantry unit and inclusion in the current edition of the NSF Listing of Food Service Equipment.

3.3.1.3 UL certification. Acceptable evidence of meeting applicable requirements of UL 471 shall be the UL label, listing in the UL Electrical Appliance and Utilization Equipment List.

* 3.3.3 Alternate certification. In lieu of the certification specified in 3.3.1, acceptable evidence of meeting the requirements of the standards will be a certified test report from a nationally recognized independent testing laboratory, approved by the contracting officer, or for NSF certification acceptable to the medical department of the service for which the pantry units are being procured attesting that a pantry unit typical in all respects of the units to be supplied under this specification has been examined and tested, and meets all requirements of the appicable standards. When authorized in writing by the contracting officer, such examination and tests for alternate certification may be conducted by the manufacturer at the manufacturer's plant when the cognizant inspection authority has determined that adequate facilities and instrumentation are available for conducting the required tests.

* 3.3.3 Applicability. The pantry unit shall meet the dimensional requirements. Microwave oven operating requirements, coffee maker, freezer, refrigerator, ice maker, and storage compartment capacity requirements surface units heating requirements, and all other requirements of this specification. The supplier shall select the unit to be offered as meeting these requirements from his models which have NSF - approved operating and storage capacities not less than the nominal capacities specified herein. Units which have NSF - approved capacities complying with this specification, but which in other respects do not meet the requirements herein will not be acceptable.

* 3.4 Standard commercial product. The pantry unit shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the unit being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

* 3.5 Interchangeability of items. All pantry units of the same classification furnished under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts. No deviations will be acceptable without prior approval of the contracting officer.

* 3.6 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

* 3.6.1 Steel. Minimum thickness and tolerance of sheet steel shall conform to the requirements of ASTM A480 for the gauge specified. Nominal thickness as stated herein is included for reference.

* 3.6.1.1 Corrosion-resisting steel. Corrosion-resisting steel shall be class 302 or 304 of ASTM A167, annealed or tempered to suit the intended application. The surface finish shall be No. 3 as defined in ASTM A480, except that concealed surfaces may be finished in accordance with the manufacturer's standard practice.

* 3.6.2 Dissimilar metals. In fabricating the pantry unit, the use of dissimilar metal in intimate contact with each other shall be avoided wherever possible to minimize galvanic corrosion. When use of dissimilar metals cannot be avoided, the joints or contact areas shall be protected against galvanic corrosion by plating, coating, gasketing, or other interposing material unless protection is inherently provided by area relationships of the anodic and cathodic materials. Bolts, nuts, pins, screws, and other fastenings shall be of the same material as the metals joined or shall be cathodic to the metals joined.

* 3.7 Design. The pantry unit shall be designed as an integral prefabricated assembly, except as otherwise specified herein. The unit shall be designed to facilitate maintenance, and permit servicing each component from the front, without disassembling the unit. The design of the unit shall be such as to prevent conditions hazardous to personnel or deleterious to equipment. The design shall insure the structural stability, performance, service, and safety requirements specified. Ample protection against electrical shock shall be provided. Circuit panel shall not be located under the sink where leaking water connections can spray water onto the circuit panel. All screw threads shall conform to FED-STD-H28.

* 3.8 Construction. The pantry unit shall be of welded, integral construction, with sheets of corrosion-resisting steel as specified in 3.6.1.1. The unit and component parts thereof shall be constructed in accordance with the NSF No. 2, C-2, 4, 7, and 12, and as specified herein. When a welded steel frame is required, corrosion-resisting steel sheets shall

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the currentversion before use.

cover a corrosion-resisting frame having a minimum thickness of 0.0187 inch. The frame shall be rigidly braced to prevent distortion and buckling, and shall adequately support all components and accessories. The unit shall consist of base, walls, and panels, ice-making machine with storage bin and dispenser, refrigerator, electric range surface units, microwave oven(s), coffee maker, garbage disposal, sink, counter top, control panel, hot and cold water faucet, storage cabinets and drawers, waste container, and lighting facilities. The unit shall be of the classification specified (see 1.2 and 6.2).

* 3.8.1 Base. Unless otherwise specified (see 6.2), the base shall be recessed approximately 3 inches at the front, shall be removable to permit installation of the unit directly on the floor. The base shall be not less than 3 inches high and approximately the width of the unit.

3.8.2 Walls and panels. The walls and panels shall be rigid, and distortion free, and shall adequately support all components and accessories, as required.

* 3.8.3 Ice-making machine. The ice-making machine shall be complete, self-contained, and mounted over the counter at the sink area as an integral part of the pantry unit. The ice-making machine shall include a compressor, motor, condenser, evaporator, receiver, storage bin, dispenser, controls, and all components and accessories necessory for efficient, automatic making, storing, and dispensing uncontaminated ice. Unless otherwise specified (see 6.2), granular ice shall be produced at the rate of not less than 350 pounds (lb) per day at standard rating conditions of 90° Fahrenheit (F) inlet water temperature and discharged into a storage bin having a minimum capacity of 60 lb. The bin shall contain an automatic control to start or stop the ice-making process at predetermined ice levels, and shall be located in an insulated compartment of the pantry unit. All joints and corners shall be welded and ground smooth, have inside seams filled, and corners designed for easy cleaning. A power-driven, manually operated dispenser that accurately controls the amount of ice required shall be conveniently located above the sink to prevent contamination of dispensed ice. The storage bin and dispenser shall be readily removable to permit autoclaving and periodic cleaning without tools. The ice-making machine shall be provided with a safety control to stop the ice-making process. This control would operate to prevent ice accumulation in the ice chute in the event of bin control failure. The water supply inlet shall be conveniently located at a point higher than the outlet, drain, and overflow, and shall contain a check valve or utilize other means to prevent backflow. The refrigeration system shall be charged with the proper amount of freon R-12 refrigerant for operation. A control shall be furnished to automatically stop the ice-making machine on occasions when the water supply is insufficient. Protective devices shall not interfere with operation and maintenance of the ice-making machine. The motor shall be rated and constructed in accordance with the applicable provisions of NEMA MG-1. The compressor machine shall operate on a control 120-volt, single-phase, 60-Hertz (Hz), alternating current (ac) system. Motors shall be provided with overload protection in accordance with NFPA Article 430. When specified (see 6.2), a water-cooled condenser shall be substituted for the air-cooled condenser where ventilation is inadequate. When a water-cooled condenser is required an automatic regulating valve shall be provided to control water flow.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

* 3.8.4 Refrigerator. The refrigerator shall conform to UL 471. The refrigerator shall be complete, self-contained, and mounted as an integral part of the pantry unit. The refrigerator shall have a storage capacity of approximately 6.6 cubic feet (cu ft), shall be self-defrosting, and shall be used for general food-storage. The average refrigerator air temperature shall be 36°F in an ambient temperature of 90°F, and 41°F in an ambient temperature of 110°F. The defrosting operation shall not raise the average air temperature of the food storage compartment more than 10° F. The refrigeration system shall consist of a compressor, motor, condenser, evaporator, tray slide with removable corrosion-resisting steel shelves and two corrosion-resisting steel hinged doors, and all components and accessories necessary for storing food at the required temperature, and for automatic defrosting of the refrigerator unit without food removal. When specified (see 6.2), a frozen food storage compartment of approximately 2.2 cu ft shall be furnished. The refrigeration system shall be charged with the proper amount of Freon R-12 refrigerant for operation. The motor shall be rated and constructed in accordance with the applicable provisions of NEMA MG-1. The compressor shall be of the hermetic type, and meet the performance requirements specified when operated on nominal 120-volt, single phase, 60 cycle, ac system. Where applicable, the condenser shall be of the same cooling type as the condenser in the ice-maker.

* 3.8.5 Electric range surface units. The pantry unit shall have two electric range surface units integral with the counter top. The heating units shall be 7 inches in diameter. Heating elements shall conform to the requirements of UL 1030. Elements shall be tubular construction, and rated at 1500 watts for operation on a nominal 120/208-volt, 60 Hz, single phase, ac system. A refrigerator pan shall be mounted under each heating unit. The unit shall be removable to permit easy access to or removal of, the pan for cleaning. The controls shall be accessible without reaching over burners. The front or rear surface unit shall be furnished with an automatic, continuous temperature control by means of which milk can be warmed without scalding, hot water can be supplied without boiling, and accidental burning or breakage of the heating vessel can be avoided. The front or rear unit shall be controlled by a seven-position rotary switch. A pilot light located in close proximity to the control shall indicate the range unit being heated.

* 3.8.6 Sink. The sink shall be complete with all components and accessories necessary for use. The sink, with coved corners, shall have dimensions approximately 14 inches by 16 inches by 6-1/2 inches; shall be integral with the counter top, and equipped with a combination hot-and-cold-water faucet suitable for connection to a 1/2-inch water supply and a 1-1/2 inch standard pipe size drain for connection to the waste pipe. A gooseneck type faucet with a mixing faucet with either wrist-blade controls or a single control arm shall be furnished as specified (see 6.2). When specified (see 6.2), a built-in instant hot water dispenser and a garbage disposer shall be provided. The waste disposal unit shall be supplied with a built-in reset breaker switch. When a water cooled condenser or waste disposer is required (see 3.8.3 and 3.8.4), the cold water service shall be a minimum of 1/2-inch iron pipe size.

* 3.8.7 Microwave oven(s). Pantry units shall be provided with one or two microwave oven(s) conforming to S-O-001425 or with storage space for future installation of oven(s), as specified (see 6.2). Clear storage dimensions shall be approximately 24 inches wide by 24 inches deep by 16 inches high. The pantry unit shall be prewired for connection of the ovens to electrical

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

supply. Push-button timer shall be furnished with each oven. Ovens shall be mounted above counter with not less than 15-1/2 inches clearance, and shall be removable without special tools to permit servicing. Microwave oven(s) shall be commercial type with not less than 1200 watt microwave power output, operating on 208 volts, 60 Hz, single phase.

* 3.8.8 Coffee maker. A built-in electric automatic drip-filter type coffee maker shall be capable of brewing not less than 60 cups of coffee per hour. A heat-resistant brewing cone to hold disposable filter papers and a heat-resistant glass bowl having a minimum capacity of nine cups shall be furnished. The filter paper shall be capable to hold at least 3-1/2 ounces of coffee. A separate on-off switch to control the coffee maker shall also be supplied.

3.8.9 Counter top. The counter top shall extend the full length of the pantry unit, shall be an integral part of the sink and hot plates, and shall have an inverted "V" front edge to prevent spillage from overflowing.

* 3.8.10 Control panel. The control panel shall include controls and indicator lights for the electric range surface units, lighting switch, and a duplex, 120-volt, 15-ampere, grounded, convenience outlet. The control panel shall be at a suitable viewing angle either directly under the counter or on the splashback of the pantry unit. All controls and outlet shall be above the counter top and accessible without reaching over the sink and burners. Receptacles shall conform to W-C-596.

3.8.11 Waste container. The waste container shall be concealed by a hinged, corrosion-resistant steel door, and shall be conveniently located for removal, emptying, and cleaning. The waste container may be aluminum or corrosion-resisting steel, at the option of the manufacturer. The door shall be provided with a stop, and shall be easily operated.

3.8.12 Storage compartments. The storage compartments shall be as specified in 3.8.12.1 and 3.8.12.2.

3.8.12.1 Storage drawers. Storage drawers shall be provided for storing silver, bread, utensils, and other supplies. Drawers shall be as specified herein and otherwise in accordance with the manufacturer's standard practice. The drawers shall open and close easily and silently, shall close flush and even with the face of the pantry unit, move on nylon roller slides, have coved corners, and be easily removable for cleaning. For normal use, suitable stops shall be provided to prevent complete withdrawal from the unit.

3.8.12.2 Storage cabinets. Unless otherwise specified (see 6.2), two storage cabinets shall be provided with shelves, and with easily and silently operated, hinged doors having suitable stops. One cabinet shall be equipped with three removable quietly operated slide-out shelves to allow easy access to contents. The shelves shall move on slides and shall be easily removable for cleaning. For normal use, sliding shelves shall have suitable stops to prevent complete withdrawal from the cabinet. The other cabinet shall contain two fixed shelves and a door rack for storing supplies.

* 3.8.13 Lighting. The pantry unit shall have adequate fluorescent lighting fixture(s) complete with all components and accessories to provide glare-free illumination. The switch for operating the light(s) shall be located on the control panel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

3.8.14 Electrical wiring and components. All wiring practices, conductors, and component ratings shall conform to the applicable requirements of the NFPA No. 70. The electrical source of supply shall be 120/208 volts, 60 Hz, three phase. Electrical power outlets shall be provided as specified herein (see 3.8.10). A wiring diagram shall be furnished with each pantry unit.

3.9 Dust cap. When specified (see 6.2), a corrosion-resisting steel sloping top shall be provided for use as a dust cap in open installations.

* 3.10 Recessed installations. When a recessed installation of the pantry unit is specified (see 6.2), the front edge shall be flush with the surrounding enclosure. When required, a corrosion-resisting steel trim shall cover all edges of the recessed pantry unit. A corrosion-resisting steel removable grill shall be furnished.

3.11 Accessories. Suitable paper cup-, soap-, and paper towel-dispensers shall be conveniently located on the pantry unit.

3.12 Lubrication. Parts requiring lubrication shall be lubricated with the manufacturer's standard lubricants, prior to shipment.

* 3.13 Fungus resistance. When specified (see 6.2), electrical components and circuit elements, including terminal and circuit connections, shall be coated with varnish conforming to MIL-V-173, except that:

(a) Components and elements inherently inert to fungi or in hermetically sealed enclosures need not be coated.
(b) Current-carrying contact surfaces, such as relay contact points, shall not be coated.

* 3.14 Identification marking. Identification shall be permanently and legibly marked directly on the pantry unit or on a corrosion-resisting metal plate securely attached to the unit at the source of manufacturer. Identification shall include the manufacturer's model and serial number, name and trademark to be readily identifiable to the manufacturer.

* 3.15 Electromagnetic interference suppression. When specified (see 6.2), equipment procured under this specification shall be designed and equipped to meet the electromagnetic interference control requirements and test limits in accordance with MIL-STD-461 for the class of equipment and emission requirements specified.

3.16 Instruction Plates. When special procedures or precautions for operating of servicing the pantry unit must be observed, instruction plates shall be provided for each unit. Plates shall be of the same material as the nameplate used or identification marking and shall be securely attached to the equipment in a suitable location.

* 3.17 Commercial publications. Manufacturer's standard commercial publication shall be furnished (see 6.3).

* 3.18 Spare and maintenance parts. Spare and maintenance parts shall be furnished (see 6.2).

3.19 Workmanship. Workmanship shall be such as to produce pantry units that are in accordance with the requirements of this specification and insure proper functioning of all parts of the unit.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

3.19.1 Steel fabrications. Steel used in fabrication of the pantry units shall be free from kinks and sharp bends. The straightening of material shall be accomplished by methods that will not cause injury to the metal. Shearing and chipping shall be done neatly and accurately. Corners shall be square and true. Flame cutting, with a tip suitable for the thickness of metal, may be substituted for shearing or sawing. Re-entrant cuts shall be made in the best possible manner. All bends of a major character shall be made with controlled means to insure uniformity of size and shape.

3.19.2 Castings. Castings shall have a close-grained structure of uniform quality, free from blow-holes, porosity, hard spots, shrinkage defects, cracks, or other injurious defects. Before inspection, castings shall be smooth and well cleaned by sand blasting, tumbling, pickling, or other approved process, and shall not be repaired, plugged, or welded without authorization by the contracting officer.

3.19.3 Bolted and riveted connections. The holes shall be accurately punched, drilled, rammed, or cast, and adjacent edges shall be free of burrs or fins that may interfere with proper seating of bolt or rivet heads, nuts, or washers. When parts subject to vibration are assembled with bolts, cap screws, or studs, the contractor shall provide lockwashers, castellated nuts with cotter pins, safety wire, or antivibration self-locking nuts drawn to proper tension.

3.19.4 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter.

3.19.5 Machine work. Tolerence and gages of metal fits shall conform to the limitations specified and shall otherwise conform to the standards of good commercial practice. Finished contact and bearing surfaces shall be true and exact.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Standards compliance. The contractor shall make available to the contracting officer or his authorized representative evidence of compliance with the standards cited in 3.3. Certification specified under 3.3.1 will be accepted as evidence of compliance.

* 4.2 Certification of inspection. Inspections shall be classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).
c. Packaging inspection (see 4.7).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

* 4.2.1 First article inspection. First article inspection shall be performed on one pantry unit when a first article sample is required (see 3.2 and 6.2). The first article may be a standard production item from the contractor's current inventory provided the cabinet meets the requirements of this specification and is representative of the design, construction and manufacturing techniques applicable to the remaining pantry units to be furnished under the contract.

* 4.2.2 Quality conformance inspection. Quality conformance inspection shall be performed on the samples selected in accordance with 4.4. This inspection shall include the examination of 4.5 and the test of 4.6.1.

* 4.3 Inspection lot. A lot shall consist of all pantry units of the same type, class, style, and size manufactured under the same condition and offered for delivery at the same time.

* 4.4 Sampling.

* 4.4.1 Sampling for examination. A random sample of pantry units shall be selected from each lot offered to the Government in accordance with the provisions set for in MIL-STD-105. The inspection level shall be II with an Acceptable Quality Level (AQL) of 1.5 for major defects and 4.0 for minor defects expressed in terms of defects per hundred units.

* 4.4.2 Sampling for tests. A random sample of pantry units shall be selected from each lot offered to the Government in accordance with the provisions set forth in MIL-STD-105 at inspection level S-2. The AQL shall be 4.0 of defects per hundred units.

* 4.5 Visual examination. The pantry unit shall be examined visually in accordance with the classification of defects set forth in table I.

TABLE I. Classification of defects.

Categories	Defect
Critical:	
None defined	
Major:	
101	Type, class, style, or size not as specified (see 1.2).
102	Parts, components, and assemblies not identical to permit interchangeability (see 3.5).
103	Material not as specified (see 3.6).
104	Minimum thickness of sheet steel not in conformance with ASTM A480 (see 3.6.1).
105	Corrosion-resisting steel not class 302 or 304 of ASTM A167; surface finish not No. 3 of ASTM A480 (see 3.6.1).
106	Design not as specified (see 3.7).
107	Construction not as specified; not in accordance with NSF No. 2, 4, 7, 12, and C-2; frame not braced, does not support components and accessories; components missing or not as specified; unit not size specified (see 3.8).
108	Base not as specified (see 3.8.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects - Continued.

Categories	Defect
109	Walls and panels not rigid; do not support components and accessories (see 3.8.2).
110	Ice-making machine not complete, self-contained, mounted over the sink; components missing or not operating: ice not produced as required; storage bin not of minimum capacity; automatic control not operating; dispenser not operating as required; water supply not as specified; refrigerating system not as required; motor not as specified, not provided with overload protection (see 3.8.3).
111	Refrigerator not as specified; not conform to UL 471; storage capacity not as required; components missing; frozen food compartment capacity not as specified when provided (see 3.8.4).
112	Electric range surface units not as required; not of specified size, construction, or rating; reflector parts missing; heating unit not removable for cleaning; automatic temperature control for rear unit missing, or not operating: front unit suitable not as required; controls not accessible without reaching over burners; pilot lights missing, or not located as required (see 3.8.5).
113	Sink not complete, not size required; gooseneck type faucet not as specified, and drain not size specified; hot water dispenser, garbage dispenser not provided when required; cold water supply not specified size when water cooled condenser or waste dispenser is required (see 3.8.6).
114	Microwave oven not in conformance with S-O-001425; storage space not of required size for installation of future oven; pantry unit not prewired; push button timer missing or not operating; clearance not as required; ovens not mounted as required, not removable without special tools minimum microwave power output not as specified (see 3.8.7).
115	Coffee maker not as required, does not brew minimum number of cups; brewing cone and bowl not heat resisting, not of required capacity; filter paper not as required; control switch not as required, missing (see 3.8.8).
116	Counter top does not extend full length of unit, not integral part of sink and hot plates, front edge not inverted "V" type to prevent spillage (see 3.8.9).
117	Control panel not as required; controls, indicator lights missing; lighting switch missing; outlet missing, not as required (see 3.8.10).
118	Waste container not as required, not conveniently located; door not provided with stop, not easily operated (see 3.8.11).
119	Storage drawers, cabinets not as required; stops missing, does not prevent drawers from withdrawal, doors opening more than required, and shelves from withdrawal; drawers, shelves not easily cleanable; door rack missing (see 3.8.12.1 and 3.8.12.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects - Continued.

Categories	Defect
120	Lighting fixtures not as specified; components missing, switch not located on control panel (see 3.8.13).
121	Wiring, wiring practices, and com]onent ratings not in conformance with NFPA No. 70; outlets, wiring diagram missing (see 3.8.14).
122	Dust cap missing, when required (see 3.9).
123	Trim not provided as required for recessed installation; grill not provided (see 3.10).
124	Cup-, soap-, and towel-dispensers missing, not located in convenient place (see 3.11).
125	Parts not lubricated (see 3.12).
126	Inadequate fungus treatment of electrical components (see 3.13).
127	Electromagnetic interference suppression not in accordance with MIL-STD-461 for the class and emission requirements specified herein (see 3.15).
128	Instruction plates not as specified or missing (see 3.16).
129	Spare and maintenenace parts not as specified (see 3.18).
130	Workmanship not as specified (see 3.19).
Minors:	
201	Identification marking not as specified (see 3.14).
202	Manufacturer's standard publication missing (see 3.17).

* 4.6 Tests.

* 4.6.1 Operational test. The first article sample and each item selected in 4.4 shall be completely assembled and connected to the applicable water, electric, and drainage service. Each component shall be operated to determine compliance with the requirements of this specification. There shall be no evidence of failure and all controls shall operate in accordance with their design function.

* 4.6.2 Electromagnetic interference (EMI) control test. When EMI control is required (see 3.16), a pantry unit equipped for the reduction of EMI shall be tested by the supplier in accordance with test methods CE03 and RE02 of MIL-STD-462. The supplier shall furnish the contracting officer, for approval, the interference control plan, the EMI test plan, and the test report required in MIL-STD-461. Upon approval of the test report by the contracting officer and provided all other requirements of the specification are met, the test sample shall be used as a model for all other units.

* 4.7 Packaging inspection. The preservation, packing and marking of the pantry units shall be inspected in accordance with MIL-K-43875.

* 5. PACKAGING

* 5.1 Preservation packing and marking. Unless otherwise specified (see 6.2), the pantry unit shall be preserved, packed and marked in accordance with MIL-K-43875. The degree of preservation and packing shall be as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Pantry units covered by this specification are intended for use in hospitals for the preparation, storage, and service of prescribed nourishment and supplementary between-meal diets. The unit includes facilities for making, storing, and dispensing ice, and for preparing hot or cold liquids and foods. The pantry unit may also be used in small dining rooms, canteens, nursing homes, and service clubs.

* 6.2 Ordering data. Purchasers should exercise any desired options offered herein and acquisition documents should specify:

a. Title, number, and date of this specification.
b. Type, class, style, and size pantry unit required (see 1.2 and 3.8).
c. When specifications and standards shall be other than as specified (see 2.1.1).
d. When a first article is required for inspection and approval (see 3.2, 4.2.1 and 6.4).
e. Construction of the base, if other than specified (see 3.8.1).
f. Whether ice shall be other than granular, rate produced per day, and bin storage capacity, if different (see 3.8.3).
g. When water-cooled condenser is required for ice-maker and refrigerator (see 3.8.3 and 3.8.4).
h. When frozen food storage is required (see 3.8.4).
i. Type of faucet and control; when hot water dispenser and garbage dispenser are required (see 3.8.6).
j. When microwave oven(s) or storage space is required (see 3.8.7).
k. Provision for storage cabinets, if other than specified (see 3.8.12.2).
l. When a dust cap is required (see 3.9).
m. When the pantry unit shall be recessed (see 3.10).
n. When fungus resistance treatment is required (see 3.13).
o. When electromagentic interference suppression is required (see 3.15).
p. Equipment class per MIL-STD-461 (see 3.15).
q. Spare and maintenance parts required (see 3.18).
r. If preservation, packing, and marking is other than specified (see 5.1).
s. Degree of preservation and packing required (see 5.1).

* 6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item consisting of one complete pantry unit or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of (one), (two), etc unit(s). The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Source: https://assist.dla.mil Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Navy - YD

Project No. 7310-N521

Review activities:

Army - MD
Navy - MS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. 7310-N521

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-82032A - PANTRY UNIT

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

★ U.S. Government Printing Office: 1976—703-178/3081 2-1

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:38Z
Check the source to verify that this is the currentversion before use.

FOLD

DEPARTMENT OF THE NAVY

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.