MIL-R-82047B
22 October 1987
SUPERSEDING
MIL-R-82047A
5 November 1968

MILITARY SPECIFICATION

REFRIGERATORS, MECHANICAL, STORAGE STAND (FOR BULK MILK DISPENSERS)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers refrigerated storage stands designed to store filled bulk milk containers and to serve as a counter-height stand for supporting a bulk milk dispenser.

1.2 Classification. The refrigerated storage stands shall be of the following sizes and styles, as specified (see 6.2.1):

Size 2-5 - Storage capacity for two 5-gallon (18.9 liters [L]) milk cans.
Size 3-5 - Storage capacity for three 5-gallon (18.9 L) milk cans.

Style A - Leg-mounted.
Style B - Caster-mounted.
Style C - Mounted for shipboard use.

1.2.1 Definitive specification part number. The specification part number is a definitive part number which will be formulated to identify each item covered by this specification. The part number will be formulated by selecting from the requirement options available in this specification as follows:

Definitive specification part number	M82047	X	X
Military specification number			
Size designator (see 1.2.1.1)			
Style designator (see 1.2.1.2)			

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

1.2.1.1 Size designator. A one position field used to designate size. (A-storage capacity for two 5-gallon milk cans, B-storage capacity for three 5-gallon milk cans).

1.2.1.2 Style designator. A one position field used to designate style. (1-leg mounted, 2-caster mounted, 3-mounted for shipboard use).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

OO-D-450 - Dispensers, Bulk Milk, Mechanically Cooled (and Containers, Milk).

MILITARY

MIL-R-12323 - Refrigerators and Related Equipment, Packaging and Packing of.
MIL-C-22785 - Can, Beverage, Dispenser.

STANDARD

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of specifications, standards, handbooks, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

AIR CONDITIONING AND REFRIGERATION INSTITUTE (ARI)

ARI 520 - Standard for Positive Displacement Refrigerant Compressor and Condensing Units.

(Application for copies should be addressed to Air-Conditioning and Refrigeration Institute, 1501 Wilson Boulevard, Arlington, VA 22209.)

AMERICAN SOCIETY OF HEATING, REFRIGERATING, AND AIR-CONDITIONING ENGINEERS (ASHRAE)

ASHRAE Handbook, 1985 Fundamentals

(Application for copies should be addressed to American Society of Heating, Refrigerating, and Air-Conditioning, 1791 Tullie Circle, NE, Atlanta, GA 30329.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.
A176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

No. 7 - Food Service Refrigerators and Food Service Storage Freezers. Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Road, P. O. Box 1468, Ann Arbor, MI 48106.)

UNDERWRITERS LABORATORIES INC. (UL)

UL 471 - Commercial Refrigerators and Freezers.
UL Electrical Appliance and Utilization Equipment Directory.

(Application for copies should be addressed to the Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The refrigerated storage stands shall consist essentially of an insulated storage compartment having a front-mounted, insulated door and a top designed specifically to support a fully-loaded bulk milk dispenser conforming to either type I or type II of OO-D-450. The size 2-5 stand shall support a size 2-5 dispenser; the size 3-5 stand shall support a size 3-5 dispenser. The stand shall include a complete refrigeration system with automatic controls necessary to maintain the operating temperatures specified herein.

3.2 First article. When specified (see 6.2.1), the contractor shall furnish one storage stand of the classification required for first article inspection and approval (see 4.2.1 and 6.4).

3.3 Standard commercial product. The storage stand shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the storage stand being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.4 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.5 Codes and standards. The storage stand shall conform to the requirements of UL 471 and NSF No. 7, as applicable.

3.6 Compliance. Prior to approval of the first article, if one is specified, or prior to approval of the first shipment, the contractor shall make available satisfactory evidence to the contracting officer, or his authorized representative, satisfactory evidence that the storage stand he proposes to furnish under this specification meets the requirements of the standards in paragraph 3.5, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

3.6.1 Applicability. Details for equipment construction, design, and performance covered by this specification shall be supplementary to the requirements of the standards cited in 3.5 and compliance with and approval under the UL or NSF standard shall not relieve the supplier of the responsibility for meeting the requirements of this specification.

3.6.2 UL certification. Acceptable evidence of meeting the requirements of UL 471 shall be the UL certification symbol or label, listing in the model number in the UL Electrical Appliance and Utilization Equipment Directory, or a certified test report (see 6.2.1), from a recognized independent testing laboratory indicating the storage stand has been tested and conforms to NSF No. 7. Such evidence must be acceptable to the contracting officer.

3.6.3 NSF certification. Acceptable evidence of meeting the requirements of this NSF No. 7 shall be the NSF certification symbol or label, listing in the current edition of the NSF seal on the refrigerated storage stand, or a certified test report (see 6.2.1), from a recognized independent testing laboratory indicating the storage stand has been tested and conforms to NSF No. 7. Such evidence must be acceptable to the contracting officer.

3.7 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.7.1 Corrosion-resistant steel. Corrosion-resistant (stainless) steel specified herein for the construction of the exterior shell and inner liner shall be any class 302 or 304 of ASTM A167 or class 430 of ASTM A176.

3.7.2 Insulation. Insulation shall be in accordance with NSF No. 7. Insulation shall be of a material and so installed that compaction, settlement, or separation of the insulation will not occur under normal conditions of shipment and operation. Insulation shall be closed and sealed to afford protection against condensation, spillage, and seepage. Insulation shall be vapor-proofed to prevent undue migration of moisture vapor. The thickness of insulation shall be sufficient to insure compliance with all performance requirements of 3.9.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the currentversion before use.

3.7.3 Refrigerant. The refrigerant shall be dichlorodiflouromethane (12) or chlorodiflouromethane (22). The refrigerants shall conform to applicable standards of the American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. (ASHRAE).

3.8 Design. The storage stands shall be designed and constructed to rigidly support on the top a fully-loaded bulk milk dispenser of the applicable type and size specified in 3.1 and to simultaneously support in the storage compartment a full complement of bulk milk containers. The dimensions of the units shall be as specified in table I. The design of the stands shall be predicated on the size, weight, and loading impact of filled, 5-gallon (18.9 L), dispenser-type milk cans conforming to MIL-C-22785. The stands shall also be suitable for use with the plastic, single-service and multiple-service bulk milk container specified in OO-D-450.

TABLE I. Dimensions (inches).

Refrigerator size	Acceptable range of exterior dimensions			Minimum interior dimensions		
	Height	Width	Depth	Height	Width	Depth
2-5	34-36 86.36- 914.44mm	27-30 685.8-762mm	24-25 609.6- 635 mm	22 558.8mm	22 558.2mm	11 279.4mm
3-5	34-36 863.6- 914.4mm	38-40 965.2- 1016mm	24-25 609.6- 635mm	22 558.8mm	32 558.8mm	11 279.4mm

3.9 Performance. The refrigerated stands shall meet the following performance requirements:

a. In an ambient test temperature of 100 degrees Fahrenheit (°F) [37.8 Celsius (C)], the refrigeration system shall be capable of lowering the temperature of the empty storage compartment from 100°F (37.8°C) to a stabilized temperature of 40°F ± 2°F (4.44° ±.94°C) in not more than 60 minutes.
b. The unit, when loaded to capacity with filled bulk milk containers, shall, after stabilization, be capable of maintaining the compartment temperature at 40°F ± 2°F (4.44° ±.94°C) in an ambient test temperature of 100°F (37.8°C) or any constant or fluctuating temperature between 50°F (10°C) and 100°F (37.8°C).
c. When the compartment temperature has been stabilized at 40°F ± 2°F (4.44° ±.94°C), the maximum operating time in an ambient test temperature of 100°F (37.8°C) under no load conditions shall be 75 percent of any consecutive 3-hour period of operation.

3.10 Construction. The storage compartment shall consist of an outer shell, inner liner, framing, door, hardware, and a leg- or caster-mounting. The outer shell and inner liner shall enclose insulation meeting the requirements of 3.7.2.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:38Z
Check the source to verify that this is the current version before use.

3.10.1 Outer shell. The outer shell for the storage compartment shall be fabricated or formed of corrosion-resistant steel of the same thickness as used on the models approved under the standards cited in 3.6. Removable panels or covers shall be provided as required to provide ready access for servicing of the refrigeration system.

3.10.2 Inner liner. The walls and top of the inner liner shall be fabricated or formed of corrosion-resistant steel of a thickness not less than 24 gage. The liner bottom shall be corrosion-resistant steel with a thickness of not less than 18 gage. The liner bottom shall be formed and braced to support a full complement of fully-loaded bulk milk cans and to withstand without permanent deflection or distortion the impact normally associated with the loading operation. The liner button shall be connected to the liner walls so that no liquid can leak into the insulation. This connection shall be able to withstand the impact of the loading operation.

3.10.3 Framing. Framing shall be required to support the dispenser and the fully-loaded storage compartment, and to house the components of the refrigeration system. The framing shall consist of structural steel shapes or plates with a thickness not less than 12 gage. The steel framing shall be plated or treated and painted to resist corrosion in accordance with the manufacturer's standard practice.

3.10.4 Door. The door shall consist of an inner and outer liner of the material and thickness specified for the cabinet liner and shell. Insulation shall be as specified in 3.7.2. The door shall be fitted with an NSF-approved gasket. Door framing shall include suitable plastic or synthetic rubber breaker strips to minimize conduction between the cabinet liner and shell. The door shall be hinged on the right unless left side hinges are specified (see 6.2.1). A thermometer conforming to NSF No. 7 shall be mounted on the door.

3.10.5 Hardware. The door latch, striker plate, hinges, and other miscellaneous hardware shall be fabricated of corrosion-resistant steel or of chromium-plated ferrous or nonferrous metal. Except for copper alloys, chromium plating shall be applied over a base coating of copper followed by a nickel coating.

3.10.6 Mounting. The stands shall be mounted on legs or on casters in accordance with the style specified. Two of the four casters on the style B units shall be equipped with foot-operated locking brakes. Legs, feet, and casters shall conform to the applicable requirements of NSF Standard No. 7. For shipboard use, legs shall be contracted of corrosion-resisting steel and adequately constructed to permit secure attachment to mounting pad or steel deck.

3.11 Refrigeration system. The refrigeration system shall consist essentially of a hermetic motor-compressor unit, a static or forced convection, an air-cooled condenser, a drier, evaporator sections with capillary tube or thermal expansion valve, and an automatic thermostat

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

control. Design, construction, and rating of the system shall be in accordance with ARI 520. The condensing unit shall have an application rating (not a standard rating) to meet the performance requirements of 3.9 at the specified ambient temperatures. In no case shall the condensing unit manufacturer's established rating be less than 1/8 horsepower (hp) (93.2 watts (W)) for size 2-5 or less than 1/6 hp (.124W) for size 3-5. Refrigerant systems shall be completely dehydrated, fully charged, and tested for leaks prior to shipment. Unless otherwise specified (see 6.2.1), the refrigeration system shall be designed for operation on nominal 120-volt, 60 hertz, alternating current. A low pressure sensing switch shall be provided in the event that loss of refrigerant charge becomes sufficiently low and shut off the unit automatically. The low pressure sensing switch shall be of the manual reset type.

3.12 Identification marking. Identification shall be permanently and legibly marked directly on the storage stand or on a corrosion-resisting metal plate securely attached to the storage stand at the source of manufacturer. Identification shall include the manufacturer's model and serial number, name and trademark to be readily identifiable to the manufacturer.

3.13 Finish. The exterior cabinet surfaces and the interior compartment surfaces shall be furnished in accordance with NSF No. 7.

3.14 Spare parts. When specified (see 6.2.1), spare parts shall be furnished and shipped with each unit. The spare parts required and the quantity thereof shall be as specified in the contract, or, when applicable, shall be determined in accordance with the provisioning procedures of the contract.

3.15 Workmanship.

3.15.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.15.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.15.3 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

3.15.4 Solder. All surfaces to be soldered (when applicable) shall be thoroughly cleaned prior to soldering. Solder joints shall be smooth with no pin holes.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one storage stand when a first article is required (see 3.2 and 6.2.1). This inspection shall include the examinations of 4.4 and the tests of 4.5. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examinations of 4.4, the tests of 4.6, and the packaging inspection of 4.7. This inspection shall be performed on the samples selected in accordance with 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of product shall be one storage stand. All units offered for delivery at one time shall be considered a lot for the purpose of inspection. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

4.3.1 Sampling for in-product examination. Sampling for examination shall be on the manufacturer's established quality control program.

4.3.2 Sampling for examination. Examination shall be based on inspection level II and an Acceptable Quality Level (AQL) of 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.3.3 Sampling for tests. Tests shall be based on inspection level S-4 and an AQL of 2.5 percent defective.

4.4 Examination.

4.4.1 In-process examination. The units shall be examined during fabrication and assembly in accordance with the manufacturer's established quality control program. The quality control methods and procedures shall assure compliance with the requirements of this specification throughout all areas of contract performance including the receipt and identification of material, fabrication of the cabinet, installation of insulation and evaporator sections, plating and painting of parts, and final assembly of the units including the installation and check-out of the refrigeration system and controls. The quality control program shall be subject to surveillance by the procuring agency or designated representatives thereof. Failure of the manufacturer to demonstrate that adequate quality control was applied to lots submitted for acceptance by the government may be cause for rejection of the lots.

4.4.2 End-product examination. The first article sample, if furnished, and sample units selected in accordance with 4.3.2 shall be visually examined to determine conformance with this specification. The examination shall be as specified in table II. If the number of defective units is equal to or greater than the rejection number applicable to the specified AQL, the lot represented by the sample units shall be rejected. Each attribute within each classification of multiple defects shall constitute one defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects.

Classification	Defects	Requirement paragraph
Critical		
1	Any defect contributing to unsanitary or unsafe conditions.	3.6
Major:		
101	Refrigerated stands not of specified description.	1.2 & 3.1
102	Interchangeability not provided for.	3.4
103	Materials not as specified.	3.7
104	Stainless steel not as specified.	3.7.1
105	Insulation not as specified.	3.7.2
106	Refrigerant not as specified.	3.7.3
107	Design not as specified. Dimensions not within specified limits.	3.8
108	Outer shell and inner liner do not enclose insulation.	3.10
109	Outer shell not as specified. Ready access for servicing not provided for.	3.10.1
110	Inner liner not of proper material, thickness, or design.	3.10.2
111	Framing not of proper design or thickness. Framing not made to resist corrosion.	3.10.3
112	Door not of proper material, thickness, and design.	3.10.4
113	Breaker strips not furnished or not of proper material.	3.10.4
114	Thermometer not of proper type or not mounted on door.	3.10.4
115	Refrigeration system not as specified.	3.11
116	Finish not as specified.	3.13
117	Spare parts missing.	3.14
118	Steel fabrication not as specified.	3.15.1
119	Welding not as specified.	3.15.3
120	Soldering not as specified.	3.15.4
Minor:		
201	Door not hinged as specified.	3.10.4
202	Hardware missing or not of material specified.	3.10.5
203	Stands not mounted as specified. Mountings not as specified.	3.10.6
204	Identification marking missing, incomplete, or not as specified. Metal plate not as specified.	3.12
205	Bolted connections not as specified.	3.15.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

4.5 First article tests.

4.5.1 Performance test. The first article sample shall be tested to verify compliance with the performance requirements of 3.9. This test shall be made under a minimum ambient room test temperature of 100°F (37.8°C). Place precalibrated temperature measuring instruments, one in each of the four top corners of the storage compartment, to obtain interior air-temperature readings. Instruments shall not interfere with the loading operation or cause instrument error due to contact with material other than air. Where more than one temperature reading is obtained for the same characteristic, the average reading shall be used for determining conformance. Perform the following:

a. With the storage compartment at a test temperature of 100°F (37.8°C), operate the unit until the temperature of the empty compartment attains an average temperature of 40°F (4.44°) and record the time required.
b. Load the storage compartment with a full complement of bulk milk containers filled either with water or milk and, after the temperature of the compartment has stabilized at 40°F ± 2°F (4.44° ±.94°C), continue operation of the unit for a period of three hours to verify compliance with 3.8b and 3.8c. During this test run, the thermometer required under 3.10.4 shall be checked against the readings of the precalibrated instruments to verify compliance with the accuracy of ± 2°F (±.94°C) required under NSF No. 7.
c. Leakage test to determine compliance with 3.10: The refrigeration system shall be tested with an electronic leak detector. In accordance with this test and the test of 4.6.3d, the largest permissible leak shall be 9.5 (.281L) ounces per year. Leakage above this rate shall be cause for rejection.

4.5.2 Structural test. The refrigerated stand shall be loaded on top with a dispenser containing a full complement of milk cans filled with water or a loading equivalent in weight and distribution shall be applied to the top. The storage compartment shall also be loaded with filled milk cans. The stand shall be examined for rigidity, deformation, structural failure, and damage to the stand itself is capable of sustaining without damage normal loading impact.

4.6 Quality conformance tests.

4.6.1 Functional tests. Sample units selected in accordance with 4.3.3 shall be tested to verify compliance with the performance requirements of 3.9 except that loading the compartment with milk cans will not be required and the test may be conducted in the ambient temperature at the test site provided the ambient temperature is 65°F (18.3°C) or more. The test shall be conducted for a period of not less than one hour after the compartment temperature has stabilized at 40°F ± 2°F (4.44° ±.94°C). Failure of a sample unit to maintain the temperature within the limits specified shall be cause for rejection of the unit.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:38Z
Check the source to verify that this is the current version before use.

4.6.2 Thermometer tests. During the tests of 4.6.1, the thermometers shall be checked as specified in 4.5.1b.

4.6.3 Operational test. Each end item shall be operated to determine compliance with the requirements specified herein. The test shall be conducted at ambient room temperatures provided the ambient temperature is 65°F (18.3°C) or more. Any of the following defects shall be cause for rejection:

a. Failure of refrigerator to start (see 3.11).
b. Current draw above maximum nameplate rating at rated voltage (see 3.9 and 3.11).
c. Failure of door thermostat to operate (see 3.10.4).
d. Leaks in refrigeration system (see 3.11 and 4.5.1c).

4.7 Packaging inspection. Preservation, packing, and marking shall be inspected in accordance with the requirements of section 4 of MIL-R-12323.

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-R-12323 with the level of preservation and the level of packing as specified (see 6.2.1).

6. NOTES

6.1 Intended use. The refrigerated storage stands are intended for use with bulk milk dispensers in dining facilities, cafeterias, hospitals, soda-fountains, and any other installations where milk is to be refrigerated and dispensed in a sanitary manner.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Size and style required (see 1.2).
c. When a first article sample is required (see 3.2 and 4.2.1).
d. When door shall be hinged on the left instead of the right (see 3.10.4).
e. When the refrigeration system shall be designed for operation on a power supply other than as specified (see 3.11).
f. When spare parts are required and the parts and quantities to be furnished (see 3.14).
g. Level of preservation and level of packing required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements shall be developed as specified by an approved Data Item Description (DD Form 1664) and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data shall be delivered by the contractor in accordance with the contract or purchase order requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first article sample or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit of each size and style required. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Subject term (key word) listing.

Refrigerated storage stand
Bulk milk dispenser
Food service equipment

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Navy - YD
Air Force - 99

Review Activities:
Navy - MC, MS, SA,
Air Force - 82
DLA - GS

User Activities:
Navy - CG, SA

Preparing Activity:
Navy - YD

(Project 4110-0386)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Commanding Officer
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:38Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-82047B	REFRIGERATORS, MECHANICAL, STORAGE STAND (FOR BULK MILK DISPENSERS)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:38Z
Check the source to verify that this is the current version before use.