MIL-T-82080C(YD)
16 December 1983
SUPERSEDING
MIL-T-82080B(YD)
28 August 1978

MILITARY SPECIFICATION

TRUCK, FIREFIGHTING; AIRCRAFT CRASH AND RESCUE, 11,000 POUND GVW, 4 BY 4

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 This specification covers a commercial, gasoline-engine-driven, four-wheel, four-wheel drive truck with a service maintenance body equipped with a twin agent fire extinguisher unit, aqueous film forming foam (AFFF) and Halon 1211.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

BB-N-411 - Nitrogen, Technical.

MILITARY

MIL-F-24385 - Fire Extinguishing Agent, Aqueous Film Forming Foam (AFFF) Liquid Concentrate, Six Percent, for Fresh and Sea Water.
MIL-B-38741 - Bromochlorodifluoromethane Halon 1211

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED STD No. 595 - Colors.

MILITARY

MIL-STD-281 - Automobiles, Trucks, Truck-Tractors, Trailers and Trailer Dollies, Preservation and Packaging of.
MIL-STD-1223 - Non-Tactical Wheeled Vehicles Treatment, Painting, Rustproofing, Identification Marking, and Data Plates Standards.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Code of Federal Regulations, Title 45, Part 1201 - New Motor Vehicles and Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852.)

*2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section VIII.
Pressure Vessels, Division 1.

(Application for copies should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

No. 412 - Evaluating Foam Fire Equipment Aircraft Rescue and Fire-fighting Vehicles.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

T&RA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The truck shall be a four-wheel, four-wheel drive, gasoline-engine-driven truck cab-and-chassis having a gross vehicle weight rating (gvw) of not less than 11,000 pounds (lb). The truck shall be equipped with a service maintenance body. The truck shall be provided with a skid mounted twin agent fire extinguisher unit installed in the load space of the maintenance body.

3.2 First article. When specified (see 6.1), the contractor shall furnish a truck for first article inspection and approval (see 4.2.1 and 6.3).

3.3 Standard truck, components, and accessories. Except as specified in 3.3.1 through 3.3.8, the truck, components, and accessories shall be standard or optional items which meet or exceed the requirements of this specification. All items shall be as represented and rated in the manufacturer's sales information, including special or mounted equipment. Sales information shall be limited to specifications and technical material identical to that furnished to the authorized company representative for selection of truck models and components.

3.3.1 Drain plugs. Drain plugs installed in the rear axle shall be of the permanent type.

Source: https://assist.dla.mil -- Downloaded: 20260410-26T04:39Z
Check the source to verify that this is the current version before use.

3.3.2 Heavy-duty cooling system. A heavy-duty cooling system shall be furnished that shall maintain engine coolant at a temperature below the boiling point with truck loaded to rated gvw, and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 110° Fahrenheit (F).

3.3.3 Coolant recovery system. An overflow coolant recovery system shall be furnished. The coolant recovery system shall include an unbreakable translucent reservoir of not less than 2-quart capacity. The reservoir shall be located in a position readily visible for checking coolant level.

3.3.4 Towing devices. Not less than two hooks, loops, or pins, mounted to the frame or to rigid members which are attached to the frame, shall be furnished in front and rear of the truck for towing purposes.

3.3.5 Radio noise suppressors. The truck chassis shall be equipped with radio noise suppressors conforming to SAE J552. Electromagnetic radiation from the truck chassis shall be within the limits of SAE J551.

3.3.6 Engine hour meter. An engine hour meter of the oil pressure type, having a totalizing mechanism of not less than 9,999 hours, shall be furnished for the truck chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to insure continuous trouble-free performance under severe operating conditions. Engine hour meter shall be mounted on the truck cab instrument panel.

* 3.3.7 Air pollution control. Trucks shall comply with the EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicles Engines in effect on the date of manufacture.

3.3.8 Sound level. The exterior sound level produced by the truck shall not exceed the noise limits established by the EPA. The interior sound level shall be in accordance with DoT Motor Carrier Safety Regulations, section 393.94.

3.4 Identical items. All units of the same classification furnished under any specific contract shall be physically and mechanically identical. The requirement includes parts, assemblies, components, and accessories. No deviations will be acceptable without written approval of the contracting officer.

3.5 Performance. The fully equipped truck, loaded to rated gvw, shall be capable of performing the following:

a. Parking brake holding the truck on a 30 percent grade in both ascending and descending positions.
b. Service brakes holding the truck on a 30 percent grade in both ascending and descending positions.
c. Service brakes bringing the truck to a stop within a braking distance of 30 feet from a speed of 20 miles per hour (mph) on a dry, smooth level surface free from loose material.
d. Maintaining a maximum speed of not less than 55 mph on dry, level, paved roadway.
e. Accelerating on a level road from a standing start to a speed of 50 mph in 30 seconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

f. Maintaining a sustained speed when ascending a 30 percent grade in low speed range.
g. There shall be no evidence of body distortion, water leakage, tire and body contact, malfunction of components, irregular chassis noise, vibration or sway, when subjected to a road test of 50 miles over paved roadway at not less than 55 mph; 25 miles over graded dirt roadway at not less than 25 mph; and 25 miles off highway over cross-country terrain at speeds up to 15 mph with ground and grade conditions requiring four-wheel drive.

3.6 General design.

3.6.1 Federal Motor Vehicle Safety Standards. The truck shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

* 3.6.2 Weight rating and distribution. The manufacturer's gross vehicle weight rating (gvw) for the fire truck chassis furnished shall not be less than 11,000 lb. The total gross weight of the complete truck shall not exceed the manufacturer's gvw when fully equipped as specified herein, including all specified equipment, serviced with fuel, water and lubricants, and fully charged twin agent fire extinuisher unit as specified in 3.9, 3.9.1 and 3.9.2. Weight distribution ratio between the front and rear axle shall be such as to insure postive traction at the front and rear wheels and postive steering at the front wheels under all operating conditions specified herein.

* 3.6.3 Cab-to axle. The cab-to-axle dimension shall be not less than 60 inches on truck with conventional cab and the cab-to-axle dimension shall be not less than 54 inches on truck with crew cab.

* 3.6.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.7 Chassis components.

* 3.7.1 Engine. The truck engine shall be an eight cylinder gasoline engine having horsepower (hp), torque, and speed characteristics to satisfactorily meet all vehicular performance requirements specified herein. At manufacturer's rated governed speed, the engine shall develop not less than 185 net hp and shall have a net torque rating of not less than 220 pound-feet. The engine furnished shall produce the required performance on unleaded gasoline.

3.7.1.1 Oil filter. Full flow type oil filter shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.7.1.2 Governor. If required, an engine governor shall be furnished and set and sealed to limit engine to maximum recommended operating speed.

3.7.2 Electrical system.

3.7.2.1 Ignition system. Ignition system of 12-volt (V) potential shall be furnished. Alternator of not less than 130 ampere (A) rated capacity, and which provides not less than 7A direct current output at normal engine idle speed, shall be furnished.

3.7.2.2 Battery. The battery shall be maintenance free 12V potential. The total reserve capacity rating shall be not less than 110 minutes and the total cold cranking rating at 0°F shall be not less than 450A. Cold cranking and reserve capacity ratings shall be in accordance with SAE J537.

3.7.2.3 Lighting. All truck lights, reflectors, and wiring shall be as specified herein and shall conform to DoT Motor Carrier Safety Regulations, sections 393.12, 393.19 through 393.31, and 393.33. Lights and reflectors shall not be mounted on vertical surfaces of rub rails or bumpers. Rear identification lights shall be protected from damage when mounted near the rear bumper step.

* 3.7.2.4 Lights. All lights shall be mounted in such a manner as to prevent being obscured by riding personnel or mounted equipment. All metal rims, shells, mounting arms, and bases of all exterior lights shall be chromium plated. Stoplights and taillights shall be flush mounted at the rear of the body. The following additional lighting shall be furnished and shall be provided with overload protection:

a. Two chromium plated spotlights, one on each side of cowl or windshield. One end of the light housing shall be equipped with a clear lens, the other end with a red lens. The red light shall function as a flashing light with control switch located at the light. Controls for the spotlight beam and housing movement shall be inside the cab. Movement shall be through a horizontal included angle of at least 270°, and a vertical angle of at least 90° above and 35° below horizontal.
b. Two shielded engine compartment lights, arranged to illuminate both sides of the engine. Switch(s) are to be mounted on the cab instrument panel and identified.
c. Two automatic back-up lights, not less than 6-inch diameter, flush mounted at rear of body.
d. Two rear mounted, alternate flashing, red warning lights. The lights shall be sealed beam and not less than 6 inches in diameter. The control switch shall be in the cab on the instrument panel, and shall be identified.

* 3.7.3 Fuel system. Fuel system shall conform to DoT Motor Carrier Safety Regulations, section 393.65 and 393.67.

3.7.3.1 Air cleaner. An air cleaner shall be furnished. When equipped with an oil-bath type, oil capacity shall be not less than 1 pint.

* 3.7.3.2 Fuel tank. The fuel tank shall be the manufacturer's standard, and the fuel tank capacity shall be not less than 20 gallons.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.7.4 Exhaust system. Exhaust system shall conform to DoT Motor Carrier Safety Regulations, section 393.83. Muffler and other portions of exhaust system shall be manufacturer's standard. A shield plate shall be installed, where necessary, to prevent spilled fuel from coming in contact with the exhaust system.

* 3.7.5 Automatic transmission. The truck shall be provided with an automatic transmission of a fixed ratio type and shall provide continuous drive. The fixed ratio type shall include a hydraulic torque converter and not less than three forward speeds. The normal driving range selector position shall provide not less than three gear ratios without movement of the selector.

* 3.7.5.1 Transfer case. A two-speed type transfer case shall be provided. The transfer case shall provide for driver selection of either two-wheel or four-wheel drive.

3.7.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.7.7 Frame. Chassis frame shall be manufacturer's standard for the truck furnished.

3.7.8 Suspension. Truck shall be equipped with suspension system, with components having a rated capacity at least equal to the load imposed on each member, plus at least 10 percent, measured at the ground, with truck loaded to specified gvw. When suspension is rated at the spring pads, unsprung weight shall be deducted. Truck shall be equipped with hydraulic, double-acting, shock absorbers on the front and rear wheels.

3.7.9 Axles. The front axle shall have a rated capacity of not less than 4,500 lb, and the rear axle shall have a rated capacity of not less than 7,500 lb. Rear axle shall be provided with positive-traction or limited-slip differential.

3.7.10 Wheels, rims, tires, and tubes. Truck shall be equipped with single front and single or dual rear wheels. Rim sizes shall be the same for all wheels on the truck. Tire size and ply rating (load range) shall be the same for all tires on the truck. Rim and tire ratings shall conform to T&RA recommendations for the type and size of tires furnished.

* 3.7.10.1 Tires. Tires shall be steel belted radial, tube or tubeless type with nondirectional mud and snow tread. Tires shall have a rated capacity at least equal to the load imposed on each tire measured at each wheel, at the ground, with truck loaded to specified gvw.

3.7.10.2 Inner tubes. When tube-type tires are furnished, inner tubes shall be of proper size for tires furnished. When mounted on other than drop center rims, tire flaps shall be installed.

* 3.7.10.3 Spare wheel assembly. A spare wheel and mounted spare tire shall be furnished and stowed in the truck for shipment. The spare tire shall be of the same size, tread design, and ply rating as the tires in use on the truck.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.7.11 Brakes. Brakes shall conform to DoT Motor Carrier Safety Regulations, sections 393.40, 393.41, 393.42, 393.45 through 393.51, and as specified herein.

3.7.11.1 Service brakes. Truck shall be equippd with power assisted hydraulic actuated, four-wheel, service brakes.

3.7.11.2 Parking brake. Truck shall be equipped with parking brake.

3.7.12 Steering. Truck shall be equipped with power assist steering. Mechanical type steering capability shall be available in event of loss of power assist steering.

* 3.7.13 Cab. Unless otherwise specified, the chassis manufacturer shall furnish any type of his standard or optional full width cab. Cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, with at least the curbside door equipped with external, key-operated lock. Drip rails shall be installed above the cab doors. Cab shall have upholstered, full-width, adjustable seat and back or individual, adjustable, driver's seat and individual passenger seat. The color of the upholstery and the interior finish shall be compatible with the exterior color. White upholstery shall not be furnished. Interior lighting shall be provided. Manufacturer's standard fastenings and two pairs of seat belts shall be installed on the vehicle.

* 3.7.13.1 Crew-cab. When specified (see 6.1), a four-door full width, crew-cab shall be furnished in lieu of the standard full width cab. Cab shall be equipped with two upholstered, full width, seats and backs. The front seat shall be adjustable. Fastenings and three pairs of seat belts shall be installed for both front and rear seats. Cab doors shall be equipped with locks operable from inside the cab through mechanical linkage, with both front doors equipped with external key-operated locks. Cab doors shall have windows with crank-operated window regulators. A rear window shall be provided. Interior lighting shall be provided. The cab roof shall be one piece construction; or, if welded, the roof shall give the appearance of one piece, with weld seams being continuous, waterproof, and free of visible seams, bumps or protrusions. Full length drip moldings shall be mounted above doors. When crew cab is furnished, the cab-to-axle dimension shall be measured from the back face of the crew-cab.

* 3.7.13.1.1 Seat spacing. With the front seat adjusted to the extreme forward position there shall be not less than 30 inches, measured in a horizontal plane, between the front of the rear seat-back and the rear of the front seat-back. A kick-space height of not less than 2-3/4 inches shall be maintained between the floor and the rear of the front seat in all positions of adjustment. Leg room and space forward of the front seat shall be equivalent to that provided ahead of seat in a two-door standard cab.

3.7.14 Windshield wipers and washers. Truck shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by electric motor(s).

3.7.15 Heater and defroster. Hot water heater shall be provided. Heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to floor and to defroster louvers. Heater shall be complete with blower and mounted controls convenient to the driver.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.7.16 Controls and operating mechanism. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

* 3.7.17 Front bumper. Except as specified herein, manufacturer's standard front bumper shall be furnished. When front mounted winch is furnished, the front bumper shall be the chassis manufacturer's or winch manufacturer's standard full width type designed for installation and operation of front mounted winch.

3.7.18 Rear end protection. Rear end of truck shall be protected in accordance with DoT Motor Carrier Safety Regulations, section 393.86. A combination channel rear bumper with riser and full width safety tread step shall be provided. The step tread width shall be not less than 10 inches in width, from front to rear. The rear step shall be capable of supporting a 200 lb firefighter.

* 3.7.19 Rearview mirrors. Outside rearview mirrors, each with at least three supporting arms, shall be mounted on each side of the cab. Combination (flat and convex) mirrors, enclosed in a common housing, shall be furnished. Each combination mirror shall have at least 40 square inches of flat reflective area and a convex surface having at least 20 square inches of reflective area.

3.7.20 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

a. Inside rearview mirror.
b. Key type ignition switch.
c. Ammeter or charging indicator.
d. Fuel gage.
e. Oil pressure gage or indicator.
f. Engine temperature gage or indicator.
g. Speedometer with recording odometer.
h. Ash receptacle
i. Dual sunvisors.
j. Door mounted armrest on driver's side.
k. Driver's compartment ventilator other than window.
l. Manufacturer's standard electric horn.

* 3.7.21 Winch. When specified (see 6.1), a winch assembly shall be provided on the front of vehicle and shall be powered from the vehicle electrical system. The winch shall be wound with not less than 150 feet of wire rope with end chain and hook. Winch single line pull rating on the bare drum, and the nominal breaking strength of the wire rope, chain and hook, shall be not less than 8000 lbs. Wire rope shall be of improved plow steel, preformed, regular lay, Seale construction with fiber core. Winch shall be suitable for hoisting as well as for assisting truck to negotiate difficult terrain. Winch shall have forward and reverse drum-drive and a drum clutch to permit free spooling of the cable. Winch shall be equipped with a four-way roller guide.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

3.8 Body. The body shall be of the service maintenance type having a center load space with enclosed compartments at both sides. Any area of 1 square foot shall be capable of sustaining a live load of 300 lb in the load space and 100 lb in the cabinets without permanent distortion.

* 3.8.1 Body dimensions. The main body dimensions shall be as follows:

Dimension	Inches
Overall length, not less than	108
Overall width, not less than	77
Depth of compartment sections, each outside dimension, not less than	14
Height of compartment sections, not less than	37
Height from floor line to top of compartment sections, not less than	21
Center load space width, between wheel wells not less than	42
Center load space width, between cabinets not less than	47

When crew-cab is furnished, the overall length of the body may be reduced from a minimum of 108 inches to a minimum of 98 inches.

* 3.8.2 Body materials. The truck body shall be alloyed coated galvannealed type steel construction of not less than 16 gage or a fiberglass molded one-piece body.

* 3.8.2.1 Steel cabinet materials and construction. Cabinet headers shall be not less than 16 gage (.0598 inch) galvannealed steel. Cabinet backs, partitions and shelves shall be of not less than 18 gage (0.0478 inch) galvannealed steel. Cabinet doors shall be of galvannealed steel exterior panel of not less than 16 gage (.0598 inch) and inside panel of not less than 18 gage (0.0478 inch).

3.8.2.2 Fiberglass body and cabinet. The truck's body and cabinets shall be a solid one-piece molded unit constructed of fiberglass reinforced plastic laminate having a center load space with three compartments (cabinets) on each side. The material construction shall have adequate buildup containing the proper resin/catalyst, laminated with reinforcing mats or woven fabric/roving to provide the strength required for the type of body and payload specified herein. A gel coat or surface coat shall be provided on the exterior surface containing the matching color specified for the truck chassis and to present a smooth exterior finish. Replaceable steel rock guards of at least 16 gage shall be provided at the rear of the wheel wells. The load bed and the top outside surface of the cabinet compartments shall have a nonslip surface.

* 3.8.3 Body compartment arrangement for standard cab. Cabinet arrangement and characteristic details shall be as follows:

a. One full height vertical compartment with not less than two adjustable shelves shall be provided each side of the body at the front. The front compartment shall have a minimum door frame size of 30 by 28 inches.
b. One full height vertical compartment located at the rear of the wheelhousing on each side of the body shall be provided. The minimum door frame size shall be 30 by 18 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

c. One horizontal compartment with not less than one full length tray type shelf shall be provided on each side of the body located above the wheelhousing. The minimum door frame size shall be 10 by 36 inches.
d. All steel and fiberglass doors shall be of double panel, reinforced construction having continuous rod or hem type, heavy-duty hinges with stainless steel hinge pins and stainless steel, bronze, or nylon insert sockets. Fiberglass doors shall be reinforced to eliminate deflection with minimum panel thickness of 3/16 inch. Steel door construction shall be as specified in 3.8.2.1. All doors shall be built with water troughs or drip rails to insure the carrying off of rain and wash water. Horizontal doors shall be equipped with support chains and the vertical doors shall be equipped with hold-open devices. All doors shall be equipped with recessed type door handles, slam action catches, and cylinder locks keyed alike.
e. Load compartment floor and top of each compartment shall be constructed of safety tread steel plate if body is of steel construction or heavy reinforced fiberglass with non-skid coating if body is fiberglass. The front part of the floor shall be provided with two drain holes.
f. A nonvision obstruction cab rear window guard of rugged construction shall be provided.

* 3.8.3.1 Body compartment arragement for crew cab. Cabinet arrangement and caracteristic detail for crew cab when furnished, shall be as follows:

a. One full height vertical comp rtment with not less than two adjustable shelves shall be provided eac. side of the body at the front. The front compartment shall have a minimum door frame size of 17 by 38 inches.
b. One full height vertical compartment located at the rear of the wheelhouse on each side of the body shall be provided. The minimum door frame size shall be 26 by 34 inches.
c. Requirements specified in 3.8.3. c.,d.,e., and f. shall also apply.

3.8.4 Deck lights. Two chromium plated, 6-inch diameter, sealed beam, 100 watt deck lights (spotlights) with weatherproof switch shall be provided, one each mounted at the rear of the truck on top of each side body compartment section. The deck lights shall be adjustable, capable of 360° rotation and 180° vertical movement.

3.8.5 Handrails. A handrail shall be provided and mounted at the rear of each side body compartment section for use of personnel in mounting rear bumper step (see 3.7.18).

* 3.8.6 Warning light. A cab roof mounted lightbar, with built-in public address system speaker, shall be furnished. Light beams shall be reflected to the front and rear. The warning light and roof bar shall be Federal "Twinsonic", Dietz "Omni-chief", or equal. The sealed beam lamps shall be high intensity, red and white in color. The light system housing shall be clear. A single control shall be provided with a red pilot light indicating the "ON" position. The pilot light shall be located in the cab on the instrument panel. The speaker shall be as specified in 3.8.6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

* 3.8.6.1 Electronic siren, public address, and radio amplifier system. An electronic siren system with selector controls for the siren, public address and radio amplification through an external speaker shall be provided. System sound intensity shall be not less than 98 decibels at a distance of 100 feet from the speaker. The speaker shall be at least 100 watt. The amplifier and controls shall be installed inside the vehicle in a location accessible to the driver and assistant driver. A microphone of the magnetic noise canceling type, connected by a coiled cord, shall be provided and located in a position convenient for use. Microphone stowage shall be provided on the instrument panel. The system shall permit broadcasting routine and emergency announcements from an on-board Government installed radio. The amplifier shall include volume control and selection of "Radio", "P.A.", "Manual", "Yelp", "Wail", and "HiLo" (European) modes. Switch position shall be identified. A two-way radio audio top cable for rebroadcasting 2-way messages through the PA system shall be furnished. The speaker shall be fitted with a weather-proof housing and shall be suitable for installation on the cab roof bar.

* 3.9 Twin agent fire extinguisher unit. A skid-mounted twin agent fire extinguisher unit shall be provided and installed in the load space of the service maintenance body. The twin agents shall be an AFFF fire-fighting agent and a Halon 1211 firefighting agent. The AFFF agent shall conform to MIL-F-24385. The Halon 1211 agent shall conform to MIL-B-38741. The twin agent fire extinguisher unit shall consist of an AFFF agent tank, Halon 1211 agent tank, nitrogen cylinder(s), piping, pressure regulators, controls, discharge hoses, nozzle, hose reel, and other equipment specified herein. The overall height of unit shall be not more than 50 inches and the overall width of unit shall be not more than 46 inches. The skid frame shall fit between the standard 42-inch width wheelwells in the center load space of the truck body. The overall length of the twin agent unit shall be not more than 98 inches and the weight of the fully charged unit shall be not more than 3,800 lb. The twin agent fire extinguisher unit, performing through 100 feet of 1-inch hose and nozzle, as specified in 3.9.7, shall be capable of the following:

a. Discharging the AFFF premixed solution, at an ambient temperature of 65°F to 85°F, with constant flow rate of 60 gallons per minute (gpm) at 100 pounds-force per square inch gage (psig) pressure.
b. Discharging the Halon 1211, at an ambient temperature of 65°F to 85°F, within a minimum-maximum range of 5.0 to 5.5 pounds per second at 100 psig pressure.

The twin agent fire extinguisher unit shall be capable of providing simultaneously, an average flow rate of 60 gpm of AFFF agent and 5.5 lb per second of Halon 1211 at any hose length from 25 to 100 feet.

3.9.1 Agent tank, AFFF. The AFFF agent tank shall have a capacity of not less than 200 gallons of 6 percent AFFF liquid concentrate solution. The tank shall be constructed and certified in accordance with the current ASME Boiler and Pressure Vessel Code, section VIII, Division 1, for a design working pressure of at least 230 psig. The tank shall be fabricated from material resistant to corrosion by the AFFF agent to be stored, or a suitable lining material shall be provided. A fill opening at least 4 inches in diameter and a drain line 1 inch in diameter shall be provided. The fill opening shall be provided with straight through unencumbered access to the tank, without dog-legs or off-sets, to permit stirring and gaging of the contents and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

inspection of the interior. The fill pipe shall extend into the tank to sufficient depth to preclude foaming. A reseating type relief valve, capable of preventing pressures in excess of 110 percent of the design working pressure, shall be provided on the tank. A temperature relief valve or fuse plug set for a minimum of 195°F shall be installed. A vent line with a quarter-turn valve shall be provided on the top of the tank for blowdown purpose to insure zero pressure before opening the fill cap.

3.9.1.1 Fill cap. The fill cap on the AFFF tank shall be provided with a safety vent hole so that cap is pressure venting while at least 3-1/2 threads are still engaged. The fill cap arrangement shall be such that the male threads are a part of the tank and the female threads are a part of the cap. When required, an extension spanner wrench for easy removal of the fill cap shall be supplied and installed beneath the hose reel.

3.9.1.2 Tank funnel. A suitable funnel shall be provided for easy loading of AFFF liquid agent.

* 3.9.2 Halon 1211 agent system. A Halon 1211 liquified gas type agent system shall be provided. The system shall consist of an agent tank with a capacity of 200 lb of agent; a cylinder of high pressure nitrogen for expelling the agent and purging the system; a manual rewind hose reel assembly as specified in 3.9.8, fitted with 100 feet of one-inch hose, as specified in 3.9.7, and a Halon nozzle as specfied in 3.9.9 and related control valves, gages, and piping.

* 3.9.2.1. Halon 1211 agent tank. The Halon 1211 agent tank shall be constructed and certified in accordance with Section VIII, Division 1, of the current ASME Boiler and Pressure Vessel Code, and shall operate at pressures of at least 230 psi. The tank shall be a horizonatal type cylinder designed for easy maintenance and handling. The Halon 1211 agent tank shall be provided with the necessary accessory conponents that allow for servicing and filling the tank. Couplings shall be of the quick disconnect type. The tank shall be provided with a liquid level gage (sight glass). The Halon 1211 charging hose shall be furnished with the tank fill system. All connectors and gages shall be readily visible and installed at an accessable location. The tank shall be provided with a spring-loaded relief valve capable of preventing pressure in excess of 110 percent of the design working pressure.

3.9.3 Nitrogen propellant system. A nitrogen gas propellant system for the twin firefighting agents shall be provided. Nitrogen gas cylinder(s) having adequate capacity and pressure to provide performance requirements specified in 3.9 shall be furnished. The propellant gas cylinder(s) shall be in accordance with DoT requirements and regulations. The gas cylinder(s) shall be compatible with nitrogen gas conforming to BB-N-411, type 1, class 1, grade B. The cylinder(s) shall be provided with a pressure gage indicating the cylinder gas pressure and shall be located within view of the operator for ease in checking. The pressure gage shall indicate at all times the pressure in the nitrogen gas cylinder(s) without opening any valves. A quick-opening lever operated valve, requiring only a quarter turn or a 90° traverse lifting of a lever, to release the nitrogen gas and capable of being easily reset by manually turning, cocking, or repositioning valve handle or pin shall be provided, and shall be located at the control panel (see 3.9.6). Design and placement of the nitrogen gas cylinder(s) shall be such that provision shall be made for quick and easy replacement after each use. The total

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

capacity of the nitrogen cylinder(s) shall be such that when the cylinder(s) is fully charged, sufficient nitrogen propellant shall be available to fully expel all agents, and permit purging of all piping and hose lines after use. Safety relief valve shall be provided on nitrogen gas cylinder(s). The nitrogen gas cylinder(s) shall be empty when the truck is prepared for shipment. A tag shall be attached to the cylinder(s) in a conspicuous location, indicating: CYLINDER(S) ARE EMPTY, FILL WITH NITROGEN GAS BEFORE PLACING INTO OPERATION.

* 3.9.4 Piping. A piping system, with an effective nitrogen gas pressurization to insure proper discharge of the AFFF agent and Halon 1211 agent, shall be provided. Piping system shall include any additional agent tank fittings and valves required for the pressurization, discharge, venting, and flushing of the twin agent fire extinguisher unit. Piping shall be designed to minimize friction losses at the design flow rates. The piping system shall permit depressurization and purging of all lines and tanks without loss of remaining agent. Check valves shall be used to prevent backflow into the gas regulators from the AFFF agent tank. Check valves shall be used to restrain the agents from entering the hose lines until pressurization takes place. All valves and piping shall be resistant to corrosion by the AFFF agent. No black or galvanized iron, if furnished, shall be in contact with the AFFF. Potential galvanic corrosion points shall be eliminated by proper choice of material. Care shall be taken to prevent loosening of joints or breaking of pipes or connection due to shock and vibration. Approved flex type hose may be furnished.

3.9.5 Pressure regulator(s). The gas flow rate of the regulator or regulators and gas piping system shall effect a pressure level of 80 percent of the working pressure within 10 seconds of cylinder valve operation on both of the agent tanks. Dead end setting of the regulator(s) shall be within 95 to 110 percent of maximum working pressure. The regulator(s) shall have an integral relief valve set to relieve at 110 percent of the tank's design working pressure and be capable of handling the full regulator gas flow. The regulator pressure setting shall be adjusted by the manufacturer and sealed in a manner to discourage manipulation in the field.

* 3.9.6 Controls. Operating controls and gages to pressurize the twin agent fire extinguisher unit shall be located near the nozzle stowed position within reach and view of the operator as he is positioned at the rear of the truck. Not more than two manual control manipulations (exclusive of discharge nozzle) shall be allowed to pressurize twin agent unit to the discharge nozzle. Operational instruction and product marking plates specified in 3.9.11 shall be mounted on the control panel.

3.9.7 Discharge hoses. The discharge hoses for both AFFF and Halon 1211 agent shall be noncollapsible twin hose of 1-inch inside diameter and shall be 100 feet long. The 1-inch hose shall be used for the AFFF agent and the Halon 1211 agent. The twin discharge hose shall be capable of withstanding twice the full tank pressure and shall be tested with couplings to this pressure for 5 minutes with no leakage or damage.

* 3.9.8 Hose reel. A manual hose reel shall be an integral part of the extinguisher unit, positioned so that when the extinguisher unit is placed on the truck bed, access to the nozzle shall be from the rear of the truck within easy reach of a firefighter while standing on the ground. The design shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

provide for ease of rapid removal and restowage of the 100 foot length twin agent hoses. A means of restraining the discharge nozzle in a readily accessible stowed position shall be incorporated. The reel shall be equipped with adequate vertical and horizontal rollers and guides to reduce hose chafing and friction when on either side of the truck. The reel shall be equipped with an adjustable positive tension friction brake to prevent hose from unreeling when not desired. The discharge hoses shall be capable of being used in incremental payout lengths and shall not be required to pay out the full 100 feet for operational use, a removable crank handle shall be provided and provisions shall be made to properly stow the handle after reel has been rewound and not in use.

* 3.9.9 Discharge nozzle. The twin agent unit discharge hoses shall be provided with a dual agent handline nozzle that dispenses both Halon 1211 and AFFF agent. The twin agent nozzle assembly shall incorporate dual dispensing barrels in an over/under arrangement mounted on a single pistol grip handle. The over/under arrangement Halon 1211 discharge barrel shall be located above the AFFF barrel. Both Halon 1211 and AFFF agent valves shall be of the quarter turn ball type with paddle type handles. The AFFF agent discharge tip shall be a constant flow variable stream type with a flow rating of 60 gpm at 100 psig. The AFFF discharge shall have a straight stream performance range of at least 50 feet at a 3-foot width and a dispersed pattern of at least 20 feet at a range of 15 to 20 feet. The Halon nozzle shall be position type--vapor discharge and straight stream. The nozzle shall discharge at a rate of 5-5-1/2 lb per second and shall deliver a straight stream with a range of 35 feet and a vapor stream of 10-15 feet from the end of the nozzle.

3.9.10 Skid. The twin agent fire extinguisher unit shall be mounted on a skid. Skid shall be crashworthy secured with removable fastenings to the floor of the maintenance body. The framing incorporated with the skid mount shall be provided with four lifting eyes for placing and removing unit from the truck bed.

3.9.11 Operation and product markings. Destruction resistant, embossed, aluminum plates shall be permanently and legibly marked for identification and use of the extinguisher unit. The plates shall be permanently mounted on the control panel at the rear so that they may be easily read by personnel standing on the ground at the rear of the truck.

3.9.11.1 Operation markings. A plate or plates shall be marked with the following:

a. Complete and detailed activating instructions for placing the equipment in operation shall be printed in not less than 1/2 inch red letters on a contrasting background.
b. After use instructions and maintenance instructions shall be provided.
c. A statement shall be shown that the gas cylinder(s) shall be replaced if the pressure during storage drops below a specified level. (Contractor to insert proper level.)
d. Storage and maintenance instructions shall include precautions against subfreezing temperature exposure of the equipment.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the currentversion before use.

3.9.11.2 Product markings. The plate shall be marked with the following:

a. Name and model number of unit.
b. Name and address of manufacturer.
c. Serial number of unit.

3.9.11.3 Agent refilling table. A table for the AFFF agent shall be provided, indicating the amount of agent necessary to either completely or partially refill the agent tank after use, by measuring the distance in inches from the top of the tank to the remaining level of agent.

* 3.9.12 Agent identification. AFFF agent tank fill cap shall be painted blue. Halon 1211 tank shall be painted red.

* 3.9.13 Fire rescue equipment. The following items of rescue equipment shall be furnished and stowed in the body compartments:

a. A SIERRA Aircraft Rescue Crash Kit (USAF developed) identical to HALPRIN SUPPLY Company Model CRK-5 or equal.

3.10 Lubrication. Lubrication means shall be provided for all parts of the equipment normally requiring lubrications. Where the use of high lubricating pressure will damage grease seals or other parts, fittings with pressure release shall be used. The truck shall be lubricated prior to delivery and shall be conspicuously ragged to identify the lubricants and their temperature range.

* 3.11 Treatment and painting. The exterior and interior surfaces of the truck, cab, maintenance body, equipment cabinets, and the exterior surfaces of the fire extinguisher unit shall be cleaned, treated, and painted in accordance with MIL-STD-1223 requirements except that the exterior trim shall be painted to match the vehicle exterior color. The vehicle finish color shall be gloss lime yellow No. 13670 as listed in FED STD No. 595. The finish color of the equipment steel cabinet tops and the top of the rear step bumper shall be aluminum. If a fiberglass body is provided, the color as specified shall be in the gel coat.

3.12 Rustproofing. The truck cab, frame, wheel wells, and all exposed underside body metal components shall be rustproofed in accordance with MIL-STD-1223.

3.13 Identification marking and data plates. Identification marking, registration numbers, and data plates for the truck, shall be in accordance with MIL-STD-1223, as specified for the Navy.

3.14 Servicing and adjusting. Prior to acceptance of the truck by the Government inspector, contractor shall service and adjust each truck and its mounted equipment for operational use, including at least the following: Adjustment of lights; adjustment of engine; adjustment of electrical and brake system; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine, running gear, and mounted equipment.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the currentversion before use.

3.15 Workmanship.

3.15.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.15.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.15.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.15.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.15.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

* 4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the currentversion before use.

4.2.1 First article inspection. The first article inspection shall be performed on one truck when a first article is required (see 3.2 and 6.1). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

* 4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.5, and the packaging inspection of 4.6.

4.3 Examination. Each truck shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 First article tests. When first article is required, the first article shall be subjected to the tests specified in 4.4.1 through 4.4.3.6. The first article tests shall be conducted by the contractor at test sites that will enable the truck to perform and be evaluated for compliance to the tests specified in 4.4.1 through 4.4.3.6. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all trucks until corrective action has been taken.

4.4.1 Truck weight. The truck shall be weighed to determine curb weight and distribution of curb weight on front and rear axle. The iumposed loading on front and rear axle will be computed using the curb weight, the operator weight at 175 lb, and the payload uniformly distributed over the vehicle load area, to provide the specified rated gvw. Calculated imposed loads on front and rear axle will be utilized to ascertain that the suspension, and tires furnished are of adequate capacity to meet specification requirements.

4.4.2 Operational tests. The truck shall be loaded to its rated gvw, as specified in 3.6.2, and operated to verify performance requirements specified in 3.5 a. through g. During these tests, the functioning of the engine, power train, steering, brakes, truck and body lighting systems, controls, and instruments shall be observed for effective operation.

4.4.3 Twin agent fire extinguisher unit tests.

* 4.4.3.1 Agent tanks pressure test. The AFFF agent tank and the Halon 1211 agent tank shall be pressure tested. Each tank shall be pressurized to 150 percent of the design working pressure and the pressure held for 15 minutes. There shall be no evidence of leakage, permanent distortion, or other defects. Openings not subjected to this test shall be plugged.

4.4.3.2 Agent tank pressure relief valve test. Each agent tank pressure relief valve shall be tested to determine conformance to 3.9.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

4.4.3.3 Discharge hoses pressure test. Discharge hoses shall be hydrostatically tested to 600 psig pressure for 5 minutes to determine conformance to 3.9.7.

* 4.4.3.4 Operating characteristics test. Each discharge nozzle shall be individually performance tested as specified herein at a hose length of 100 feet. The AFFF shall be discharged at an ambient temperature of 65°F to 85°F. The rate of discharge of premixed solution shall be constant flow of 60 gpm. The AFFF product, as produced by the specified nozzle in 3.9.9, shall be sampled and tested in accordance with the procedures set forth in current edition of NFPA No. 412. The resultant AFFF shall have a minimum expansion of three with a minimum 25 percemt drain of 1 minute. The AFFF nozzle shall have performance patterns as specified in 3.9.9. The rate of discharge of the Halon 1211 shall be 5.0 to 5.5 lb per second at the beginning of discharge and the effective reach of the Halon 1211 stream shall be as specified in 3.9.9. A minimum of 95 percent of the Halon 1211 contents shall be discharged at a rate not less than 5 lb and not more than 5.5 lb per second. The full contents of each agent tank shall be discharged during the above individual tests. Each agent container shall attain 80 percent of their working pressure within 10 seconds of system activation.

4.4.3.5 Recharging test. After complete discharge of the agent tanks during tests in 4.4.3.4, the unit shall be fully recharged in order to observe any problems or inadequacies in filling and to make ready to perform tests specified in 4.4.3.6.

4.4.3.6 Dual discharge operating test. A performance test shall be conducted with both AFFF and Halon 1211 discharge nozzles operating simultaneously with 50 feet of the discharge hoses still remaining on the reel. Average rate of flow shall be not less than 60 gpm for AFFF and not less than 5 and not more than 5.5 lb per second for the Halon 1211. The full contents of each agent tank shall be discharged during the test.

4.4.4 Production sample. Upon acceptance of the first article, it shall remain at the manufacturing facility as a production sample, and be the last truck shipped on the contract. The first article shall be reconditioned, including replacement of abnormally worn parts and paint touch-up or repainting, prior to delivery to enable it to be accepted as a contract item. The contractor shall maintain the first article in a serviceable condition for the duration of the contract.

4.5 Quality conformance tests. Each production truck shall be operated and tested as specified in 4.5.1 and 4.5.2.

4.5.1 Operational tests. Each production truck shall be loaded to its rated gvw as specified in 3.6.2 and operated as follows:

a. Five miles over paved roads at speeds not less than 65 mph.
b. Five miles over graded dirt roads at speeds up to 25 mph.
c. Five miles off highway over cross-country terrain at speeds up to 15 mph with ground and grade conditions requiring four-wheel drive.

During these tests, the functioning of the engine, power train, steering, brakes, truck and body lighting systems, controls, and instruments shall be observed for effective operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

4.5.2 Twin agent extinguisher test. The twin agent extinguisher unit on each production truck shall be tested in accordance with the requirements specified in 4.4.3.6.

4.6 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packaged in accordance with the contractor's standard practice. When specified (see 6.1), equipment shall be preserved and packaged in accordance with the mobile requirements of MIL-STD-281 with the level of preservation and packaging as specified (see 6.1).

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When a first article is required for inspection and approval (see 3.2, 4.2.1, and 6.3).
c. When crew-cab is required (see 3.7.13.1).
d. When front mounted winch is required (see 3.7.21)
e. When vehicle shall be processed in accordance with MIL-STD-281 with the level of preservation and packaging as required (see 5.1)

6.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.3 First article. When a first article inspection is required, the truck will be tested and should be a first production item consisting of one complete truck or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one complete unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Performance Prediction. Completed copies of SAE Truck Ability Prediction Procedure form and computation for low speed requirements for each vehicle model furnished under contract should be submitted as specified in the contract. The SAE work sheet item should include vehicle model number, wheelbase, engine model number, and vehicle type. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still, dry, air. The factors to be used in predicting truck ability are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

Table 1. Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2. Altitude factor. - 1.00
Table 3. Rolling factor. - 1.613
Table 4. Area factor. - 0.173
Table 5. Velocity factor. - 250.0
Table 6. Altitude factor. - 1.00
Table 7. Chassis friction horsepower. Use applicable po er unit gvw (gross vehicle weight) (to nearest, higher 1,000 pounds) and the engine r/min (revolutions per minute) (to nearest 100 revolutions) which is required for 50 mp/h geared speed. For gvw and engine speed beyond the range of this table, factors shall be extrapolated.
Table 8. Grade factor - 0.75
Table 8A. Correction factor. - NOT required.
Table 9. Road factor. - 0.0

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Navy - YD

Preparing activity:

Navy - YD

Project No. 4120-N187

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Commander
Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAG
NECESSAR
IF MAILEC
IN THE
UNITED STA

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Construction Battalion Center (156)
Port Hueneme, CA 93043

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side) Project No. 4120-N187

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-82080C(YD)	TRUCK, FIREFIGHTING; AIRCRAFT CRASH AND RESCUE, 11,000 POUND GVW, 4 BY 4

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.