| NOT MEASUREMENT |
| SENSITIVE |

MIL-T-82080D(YD)
24 August 1989
SUPERSEDING
MIL-T-82080C(YD)
16 December 1983

MILITARY SPECIFICATION

TRUCK, FIREFIGHTING: AIRCRAFT CRASH AND RESCUE, 16,000 POUND GVW, 4 BY 4

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a commercial, diesel-engine-driven, four-wheel, four-wheel drive truck with a service maintenance body equipped with a twin agent fire extinguisher unit, aqueous film forming foam (AFFF) and Halon 1211.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4210

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting and Starting.
BB-N-411 - Nitrogen, Technical.

MILITARY

MIL-F-24385 - Fire Extinguishing Agent, AFFF Liquid Concentrate, Sea Water.
MIL-B-38741 - Bromochlorodifluoromethane, Technical.

STANDARDS

FEDERAL

FED-STD-297 - Rustproofing of Commercial (nontactical) Vehicles
FED-STD-595 - Colors.

MILITARY

MIL-STD-281 - Automobiles, Trucks, Truck-Tractors, Trailers and Trailer Dollies, Preservation and Packing of.
MIL-STD-889 - Dissimilar Metals.
MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking, and Data Plates.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents. The following other Government document form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines: Certification and Test Procedures.
Interstate Motor Carrier Noise Emission Standards.
Motor Vehicle Air Pollution Standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852; or CFR, Title 40 should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which is current on the date of the solicitation (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME Boiler and Pressure Vessel Code, Section VIII.
ASME Pressure Vessels, Division I.

(Application for copies should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 412 - Evaluating Foam Fire Equipment Aircraft Rescue and Firefighting Vehicles.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE J534 - Lubrication Fittings.
SAE J537 - Storage Batteries.
SAE J551 - Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, Suite 304, OH 44313.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The truck shall be a four-wheel, four-wheel drive, diesel-driven truck cab-and-chassis having a gross vehicle weight rating (gvwr) of not less than 16,000 pounds (lb). The truck shall be equipped with a service maintenance body. The truck shall be provided with a skid mounted twin agent fire extinguisher unit installed in the load space of the maintenance body.

3.2 First article. When specified (see 6.2), the contractor shall furnish a truck for first article inspection and approval (see 4.2.1 and 6.3).

3.3 Standard truck, components, and accessories. Except as specified in 3.3.1 through 3.3.8, the truck, components, and accessories shall be standard or optional items which meet or exceed the requirements of this document. All items shall be as represented and rated in the manufacturer's sales information, including special or mounted equipment. sales information shall be limited to specifications and technical material identical to that furnished to the authorized company representative for selection of truck models and components.

3.3.1 Drain plugs. Drain plugs installed in the rear axle shall be of the permanent type.

3.3.2 Heavy-duty cooling system. A heavy-duty cooling system shall be furnished that shall maintain engine coolant at a temperature below the boiling point with truck loaded to rated gvw, and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 110 Fahrenheit (F).

3.3.3 Coolant recovery system. An overflow coolant recovery system shall be furnished. The coolant recovery system shall include an unbreakable translucent reservoir of not less than 2-quart capacity. The reservoir shall be located in a position readily visible for checking coolant level.

3.3.4 Towing devices. Not less than two hooks, loops, or pins, mounted to the frame or to rigid members which are attached to the frame shall be furnished in front and rear of the truck for towing purposes.

3.3.5 Radio interference suppression. The vehicle shall be suppressed to limit the electromagnetic radiation in accordance with SAE J551. Any body equipment emitting radiation shall be suppressed to the same level as the vehicle chassis.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

3.3.6 Engine hour meter. An engine hour meter of the oil pressure type, having a totalizing mechanism of not less than 9,999 hours, shall be furnished for the truck chassis engine to register accurately the number of hours of operating time. The meter shall be rugged construction to insure continous trouble-free performance under severe operating conditions. Engine hour meter shall be mounted on the truck cab instrument panel or in the engine compartment in a readable location.

3.3.7 Air pollution control. Trucks shall comply with the EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicles Engines in effect on the date of manufacture.

3.3.8 Sound level. The exterior sound level produced by the truck shall not exceed the noise limits established by the EPA. The interior sound level shall be in accordance with DoT Federal Motor Carrier Safety Regulations, section 393.94.

3.3.9 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.4 Identical items. All units of the same classification furnished under any specific contract shall be physically and mechanically identical. The requirement includes parts, assemblies, components, and accessories. No deviations will be acceptable without written approval of the contracting officer.

3.5 Performance. The fully equipped truck, loaded to rated gvw, shall be capable of performing the following:

a. Parking brake holding the truck on a 30 percent grade in both ascending and descending positions.
b. Service brakes holding the truck on a 30 percent grade in both ascending and descending positions.
c. Service brakes bringing the truck to a stop within a braking distance of 30 feet from a speed of 20 miles per hour (mph) on a dry, smooth level surface free from loose material.
d. Maintaining a maximum speed of not less than 55 mph on dry, level, paved roadway.
e. Accelerating on a level road from a standing start to a speed of 50 mph in 30 seconds.
f. Maintaining a sustained speed when ascending a 30 percent grade in low speed range.
g. There shall be no evidence of body distortion, water leakage, tire and body contact, malfunction of components, irregular chassis noise, vibration or sway, when subjected to a road test of 50 miles over paved roadway at not less than 55 mph; 25 miles over graded dirt roadway at not less than 25 mph; and 25 miles off highway over cross-country terrain at speeds up to 15 mph with ground and grade conditions requiring four-wheel drive.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.6 General design.

3.6.1 Federal Motor Vehicle Safety Standards. The truck shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.6.2 Weight rating and distribution. The manufacturer's gvwr for the fire truck chassis furnished shall not be less than 16,000 lb. The total gross weight of the complete truck shall not exceed the manufacturer's gvwr when fully equipped as specified herein, including specified equipment, serviced with fuel, water and lubricants, and fully charged twin agent fire extinguisher unit as specified in 3.9, 3.9.1 and 3.9.2. Weight distribution ratio between the front and rear axles shall be such as to insure positive traction at the front and rear wheels and positive steering at the front wheels under all operating conditions specified herein.

3.6.3 Cab-to axle. The cab-to-axle dimension shall be not less than 60 inches on truck with conventional cab and the cab-to-axle dimension shall be not less than 54 inches on truck with crew cab.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. Unless otherwise specified, none of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification.

3.7 Chassis components.

3.7.1 Engine. The truck engine shall be a diesel engine having the horsepower, torque and speed characteristics to satisfactorily meet all required truck performance specified herein at specified gvwr. The diesel engine shall be a liquid cooled, compression ignition, 2-stroke or 4-stroke cycle engine. The engine furnished shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

3.7.1.1 Oil filter. Full flow type oil filter shall be furnished.

3.7.1.2 Governor. If required, an engine governor shall be furnished and set and sealed to limit engine to maximum recommended operating speed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.7.2 Electrical system.

3.7.2.1 Starting system. For diesel engine driven vehicles, a 12- or 24-volt (V) direct current (dc) starting system, with a 12-Vdc lighting system, shall be furnished. A minimum 130-ampere alternator shall be furnished. Engine starting equipment shall include an ether starting system or glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. Measured shot type ether systems shall be key-operated or manually-operated from the driver's compartment and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

3.7.2.2 Batteries. A dual 12V battery system shall be furnished. Each battery in the system shall be 12V maintenance free with characteristics listed in W-B-131. Each battery shall be rated in terms of cold cranking capacity at 0 degrees (°) F in accordance with SAE J537. Batteries shall be mounted in an acid resistant box or frame in a protected and easily accessibly location.

3.7.2.3 Lighting. All truck lights, reflectors, and wiring shall be as specified herein and shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.12, 393.19 through 393.31 and 393.33. Lights and reflectors shall not be mounted on vertical surfaces of rub rails or bumpers. Rear identification lights shall be protected from damage when mounted near the rear bumper step.

3.7.2.4 Lights. All lights shall be mounted in such a manner as to prevent being obscured by riding personnel or mounted equipment. All metal rims, shells, mounting arms, and bases of all exterior lights shall be chromium plated. Stoplights and tail lights shall be flushed mounted at the rear of the body. The following additional lighting shall be furnished and shall be provided with overload protection:

a. Two chromium plated spotlights, one on each side of cowl or windshield. One end of the light housing shall be equipped with a clear lens, the other end with a red lens. The red light shall function as a flashing light with control switch located at the light. Controls for the spotlight beam and housing movement shall be inside the cab. Movement shall be through a horizontal included angle of at least 270°, and a vertical angle of at least 90° above and 35° below horizontal.
b. Two shielded engine compartment lights, arranged to illuminate both sides of the engine. Switch(s) are to be mounted on the cab and identified.
c. Two automatic back-up lights, not less than 4-inch diameter, flush mounted at rear of body.
d. Two rear mounted, alternate flashing, red warning lights. The lights shall be sealed beam and not less than 4 inches in diameter. The control switch shall be in the cab on the instrument panel, and shall be identified.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

3.7.3 Fuel system. Fuel system shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.65 and 303.67.

3.7.3.1 Air cleaner. An air cleaner shall be furnished.

3.7.3.2 Fuel tank. The fuel tank shall be the manufacturer's standard, and the fuel tank capacity shall be not less than 40 gallons. When more than one tank is furnished means shall be provided to assure equalized fuel level in both tanks.

3.7.4 Exhaust system. Exhaust system conform to DoT Federal Motor Carrier Safety Regulations, section 393.83. Muffler and other portions of exhaust system shall be manufacturer's standard. A shield plate shall be installed, where necessary to prevent spilled fuel from coming in contact with the exhaust system.

* 3.7.5 Automatic transmission. The truck shall be provided with an automatic transmission of a fixed ratio type and shall provide continuous drive. The fixed ratio type shall include a hydraulic torque converter and not less than four forward speeds. The normal driving range selector position shall provide not less than four gear ratios without movement of the selector.

3.7.5.1 Transfer case. A two-speed type transfer case shall be provided. The transfer case shall provide for driver selection of either two-wheel or four-wheel drive.

3.7.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.7.7 Frame. Chassis frame shall be manufacturer's standard for the truck furnished.

3.7.8 Suspension. Truck shall be equipped with suspension system, with components having a rated capacity at least equal to the load imposed on each member, plus at least 10 percent, measured at the ground, with truck loaded to specified gvwr. When suspension is rated at the spring pads, unsrung weight shall be deducted. Truck shall be equipped with hydraulic, double-acting, shock absorbers on the front and rear wheels.

* 3.7.9 Axles. The front and rear axle ratings shall be at least equal to the loads imposed measured at the ground with the vehicle loaded to specified gvwr. Rear axle shall be provided with positive-traction or limited-slip differential.

* 3.7.10 Wheels, rims, tires, and tubes. Truck shall be equipped with single front and dual rear wheels. Rim sizes shall be the same for all wheels on the truck. Tire size and ply rating (load range) shall be the same for all tires on the truck. Rim and tire ratings shall conform to TRA recommendations for the type and size of tires furnished. Disk type wheels shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.7.10.1 Tires. Tires shall be steel belted radial, tube or tubeless type with nondirectional mud and snow tread. Tires shall have a rated capacity at least equal to the load imposed on each tire measured at each wheel, at the ground, with truck loaded to specified gvwr.

3.7.10.2 Inner tubes. When tube-type tires are furnished, inner tubes shall be of proper size for tires furnished. When mounted on other than drop center rims, tire flaps shall be installed.

3.7.10.3 Spare wheel assembly. A spare wheel and mounted spare tire shall be furnished and stowed in the truck for shipment. The spare tire shall be of the same size, tread design, and ply rating as the tires in use on the truck.

3.7.11 Brakes. Brakes shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.40, 393.41, 393.42, 393.45 through 393.51, and as specified herein.

3.7.11.1 Service brakes. Truck shall be equipped with power assisted hydraulic actuated or full air four-wheel service brakes.

3.7.11.2 Parking brake. Truck shall be equipped with parking brake.

3.7.12 Steering. Truck shall be equipped with power assist steering. Mechanical type steering capability shall be available in event of loss of power assist steering.

3.7.13 Cab. Unless otherwise specified, the chassis manufacturer shall furnish any type of his standard or optional full width cab. Cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, with at least the curbside door equipped with external, key-operated lock. Drip rails shall be installed above the cab doors. Cab shall have upholstered, full-width, adjustable seat and back or individual, adjustable, driver's seat and individual passenger seat. The color of the upholstery and the interior finish shall be compatible with the exterior color. White upholstery shall not be furnished. Interior lighting shall be provided. Manufacturer's standard fastenings and two pairs of seat belts shall be installed on the vehicle.

3.7.13.1 Crew-cab. When specified (see 6.2), a four-door, crew-cab shall be furnished in lieu of the standard full width cab. Cab shall be equipped with two upholstered, full width, seats and backs. The front seat shall be adjustable. Fastenings and three pairs of seat belts shall be installed for both front and rear seats. Cab doors shall be equipped with locks operable from inside the cab through mechanical linkage, with both front doors equipped with external key-operated locks. Cab doors shall have windows with crank-operated window regulators. A rear window shall be provided. Interior lighting shall be provided. The cab roof shall be of one one piece construction; or, if welded, the roof shall give the appearance of one piece, with weld seams being continuous, waterproof, and free of visible seams, bumps or protrusions. When furnished by the manufacturer, full length drip moldings shall be mounted above doors. When crew cab is specified, the cab-to-axle dimension shall be measured from the back face of the crew-cab.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

3.7.13.1.1 Seat spacing. With the front seat adjusted to the extreme rearward position there shall be not less than 30 inches, measured in a horizontal plane, between the front of the rear seat-back and the rear of the front seat-back. A kick-space height of not less than 2-3/4 inches shall be maintained between the floor and the rear of the front seat in all positions of adjustment. Leg room and space forward of the front seat shall be equivalent to that provided ahead of seat in a two-door standard cab.

3.7.14 Windshield wipers and washers. Truck shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed and intermittent type and operated by electric motor(s).

3.7.15 Heater and defroster. Hot water heater shall be provided. Heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to floor and to defroster louvers. Heater shall be complete with blower and mounted controls convenient to the driver.

3.7.16 Controls and operating mechanism. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit to operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

3.7.17 Front bumper. Except as specified herein, manufacturer's standard front bumper shall be furnished. When front mounted winch is furnished, the front bumper shall be the chassis manufacturer's or winch manufacturer's standard full width type designed for installation and operation of front mounted winch.

3.7.18 Rear end protection. Rear end of truck shall be protected in accordance with DoT Federal Motor Carrier Safety Regulations, section 393.86. A combination channel rear bumper with riser and full width safety tread step shall be provided. The step tread width shall be not less than 10 inches in width, from front to rear. The rear step shall be capable of supporting a 200 lb firefighter.

3.7.19 Rearview mirrors. Outside rearview mirrors, each with at least three supporting arms, shall be mounted on each side of the cab. Combination (flat and convex) mirrors, enclosed in a common housing, shall be furnished. Each combination shall have at least 40 square inches of flat reflective area and a convex surface having at least 20 square inches of reflective area.

3.7.20 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

a. Key type ignition switch.
b. Ammeter or charging indicator.
c. Fuel gage.
d. Oil pressure gage or indicator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

e. Engine temperature gage or indicator.
f. Speedometer with recording odometer.
g. Dual sunvisors.
h. Door mounted armrest on driver's side.
i. Driver's compartment ventilator other than window.
j. Manufacturer's standard electric horn.

3.7.21 Winch. When specified (see 6.2), a winch assembly shall be provided on the front of vehicle and shall be powered from the vehicle electrical system. The winch shall be wound with not less than 150 feet of wire rope with hook. Winch single line pull rating on the bare drum and the nominal breaking strength of the wire rope shall be not less than 8000 lbs. Wire rope shall be of improved plow steel, preformed, regular lay construction with fiber core. Winch shall be suitable for hoisting as well as for assisting truck to negotiate difficult terrain. Winch shall have forward and reverse drum-drive and a drum clutch to permit free spooling of the cable. Winch shall be equipped with a four-way roller guide.

3.8 Body. The fire truck shall be equipped with a body which shall incorporate the fire extinguishing twin agent unit, equipment compartments, rear platform, and firefighting accessory equipment. The body and compartment construction structural members shall be aluminum alloy having not less than 42,000 pounds-force per square inch (psi) ultimate strength and 35,000 psi yield strength with thickness of not less than 0.125 inch. The body shall be reinforced at all stress concentration points where equipment and compartments are attached. The body shall be designed for mounting on a 16,000 lb. GVW cab and chassis with dual rear wheels.

3.8.1 Body dimensions.

Dimensions	Inches
Overall length, not less than	108
Overall width, not less than	77
Depth of compartment sections, each outside dimension, not less than	20
Height of compartment sections (Height from floor line to top of compartment sections)	Same height as truck cab
Center load space width, between wheel wells not less than	42
Center load space width between compartments not less than	47

3.8.2 Material and construction for equipment compartments. All equipment compartments specified here on shall be made of aluminum. The width of the side compartments shall be not less than 20 inches. The height of the compartments shall be from the running board to the same height of the truck cab. Each compartment shall have a door, hinged forward with full length stainless steel hinges and recessed stainless steel paddle type handles operable with heavy gloved hands. The door shall be heavy-duty, reinforced, double panel type with exterior plate thickness to be not less than 0.090-inch

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:39Z
Check the source to verify that this is the currenversion before use.

aluminum, and the interior door panel to be constructed of not less than 0.090 inch aluminum. The compartment doors shall be full gasketed with heat resistant, neoprene sponge type material to insure a watertight seal. The doors shall be equipped with a stainless steel, spring type door hold open device, that will limit door opening will allow for easy one hand release for closure. Door catches and latches shall be heavy-duty type and shall be corrosion-resistant. Each compartment shall be illuminated. The compartment lights shall be controlled by a master control switch, with indicator light, located on the pump instrument panel. The compartment top shall be of continuous heavy-duty aluminum diamond plate surface, the same as furnished for the running boards, walkway, and rear platform surfaces. Provisions shall be incorporated into the compartment design to permit flushing and cleaning of the inside. Design of the compartment shall prevent entry of dirt and water with doors closed. Drip rails shall be provided over each compartment.

* 3.8.3 Body compartment arrangement. Compartment arrangement and characteristic details shall be as follows:

a. One full height vertical compartment with two adjustable shelves shall be provided at front of the rear wheels (behind cab) on each side of the body. These front compartments shall have double doors vertically hinged with a "clear" door opening of at least 44 inches high and 31 inches wide.
b. One full height vertical compartment shall be located at the rear of the wheel housing on each side of the body. These rear body compartments shall have single, vertically hinged doors with "clear" opening of at least 44 inches high and 22 inches wide.
c. A center compartment above the near wheels shall be provided on each side of the body. These center compartments shall have double doors, vertically hinged with "clear" door opening of at least 36 inches wide and 25 inches high.

3.8.4 Deck lights. The chromium plated, 6-inch diameter,sealed beam, 100 watt deck lights (spotlights) with weatherproof switch shall be provided, one each mounted at the rear of the truck on top of each side body compartment section. The deck lights shall be adjustable, capable of 360° rotation and 180° vertical movement.

3.8.5 Handrails. A handrail shall be provided and mounted at the rear of each side body compartment section for use of personnel in mounting rear bumper step (see 3.7.18).

3.8.6 Warning light. A cab roof mounted lightbar with built-in public address system speaker, shall be furnished. Light beams shall be reflected to the front and rear. The warning light and roof bar shall be Federal "Twinsonic", Dietz "Omni-chief", or equal. The sealed beam lamps shall be high intensity, red and white in color. The light system housing shall be clear. A single control shall be provided with a red pilot light indicating the "ON" position. The pilot light shall be located in the cab on the instrument panel. The speaker shall be as specified in 3.8.6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

3.8.6.1 Electronic siren, public address, and radio amplifier systems. An electronic siren system with selector controls for the siren, public address and radio amplification through an external speaker shall be provided. System sound intensity shall be not less than 98 decibels at a distance of 100 feet from the speaker. The speaker shall be at least 100 watt. The amplifier and controls shall be installed inside the vehicle in a location accessible to the driver and assistant driver. A microphone of the magnetic noise canceling type, connected by a coiled cord, shall be provided and located in a position convenient for use. Microphone stowage shall be provided on the instrument panel. The system shall permit broadcasting routine and emergency announcements from an on-board Government installed radio. The amplifier shall include volume control and selection of "Radio", "P.A.". "Manual", "Yelp", "Wail", and "HiLo" (European) modes. Switch position shall be identified. A two-way radio audio top cable for rebroadcasting 2-way messages through the PA system shall be furnished. The speaker shall be fitted with a weather-proof housing and shall be suitable for installation on the cab roof bar.

3.9 Twin agent fire extinguisher unit. A skid-mounted twin agent fire extinguisher unit shall be provided and installed in the load space of the service maintenance body. The twin agents shall be an AFFF fire-fighting agent and a Halon 1211 firefighting agent. The AFFF agent shall conform to MIL-F-24385. The Halon 1211 agent shall conform to MIL-B-38741. The twin agent fire extinguisher unit shall consist of an AFFF agent tank, Halon 1211 agent tank, nitrogen cylinder(s), piping, pressure regulators, controls, discharge hoses, nozzle, hose reel, and other equipment specified herein. The overall height of unit shall be not more than 50 inches and the overall width of unit shall be not more than 46 inches. The skid frame shall fit between the standard 42-inch width wheelwells in the center load space of the truck body. The overall length of the twin agent unit shall be not more than 98 inches and the weight of the fully charged unit shall be not more than 3,800 lb. The twin agent fire extinguisher unit performing through 100 feet of 1-inch hose and nozzle, as specified in 3.9.7 shall be capable of the following:

a. Discharging the AFFF premixed solution at an ambient temperature of 65°F to 85°F with constant flow rate of 60 gallons per minute (gpm) at 100 pounds-force per square inch gage (psig) pressure.
b. Discharging the Halon 1211 at an ambient temperature of 65°F to 85°F within a minimum-maximum range of 5.0 to 5.5 pounds per second at 100 psig pressure.

The twin agent fire extinguisher unit shall be capable of providing simultaneously an average flow rate of 60 gpm of AFFF agent and 5.5 lb per second of Halon 1211 at any hose length from 25 to 100 feet.

3.9.1 Agent tank, AFFF. The AFFF tank shall have a capacity of not less than 200 gallons of 6 percent AFFF liquid concentrate solution. The tank shall be constructed and certified in accordance with the current ASME Boiler and Pressure Vessel Code, section VIII, Division 1, for a design working pressure of at least 230 psig. The tank shall be fabricated from material resistant to corrosion by the AFFF agent to be stored or a suitable lining

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the currentversion before use.

material shall be provided. A fill opening at least 4 inches in diameter and a drain line 1 inch in diameter shall be provided. A fill opening shall be provided with straight through unencumbered access to the tank without dog-legs or off-sets, to permit stirring and gaging of the contents and inspection of the interior. A reseating type relief valve, capable of preventing pressures in excess of 110 percent of the design working pressure shall be provided on the tank. A temperature relief valve or fuse plug set for a minimum of 195°F shall be installed. A vent line shall be provided on the top of the tank. This vent line shall be provided with a quarter-turn valve for blowdown purpose and to insure zero pressure before opening the fill cap. The vent line may be used to purge the hose line.

3.9.1.1 Fill cap. The fill cap on the AFFF tank shall be provided with a safety vent hole so that cap is pressure venting while at least 3-1/2 are still engaged. The fill cap arrangement shall be such that the male threads are a part of the tank and the female threads are a part of the tank and the female threads are a part of the cap. When required, an extension spanner wrench for easy removal of the fill cap shall be supplied and installed beneath the hose real.

3.9.1.2 Tank funnel. A funnel shall be provided of sufficient size and length to facilitate easy loading and preclude foaming of the AFFF liquid agent.

* 3.9.2 Halon 1211 agent system. A Halon 1211 liquified gas type agent system shall be provided. The system shall consist of an agent tank with a capacity of 200 lb of agent; a cylinder of high pressure nitrogen for expelling the agent and purging the system; a manual rewind hose reel assembly as specified in 3.9.8, fitted with 100 feet of one-inch hose, as specified in 3.9.7, and a Halon nozzle as specified 3.9.9 and related control valves, gages, and piping.

* 3.9.2.1 Halon 1211 agent tank. The Halon 1211 agent tank shall be constructed and certified in accordance with section VIII, Division 1, of the current ASME Boiler and Pressure Vessel Code, and shall operate at pressures of at least 230 psi. The tank shall be a horizontal type cylinder designed for easy maintenance and handling. The Halon 1211 agent tank shall be provided with the necessary components that allow for servicing and filling the tank. Couplings shall be of the quick disconnect type. The Halon tank shall be provided with a float-type liquid level dial gauge. The Halon 1211 charging hose shall be furnished with the tank fill system. All connectors and gages shall be readily visible and installed at an accessible location. The tank shall be provided with a spring-loaded relief valve capable of preventing pressure in excess of 110 percent of the design working pressure.

3.9.3 Nitrogen propellant system. A nitrogen gas propellant system for the twin firefighting agents shall be provided. Nitrogen gas cylinder(s) having adequate capacity and pressure to provide performance requirements specified in 3.9 shall be furnished. The propellant gas cylinder(s) shall be in accordance with DoT requirements and regulations. The gas cylinder(s) shall be compatible with nitrogen gas conforming to BB-N-411, type 1, class 1,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

grade B. The cylinder(s) shall be provided with a pressure gage indicating the cylinder gas pressure and shall be located within view of the operator for ease in checking. The pressure gage shall indicate at all times the pressure in the nitrogen gas cylinder(s) without opening any valves. A quick-opening lever operated valve, requiring only a quarter turn or a 90° traverse lifting of a lever, to release the nitrogen gas and capable of being easily reset by manually turning, cocking, or repositioning valve handle or pin shall be provided, and shall be located at the control panel (see 3.9.6). Design and placement of the nitrogen gas cylinder(s) shall be such that provision shall be made for quick and easy replacement after each use. The total capacity of the nitrogen cylinder(s) shall be such that when the cylinder(s) is fully charged, sufficient nitrogen propellant shall be available to fully expel all agents, and permit purging of all piping and hose lines after use. Safety relief valve shall be provided on nitrogen gas cylinder(s). The nitrogen gas cylinder(s) shall be empty when the truck is prepared for shipment. A tag shall be attached to the cylinder(s) in a conspicuous location, indicating: CYLINDER(S) ARE EMPTY, FILL WITH NITROGEN GAS BEFORE PLACING INTO OPERATION. Spare nitrogen cylinder(s) of the same number, size and capacity to provide performance requirements specified in 3.9 shall be furnished and stowed in the truck for shipment.

3.9.4 Piping. A piping system with an effective nitrogen gas pressurization to insure proper discharge of AFFF agent and Halon 1211 agent shall be provided. Piping system shall include any additional agent tank fittings and valves required for the pressurization, discharge, venting, and flushing of the twin agent fire extinguisher unit. Piping shall be designed to minimize friction losses at the design flow rates. The piping system shall permit depressurization and purging of all lines and tanks without loss of remaining agent. Check valves shall be used to prevent backflow into the gas regulators from the AFFF agent tank. Check valves shall be used to restrain the agents from entering the hose lines until pressurization takes place. All valves and piping shall be resistant to corrosion by the AFFF agent. No black or galvanized iron, if furnished, shall be in contact with the AFFF. Potential galvanic corrosion points shall be eliminated by proper choice of material. Care shall be taken to prevent loosening of joints or breaking of pipes or connection due to shock and vibration. Approved flex type hose may be furnished.

3.9.5 Pressure regulator(s). The gas flow rate of the regulator or regulators and gas piping system shall effect a pressure level of 80 percent of the working pressure within 10 seconds of cylinder valve operation on both of the agent tanks. Dead end setting of the regulator(s) shall be within 95 to 110 percent of maximum working pressure. The regulator(s) shall have an integral relief valve set to relieve at 110 percent of the tank's design working pressure and be capable of handling the full regulator gas flow. The regulator pressure setting shall be adjusted by the manufacturer and sealed in a manner to discourage manipulation in the field.

3.9.6 Controls. Operating controls and gages to pressurize the twin agent fire extinguisher unit shall be located near the nozzle stowed position within reach and view of the operator as he is positioned at the rear of the truck. Not more than two manual control manipulations per agent (exclusive of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

discharge nozzle) shall be allowed to pressurize twin agent unit to the discharge nozzle. Operational instruction and product marking plates specified in 3.9.11 shall be mounted on the control panel.

3.9.7 Discharge hoses. The discharge hoses for both AFFF and Halon 1211 agent shall be noncollapsible twin hose of 1-inch inside diameter and shall be 100 feet long. The 1-inch hose shall be used for the AFFF agent and the Halon 1211 agent. The twin discharge hose shall be capable of withstanding twice the full tank pressure and shall be tested with couplings to this pressure for 5 minutes with no leakage or damage.

3.9.8 Hose reel. A manual hose reel shall be an integral part of the extinguisher unit, positioned so that when the extinguisher unit is placed on the truck bed, access to the nozzle shall be from the rear of the truck within easy reach of a firefighter while standing on the ground. The design shall provide for ease of rapid removal and restowage of the 100 foot length twin agent hoses. A means of restraining the discharge nozzle in a readily accessible stowed position shall be incorporated. The reel shall be equipped with adequate vertical and horizontal rollers and guides to reduce hose chafting and friction when on either side of the truck. The reel shall be equipped with an adjustable positive tension friction brake to prevent hose from unreeling when not desired. The discharge hoses shall be capable of being used in incremental payout lengths and shall not be required to pay out the full 100 feet for operational use, a removable crank handle shall be provided and provisions shall be made to properly stow the handle after reel has been rewound and not in use.

3.9.9 Discharge nozzle. The twin agent unit discharge hoses shall be provided with a dual agent handline nozzle that dispenses both Halon 1211 and AFFF agent. The twin agent nozzle assembly shall incorporate dual dispensing barrels in an over/under arrangement mounted on a single pistol grip handle. The over/under arrangement Halon 1211 discharge barrel shall be located above the AFFF barrel. Both Halon 1211 and AFFF agent valves shall be of the quarter turn ball type with paddle type handles. The AFFF agent discharge tip shall be a constant flow variable stream type with a flow rating of 60 gpm at 100 psig. The AFFF discharge shall have a straight stream performance range of at least 50 feet at a 3-foot width and a dispersed pattern of at least 20 feet at a range of 15 to 20 feet. The Halon nozzle shall be position type -- vapor discharge and straight stream. The nozzle shall discharge at a rate of 5-5-1/2 lb per second and shall deliver a straight stream with a range of 35 feet and a vapor stream of 10-15 feet from the end of the nozzle.

3.9.10 Skid. The twin agent fire extinguisher unit shall be mounted on a skid. Skid shall be crashworthy secured with removable fastenings to the floor of the maintenance body. The framing incorporated with the skid mount shall be provided with four lifting eyes for placing and removing unit from the truck bed.

3.9.11 Operation and product markings. Destruction resistant, embossed, aluminum plates shall be permanently and legibly marked for identification and use of the extinguisher unit. The plates shall be permanently mounted on the control panel at the rear so that they may be easily read by personnel standing on the ground at the rear of the truck.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

* 3.9.11.1 Operation markings. A plate or plates shall be marked with the following:

a. Complete and detailed activating instructions for placing the equipment in operation shall be printed in not less than 1/2 inch red letters on a contrasting background.
b. After use instructions and maintenance instructions shall be provided.
c. A statement shall be shown that the gas cylinder(s) shall be replaced if the pressure during storage drops below a specified level (Contractor to insert proper level.)
d. Storage and maintenance instructions shall include precautions against subfreezing temperature exposure of the equipment.

3.9.11.2 Product markings. The plate shall be marked with the following:

a. Name and model number of unit.
b. Name and address of manufacturer.
c. Serial number of unit.

3.9.11.3 Agent refilling table. A table for the AFFF agent shall be provided, indicating the amount of agent necessary to either completely or partially refill the agent tank after use, by measuring the distance in inches from the top of the tank to the remaining level of agent.

3.9.12 Agent identification. AFFF agent tank fill cap shall be painted blue. Halon 1211 tank shall be painted red.

3.9.13 Fire rescue equipment. The following items of rescue equipment shall be furnished and stowed in the body compartments:

A SIERRA Aircraft Rescue Crash Kit (USAF developed) identical to HALPRIN SUPPLY Company Model CRK-5 or equal.

3.10 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 psi or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.11 Treatment and painting. The exterior and interior surfaces of the truck, cab, maintenance body, equipment cabinets, and the exterior surfaces of the fire extinguisher unit shall be cleaned, treated, and painted in accordance with MIL-STD-1223 requirements except that the exterior trim shall be painted to match the vehicle exterior color. The vehicle finish color shall be gloss lime yellow No. 13670 as listed in FED-STD-595. The finish color of the equipment steel cabinet tops and the top of the rear step bumper shall be aluminum. If a fiberglass body is provided, the color as specified shall be in the gel coat.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

3.12 Rustproofing. The truck cab, frame, wheel wells, and all exposed underside body metal components shall be rustproofed in accordance with FED-STD-297.

3.13 Identification marking and data plates. Identification marking, registration numbers, and data plates for the truck shall be in accordance with MIL-STD-1223, as specified for the Navy.

3.14 Servicing and adjusting. Prior to acceptance of the truck by the Government, the contractor shall service and adjust the each truck for immediate operational use as required in the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.
b. Adjustment of brakes.
c. Proper functioning of all lighting and electrical systems.
d. Wheel alignment (when required).
e. Adjustment of engine to include tune-up (when required).
f. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.
g. Cooling system filled to capacity with a clean solution of equal parts by volume of water and antifreeze (ethylene glycol).

The truck shall be conspicuously tagged to identify the lubricants and their temperature range.

3.15 Workmanship.

3.15.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.15.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.15.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.15.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.15.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

* 3.15.6 Dissimilar metals. Unless protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

4.2.1 First article inspection. The first article inspection shall be performed on one truck when a first article is required (see 3.2 , 6.2, and 6.4). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.5, and the packaging inspection of 4.6.

4.4 First article tests. When first article is required, the first article shall be subjected to the tests specified in 4.4.1 through 4.4.3.6. The first article tests shall be conducted by the contractor at test sites that will enable the truck to perform and be evaluated for compliance to the tests specified in 4.4.1 through 4.4.3.6. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all trucks until corrective action has been taken.

4.4.1 Truck weight. The truck shall be weighed to determine curb weight and distribution of curb weight on front and rear axle. The imposed loading on front and rear axle will be computed using the curb weight, the operator weight at 175 lb and the payload uniformly distributed over the vehicle load area, to provide the specified rated gvw. Calculated imposed loads on front and rear axle will be utilized to ascertain that the suspension and tires furnished are of adequate capacity to meet specification requirements.

4.4.2 Operational tests. The truck shall be loaded to its rated gvw, as specified in 3.6.2, and operated to verify performance requirements specified in 3.5a through g. During these tests, the functioning of the engine, power train, steering, brakes, truck and body lighting systems, controls, and instruments shall be observed for effective operation.

4.4.3 Twin agent fire extinguisher unit tests.

4.4.3.1 Agent tanks pressure test. The AFFF agent tank and the Halon 1211 agent tank shall be pressure tested. Each tank shall be pressurized to 150 percent of the design working pressure and the pressure held for 15 minutes. There shall be no evidence of leakage, permanent distortion or other defects. Openings not subjected to this test shall be plugged.

4.4.3.2 Agent tank pressure relief valve test. Each agent tank pressure relief valve shall be tested to determine conformance to 3.9.1.

4.4.3.3 Discharge hoses pressure test. Discharge hoses shall be hydrostatically tested to 600 psig pressure for 5 minutes to determine conformance to 3.9.7.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:39Z
Check the source to verify that this is the currentversion before use.

4.4.3.4 Operating characteristics test. Each discharge nozzle shall be individually performance tested as specified herein at a hose length of 100 feet. The AFFF product, as produced by the specified nozzle in 3.9.9, shall be sampled and tested in accordance with procedures set forth in current edition of NFPA No. 412. The resultant AFFF shall have a minimum expansion of three with a minimum 25 percent drain of 1 minute. The AFFF nozzle shall have performance pattern as specified in 3.9.9. The rate of discharge of the Halon 1211 shall be 5.0 to 5.5 lb per second at the beginning of discharge and the effective reach of the Halon 1211 stream shall be as specified in 3.9.9. A minimum of 95 percent of the Halon 1211 contents shall be discharged at a rate not less than 5 lb and not more than 5.5 lb per second. The full contents of each agent tank shall be discharged during the above individual tests. Each agent container shall attain 80 percent of their working pressure within 10 seconds of system activation.

4.4.3.5 Recharging test. After complete discharge of the agent tanks during tests in 4.4.3.4, the unit shall be fully recharged in order to observe any problems or inadequacies in filling and to make ready to perform tests specified in 4.4.3.6.

4.4.3.6 Dual discharge operating test. A performance test shall be conducted with both AFFF and Halon 1211 discharge nozzles operating simultaneously with 50 feet of the discharge hoses still remaining on the reel. Average rate of flow shall be not less than 60 gpm for AFFF and not less than 5 and not more than 5.5 lb per second for the Halon 1211. The full contents of each agent tank shall be discharged during the test.

4.4.4 Production sample. Upon acceptance of the first article, it shall remain at the manufacturing facility as a production sample and be the last truck shipped on the contract. The first article shall be reconditioned indicating replacement of of abnormally worn parts and paint touch-up or repainting, prior to delivery to enable it to be accepted as a contract item. The contractor shall maintain the first article in a serviceable condition for the duration of the contract.

4.5 Quality conformance tests. Each production truck shall be operated and tested as specified in 4.5.1 and 4.5.2.

4.5.1 Operational tests. Each production truck shall be loaded to its rated gvw as specified in 3.6.2 and operated as follows:

a. Five miles over paved roads at speeds not less than 65 mph.
b. Five miles over graded dirt roads at speeds up to 25 mph.
c. Five miles off highway over cross-country terrain at speeds up to 15 mph with ground and grade conditions requiring four-wheel drive.

During these tests the functioning of the engine, power train, steering, brakes, truck and body lighting systems, controls, and instruments shall be observed for effective operation.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:39Z
Check the source to verify that this is the current version before use.

4.5.2 Twin agent extinguisher test. The twin agent extinguisher unit on each production truck shall be tested in accordance with the requirements specified in 4.4.3.6.

4.6 Packing instruction. The vehicle shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packaged in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved and packaged in accordance with the mobile requirements of MIL-STD-281 with the level of preservation and packing as specified (see 6.2).

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The firetruck covered by this document is intended for aircraft crash and rescue operation within military installations.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required for inspection and approval (see 3.2, 4.2.1, and 6.4).
d. When crew-cab is is required (see 3.7.13.1).
e. When front mounted winch is required (see 3.7.21).
f. When vehicle shall be processed in accordance with MIL-STD-281 with the level of preservation and packing as required (see 5.1).

6.3 Data requirements. When this document is used in an acquisition and data are required to be delivered, the data requirements should be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data should be delivered by the contractor in accordance with the contract or purchase order requirements.

6.4 First article. When a first article inspection is required, the truck will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Diesel engine
Fire extinguishing truck
Firefighting truck
Performance

6.6 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Navy - YD

Preparing Activity:
Navy - YD

(Project 4120-N343)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-82080D(YD)	Truck, Firefighting: Aircraft Crash and Rescue, 16,000 Pound GVW, 4 By 4

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:39Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Code 156
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:39Z
Check the source to verify that this is the current version before use.