MILITARY SPECIFICATION

HOOD, ANTIFLASH

This amendment forms a part of Military Specification MIL-H-2849D dated 23 June 1980, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Paragraph 2.1: Delete and substitute:
"2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Under "SPECIFICATIONS FEDERAL": Add "NN-P-71 - Pallet, Material Handling, Wood, Stringer, Construction, 2 way and 4 way"

Under "SPECIFICATION MILITARY": Add:
"MIL-P-15011 - Pallet, Material Handling, Wood, Post Construction, 4 way Entry"
"MIL-T-43548 - Thread, Polyester, Cotton-covered and Rayon Covered"

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-16T15:48Z
Check the source to verify that this is the current version before use.

PAGE 2

Under "STANDARD MILITARY": Add: "MIL-STD-147 - Palletized Unit Loads"

Before "LAWS AND REGULATIONS" insert the following paragraph:
"2.1.2. Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation."

Paragraph 2.2 Delete lines 1 through 4 and substitute the following:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation."

Add new paragraph:
"2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

PAGE 3

Paragraph 3.2: Delete and substitute:
"3.2 First article. When specified, the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.3 and 6.2)."

Paragraph 3.3.2, at the end of paragraph add: "As an alternate, cotton covered or rayon covered polyester thread, ticket no. 40, 3 ply of MIL-T-43548 may be substituted for the cotton thread."

Paragraph 3.3.3, Line 2, after class 1, add: "except that water repellent, mildew resistant treatment is optional."

Paragraph 3.3.4, line 2: Delete "Type I" and substitute "Type VI".

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:48Z
Check the source to verify that this is the current version before use.

PAGE 4

Paragraph 3.7, at the end of paragraph: Delete period and add: "provided the finished hood is identical to that produced by following the sequence as listed in Table II."

PAGE 6

Table II, operation 4: Delete stitch type "517 and 518".

Table II, Operation 5: Delete paragraph "a" and substitute "a. Stitch continuously around the raw edge of hem simultaneously positioning and catching the bottom edge of the label in the line of stitching at center back. Stitch type 503, 504, 602, Seam type EFd-1, Stitches/Inch 10-12, Thread 40/3, 40/3."

PAGE 7

Paragraph 4.1, Line 2: Delete "or purchase order".

Paragraph 4.1.1, Delete paragraph and substitute:
"4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

Add new paragraph:
"4.1.2 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification."

Paragraph 4.4, line 3: Delete "herein".

PAGE 10

Paragraph 4.4.2.1 Visual examination. Following last defect add:
"4.4.2.2. Dimensional examination. The hoods shall be examined for dimensional defects. Any dimension that is not within specified tolerances shall be classified as a measurement defect.

Source: https://assist.dla.mil -- Downloaded: 202640-16T15:48Z
Check the source to verify that this is the current version before use.

4.4.2.3 Inspection levels and acceptable quality levels. The inspection levels and the acceptable quality levels (AQL's) expressed in defects per 100 units (DHU) shall be as follows:

	AQL	Inspection level
For visual examination in 4.4.2.1:		
Major	2.5	II
Major and Minor (combined)	10.0	II
For dimensional examination in 4.4.2.2.		
One class	4.0	S-3

4.4.3 Examination of packaging requirements. An examination shall be made to determine that packaging, packing, and marking comply with Section 5 requirements of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be on the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling, bulged or distorted container.
Content	Number of hoods per bundle is more or less than specified.1/ Number of bundles per shipping container is more or less than specified.2/

1/ For this defect, one bundle from each shipping container in sample shall be examined.
2/ For this defect, two shipping containers in the sample shall be examined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:48Z
Check the source to verify that this is the current version before use.

PAGE 10 (cont'd)

4.4.4 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packed. The lot size shall be the number of palletized unit loads in the end item inspected lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5 in accordance with MIL-STD-105.

Examine	Defect
Finished dimensions	Length, width,or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application."

Paragraph 5.1, Line 1: Delete "of" and substitute "OR".

Paragraph 5.1.1 Level A, Line 2: Delete paragraph number "5.1.1" and the words "Unit packaging".

PAGE 11

Paragraph 5.2.1 Delete the first sentence and substitute "Two hundred and forty (240) hoods, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to type CF, class weather-resistant grade V15c, variety DW, style RSC of PPP-B-636. The fiberboard used for the liner shall be class weather-resistant in accordance with PPP-B-636."

Paragraph 5.2.2 Delete the first sentence and substitute "Two hundred and forty (240) hoods, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to type CF, class domestic grade 275, variety DW of PPP-B-636. The fiberboard used for the liner shall be class domestic in accordance with PPP-B-636."

Paragraph 5.2.2.1 Delete entire paragraph.

Source: https://assist.dla.mil -- Downloaded: 20260-16T15:48Z
Check the source to verify that this is the current version before use.

PAGE 11 (cont'd)

Paragraph 5.2.3 Line 1: Delete: "Commercial Hoods, preserved-packaged" and substitute "Level C. Item packaged,".

Add new paragraph:
"5.4 Palletization. When specified (see 6.2) items packed as specified shall be palletized on a 4-way entry pallet in accordance with load type 1A of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C, K, and L or film bonding means. Pallet pattern shall be in accordance with the appendix of MIL-STD-147."

The pallet shall be 4-way, Type IV, V or VIII, Class 1, Style A, Size 2, wood group I, II, III or IV, Grade A of NN-P-71, or 4-way, Style 1, Size A, Type I, Class 1 of wood group I, II, III, or IV, Grade A of MIL-P-15011. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer."

PAGE 12

Paragraph 6.2 Delete instruction "b" in its entirety and substitute:
"b. When a first article sample is required (see 3.2 and 4.3) the item will be tested and should be a first article sample. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, quantity, and testing and approval of the first article."

Paragraph 6.2 Delete instruction "d" in its entirety and add:
"d. When palletization is required (see 5.4)."

Add new paragraph:
"6.4 Subject term (key word) listing:
Anti-flash gear
Cotton,100%
Hood, sock
protective covering

Custodian:
Navy - NU

Review Activities:
Navy - SH

User Activity:
Navy - CG

Preparing Activity:
Navy - NU

Project No. 8415-0526

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:48Z
Check the source to verify that this is the current version before use.