MILITARY SPECIFICATION

CARBON REMOVING COMPOUND (FOR USE IN AGITATED TANK)

This amendment forms a part of Military Specification MIL-C-19853C, dated 22 April 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

1.2, (a) Line 2: After the word "types" add: "and classes"
(b) Below type designators, add: "Class 1 - Unsealed (Single layer)
"Class 2 - Sealed (Two layers)"

Page 2

2.2, Under ASTM, add: "ASTM E 70 pH of Aqueous Solutions with the Glass Electrode"

Page 3

3.2, line 3: Delete "(see 6.6)"

3.4, line 1: (a) Change paragraph title to read "pH of seal"
(b) Delete "The alkalinity of the carbon removing compound" and substitute "The pH of the carbon removing compound seal"

3.5, line 3: After "1.15" add: "for the organic layer and not more than 1.09 for the aqueous layer"

3.6, line 1: Delete "The carbon removing compound," and substitute: "Class 1 compound and the solvent layer of class 2 compound,"

3.7, line 1: Before the word "carbon" add: "the class 1 compound and the solvent layer of the class 2"

3.8, Delete and substitute: "3.8 Separation of layers (Class 1 only). When class 1 compound is tested as specified in 4.5.5, the resulting mixture, after standing two hours, shall separate sharply into two distinct layers with no evidence of clots, curd, or precipitate. The aqueous layer shall be uppermost and the aqueous volume for each type shall be:

Type I upper layer - 25 ± 2 mls.
Type II upper layer - 20 $\overline{+}$ 7, -2 mls."

FSC 6850

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:47Z
Check the source to verify that this is the current version before use.

Page 3 (continued)

3.9, line 1: After "Type II" add ", class 1 compound and the solvent layer of type II, class 2"

Page 4

Correct paragraph number for "Temperature cycle (stability)" from "3.17" to "3.18"

Page 5

Add new paragraph: "3.20 Seal content (class 2 only). The seal content of class 2 compounds when determined in accordance with 4.5.17, shall not be less than 10 percent nor more than 15 percent of the total volume of the two-layer compound."

Page 7

4.5.1, delete and substitute: "4.5.1 pH of seal. The pH of the aqueous layer of class 2 carbon removing compounds shall be determined in accordance with ASTM E 70."

Page 8

4.5.3.1, line 2: Delete "The carbon removing compound" and substitute "Class 1 compound and the organic layer of class 2 compound"

4.5.5, in paragraph title: Delete "Type I" and substitute "Class 1"

Page 9

Correct paragraph number "4.6.5.1.2" to "4.5.6.1.2"

4.5.8.1: (a) Line 1: Delete "distilled water to the" and substitute: "1% sodium chromate solution to the class 1"
(b) Line 4: Delete "one hour" and substitute: "two hours"
(c) At end of paragraph: Add "Class 2 compounds shall be tested as received."

Page 10

4.5.10, line 2: Delete "trichloroethylene" and substitute "1,1,1 - trichloroethane"

Page 11

4.5.13, in paragraph title: Delete "Type I" and substitute "Class 2"

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:47Z
Check the source to verify that this is the current version before use.

Page 12

4.5.16.2, line 12: Delete "1 hour" and substitute: "two hours"

Add new paragraph: "4.5.17 Seal content (class 2 only). One hundred milliliters of thoroughly shaken class 2 compound shall be placed in a 100 ml graduated cylinder equipped with a stopper. Insert the stopper and allow the cylinder to stand undisturbed overnight. Determine the volume of the upper and lower layer. From these values the percent by volume of the seal (upper layer) shall be calculated."

6.1, line 6: Delete last sentence and substitute: "A 1.0 percent sodium chromate solution should be added to class 1 products to retard evaporation."

Page 14

6.6, delete in entirety

6.7, delete in entirety and substitute: "6.7 Cross reference of classification. The classification under this amendment is as follows:

MIL-C-19853C, Amend-1	MIL-C-19853C	MIL-C-19853B
Type I, Class 1	Type I	Type I
Type I, Class 2	-	-
Type II, Class 1	Type II	-
Type II, Class 2	-	Type II

Page 15

Table I, at end of Table add:

"Workmanship	3.19	-
Seal content	3.20	4.5.17"

Custodians:
Navy - AS
Air Force - 11

Review activities:
Navy - MS
DLS - GS

Preparing activity:
Navy - AS

(Project No. 6850-0737)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:47Z
Check the source to verify that this is the current version before use.