MIL-F-19924(NOrd)
AMENDMENT - 1

5 February 1958

MILITARY SPECIFICATION
FEED MECHANISMS, 20MM, MARK 7 MODS 0 AND 2

This amendment forms a part of Military Specification MIL-F-19924(NOrd), dated 19 June 1957.

Page 10 paragraph 4.3.2.13 - Delete in its entirety and substitute the following:

4.3.2.13 Feed Mechanisms Mark 7 Mod 2. -

4.3.2.13.1 Insulation and circuit-resistance test. - Feed mechanisms Mark 7 Mod 2 shall be tested with a 500-volt Bridge-Megger for insulation and circuit resistance as follows:

a. The circuit shall have a resistance of not less than 500 megohms with the valve stem "out" when leads of the megger are connected between pin A and pin B of the switch (see BUORD drawing No. 1411272).

b. Resistance to ground of pin A and pin B shall not be less than 500 Megohms with the valve stem "in", and with valve stem "out".

4.3.2.13.2 Continuity test. - The resistance between pin A and pin B of the switch (see BUORD drawing 1411272), when valve stem is "in", shall not be more than 3 ohms when checked with an ohmmeter or a wheatstone bridge.

DO NOT DESTROY MIL-F-19924(NOrd)

FSC 1005

NAVY-OPPO PRINC, WASH., D.C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:54Z
Check the source to verify that this is the current version before use.