MILITARY SPECIFICATION

CAPACITORS, FIXED, PLASTIC (OR PAPER-PLASTIC) DIELECTRIC, (HERMETICALLY SEALED IN METAL, CERAMIC, OR GLASS CASES), ESTABLISHED AND NON-ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-19978E, dated 22 November 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 17

4.6.2.1.1.2, delete and substitute:

"4.6.2.1.1.2 For FR levels M, P, R, and S. In addition to the tests specified in 4.6.2.1.1.1, a minimum of 10 sample units from each inspection lot (see 4.6.1.1) shall be subjected to subgroup 4 of table XII (see 4.6.1.3.3). Allowable failures shall be as specified in table IV of MIL-STD-690."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - OS, MC, SH

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5910-1571)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:59Z
Check the source to verify that this is the current version before use.