MILITARY SPECIFICATION

CAPACITORS, FIXED, PLASTIC (OR PAPER-PLASTIC) DIELECTRIC,
(HERMETICALLY SEALED IN METAL, CERAMIC, OR GLASS CASES),
ESTABLISHED AND NON-ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-19978E, dated 22 November 1985, and and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 15

* TABLE X, footnote 1, delete and substitute:

"1/ For all ER styles.
FR level L-burn-in 1.0 percent AQL; radiographic: Not applicable.
FR level M-burn-in 100 percent; radiographic: Not applicable.
FR levels P, R, and S; burn-in and radiographic: 100 percent."

PAGE 17

4.6.2.1.1.2, delete and substitute:

"4.6.2.1.1.2 For FR levels M, P, R, and S. In addition to the tests specified in 4.6.2.1.1.1, a minimum of 10 sample units from each inspection lot (see 4.6.1.1) shall be subjected to subgroup 4 of table XII (see 4.6.1.3.3). Allowable failures shall be as specified in table IV of MIL-STD-690."

The margin of this amendment is marked with an asterisk to indicate where a change (addition, modification, correction, deletion) from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - MC, OS, SH

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5910-1592)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:59Z
Check the source to verify that this is the current version before use.