INCH-POUND

MIL-C-19978F
31 March 1994
SUPERSEDING
MIL-C-19978E
22 November 1985

MILITARY SPECIFICATION

CAPACITORS, FIXED, PLASTIC (OR PAPER-PLASTIC) DIELECTRIC, (HERMETICALLY SEALED IN METAL, CERAMIC, OR GLASS CASES), ESTABLISHED AND NON-ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the general requirements for established reliability (ER) and non-established reliability (non-ER), direct current (dc), plastic or paper-plastic dielectric, fixed capacitors, hermetically sealed in metal or ceramic or glass cases. Capacitors meeting the established reliability requirements specified herein have failure rate (FR) levels ranging from 1.0 percent to 0.001 percent per 1,000 hours (see 1.2.1.9). These FR levels are established at a 90-percent confidence level and maintained at a 10-percent producer's risk and are based on life tests performed at maximum rated voltage and maximum rated temperature. An acceleration factor of 5:1 has been used to relate the life test data obtained at 140 percent of rated dc voltage at the applicable high test temperature to the rated voltage at the applicable high test temperature. This specification also covers removable mounting retainers for use with applicable capacitors (see 3.1). A part per million (ppm) quality system is used for documenting and reporting the average outgoing quality of ER capacitors supplied to this specification. Statistical process control (SPC) techniques are required in the manufacturing process to minimize variation in production of ER capacitors supplied to the requirements of this specification.

1.2 Classification.

1.2.1 Part or Identifying Number (PIN). The PIN shall be in the following form and as specified (see 3.1 and 6.2).

ER

CQR09	A	1	M	C	152	K	1	M
ER style 1.2.1.1	Terminal 1.2.1.2	Circuit 1.2.1.3	Charac-teristic 1.2.1.4	Voltage 1.2.1.5	Capacitance 1.2.1.6	Capacitance tolerance 1.2.1.7	Vibration grade 1.2.1.8	Failure rate level 1.2.1.9

NON-ER

CQ09	A	1	M	C	152	K	1
ER style 1.2.1.1	Terminal 1.2.1.2	Circuit 1.2.1.3	Charac-teristic 1.2.1.4	Voltage 1.2.1.5	Capacitance 1.2.1.6	Capacitance tolerance 1.2.1.7	Vibration grade 1.2.1.8

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: 645 LOG/LGME, Gentile Station 1060 Hamilton Street, Dayton, OH 45444-5400, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

1.2.1.1 Style. The style is identified by either the three-letter symbol "CQR" or the two-letter symbol "CQ" followed by a two-digit number. The letters identify plastic (or paper-plastic) dielectric, fixed capacitor, hermetically sealed in metal, ceramic, or glass cases. The symbol "CQR" identifies established reliability (ER) capacitors; the symbol "CQ" identifies capacitors for which no specific reliability requirements are specified (non-ER). The first digit following the letter symbols identifies the general shape of the case, and the second digit identifies specific details other than case size. Each style designation may include a family of case sizes.



1.2.1.2 Terminal. The terminal is identified by a single letter in accordance with table I.

TABLE I. Terminal.

Symbol	Type of terminal
A	Axial wire lead
B	Solder lug (nonremovable)
C	Threaded stud and nuts
D and H	Pillar insulator for use at altitudes up to 7,500 feet (22.8 inches of mercury)
E	Pillar insulator for use at altitudes up to 50,000 feet (3.4 inches of mercury)

1.2.1.3 Circuit. The circuit diagram and the number of terminals are identified by a single digit in accordance with table II.

TABLE II. Circuit diagram and number of terminals.

Symbol	Circuit diagram	Number of terminals
1		2
3		2

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

1.2.1.4 Characteristic. The characteristic is identified by a single letter in accordance with table III.

TABLE III. Characteristic.

Characteristic	Values of characteristics						
	E	F and G	K 2/	M	P	Q	T
High ambient test temperature, degrees centigrade ±3°C 1/	85	85	125	85	65	125	170
Low ambient test temperature, degrees centigrade +0°C, -5°C	-65	-55	-65	-65	-65	-55	-65
Life-test dc voltage, in percent of the dc voltage rating (see 4.7.21):							
Watt-second group (see 6.5.3):							
I (0.5 watt-second and less)	140	140	140	140	140	150	140
II (0.5+ to 5 watt-seconds)	140	130	140 3/	---	---	---	---
III (5+ to 50 watt-seconds)	140	110	140	---	---	---	---
IV (greater than 50 watt-seconds)	140	90	140	---	---	---	---
Flashpoint of impregnant or filling compound, degrees centigrade	142	135	142	142	142	142	217

1/ For characteristic K, voltage derating may be necessary at the high ambient test temperature (see 3.1).
2/ For tubular units of characteristic K rated at 1,000 volts dc, life test voltage shall be 1,200 volts.
3/ For tubular units of characteristic K in watt-seconds group II, use 130 percent of the dc voltage rating at 40°C for life-test dc voltage.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the currentversion before use.

1.2.1.5 Voltage. The dc voltage rating for continuous operation at the high ambient test temperature specified in table III (except for characteristic K which is for 85°C operation), is identified by a single letter in accordance with table IV.

TABLE IV. DC voltage rating.

Symbol	DC voltage rating 1/	Symbol	DC voltage rating 1/
	Volts		Volts
Z	30	K	2,500
A	50	L	3,000
B	100	M	4,000
C	200	N	5,000
D	300	P	6,000
E	400	R	7,500
F	600	S	10,000
G	1,000	T	12,500
H	1,500	U	15,000
J	2,000		

1/ For characteristic K, voltage derating may be necessary at the high ambient test temperature (see 3.1).

1.2.1.6 Capacitance. The nominal capacitance value expressed in picofarads (pF) is identified by a three-digit number; the first two digits represent significant figures and the last digit specifies the number of zeros to follow.

1.2.1.7 Capacitance tolerance. The capacitance tolerance in percent is identified by a single letter in accordance with table V.

TABLE V. Capacitance tolerance.

Symbol	Capacitance tolerance
	Percent (±)
F	1
G	2
J	5
K	10

1.2.1.8 Vibration grade. The vibration grade is identified by a single digit in accordance with table VI.

TABLE VI. Vibration grade.

Symbol	Frequency range	Acceleration
	Hz	G
1	10 to 55 inclusive	---
3	10 to 2,000 inclusive	15

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

1.2.1.9 Failure rate level. The failure level in percent per 1,000 hours is identified by a single letter in accordance with table VII, and is based on rated voltage at the high test temperature, as applicable.

TABLE VII. Failure rate level.

Symbol	Failure rate level (percent per 1,000 hours)
M	1.0
P	0.1
R	0.01
S	0.001

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-I-10 - Insulating Compound, Electrical, Ceramic, Class L.
MIL-C-39028 - Capacitors, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts.
MIL-STD-690 - Failure Rate Sampling Plans and Procedures.
MIL-STD-790 - Product Assurance Program for Electronic Parts Specifications.
MIL-STD-810 - Environmental Test Methods and Engineering Guidelines.
MIL-STD-1285 - Marking of Electrical and Electronic Parts.
MIL-STD-45662 - Calibration System Requirements.

(See Supplement 1 for list of associated specification sheets.)

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D92-57 - Method of Test for Flash and Fire Points by Cleveland Open Cup.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

ELECTRONIC INDUSTRIES ASSOCIATION (EIA)

EIA-554 - Assessment of Outgoing Nonconforming levels in Parts Per Million (ppm).
EIA-557 - Statistical Process Control Systems.

(Application for copies should be addressed to the Electronic Industries Association (EIA), 2001 Pennsylvania Avenue, N.W., Washington DC 20006.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Specification sheets. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheets. In the event of any conflict between requirements of this specification and the specification sheet, the latter shall govern (see 6.2).

3.2 Qualification. Capacitors and retainers furnished under this specification shall be products which are authorized by the qualifying activity for listing on the applicable qualified products list (QPL) at the time of award of contract (see 4.4 and 6.4). In addition, the manufacturer shall obtain certification from the qualifying activity that the reliability assurance requirements of 4.1.1 have been met and are being maintained for the ER styles. Authorized distributors which are approved to MIL-STD-790 distributor requirements by the QPL manufacturers are listed in the QPL.

3.3 Reliability and quality (ER styles only).

3.3.1 Reliability. Reliability of ER capacitors furnished under this specification shall be established and maintained in accordance with the procedures and requirements specified in MIL-STD-790 and MIL-STD-690 with details specified in 4.1.1, 4.4.4, and 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

3.3.2 Quality.

3.3.2.1 Statistical process control (SPC). The manufacturer shall implement and use SPC techniques in the manufacturing process for ER parts covered by this specification. The SPC program shall be developed and maintained in accordance with all the requirements of EIA-557. The SPC program shall be documented and maintained as part of the overall product assurance program as specified in MIL-STD-790. The implementation date for SPC shall be 12 months from the date of this specification. Processes for application of SPC techniques should include but are not limited to the following.

a. Pre-assembly.

b. Assembly.

c. Encapsulation.

d. Packaging.

3.3.2.2 Quality levels. The quality of lots which have been subjected to and have passed the subgroup 1, 100 percent screening inspections of group A inspection shall be established and maintained in accordance with 4.6.1.2.1.2.3 and EIA-554, method B. Individual ppm defect levels (i.e., ppm-2 and ppm-3) and overall ppm defect level (i.e., ppm-5) shall be established based on the tests prescribed in the subgroup 2 tests of the group A inspections. The defect level for ppm-2 shall be less than 100 ppm. Data shall not be excluded from the appropriate ppm calculation unless specifically authorized by the qualifying activity. Guidance for exclusion of data is specified in EIA-554.

3.3.2.3 Noncompliance. The contractor shall notify the qualifying activity when the 100 ppm level is reached or exceeded for ppm-2. The contractor shall provide sufficient information to the qualifying activity documenting the causes of the problem and what corrective action is being taken. Failure to correct this problem shall be the basis for removal of the affected product from the QPL.

3.4 Material. The material shall be as specified herein; however, when a definite material is not specified, a material shall be used which will enable the capacitors to meet the performance requirements of this specification. Acceptance or approval of any constituent material shall not be construed as a guarantee of the acceptance of the finished product.

3.4.1 Impregnant and filling compounds. Compounds used in the impregnation and filling of capacitors shall be chemically inactive with respect to the capacitor element and the case (see 3.5.1). The compound, either in the state of original application or as a result of having aged, shall have no adverse effect on the performance of the capacitor. For liquid-filled capacitors, the same material shall be used for impregnating as is used for filling (see 6.3).

3.4.2 Dielectric material. Dielectric material (see 3.1) utilized in the fabrication of capacitors shall be one of the following materials.

Characteristic	Material
E, F, G, and K	Paper and polyethylene terephthalate
M	Polyethylene terephthalate
P	Polystyrene
Q	Polycarbonate
T	Polytetrafluoroethylene

3.5 Design and construction. Capacitors and retainers shall be of the design, construction, and physical dimensions specified (see 3.1).

3.5.1 Case. Each capacitor shall be enclosed in a hermetically-sealed metal or ceramic or glass case (see 3.1) which will prevent leakage of the impregnant or filling compound and, in addition, will protect the capacitor element from moisture and mechanical damage under all test conditions specified herein. Ceramic used for case materials shall conform to MIL-I-10. The use of exterior cardboard sleeves for insulating purposes shall not be permitted. Transparent, shrink fitted plastic insulation shall be used for the sleeves and shall lap over the ends of the capacitor body. Insulating sleeve thickness shall not exceed .005 inch (0.13 mm). Marking shall not be applied to the insulating sleeve.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

3.5.2 Noninductive construction. Unless otherwise specified (see 3.1), tubular capacitors shall be of extended-foil construction. When tab construction is used, each pair of tabs shall be brought from opposite foils within one turn of the foil winding from each other, unless otherwise specified (see 3.1).

3.5.3 Terminals.

3.5.3.1 Case as terminal. When the case is used as a terminal, any protective coating applied to the mounting surfaces shall be such as to provide a direct conducting path for an electric current from the case to the surface on which it is mounted.

3.5.3.2 Solder lugs and solder-lug terminals. Solder lugs and solder lug-terminals may be of any shape, provided dimensional limits are met, and shall be coated with solder having a tin content of 40 to 70 percent.

3.5.3.3 Screw terminals. Screw terminals shall be supplied with one nut, one flat washer, and one lockwasher.

3.5.3.4 Wire leads and pins. Leads and pins shall be of copper or copper covered steel. Copper covered steel leads and pins shall have a minimum of 30 percent of the conductivity of electrolytic copper. Leads and pins shall be coated with solder having a tin content of 40 to 70 percent.

3.5.3.5 Tin plated finishes. Use of tin plating is prohibited as a final finish and as an undercoat (see 6.9). Use of tin-lead (Sn-Pb) finishes are acceptable provided that the minimum lead content is three percent.

3.5.3.6 Terminal insulators. Terminal insulators shall be glass or ceramic.

3.5.4 Solder dip (retinning leads). The manufacturer may solder dip/retin the leads of product supplied to this specification provided the solder dip process has been approved by the qualifying activity.

3.5.4.1 Qualifying activity approval. Approval of the solder dip process will be based on one of the following options.

a. When the original lead finish qualified was hot solder dip lead finish 52 of MIL-STD-1276, the manufacturer shall use the same solder dip process for retinning as is used in the original manufacture of the product. (NOTE: The 200 microinch maximum thickness requirement is not applicable.)

b. When the lead originally qualified was not hot solder dip lead finish 52 of MIL-STD-1276 as prescribed in 3.5.4.1a, approval for the process to be used for solder dip shall be based on the following test procedure.

(1) Thirty samples of any capacitance value for each style and lead finish are subjected to the manufacturer's solder dip process. Following the solder process, the capacitors shall be subjected to the electrical tests of group A inspection. No defects are allowed.

(2) Ten of the 30 samples shall then be subjected to the solderability tests. No defects are allowed.

(3) The remaining 20 samples shall be subjected to the resistance to soldering heat test followed by the moisture resistance test. No defects are allowed.

3.5.4.2 Solder dip/retinning options. The manufacturer (or authorized category C distributor) may solder dip/retin as follows.

a. As a corrective action if the lot fails the group A solderability test.

b. After the group A inspection has been completed. Following the solder dip/retinning process, the CAP, DF, and IR measurements shall be performed on 100 percent of the lot. The percent defective allowable (PDA) for the electrical measurements shall be as for the subgroup 1 tests. (NOTE: If x-ray and hermetic seal are required in the group A, subgroup 1 tests, these tests shall be repeated.) Following these tests, the manufacturer shall submit the lot to the group A solderability test as specified in 4.7.15.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

3.5.5 Threaded parts. All threaded parts shall be as specified (see 3.1) and in accordance with FED-STD-H28.

3.5.5.1 Engagement of threaded parts. All threaded parts shall engage by at least three full threads.

3.5.5.2 Locking of screw-thread assemblies. All screw-thread assemblies shall be rendered resistant to loosening under vibration. Lockwashers shall be provided under all nuts.

3.6 Burn-in (ERs only, when applicable, see 3.1). When capacitors are tested as specified in 4.7.3, there shall be no evidence of damage, arcing, or breakdown.

3.7 Radiographic inspection (ERs only, when applicable, see 3.1). When capacitors are tested as specified in 4.7.4, x-ray examination shall disclose no evidence of improperly made connections, misalignments of seals or eyelets, substandard soldering or structural weakness, or solder particles or slivers attached to one end.

3.8 Thermal shock. When tested as specified in 4.7.5, capacitors and retainers shall withstand the extremes of high and low temperatures without visible damage.

3.9 Seal. When capacitors are tested as specified in 4.7.6, there shall be no continuous visible stream of bubbles or other evidence of leakage.

3.10 Dielectric withstanding voltage (DWV).

3.10.1 Capacitors. When capacitors are tested as specified in 4.7.7.1, there shall be no momentary or intermittent arcing or other indication of breakdown, nor shall there be any visible evidence of damage.

3.10.2 Sleeving (when applicable, see 3.1). When capacitors are tested as specified in 4.7.7.2, the insulating sleeve shall withstand the specified potential without breakdown.

3.11 Barometric pressure (reduced) (when applicable, see 3.1). When capacitors are tested as specified in 4.7.8, there shall be no momentary or intermittent arcing or other indication of breakdown, nor shall there be any visible evidence of damage.

3.12 Insulation resistance (IR).

3.12.1 Sleeving (when applicable, see 3.1). When measured as specified in 4.7.9, the insulation resistance shall be not less than 1,000 megohms.

3.12.2 Terminal to terminal. When measured as specified in 4.7.9, the insulation resistance shall be not less than the applicable values specified (see 3.1).

3.12.3 Terminal to case. When measured as specified in 4.7.9, the insulation resistance between any terminal and case, when the case is not a terminal, shall exceed 50,000 megohms, unless otherwise specified (see 3.1).

3.13 Capacitance. When measured as specified in 4.7.10, the capacitance shall be within the tolerance specified (see 3.1).

3.14 Dissipation factor. When measured as specified in 4.7.11, the dissipation factor shall not exceed the applicable value specified (see 3.1).

3.15 Vibration. When capacitors are tested as specified in 4.7.12, there shall be no intermittent contacts of 0.5 milliseconds (ms) or greater duration or momentary arcing, or other indication of breakdown, nor shall there be any open-or-short circuiting or evidence of mechanical damage. In addition, retainers, as tested to 4.7.12, shall exhibit no evidence of mechanical damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

3.16 Salt spray (corrosion) (metal surfaces only, see 3.1). When capacitors or retainers are tested as specified in 4.7.13, there shall be no evidence of harmful corrosion, and at least 90 percent of any exposed metal surfaces of the capacitor or retainer shall be protected by the finish. For capacitors or retainers with painted surfaces, not more than 10 percent of the surfaces shall be affected by flaking, peeling, or blistering of paint. There shall be no evidence of unwrapping of or mechanical damage to the insulating sleeves when applicable. In addition, corrosion of the terminal hardware or mounting surface shall not exceed 10 percent of the surface area. Marking shall remain legible.

NOTE: Harmful corrosion shall be construed as any type of corrosion which in any way interferes with the mechanical or electrical performance of the capacitor or retainer, as applicable.

3.17 Immersion. When tested as specified in 4.7.14, capacitors or retainers, as applicable, shall meet the following requirements:

a. Capacitors:	
Dielectric withstanding voltage:	
Insulating sleeves (when applicable, see 3.1):	Not less than 4,000 V dc.
Terminal to terminal:	As specified in 3.10.1.
Terminal to case:	As specified in 3.10.1.
Insulation resistance at 25°C:	
Insulating sleeves (when applicable, see 3.1):	Not less than 1,000 megohms.
Terminal to terminal:	Not less than 1,000 megohms. Unless otherwise specified, not less than 60 percent of the value specified in 3.12.2.
Terminal to case:	Unless otherwise specified, not less than 50 percent of the value specified in 3.12.3.
Capacitance:	Shall change not more than ±1.0 percent from the value obtained when measured as specified in 4.7.10.
Dissipation factor:	Shall not exceed 120 percent of the initial value specified (see 3.1).
b. Capacitors and retainers:	
Visual examination:	There shall be no harmful or extensive corrosion of the capacitors or retainers. The marking shall remain legible. There shall be no unwrapping of, or mechanical damage to, the insulating sleeves, when applicable.

3.18 Solderability (wire leads only, see 3.1). When capacitors are tested as specified in 4.7.15, the dipped portion of the terminals shall conform to the solid-wire termination criteria of method 208 of MIL-STD-202.

3.19 Shock (specified pulse). When capacitors are tested as specified in 4.7.16, there shall be no intermittent contacts of 0.5 ms or greater duration, or arcing or other indications of breakdown, nor shall there be any open or short circuiting or evidence of mechanical damage.

3.20 Terminal strength. When capacitors are tested as specified in 4.7.17, there shall be no mechanical damage to the capacitor or terminals.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

3.21 Dielectric absorption (when specified, see 3.1). When measured as specified in 4.7.18, the dielectric absorption shall not exceed the value specified (see 3.1).

3.22 Stability at low and high temperatures. When capacitors are tested as specified in 4.7.19, there shall be no indication of breakdown or arcing, nor shall there be any open or short circuiting or any visible evidence of mechanical damage. The capacitance changes at the specified temperatures shall not exceed the applicable limits specified (see 3.1) from value at 25°C.

3.23 Temperature coefficient (characteristic P only) (see 3.1). When measured as specified in 4.7.20, the temperature coefficient shall not exceed -120 ppm per degree Celsius (ppm/°C) ±50 ppm/°C.

3.24 Life. When tested as specified in 4.7.21, capacitors shall meet the following requirements.

a.	Insulation resistance at 25°C:	Unless otherwise specified, not less than 60 percent of the value specified in 3.12.1.
b.	Capacitance:	Shall change not more than the percent specified (see 3.1) of the initial value obtained when measured as specified in 4.7.10.
c.	Dissipation factor:	Unless otherwise specified, shall not exceed the initial value specified (see 3.1).
d.	Visual examination:	There shall be no leakage of impregnant or filling compound or deformation of the case either during or after the test.

3.25 Fungus. The manufacturer shall certify that all external materials are fungus resistant or shall perform the test specified in 4.7.22. When capacitors are tested as specified in 4.7.22, examination shall disclose no evidence of fungus growth on the external surface.

3.26 Resistance to solvents. When capacitors are tested as specified in 4.7.23, there shall be no evidence of mechanical damage and the marking shall remain legible.

3.27 Resistance to soldering heat (applicable to wire-lead capacitors only). When tested as specified in 4.7.24, capacitors shall meet the following requirements:

a.	Insulation resistance at 25°C:	As specified in 3.12.
b.	Capacitance:	Change not more than five percent from the initial value obtained when measured as specified in 4.7.10.
c.	Dissipation factor:	Shall not exceed initial limit.

3.28 Moisture resistance. When tested as specified in 4.7.25, capacitors or retainers as applicable, shall meet the following requirements.

a. Capacitors:

Dielectric withstanding voltage:

Insulating sleeves (when applicable, see 3.1):	Not less than 4,000 V dc.
Terminal to terminal:	As specified in 3.10.1
Terminals to case (circuit diagram 1 only):	As specified in 3.10.1

Insulation resistance at 25°C:

Insulating sleeves (when applicable, see 3.1):	Not less than 1,000 megohms.
Terminal to terminal:	Not less than 60 percent of the value specified in 3.12.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

Terminals to case (circuit diagram 1 only):	Not less than 50 percent of the value specified in 3.12.3.
Capacitance:	Shall change not more than ±0.5 percent (±2.0 percent for characteristic M) from the value obtained when measured as specified in 4.7.10.
Dissipation factor:	Shall not exceed 120 percent of the initial values specified (see 3.1).

b. Capacitors and retainers:

Visual examination:	There shall be no harmful or extensive corrosion of the capacitors or retainers. The marking shall remain legible. There shall be no unwrapping of, or mechanical damage to, the insulating sleeves when applicable.

3.29 Flashpoint of impregnant or filling compound. When measured as specified in 4.7.26, the flashpoint of impregnant or filling compound shall be equal to or greater than 142°C unless otherwise specified (see 3.1).


3.30 Marking.

3.30.1 Capacitors. Marking of capacitors shall conform to method I of MIL-STD-1285 and shall include the PIN, "JAN" brand, trademark (optional), source code, date code, lot symbol, and when space permits, capacitance (in µF), capacitance tolerance, and rated voltage, and when applicable, failure rate level. Unless otherwise specified (see 3.1), capacitors shall be marked as shown in the following example:

Example:

CQR09A1MC152K1M - PIN.
JAN TM 12345 - "JAN" brand (ER styles only), trademark (optional) and source code.
8520A.0011µF - Date code, lot symbol and capacitance.
10% 1000 VDC - Capacitance tolerance and rated voltage.

3.30.2 Partial marking. For tubular capacitors with case sizes of .175 by .406, .195 by .406 and .235 by .406, the following partial marking may be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

3.30.3 Retainer. Retainers shall be marked with the PIN, trademark (optional), and source code. Marking shall be on the outer surface of the retainers.

3.30.4 JAN and J marking (ER styles only). The United States Government has adopted, and is exercising legitimate control over, the certification marks "JAN" and "J", respectively, to indicate electrical equipment, namely resistors, capacitors, electron tubes and the like, procured by, or manufactured for use by, or for the Government in accordance with standard Government specifications. Accordingly, capacitors procured to, and meeting all of, the criteria specified herein and in applicable specification sheets shall bear the certification mark "JAN", except that capacitors too small to bear the certification mark "JAN" shall bear the letter "J". Capacitors furnished under contracts or orders which either permit or require deviation from the conditions or requirements specified herein and in applicable specification sheets shall not bear "JAN" or "J". In the event a capacitor sample fails to meet the requirements of this specification and the applicable specification sheets, the manufacturer shall remove the "JAN" or the "J" from the sample tested and also from all capacitors represented by the sample. The United States Government has obtained Certificate of Registration No. 504,860 for the certification mark "JAN".

3.30.5 Substitution of failure rate levels (FRL's). A manufacturer may supply to all higher FRL than to which he is qualified. Items of an exponential FRL as shown in table VIII and marked to lower FRL with procuring agency approval, are substitutable for higher FRL, and shall not be remarked unless specified in the contract or purchase order (see 6.2), the lot date codes on the parts are unchanged, and the workmanship criteria is met.

TABLE VIII. Failure rate level (FRL) substitutability.

Parts qualified to FRL	Substitutable for FRL
S	M, P, and R
R	M and P
P	M

3.30.6 Substitution of capacitance tolerance and voltage. Parts qualified and marked to tighter capacitance tolerance or higher rated voltage, with procuring agency approval, are substitutable for parts marked to looser capacitance tolerance or lower rated voltage, provided all other values, such as case size, characteristic, and leads are the same. The substitutable parts shall not be remarked unless specified in the contract or purchase order (see 6.2), the lot date code on the parts are unchanged, and the workmanship criteria are met.

3.30.7 Non-ER marking. An ER part may be marked and furnished as a non-ER part if produced on the same assembly line, and provided it is subject to and meets all the inspection requirements of the ER part.

3.31. Workmanship. Capacitors and retainers shall be processed in such a manner as to be uniform in quality and shall be free from pits, corrosion, cracks, rough edges, and other defects that will affect life, serviceability, or appearance.

3.31.1 Soldering.

3.31.1.1 Flux. No acid or acid salts shall be used in preparation for or during soldering; however, exception is permitted for preliminary tinning of electrical connections and for tinning or soldering of mechanical points not used to complete electrical circuits, but in no case shall acid salts be used where they can come in contact with insulating material. Where acid or acid salts are used as permitted herein, they shall be completely neutralized and removed immediately after use. All excess flux and solder shall be removed. Where possible, electrical connections shall be mechanically secure before soldering and electrically continuous after soldering.

3.31.1.2 Process. There shall be no sharp points or rough surfaces resulting from insufficient heating. The minimum necessary amount of flux and solder shall be used for electrical connections. Any means employed to remove an unavoidable excess of flux shall not incur the risk of loose particles of flux, brush bristles, or other foreign material remaining in or on the capacitor; flux being spread over a large area; or damage to the capacitor. Insulation material that has been subjected to heating during the soldering operation shall be undamaged and parts fastened thereto shall not have become loosened.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

3.31.2 Riveting (retainers only). The riveting operation shall be performed carefully to insure that the rivet is tight and satisfactorily headed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations or tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Product assurance program (applicable to ER parts only). A product assurance program shall be established and maintained in accordance with MIL-STD-790.

4.1.3 Test equipment and inspection facilities. Test and measuring equipment and inspection facilities of sufficient accuracy, and quality and quantity to permit performance of the required inspection shall be established and maintained by the contractor. The establishment and maintaince of a calibration system to control the accuracy of the measuring and test equipment shall be in accordance with MIL-STD-45662.

4.2 Classification of inspection. The inspection requirements specified herein are classified a s follows:

a. Qualification inspection (see 4.4).

b. Retention of qualification (non-ER styles only) (see 4.5) or verification of qualification (ER styles only) (see 4.5.1).

c. Quality conformance inspection (see 4.6).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in the "GENERAL REQUIREMENTS" of MIL-STD-202.

4.4 Qualification inspection. 1/ Qualification inspection shall be performed at a laboratory acceptable to the Government (see 6.4) on sample units produced with equipment and procedures normally used in production.

4.4.1 Sample size. The number of capacitors or retainers to be submitted for qualification inspection shall be as specified in table IX or X, respectively, or the appendix to this specification.

4.4.2 Inspection routine.

4.4.2.1 Capacitor submission. Capacitors shall be subjected to the qualification inspection specified in table IX in the order shown. All sample units shall be divided as specified in table IX for groups 1 through IX inclusive, and subjected to the inspection for their particular group; for combined voltage group submissions, each type shall be equally represented in each group.

1/ Qualification approval will be based on the successful completion of the tests specified in table IX and will not be withheld pending completion of the extended life test of 4.4.4a.

Source: https://assist.dla.mil -- Downloaded: 202640-19T06:58Z
Check the source to verify that this is the current version before use.

4.4.2.2 Retainer submission. Fourteen sample retainers shall be subjected to the examination and tests specified in table X in the order shown or the appendix to this specification. Two specimens of each type represented in a sample shall be subjected to group I tests. Retainers shall then be subjected to the tests of group II. During these tests, one set of each retainer type shall support a capacitor of the same case designation with which it is normally used (see 3.1). Tests or retainers may be run concurrently with those specified for capacitors in 4.4.2.1. Each retainer shall be considered as a specimen for the purpose of determining defectives.

4.4.3 Failures. Failures in excess of those allowed in table IX or X, as applicable, shall be cause for refusal to grant qualification approval.

4.4.4 Failure rate (FR) qualification (applicable to ER parts only). FR qualification for capacitors shall be in accordance with the general and detailed requirements of MIL-STD-690 and as follows.

a. Procedure I: Qualification at the initial FR level. Level "M" (1.0 percent) of FRSP-90 shall apply. Sample units shall be subjected to the qualification inspection specified in group V, table IX (see 4.4.2.1). The entire life test sample shall be continued on test to 6,000 hours as specified in 4.7.21.3, upon completion of the 2,000 hour qualification.

b. Procedure II: Extension of qualification to lower FR levels. To extend qualification to the "R" (0.01 percent) and "S" (0.001 percent) FR levels, data from two or more styles of similar construction may be combined.

c. Procedure III: Maintenance of FR level qualification. Maintenance period B of FRSP-10 shall apply. Regardless of the number of production lots produced during this period, the specified number of unit hours shall be accumulated to maintain qualification (see 4.6.1).

4.4.5 Quality level verification (ER styles only). The manufacturer is responsible for establishing a quality system to verify the ppm defect level of lots which are subjected to subgroup 2 tests of the group A inspections. The ppm defect level shall be based on a 6-month moving average. The manufacturer shall verify and report individual ppm categories (i.e., ppm-2 and ppm-3) and overall ppm defect level (i.e., ppm-5). In the event that the manufacturer meets or exceeds 100 ppm for ppm-2, the qualifying activity shall take the actions specified in 3.3.2.3.

4.5 Retention of qualification (non-ER styles only). To retain qualification, the supplier shall forward a report at 6 month intervals to the qualifying activity. The qualifying activity shall establish the initial reporting date. The report shall consist of the following.

a. A summary of the results of the tests performed for inspection of product for delivery (groups A and B), indicating as a minimum the number of lots that have passed and the number that have failed. The results of tests of all reworked lots shall be identified and accounted for.

b. A summary of the results of tests performed for periodic inspection (group C), including the number and mode of failures. The summary shall include results of all periodic inspection tests performed and completed during the 6 month period. If the summary of the test results indicates nonconformance with specification requirements, and corrective action acceptable to the qualifying activity has not been taken, action may be taken to remove the failing product from the QPL.

Failure to submit the report within 30 days after the end of each 6 month period may result in loss of qualification for the product. In addition to the periodic submission of inspection data, the supplier shall immediately notify the qualifying activity at any time during the 6 month period that the inspection data indicates failure of the qualified product to meet the requirements of the specification.

In the event that no production occurred during the reporting period, a report shall be submitted certifying that the manufacturer still has the capabilities and facilities necessary to produce the item. The manufacturer shall also produce enough parts during any reporting period in order to perform all applicable group C tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

TABLE IX. Qualification inspection for capacitors.

Inspection	Requirement paragraph	Method paragraph	NON-ER		ER	
			Number of sample units to be inspected	Number of defectives allowed 1/	Number of sample units to be inspected	Number of defectives allowed 1/
Group I						
Visual and mechanical examination (internal): Material, design, construction, and workmanship	3.1, 3.4, 3.5, and 3.31	4.7.2	2	0	2	0
Group II						
Visual and mechanical examination (external): Physical dimensions, marking, and workmanship 2/	3.1, 3.5, and 3.30 to 3.31.2 inclusive	4.7.2				
Burn-in (ER only, when applicable) 3/	3.6	4.7.3				
Radiographic inspection (ER only, when applicable) 3/	3.7	4.7.4				
Thermal shock 3/	3.8	4.7.5				
Seal	3.9	4.7.6	43	1	80	0
Dielectric withstanding voltage 3/	3.10	4.7.7				
Barometric pressure (reduced) (when applicable) 3/	3.11	4.7.8				
Insulation resistance 3/	3.12	4.7.9				
Capacitance 3/	3.13	4.7.10				
Dissipation factor 3/	3.14	4.7.11				
Group III						
Vibration	3.15	4.7.12				
Salt spray (corrosion) (metal case only)	3.16	4.7.13	6	1	12	1
Immersion	3.17	4.7.14				
Group IV						
Solderability (wire leads only)	3.18	4.7.15	6	1	6	1
Group V						
Shock (specified pulse)	3.19	4.7.16				
Terminal strength	3.20	4.7.17	6	1	12	1
Moisture resistance	3.21	4.7.18				
Group VI						
Dielectric absorption (when specified)	3.21	4.7.18				
Stability at low and high temperatures 3/	3.22	4.7.19	24	1	40	1
Temperature coefficient (characteristic P)	3.23	4.7.20				
Life	3.24	4.7.21				

1

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

TABLE IX. Qualification inspection for capacitors - Continued.

Inspection	Requirement paragraph	Method paragraph	NON-ER		ER	
			Number of sample units to be inspected	Number of defectives allowed 1/	Number of sample units to be inspected	Number of defectives allowed 1/
Group VII						
Fungus	3.25	4.7.22	N/A		5	1
Resistance to solvents	3.26	4.7.23			10	
Resistance to soldering heat (wire lead only)	3.27	4.7.24			5	
Moisture resistance	3.28	4.7.25				
Group VIII						
Flashpoint of impregnant or filling compound	3.29	4.7.26	2 4/		2 4/	

1/ A sample unit having one or more defects will be considered as a single defective.
2/ Marking defects are based on visual examination only and will be charged only for illegible, incomplete, or incorrect marking.
3/ Nondestructive tests.
4/ Two samples shall be taken from the .25-pound impregnant or filling compound submitted.

TABLE X. Qualification inspection for retainers.

Inspection	Requirement paragraph	Method paragraph	Number of specimens to be inspected	Number defectives allowed 1/
Group I				
Visual and mechanical examination	3.1, 3.5 to 3.5.4.2 as applicable and 3.30 to 3.31.2 inclusive	4.7.2	2	0
Group II				
Vibration 2/	3.15	4.7.12	12	1
Salt spray (corrosion)	3.16	4.7.13		
Thermal shock	3.8	4.7.5		

1/ A specimen having one or more defects shall be considered as a single defective.
2/ During vibration tests, one set of each retainer type shall support a capacitor or a dummy of comparable weight and size.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T06:58Z
Check the source to verify that this is the current version before use.

4.5.1 Verification of qualification (ER styles only). Every 6 months the manufacturer shall compile a summary of the results of quality conformance inspections and extended FR test data, in the form of a verification of qualification report, and forward it to the qualifying activity within 30 days after the end of the reporting period as the basis of continued qualification approval. In addition, the manufacturer shall immediately notify the qualifying activity whenever the FR data indicates that the manufacturer has failed to maintain the qualified FR level, or the group C inspection data indicates failure of the qualified product to meet the requirements of this specification. Continuation shall be based on evidence that over the 6-month period the following has been met:

a. Verification by the qualifying activity that the manufacturer meets the requirements of MIL-STD-790.

b. The manufacturer has not modified the design of the item.

c. The specification requirements for the item have not been amended so far as to affect the character of the item.

d. Lot rejection for group A inspection does not exceed 5 percent or one lot, whichever is greater.

e. The requirements for group C inspection are met.

f. The records of all FR tests combined substantiate that the "M" or "P" FR level has been maintained or that the manufacturer continues to meet the "R" or "S" FR level for which qualified, although the total component hours of testing may not, as yet, meet the requirements of 4.4.4c.

When Group C requirements were not met and the manufacturer has taken corrective action satisfactory to the Government, group C retesting shall be instituted. A summary of the retesting shall be forwarded to the qualifying activity within 30 days after completion of the retest.

In the event that no production occurred during the reporting period, a report shall be submitted certifying that the manufacturer still has the capabilities and facilities necessary to produce the item. The manufacturer, however, shall maintain the required number of units hours in the specified maintenance period in order to remain qualified to the applicable failure rate levels. The manufacturer shall also produce enough parts during any reporting period in order to perform all applicable group C tests.

4.6 Quality conformance inspection.

4.6.1 Inspection of product for delivery. Inspection of product for delivery shall consist of groups A and B inspections. Group B, subgroup 2 need not be completed before shipment on lots of less than 50 pieces.

4.6.1.1 Inspection and production lot.

4.6.1.1.1 Inspection lot. An inspection lot shall consist of all capacitors in one or more styles, produced under essentially the same conditions, and offered for inspection in one month. The sample selected from the lot shall be representative of the styles in the lot. ER parts shall be kept separate from non-ER parts. Styles may be grouped by characteristic as follows.

Group	Characteristic	
1	K	CQR09, CQR12, CQR13, CQR19, CQR39, CQR42, and CQR43.
2	M	CQR29, CQR32, and CQR33.
3	Q	CQR07.
4	E, F, G, or K	CQ72.
5		All non-ER styles may be grouped by characteristic.

4.6.1.1.2 Production lot. A production lot shall consist of all capacitors of the same style, voltage rating, nominal capacitance value, and voltage-temperature characteristic. The manufacture of all parts in the lot shall have been started, processed, assembled, and tested as a group. Lot identity shall be maintained throughout the manufacturing cycle.

4.6.1.2 Group A inspection. Group A inspection shall consist of the examination and tests specified in table XI or XIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

TABLE XI. Group A inspection (ER).

Inspection	Requirement paragraph	Test method paragraph	Sampling procedure
Subgroup 1			
Burn in	3.6	4.7.3	100% inspection
Radiographic inspection 1/	3.7	4.7.4	
Thermal shock	3.8	4.7.5	
Seal	3.9	4.7.6	
Dielectric withstanding voltage	3.10	4.7.7	
Insulation resistance	3.12	4.7.9	
Capacitance	3.13	4.7.10	
Dissipation factor	3.14	4.7.11	
Subgroup 2 (ppm)			
Insulation resistance (ppm-2)	3.12	4.7.9	See table XII
Capacitance (ppm-2)	3.13	4.7.10	
Dissipation factor (ppm-2)	3.14	4.7.11	
Mechanical examination: Physical dimensions only (ppm-3)	3.1 and 3.5	4.7.2	
Subgroup 3			
Visual and mechanical examination (external): Physical dimensions, Marking 2/, Workmanship	3.1, 3.5, and 3.30 to 3.31.2 inclusive	4.7.2	13 samples 0 failures
Subgroup 4			
Solderability (wire lead styles only)	3.18	4.7.15	13 samples 0 failures

1/ FR level M- radiographic: Not applicable.
2/ Marking defects are based on visual examination only.

TABLE XII. Sampling plans for ppm categories.

Lot size	Sample size	
	ppm-2	ppm-3
1 - 13	100%	100%
14 - 125	100%	13
126 - 150	125	13
151 - 280	125	20
281 - 500	125	29
501 - 1,200	125	34
1,201 - 3,200	125	42
3,201 - 10,000	192	50
10,001 - 35,000	294	60
35,001 - 150,000	294	74
150,001 - 500,000	345	90
500,001 - Up	435	102

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

TABLE XIII. Group A inspection (Non-ER).

Inspection	Requirement paragraph	Test method paragraph	Sampling procedure
Subgroup 1			
Thermal shock	3.8	4.7.5	See table XIV
Seal	3.9	4.7.6	
Dielectric withstanding voltage	3.10	4.7.7	
Insulation resistance	3.12	4.7.9	
Capacitance	3.13	4.7.10	
Dissipation factor	3.14	4.7.11	
Subgroup 2			
Visual and mechanical examination (external):			
Physical dimensions	3.1, 3.5, and 3.30 to 3.31.2 inclusive	4.7.2	13 samples 0 failures
Marking 1/			
Workmanship			
Subgroup 3			
Solderability (wire lead styles only)	3.18	4.7.15	13 samples 0 failures

1/ Marking defects are based on visual examination only.

TABLE XIV. Sample size for subgroup 1.

Lot size	Sample size
1 - 125	100%
126 - 3,200	125
3,201 - 10,000	192
10,001 - 150,000	294
150,001 - 500,000	345
500,001 - Up	435

4.6.1.2.1 ER styles.

4.6.1.2.1.1 Subgroup 1 tests. Subgroup 1 tests shall be performed on a production lot basis on 100 percent of the product supplied under this specification. Capacitors failing the tests of subgroup 1 shall be removed from the lot. If, during the 100 percent inspection, screening required that more than 5 percent of the capacitors be discarded, the entire production lot shall be rejected.

4.6.1.2.1.1.1 Manufacturer's production inspection. If the manufacturer performs tests similar to that specified in subgroup 1, table XI, as the final step of their production process, group A, subgroup 1 inspection may be waived and the data resulting from the manufacturer's production tests may be used instead. Authority to waive the subgroup 1 inspection shall be granted by the qualifying activity only. The following criteria must be complied with.

a. Tests conducted by the manufacturer during production shall be clearly identical to or more stringent than that specified for subgroup 1.

b. Manufacturer subjects 100 percent of the product supplied under this specification to their production tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

c. The parameters measured and the failure criteria shall be the same as, or more stringent than, those specified herein.

d. The lot rejection criteria is the same as, or more stringent than, that specified herein.

e. The manufacturer shall make available all information concerning the test procedures and instrumentation used in his production tests. This data shall be provided as part of the evaluation required for MIL-STD-790. The manufacturer shall also make available to the Government all records of all detail test data resulting from production tests.

f. Once approved, the manufacturer shall not change the test procedure or criteria without prior notification and concurrence by the qualifying activity.

4.6.1.2.1.2 Subgroup 2 tests (ppm categories).

4.6.1.2.1.2.1 Sampling plans. Subgroup 2 tests shall be performed on an inspection lot basis. Samples subjected to subgroup 2 shall be selected in accordance with table XI, based on the size of the inspection lot. In the event of one or more failures, the lot shall be rejected. Equipment and operators used to perform the subgroup 2 tests shall not be the same as those used in the subgroup 1, 100 percent tests.

4.6.1.2.1.2.2 Rejected lots. The rejected lot shall be segregated from new lots and those lots that have passed inspection. The rejected lot shall be 100 percent inspected for those quality characteristics found defective in the sample and any defectives found shall be removed from the lot. A new sample of parts shall then be randomly selected in accordance with table XI. If one or more defects are found in this second sample, the lot shall be rejected and shall not be supplied to this specification.

4.6.1.2.1.2.3 PPM calculations. PPM calculations shall be based on the results of the first sample check as prescribed in 4.6.1.2.1.2.1. Calculations and data exclusion shall be in accordance with EIA-554. (NOTE: PPM calculations shall not use data on the second sample submission.)

4.6.1.2.1.3 Subgroup 3 tests. Subgroup 3 shall be performed on an inspection lot basis. The sampling procedure shall be as specified in table XI.

4.6.1.2.1.3.1 Rejected lots. The rejected lot shall be segregated from new lots and those lots that have passed inspection. Lots rejected because of failures in subgroup 3 may be offered for acceptance only if the manufacturer inspects all units in the lot for those quality characteristics found defective in the sample and, after removing all defective units found, reinspects the lot using the sampling procedure specified in table XI. If one or more defects are found in the second sample, the lot shall be rejected and shall not be supplied to this specification. Resubmitted lots shall be kept separate from new lots, and shall be identified as resubmitted lots.

4.6.1.2.1.4 Subgroup 4 (solderability).

4.6.1.2.1.4.1 Inspection lot. An inspection lot for the purpose of subgroup 4 (solderability) testing shall consist of all lots manufactured with the same diameter lead wire and offered for inspection within the same work week. Each manufacturing lot shall be kept separate from every other lot. All samples belonging to a manufacturing lot shall be identified to that lot. Means of identification is at the option of the manufacturer.

4.6.1.2.1.4.2 Sampling plan. a minimum of 13 pieces shall be selected randomly from each inspection lot; however, each manufacturing lot shall be represented in the sample. If the inspection lot consists of more than 13 manufacturing lots, then a minimum of one sample shall be selected from each manufacturing lot. If there are one or more failures, the inspection lot shall be considered to have failed. The manufacturer may use electrical rejects from the subgroup 1 screening tests for all or part of the samples to be used for solderability testing.

4.6.1.2.1.4.3 Rejected lots. In the event of one or more defects, the inspection lot is rejected. The manufacturer may use one of the following options to rework the lot.

a. Each production lot that was used to form the failed inspection lot shall be individually submitted to the solderability test as required in 4.6.1.2.1.4.2. Production lots that pass the solderability test are available for shipment. Production lots failing the solderability test can be reworked only if submitted to the solder dip procedure in 4.6.1.2.1.4.3b.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

b. The manufacturer submits the failed lot to a 100 percent solder dip using a approved solder dip process in accordance with 3.5.4.2. Following the solder dip, the electrical measurements required in group A, subgroup 1 tests shall be repeated on 100 percent of the lot. The PDA for the electrical measurements shall be as for the subgroup 1 tests. (NOTE: If x-ray and hermetic seal are required in the group A, subgroup 1 tests, these tests shall be repeated.) Thirteen additional samples shall then be selected and subjected to the solderability test with zero defects allowed. If the lot fails this solderability test, the lot may be reworked a second time and retested. If the lot fails this second rework, the lot shall be considered rejected and shall not be furnished against the requirements of this specification.

4.6.1.2.1.4.4 Disposition of sample. The solderability test is considered a destructive test and samples submitted to the solderability test shall not be supplied on the contract.

4.6.1.2.2 Non-ER styles.

4.6.1.2.2.1 Sampling plan. The inspection lot shall be submitted to the sampling plan for subgroup 1 and subgroup 2 as specified in table XIII.

4.6.1.2.2.2 Rejected lots. If an inspection lot for subgroup 1 or subgroup 2 is rejected, the contractor may rework it to correct the defects, or screen out the defective units and resubmit for reinspection. Resubmitted lot shall be inspected using tightened inspection. Such lots shall be separated from new lots, and shall be clearly identified as reinspected lots.

4.6.1.2.2.3 Subgroup 3 (solderability).

4.6.1.2.2.3.1 Sampling plan. Thirteen samples shall be selected randomly from every inspection lot and subjected to the subgroup 3 solderability test. The manufacturer may use electrical rejects from the subgroup 1 screening tests for all or part of the samples to be used for solderability testing. If there are one or more defects, the lot shall be considered to have failed.

4.6.1.2.2.3.2 Rejected lots. In the event of one or more defects, the inspection lot shall be rejected. The manufacturer may use one of the following options to rework the lot.

a. Each production lot that was used to form the failed inspection lot shall be individually submitted to the solderability test as required in 4.6.1.2.2.3.1. Production lots that pass the solderability test are available for shipment. Production lots failing the solderability test can be reworked only if submitted to the solder dip procedure in 4.6.1.2.2.3.2b.

b. The manufacturer shall submit the failed lot to a 100 percent solder dip using an approved solder dip process in accordance with 3.5.4. Following the solder dip, the electrical measurements required in the group A, subgroup 1 tests shall be repeated on another 125 samples with no defects allowed. Thirteen additional samples shall then be selected and subjected to the solderability test with no defects allowed. If the lot fails this solderability test, the lot may be reworked a second time and retested.d If the lot fails this second rework, the lot shall be considered rejected and shall not be furnished against the requirements of this specification.

4.6.1.2.2.3.3 Disposition of samples. The solderability test is considered a destructive test and samples submitted to the solderability test shall not be supplied on the contract.

4.6.2 Group B inspection. Group B inspection shall consist of the inspections specified in table XV, in the order shown, and shall be made on sample units selected from the lots which have passed the group A inspection. Test data obtained shall be reviewed as part of the complete retention of qualification. Except where the results of these inspections show noncompliance with the applicable requirements (see 4.6.3.1.4), delivery of products which have passed group A shall not be delayed pending the results of group B, subgroup 2.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the currentversion before use.

TABLE XV. Group B inspection.

Inspection	Requirement paragraph	Method paragraph	ER and Non-ER	
			Number of sample units to be inspected	Number of defectives permitted
Subgroup 1				
Insulation resistance (at high ambient test temperature)	3.12	4.7.9	5	0
Dielectric absorption (when specified)	3.21	4.7.18		
Stability at low and high temperatures	3.22	4.7.19		
Temperature coefficient (characteristic P only)	3.23	4.7.20		
Barometric pressure (reduced)	3.11	4.7.8		
Subgroup 2				
Life (240 hour)	3.24	4.7.21.2.1	5	0

4.6.2.1 Reject lots. If an inspection lot is rejected as a result of failure to pass group B inspection, the lot shall not be resubmitted. However, if the lot is rejected because of failure to pass the stability at low and high temperature test of subgroup 1, the lot may be resubmitted provided the defective units are removed and the lot is then subjected to 100 percent inspection for those characteristics found defective. Resubmitted lots shall be kept separate from new lots, and shall be clearly identified as resubmitted lots. Even though the lot has been rejected, those units which were predesignated for extended life testing shall remain or be placed on test for the full length of time.

4.6.3 Periodic inspection. Periodic inspection shall consist of group C inspection. Except where the results of these inspections show noncompliance with the applicable requirement (see 4.6.3.1.4), delivery of products which have passed group A and group B inspections shall not be delayed pending results of periodic inspection.

4.6.3.1 Group C inspection. Group C inspection shall be performed on sample units which have been subjected to and have passed the applicable tests (by FR level and non-ER styles) for group A inspection and shall consist of the test specified in table XVI in the order shown. Test data shall be reviewed as part of the complete verification of qualification.

4.6.3.1.1 Sampling plan.

4.6.3.1.1.1 For all non-ER styles and FR levels. Sample units shall be selected from the first lot and thence from every two months production for subgroups 1, 2, 3, and 4. The highest watt-second rating in each style, characteristic, and voltage manufactured during the specified periods shall be represented in at least the approximate ratio of production. A different sample shall be selected for each subgroup.

4.6.3.1.1.2 For FR levels M, P, R, and S. In addition to the tests specified in 4.6.3.1.1.1, a minimum ten sample units from each inspection lot (see 4.6.1.1.1) shall be subjected to subgroup 3 of table XVI. Allowable failures shall be as specified in table IV of MIL-STD-690.

4.6.3.1.2 Failures. If the number of failures exceeds the number allowed in table XVI, the sample shall be considered to have failed.

4.6.3.1.3 Disposition of sample units. Sample units which have been subjected to group C inspection shall not be delivered on the contract or order.

Source: https://assist.dla.mil -- Downloaded: 202640-19T06:58Z
Check the source to verify that this is the current version before use.

† The requirements for group C inspection are met.

4.6.3.1.4 Noncompliance (applicable to both ER and non-ER parts). If a sample fails to pass group C inspection, the manufacturer shall notify the qualifying activity and cognizant inspection activity of such failure and take corrective action on the materials or processes, or both, as warranted, and on all units of product which can be corrected and which were manufactured under essentially the same conditions, with essentially the same materials, processes, etc., and which are considered subject to the same failure. Acceptance of the product shall be discontinued until corrective action, acceptable to the Government, has been taken. After the corrective action has been taken, group C inspection shall be repeated on additional sample units (all inspection, or the inspection which the original sample failed, at the option of the Government). Group A and group B inspections may be reinstituted; however, final acceptance shall be withheld until the group C reinspection has shown that the corrective action was successful. In the event of failure after reinspection, information concerning the failure and corrective action taken shall be furnished to the qualifying activity and the contracting officer or purchaser.

TABLE XVI. Group C inspection.

Inspection	Requirement paragraph	Method paragraph	Number of sample units to be inspected	Number of defectives allowed	
				NON-ER	ER
Subgroup 1					
Shock (specified pulse) (not applicable to ceramic- or-glass-cased units)	3.19	4.7.16	12	1	1
Vibration	3.15	4.7.12			
Salt spray (corrosion) (metal cases only)	3.16	4.7.13			
Immersion	3.17	4.7.14		1	1
Subgroup 2					
Terminal strength	3.20	4.7.17	12	1	1
Moisture resistance	3.28	4.7.25			
Dielectric withstanding voltage (sleeving only)	3.10.2	4.7.7.2			
Subgroup 3					
Life	3.24	4.7.21.2.2	12 (non-ER) ER (see 4.6.3.1.1)	1	See 4.6.3.1.1
Subgroup 4 (every 6 months)					
Resistance to solvents	3.26	4.7.23	6	N/A	1
Resistance to soldering heat (wire-lead styles only)	3.27	4.7.24			

4.6.4 Inspection of packaging. The sampling and inspection of the preservation, packing, and container marking shall be in accordance with the requirements of MIL-C-39028.

4.7 Methods of examination and test.

4.7.1 Measurement conditions.

4.7.1.1 AC measurements. Alternating-current (ac) measurements shall be made at the frequency specified. The magnitude of the ac voltage shall be limited to 1.0 volt root-mean-square (rms). The maximum dc bias voltage shall be 2.2 volts-for all ac measurements of capacitors.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

4.7.1.2 Reference measurements. When requirements are based on comparative measurements made before and after conditioning, the reference measurement shall be considered the last measurement made at 25°C ±5°C prior to conditioning. Unless reference measurements have been made within 30 days prior to the beginning of conditioning, they shall be repeated.

4.7.1.3 Power supply. The power supply used for life testing shall have a regulation of ±2 percent or less of the rated voltage. The power source employed for dc leakage current measurements shall be stabilized to at least ±100 ppm. No voltage fluctuations shall occur during measurements that would produce a variation in the current measurement as read with any acceptable dc leakage current tester used to test capacitors.

4.7.2 Visual and mechanical examination. Capacitors and retainers shall be examined to verify that the material, design, construction, physical dimensions, marking, and workmanship are in accordance with the applicable requirements (see 3.1, 3.4, to 3.5.3 inclusive, and 3.30 to 3.31.1.2 inclusive).

4.7.3 Burn-in (see 3.6) (ERs only, when applicable, see 3.1). Capacitors shall be subjected to 140 percent of the dc rated voltage at the high ambient test temperature for 48 hours +8 hours, -0 hours. During this test, capacitors shall be adequately protected against temporary voltage surges of 10 percent or more of the test voltage. After the test, capacitors shall show no evidence of damage, arcing, or breakdown.

4.7.4 Radiographic inspection (x-ray) (see 3.7) (ERs only, when applicable, see 3.1). Capacitors shall be tested in accordance with method 209 of MIL-STD-202. The following details shall apply.

a. Radiographic quality: Sufficient definition to determine that specimens are free from defects specified in 3.7.

b. Image-quality indicator: As sample part of the same type as the part being radiographed that contains either an actual or simulated defect which is at least 10 percent smaller than the smallest defect to be detected.

c. Positions of specimen: Two views perpendicular to the terminal axis. After first view, specimen shall be rotated 90 degrees for the second view.

d. Evaluation of images.

(1) Special kind of viewing equipment: Magnifying glass.

(2) Magnification: 10X.

(3) Defects to be sought in specimen: As specified in 3.7.

4.7.5 Thermal shock (see 3.8). Capacitors and retainers shall be tested in accordance with method 107 of MIL-STD-202. The following details and exceptions shall apply:

a. Test condition letter: Unless otherwise specified, B, except that during step 3, capacitors shall be conditioned at the high ambient test temperature (see 3.1).

b. Measurements before and after cycling: Not applicable.

4.7.6 Seal (see 3.9). Capacitors shall be tested in accordance with method 112, MIL-STD-202. The following details shall apply.

a. Test condition letter: As specified, see 3.1.

b. Examination after test: Capacitors shall be visually examined for evidence of leakage.

4.7.6.1 Seal (alternative test (see 3.9). For capacitors with a liquid impregnant, the following seal test may be substituted: Capacitors shall be placed on a clean sheet of absorbent paper and exposed to the applicable high ambient test temperature for a minimum of 1 hour. The capacitor shall then be visually examined for evidence of leakage of impregnant or filling compounds or bubbles from the seal. Capacitors to be subjected to the salt spray (corrosion), and immersion tests may be excluded from the seal test until after the salt spray (corrosion), and immersion tests are completed.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

4.7.7. Dielectric withstanding voltage (see 3.10).

4.7.7.1 Capacitors. Capacitors shall be tested in accordance with method 301, MIL-STD-202. The following details and exceptions shall apply:

a. Magnitude of test voltage: As specified in table XVII.

b. Nature of potential: dc.



c. Duration of application of test voltage: As specified in table XVII.

d. Points of application of test voltage: As specified in table XVII.

e. Examinations after test: Capacitors shall be visually examined for evidence of breakdown, arcing, or other visible damage.

4.7.7.2 Sleeving (see 3.10.2) (when applicable, see 3.1). With the capacitor horizontally mounted, a single loop of No. 20 AWG wire shall be secured around the insulating sleeve of the capacitor so that it extends downward from the capacitor 3 inches minimum, and the two ends of the wire twisted in about three cross turns. A 1-pound minimum weight shall then be suspended from the looped wire. After exposure in this position for a minimum of 24 hours, at the maximum rated temperature ±3°C, a dc voltage of 4,000 volts minimum, shall be applied between the case and the looped wire. The rate of voltage application shall be 500 volts per second and the duration of application of test voltage shall be 15 seconds, minimum.

TABLE XVII. Dielectric-withstanding-voltage test details.

Circuit-diagram symbol	Circuit diagram	Test points	Test connections	Magnitude of test voltage	Duration of application of voltage
				Percent rated dc voltage	Minutes
1		Terminal to terminal	1 to 2	200 1/	1 2/
		Terminal to case 3/	1 and 2 to case	200	1
3		Terminal to terminal	1 to 2 or 1 to case	200 1/	1 2/

1/ 175 percent rated dc voltage after immersion, and moisture resistance tests.
2/ For the 100-percent inspection specified in 4.6.1.2, the capacitors shall be subjected, at the option of the manufacturer, to the application of 250 percent of rated dc voltage for not less than 5 seconds, or 200 percent for not less than 15 seconds.
3/ For quality conformance inspection, application of potential may be made between each terminal individually and the case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

4.7.8 Barometric pressure (reduced) (see 3.11) (when applicable, see 3.1). Capacitors shall be tested in accordance with method 105 of MIL-STD-202. The following details and exceptions shall apply.

a. Method of mounting: By normal mounting means.

b. Test condition: Unless otherwise specified (see 3.1), capacitors shall be subjected to a pressure of 0.82 inch of mercury (80,000 feet).

c. Test during subjection to reduced pressure: Unless otherwise specified (see 3.1), a potential equal to that specified in table XVIII, as applicable, shall be applied for at least 1 minute between test points specified (see 3.1). A suitable means shall be used to detect momentary or permanent breakdown. Capacitors shall then be visually examined for evidence of damage (see 6.5.5).

TABLE XVIII. Barometric-pressure test potentials.

Case diameter	DC voltage (max) 1/
Inch	Volts
0.175	200
0.195	200
0.235	300
0.312	430
0.400	500
0.562 and up	640

1/ The dc voltage shall be limited to 200 percent of the dc voltage rating at maximum rated temperature.

4.7.9 Insulation resistance (see 3.12). Capacitors shall be tested in accordance with method 302, MIL-STD-202. The following details and exceptions shall apply.

a. Test potential:

(1) Insulating sleeves: When applicable (see 3.1). Test condition B.

(2) Terminal to terminal and terminal to case: A potential equal to the rated dc voltage (see 3.1) or 500 V dc, whichever is less.

b. Special conditions: The time constant of the measurement circuit with the capacitor connected shall not exceed 30 seconds.

c. Points of measurement:

(1) Insulating sleeves: The test potential shall be applied between the case and a piece of metal foil placed around the insulating sleeve; the metal foil shall be of such dimension as to allow at least .125 inch surface exposure of the insulating sleeve on each end (see 3.12.1).

(2) Terminal to terminal: Insulation resistance shall be measured between terminals at the maximum rated temperature, ±3°C, and at 25°C ±3°C (see 3.12.2).

(3) Terminals to case: When the case is not a terminal, the measurement shall be made between each terminal and the case at 25°C ±3°C (see 3.12.3).

d. Electrification time: 2 minutes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

4.7.10 Capacitance (see 3.13.). Capacitors shall be tested in accordance with method 305 of MIL-STD-202. The following details shall apply.

a. Test frequency: 1,000 Hertz (Hz) ±100 Hz for capacitors whose nominal capacitance does not exceed 1 μF and whose dc voltage rating does not exceed 3,000 volts. For capacitors not within these limits, measurements shall be made at a frequency of 100 Hz ±6 Hz or corrected thereto.

b. Limit of accuracy: Shall be within ±0.1 percent.

4.7.11 Dissipation factor (see 3.14). The dissipation factor shall be measured with an ac voltage not greater than 20 percent of the dc voltage rating, at a frequency of 1,000 ±100 Hz, for capacitors whose nominal capacitance does not exceed 1 μF and whose dc voltage rating does not exceed 3,000 volts. For capacitors not within these limits, measurements shall be made at a frequency of 100 Hz ±6 Hz or corrected thereto. Measurement accuracy shall be one of the following.

a. For dial reading: ±2 percent of dial reading or, .001, whichever is greater.

b. For digital readout: ±.001 percent ±2 percent of reading.

4.7.12 Vibration (see 3.1 and 3.15).

4.7.12.1 Low frequency. Capacitors shall be tested in accordance with method 201 of MIL-STD-202. The following details and exceptions shall apply.

a. Tests and measurements prior to vibration: Not applicable.

b. Method of mounting: Securely fastened by normal mounting means, except that capacitors without mounting retainers in sizes 1.562 inch long or .670 inch in diameter or larger shall be mounted by a supplemental means other than the wire leads. Wire-lead capacitors shall be secured .5 inch ±.125 inch from the case. The extraneous leads beyond the .5 inch securing point may be removed or supplemental support may be added.

c. Duration of vibration: For tubular styles: 4 hours (2 hours in each of 2 mutually perpendicular planes). For rectangular styles: 6 hours (2 hours in each of 3 mutually perpendicular planes).

d. Test and measurements during vibration: During the last 30 minutes of vibration in each direction, a signal of 1 kilohertz (kHz) ±0.2 kHz at a level of 1 volt ±0.5 volt shall be placed across the capacitor and measured with suitable ac detecting equipment to determine open - or short-circuits, or intermittent contacts. The accuracy of the detecting equipment shall be sufficient to detect any interruption with a duration of 0.5 ms or greater.

e. Examination after vibration: Capacitors shall be visually examined for evidence of mechanical damage.

4.7.12.2 High frequency. Capacitors and retainers shall be tested in accordance with method 204 of MIL-STD-202. The following details and exceptions shall apply:

a. Mounting of specimens: Capacitors shall be rigidly mounted by the body to a vibration test apparatus. Wire-lead capacitors shall be secured .5 inch ±.125 inch from the case. The extraneous leads beyond the .5 inch securing point may be removed or supplemental support may be added.

b. Electrical-load conditions: During the test, a potential of 125 percent of the dc rated voltage shall be applied between the terminals of the capacitor.

c. Test condition letter: B, with exception as specified (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

d. Measurements: During the last cycle in each direction, a signal of 1 kHz ±0.2 kHz at a level of 1 volt ±.05 volt shall be placed across the capacitor and measured with a suitable ac recording device (a permanent record is not necessary for this test) to determine open- or short-circuits, or intermittent contacts. The accuracy of the detecting equipment shall be sufficient to detect any interruption with a duration of 0.5 ms or greater.

e. Measurements and examination after vibration: After the test, with capacitors still mounted on the vibration jig, the insulating sleeve shall be tested for dielectric withstanding voltage, as specified in 4.7.7, with a potential of 2,000 V dc between the case and bracket. Capacitors and retainers shall be visually examined for evidence of mechanical damage.

4.7.13 Salt spray (corrosion) (see 3.16). Capacitors and retainers shall be tested in accordance with method 101, MIL-STD-202. The following details and exceptions shall apply.

a. Applicable salt solution: The salt solution concentration shall be 5 percent.

b. Test condition letter: B (48 hours).

c. Examination after exposure: Capacitors and retainers shall be visually examined for evidence of harmful corrosion, unwrapping of or mechanical damage to insulating sleeves (when applicable), and obliteration of marking.

4.7.14 Immersion (see 3.17). Capacitors and retainers shall be tested in accordance with method 104 of MIL-STD-202. The following details shall apply:

a. Test condition letter B.

b. Measurements after final cycle: For capacitors with insulating sleeves, dielectric withstanding voltage, and insulation resistance at 25°C shall be measured as specified in 4.7.7 and 4.7.9, respectively. The test potential shall be applied between the case and a piece of metal foil placed around the insulating sleeve; the metal foil shall be of such dimension as to allow at least .125 inch surface exposure of the insulating sleeve on each end. In addition, dielectric withstanding voltage and insulation resistance at 25°C of all capacitors shall be measured as specified in 4.7.7 and 4.7.9, respectively. Capacitors and retainers shall then be examined for harmful or extensive corrosion and obliteration of marking.

c. Examination after immersion: Capacitors shall be inspected for evidence of extensive corrosion and unwrapping of, or mechanical damage to the insulating sleeves, when applicable.

4.7.15 Solderability (wire leads only, see 3.1) (see 3.18). Capacitors shall be tested in accordance with method 208 of MIL-STD-202. The following details shall apply:

a. Number of terminations to be tested: Both leads of the capacitor shall be subjected to the solderability test.

b. Depth of immersion in flux and solder: The leads shall be immersed to within .125 inch of the capacitor body.

4.7.16 Shock (specified pulse) (see 3.19). Capacitors and retainers shall be tested in accordance with method 213 of MIL-STD-202. The following details shall apply.

a. Mounting: The body of the capacitor shall be securely fastened by mounting retainers. The leads shall be soldered to rigidly supported terminals so spaced that the length of each lead from the capacitor shall be .5 inch ±.125 inch from the edge of the supporting terminal.

b. Test condition letter: I (100 g's).

c. Electrical loading during shock: During the test, a potential of 125 percent of the dc voltage rating shall be applied between the terminals of the capacitor.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

d. Measurements during shock: During the test, observations shall be made to determine intermittent contact or arcing or open- or short-circuiting. Detecting equipment shall be sufficiently sensitive to detect any interruption with a duration of 0.5 ms or greater.

e. Examinations after test: Capacitors shall be visually examined for evidence of breakdown, arcing, fractures, or any other visible mechanical damage. Retrainers shall be visually examined for mechanical damage.

4.7.17 Terminal strength (see 3.20). Capacitors shall be tested in accordance with method 211 of MIL-STD-202. The following details and exceptions shall apply.

a. Test condition letter: As specified (see 3.1).

b. Examination after test: The capacitors and terminals shall be examined for mechanical damage.

4.7.18 Dielectric absorption (see 3.21), (when specified, see 3.1). The capacitor shall be charged at the dc voltage rating for 1 hour ±1 minute. The initial surge current shall not exceed 50 milliamperes. At the end of this period, the capacitor shall be disconnected from the power source and discharged through a 5 ohm ±5 percent resistor for 10 seconds ±1 second. The discharge resistor shall be disconnected from the capacitor at the end of the 10 second discharge period, and the voltage remaining on the capacitor (recovery voltage) shall be measured with an electrometer or other suitable device having an input resistance of 10,000 megohms or greater. Recovery voltage shall be read at the maximum voltage within a 15 minute period. The dielectric absorption shall be computed from the following formula.

$$d = \frac{V_1}{V_2} \times 100$$

Where: d = Percent dielectric absorption.
V_1 = Maximum recovery voltage.
V_2 = Charging voltage.


For an alternate production test method see figure 1.

4.7.19 Stability at low and high temperatures (see 3.22). Capacitors shall be placed in a chamber maintained at -65°C +0°C, -5°C or -55°C +0°C, -5°C (as applicable, see 3.1), and a potential equal to the dc rated voltage shall be applied at this condition for 48 hours ±4 hours. The air within the conditioning chamber shall be circulated. Before capacitors are moved from the conditioning chamber, capacitance shall be measured at the applicable low temperature (see 3.1) as specified in 4.7.9. Capacitance shall then be measured at the following temperature as specified in 4.7.9. (The measurement at each temperature shall be recorded when two successive readings taken at 5-minute intervals indicate no change in capacitance.)

25°C ±5°C
High ambient test temperature (see 3.1)
25°C ±5°C

After the test, capacitors shall be visually examined for evidence of breakdown, arcing, open- and short-circuiting, and other visible mechanical damage.

Source: https://assist.dla.mil -- Downloaded: 20260-19T06:58Z
Check the source to verify that this is the current version before use.



E = dc rated dc voltage or 100 volts dc, whichever is less (±2 percent).
R_1 and R_2 = 1,000 ohms ±20 percent. (This is not critical.)
R_3 = 5 ohms ±1 percent.
R_4 = 10,000 megohms, minimum.

Suggest use of ±1230A GR electrometer or equivalent set to 10,000 megohms range input resistance.

NOTES:
1. Charge for 5 minutes ±10 seconds with switch in position 1.
2. Switch in position 2 for 5 seconds ±0.5 second.
3. Switch in position 3 for 1 minute.
4. After 1 minute read recovery voltage and compute as a percentage of charge voltage.
5. Switch to position 4, discharge and remove.

FIGURE 1. Typical production dielectric absorption test method.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

4.7.20 Temperature coefficient (see 3.23) (characteristic P only, see 3.1). Capacitance measurements shall be made after the capacitors have been stabilized at each of the following temperatures: -65°C, +25°C, and the high ambient test temperature (see 3.1). Stability shall be indicated when no change exists in two capacitance measurements made at 5-minute intervals. Temperature coefficient shall be computed from the following formula:

$$T_C = \frac{(C_2 - C_1)\ 10^6}{(T_2 - T_1)\ C_1}$$

Where:

T_C = temperature coefficient in ppm/°C.
C_1 = capacitance at 25°C in pF.
C_2 = capacitance at test temperature in pF.
T_1 = 25°C.
T_2 = test temperature in degrees C.

4.7.21 Life (see 3.24).

4.7.21.1 2,000-hour (qualification inspection). Capacitors shall be tested in accordance with method 108 of MIL-STD-202. The following details and exceptions shall apply.

a. Distance of temperature measurements from specimens, inches: Not applicable.

b. Test temperature and tolerance: At the applicable high-test temperature, +4°C, -0°C (see 3.1).

c. Operating conditions: Capacitors shall be subjected to 140 percent of the rated dc voltage. The surge current shall be limited to between 5 milliamperes and 1 ampere. When necessary, a suitable current-limiting resistor shall be used.

d. Test condition letter: F (see table XIX).

e. Measurements during and after exposure: At the conclusion of the test, the capacitors shall be returned to the inspection conditions specified in 4.3 and shall be visually examined for evidence of mechanical damage and obliteration of marking; insulation resistance at +25°C, capacitance, and dissipation factor shall be measured as specified in 4.7.9, 4.7.10, and 4.7.11, respectively.

TABLE XIX. Life test in hours.

NON-ER capacitors			
Characteristic	Qualification	Group B	Group C
E, F, and G	240 +48, -0	240 +48, -0	---
K	240 +48, -0 1/	240 +48, -0 1/	---
M	2,000 +72, -0	240 +48, -0	1,760 +72, -0
P	240 +48, -0	240 +48, -0	---
T	240 +48, -0	240 +48, -0	---
Q	240 +48, -0	240 +48, -0	---

ER capacitors				
Style	Qualification	Group B	Group C	Extended life
CQR39, 42, and 43	240 +48, -0	---	240 +48, -0	---
FR levels M, P, R, S, for all styles except CQR39, 42, and 43	2,000 +72, -0	---	2,000 +72, -0	4,000 +72,-0

1/ Test time for characteristic K tubular capacitors with voltage ratings of 1,000 volts shall be 500 ±12 hours.

Source: https://assist.dla.mil -- Downloaded: 2026Ø10-19T06:58Z
Check the source to verify that this is the current version before use.

4.7.21.2 Hours (quality conformance inspection).

4.7.21.2.1 240-hour (group B inspection) (see 3.24). Capacitors shall be tested as specified in 4.7.21.1, except the duration of the test shall be 240 hours +48 hours, -0 hours.

4.7.21.2.2 2,000-hour (group C inspection) (see 3.24). Except as specified in the following, capacitors shall be tested as specified in 4.7.21.1.

a. Test duration: See table XIX.

b. Measurements during and after exposure: Measurements, as specified in 4.7.21.1e, shall be taken at the following intervals of exposure: During the first hour, 240 hours +48 hours, -0 hours, 1,000 hours +48 hours, -0 hours, and 2,000 hours +72 hours, -0 hours.

4.7.21.3 Extended life (see 3.24).

4.7.21.3.1 Following 2,000-hour qualification inspection. Sample units that have been subjected to 2,000 hours of life test as specified in 4.7.21.1 and 4.7.21.2.2, shall remain on test for an additional 4,000 hours +72 hours, -0 hours. After completion of the 6,000-hour life test time capacitors shall be measured as specified in 4.7.21.1e.

4.7.21.3.2 Following 240-hour group B inspection (ER parts only) (see table XIX). Sample units that have been subjected to 240 hours of life test as specified in 4.7.21.2.1, shall remain on test for an additional 5,760 hours. Measurement, as specified in 4.7.21.1e, shall be taken at the following intervals of exposure: After 240 hours +48 hours, -0 hours, 1,000 hours +48 hours, -0 hours, 2,000 hours +72 hours, -0 hours, 4,000 hours +72 hours, -0 hours, and 6,000 hours +72 hours, -0 hours.

4.7.21.3.3 Following 240-hour group B inspection (non-ER parts, characteristic M only, see table XIX). Every 3 months, 12 sample units that have successfully completed the 240-hour group B life test, shall be continued on test for an additional 1,760 hours +72 hours, -0 hours.

4.7.22 Fungus (see 3.25). Capacitors shall be tested in accordance with method 508 of MIL-STD-810. Pretest and post-test measurements are not required.

4.7.23 Resistance to solvents (see 3.26) Capacitors shall be tested in accordance with method 215 of MIL-STD-202. The following details shall apply.

a. Portion of specimen to be brushed: That portion on which marking is present.

b. Number of specimens to be tested: As specified in applicable inspection tables.

c. Permissible extent of damage: As specified in 3.26.

4.7.24 Resistance to soldering heat (see 3.27) (applicable to wire-lead capacitors only). Capacitors shall be tested in accordance with method 210 of MIL-STD-202. The following details shall apply:

a. Depth of immersion in the molten solder: To a minimum of 0.250 inch from the capacitor body.

b. Test condition letter: C, (260°C ±5°C; 10 seconds ±1 seconds).

c. Cooling time prior to measurement after test: 10 minutes ±1 minute.

d. Measurements after test: Insulation resistance, capacitance, and dissipation factor shall be measured at 25°C ±3°C as specified in 4.7.7, 4.7.8, and 4.7.9, respectively.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

4.7.25 Moisture resistance (see 3.28). Capacitors and retainers shall be tested in accordance with method 102, test condition D, MIL-STD-202, except that no measurement shall be made before and after cycling. Capacitors shall then be tested in accordance with method 106, MIL-STD-202. The following details and exceptions shall apply.

a. Initial measurements: Not applicable.

b. Polarization voltage: During steps 1 through 6, inclusive, a dc potential of 100 volts shall be applied across the terminals of 50 percent of the capacitors. No potential shall be applied to the remaining 50 percent of the capacitors.

c. Loading voltage: Not applicable.

d. Final measurements: After the final cycle, the capacitors shall be conditioned at 25°C ±5°C and a relative humidity of 50 percent ±5 percent for a period of at least 22 hours but not more. Dielectric withstanding voltage and insulation resistance at 25°C shall be measured on insulating sleeves as specified in 4.7.7 and 4.7.9, respectively. The test potential shall be applied between the case and a piece of metal foil placed around the insulating sleeve. The metal foil shall be of such dimension as to allow at least .125 inch surface exposure of the insulating sleeve on each end. In addition, dielectric withstanding voltage, insulation resistance, capacitance, and dissipation factor at 25°C, of all capacitors shall be measured as specified in 4.7.7, 4.7.9, 4.7.10, and 4.7.11, respectively.

After the test, capacitors and retainers shall be visually examined for evidence of harmful corrosion and obliteration of marking; capacitors shall be examined for unwrapping of or mechanical damage to insulated sleeves, when applicable.

4.7.26 Flashpoint of impregnant or filling compound (see 3.29). The flashpoint of impregnant or filling compound shall be measured as specified in ASTM D92-57, except that the fire point and precision do not apply. "Impregnant or filling compound" shall be substituted for the word "oil" throughout the test method.

5. PACKAGING.

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-C-39028.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use.

6.1.1 Polystyrene dielectric capacitors. Capacitors of polystyrene dielectric, because of their low dielectric absorption and radiofrequency losses, are intended primarily for use in calculators, computers, integrators, time-base oscillators, laboratory standards, and other pulse applications. The outstanding characteristics of these capacitors are low temperature coefficient and stability.

6.1.2 Polyethylene terephthalate dielectric capacitors. Capacitors of polyethylene terephthalate dielectric are intended for use in high temperature applications similar to those served by hermetically sealed paper capacitors, but where higher insulation resistance at the upper temperature limits is required.

6.1.3 Paper and polyethylene terephthalate dielectric capacitors. Capacitors of paper and polyethylene terephthalate dielectric are intended for applications where small case sizes and high temperature operation are required.

6.1.4 Polytetrafluoroethylene dielectric capacitors. Capacitors of polytetrafluoroethylene dielectric are intended for high temperature applications where high insulation resistance, small capacitance change, and low dielectric absorption are required. These capacitors exhibit excellent insulation resistance values at high temperatures.

6.1.5 Polycarbonate dielectric capacitors. Capacitors of polycarbonate dielectric are especially suitable for use in tuned circuits and precision timing due to their capacitance stability and minimum capacitance change with temperature.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

6.2 Acquisition data. Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. Title, number and date of the applicable specification sheet and the complete PIN (see 1.2.1 and 3.1).

c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

d. Whether removable mounting retainers are to be supplied with capacitors (see 3.1).

e. If remarking of parts is required to indicate FR level (see 3.30.5).

6.3 Definitions.

6.3.1 Liquid-impregnanted capacitor. A liquid-impregnanted capacitor is a capacitor in which a liquid impregnant is dominantly contained within the capacitor element, but does not occupy substantially all of the case volume not required by the capacitor element and its connection.

6.3.2 Liquid-filled capacitor. A liquid-filled capacitor is a capacitor in which a liquid impregnant occupies substantially all of the case volume not required by the capacitor element and its connections. Space may be allowed for the expansion of the liquid with temperature variations.

6.3.3 Nonmagnetic case capacitor. A nonmagnetic case capacitor is a capacitor in which no part of the case or retainer is made of magnetizable material; however, the end seal may be made of a material having a ferrous metal content in order to effect a glass-to-metal seal.

6.3.4 Hermetic seal. For the purpose of this specification, a hermetically sealed capacitor is one in which the capacitive element is contained within a sealed enclosure of ceramic, glass or metal, or combinations thereof, where sealing is accomplished by material fusion, welding, brazing, or soldering. The capacitor shall be capable of passing the seal test specified in 4.7.6 or of meeting a leak-rate requirement of not more than 1.76 by 10^{-6} cubic centimeters (cm^3) per second, when determined by any other method having sensitivity equal to or better than the stated limit. When capacitors are tested as specified in 4.7.6, there shall be no continuous visible stream of bubbles.

6.4 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time set for opening of bids, qualified for inclusion in the applicable QPL whether or not such products have actually been so listed by that date. The attention of the contractors is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the QPL is the Department of the Air Force, however, information pertaining to qualification of products may be obtained from the Defense Electronics Supply Center (DESC-ELSP), 1507 Wilmington Pike, Dayton, Ohio 45444-5764, agent for administration of the QPL. Application for qualification tests shall be made in accordance with "Provisions Governing Qualification" (see 6.4.1).

6.4.1 Provisions governing qualification. Copies of SD-6, "Provisions Governing Qualification" may be obtained upon application to the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

6.5 Application information.

6.5.1 Mounting. Capacitors covered by this specification shall be mounted by a retainer or clamp or should be potted when vibration or shock are likely to be encountered in service.

6.5.2 Voltage derating with temperature (for characteristic M). Characteristic M tubular capacitors may be used in applications up to 125°C with voltage derating as indicated in figure 2. However, insulation resistance requirements at 125°C cannot be expected to exceed 100 megohm-microfarads; greater capacitance change may be encountered, and life expectancy of the unit will be reduced.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the currentversion before use.




FIGURE 2. Intended operating temperature.

4.5.3 Energy content (in watt-seconds). The energy content of a fully charged dc capacitor is determined by the following formula:

$$W = \frac{CE^2}{2}$$

Where:

W = energy content in watt-seconds.
C = nominal capacitance in farads.
E = dc voltage rating in volts.

6.5.4 AC component. The rating given is the steady-state dc voltage, or the sum of the dc voltage and the peak ac voltage, provided that the peak ac voltage does not exceed 20 percent of the rating at 60 Hz, 15 percent at 120 Hz, or 1 percent at 10,000 Hz. Where heavy transient or pulse currents are encountered, the requirements of this specification are not sufficient to guarantee satisfactory performance, and due allowance must therefore be made in the selection of a capacitor.

6.5.5 Barometric pressure (reduced) (see 4.7.8).

6.5.5.1 Ceramic- or glass-cased tubular capacitors. The dc voltage that may be applied to ceramic- or glass-cased tubular capacitors at altitudes from 50,000 to 100,000 feet may be obtained from figure 3.

6.5.5.2 Metal-cased tubular capacitors. The dc voltage that may be applied to metal-cased tubular capacitors at altitudes other than 80,000 feet may be obtained from figure 4, except that the dc voltage rating must not be exceeded.

6.5.6 Representation of minimum insulation-resistance requirements. A graphical representation of minimum insulation-resistance requirements, as specified in the applicable specification sheet, is shown in figure 5.

6.5.7 Life at temperatures and voltages below and above rated. The failure rates used in this specification are referred to operation at rated voltage at the maximum rated temperature. The sampling plans and failure-rate determinations throughout the specification assume an acceleration factor of 5 for the life test conducted at the maximum rated temperature and 140 percent of rated voltage. Lower failure rates than those for which the manufacturer has obtained qualification may be achieved by operating the capacitors at lower voltage, or at lower temperatures, or both. Factors by which failure rates are to be multiplied under conditions other than maximum conditions are shown on figure 6 (characteristic K only).

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.




FIGURE 3. Permissible operating voltage at altitudes from 50,000 to 100,000 feet.




FIGURE 4. Permissible operating voltage at altitudes other than 80,000 feet (metal-cased tubular).

Source: https://assist.dla.mil -- Downloaded: 20261O-19T06:58Z
Check the source to verify that this is the current version before use.





FIGURE 5. Graphical representation of minimum insulation - resistance requirements by dielectric as specified in the applicable specification sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.



NOTE: Curves for 100 percent of rated voltage and higher are based on the 5th power rule and curves for 90 percent of rated voltage and below are based on the 4th power rule.

FIGURE 6. Life at temperature and voltages relative to percent rating (characteristic K only).

Source: https://assist.dla.mil -- Downloaded: 20261O-19T06:58Z
Check the source to verify that this is the current version before use.

6.6 Standard capacitor types. Equipment designers should refer to MIL-STD-198, "Capacitors, Selection and Use of", for standard capacitor types and selected values chosen from this specification. MIL-STD-198 provides a selection of standard capacitors for new equipment design.

6.7 Interchangeability and substitutability. Whenever possible, items covered by this specification shall be used to replace items covered by MIL-C-14157, "Capacitors, fixed, paper (paper-plastic) or plastic dielectric, direct current (hermetically sealed in metal cases) established reliability, general specification for" and MIL-C-25, "Capacitors, fixed, paper-dielectric, direct current (hermetically sealed in metal cases) general specification for."

6.8 Failure rate L. Failure rate L has been canceled from this specification.

6.9 Tin plated finishes. Tin plating is prohibited (see 3.5.3.5) since it may result in tin whisker growth. Tin whisker growth could adversely affect the operation of electronic equipment systems. For additional information on this matter, refer to ASTM B545 (Standard Specification for Electrodeposited Coating of Tin.)

6.10 Subject term (key word) listing.

Part Per Million (ppm)
Statistical process control (SPC)

6.11 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

APPENDIX

PROCEDURE FOR QUALIFICATION INSPECTION

10. SCOPE

10.1 Scope. This appendix details the procedure for submission of samples, with related data, for qualification inspection of capacitors and retainers covered by this specification. The procedure for extending qualification of the required sample to other capacitors and retainers covered by this specification is also outlined herein. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance only.

20. APPLICABLE DOCUMENTS. This section is not applicable to this appendix.

30. SUBMISSION

30.1 Single-type capacitor submission. The following details apply.

a. Sample size: As specified in table IX.

b. Sampling criteria: Sample units of the same style, terminal, circuit, characteristic, rated voltage, capacitance, capacitance tolerance, and vibration grade will be submitted.

c. Extent of qualification:

(1) Circuit diagram 1 will qualify circuit diagram 3 in the same capacitor design.

(2) Qualification in one characteristic does not constitute qualification in any other characteristic.

(3) Any capacitance tolerance may represent all other authorized capacitance tolerances.

(4) Vibration grade 3 will qualify vibration grade 1 provided that the designs of the capacitors are the same.

(5) Qualification of insulated styles will be the basis for qualification of uninsulated styles of the same design.

(6) Styles CQ07, CQ09, CQ13, CQR09, CQR13, CQR19, CQR29, CQR33, CQR39, and CQR49 require individual voltage and characteristic qualification. Style CQ07 will qualify style CQ06, style CQ09 will qualify styles CQ08, and CQ12; CQR09 will qualify style CQR12; CQR29 will qualify CQR32, and CQR39 will qualify CQR42, provided the type submitted has the same impregnant or filling compound. The highest capacitance value submitted in each voltage rating will confer qualification of all units of the same style and lesser capacitance with the same voltage rating.

(7) Style CQ20 qualification is limited to the watt-second rating qualified and lesser values in the same voltage rating.

(8) Qualification of ER styles will qualify applicable non-ER styles of the same characteristic, voltage rating, and case size.

(9) Qualification of style CQ72 is restricted to those capacitance values and voltage ratings equal to and less than the ratings represented within the same watt-second group of the submission. Except type CQ72D1ES105K3 will qualify units in the same watt-second group (characteristic E) with 12,500 volt ratings provided that type CQ72D1ET105K3 qualification is complete; otherwise, type CQ72D1ET504K3 will qualify lesser watt-second ratings of 12,500 volt units in characteristic E. Type CQ72D1KT254K3 will qualify type CQ72D1KS504K3 rated at 25 watt-seconds. Terminal style E4 will represent E3.

(10) Qualification approval granted for one of the lower failure rate levels will include qualification approval for all of the higher failure rate levels as indicated in table XX.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

APPENDIX

TABLE XX. FR Qualification data.

Failure rate level	Will qualify failure rate level
S	S, R, P, M
R	R, P, M
P	P, M
M	M

30.1.1 Single type retainer submission. The following details apply:

a. Sample size: As specified in table X.

b. Sampling criteria: Sample units of the same retainer designator, design and case size will be submitted.

c. Extent of qualification: Qualification will be limited to the part number submitted.

30.2 Combined type submission. Qualification of the types submitted will be a basis for qualification of the style represented, based on the same provisions stated in 30.1 with the following exceptions: Voltage ratings are grouped in table XXI for the styles shown; samples are divided equally between the two voltage ratings of each group. Voltage ratings not listed in the table are qualified separately. Styles are grouped as shown in table XXII.

TABLE XXI. Voltage rating groups.

Styles CQ07, CQ09, CQ13, CQR09, CQR13, CQR19, CQR29, CQR33, CQR39, CQR43	Style CQ20
Voltage rating	Voltage rating
600 and 400	15000 and 12500
200 and 100	10000 and 7500
50 and 30	5000 and 3000
	2000 and 1000

NOTE: In view of the relatively few sample units of each type represented, a combined-type submission will be treated similarly to a single-type submission, and the failure of one type will disqualify the entire submission.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

APPENDIX

TABLE XXII. Examples of combined-type submissions. 1/

Styles	Types to be submitted	Number of sample units to be submitted	DC voltage rating	Watt-second rating
CQ06 and CQ07	CQ07A1QA105J3	45	50	.00125
	CQ07A1QB105J3	23	100	.005
	CQ07A1QC684J3	23	200	.0136
	CQ07A1QE474J3	23	400	.0376
	CQ07A1QF224J3	23	600	.0432
CQ08, CQ09, CQ12, and CQ13	CQ09A1KC105J3	23	200	.0200
	CQ13A1KC105J3	23	200	.0200
	CQ09A1KE474J3	23	400	.0376
	CQ13A1KF474J3	23	600	.0846
	CQ09A1KG474J3	23	1,000	.235
	CQ13A1KG474J3	23	1,000	.235
	CQ09A1MZ106J3	23	30	.0045
	CQ13A1MA125J3	23	50	.0015
	CQ09A1MB685J3	23	100	.0340
	CQ13A1MC105J3	23	200	.0200
	CQ09A1ME105J3	23	400	.0800
	CQ13A1MF684J3	23	600	.1224
	CQ09A1MG224J3	23	1,000	.110
	CQ13A1MG224J3	23	1,000	.110
	CQ09A1PA105J3	23	50	.00125
	CQ13A1PA105J3	23	50	.00125
	CQ09A1PC474J3	23	200	.0094
	CQ13A1PC474J3	23	200	.0094
	CQ09A1PE154J3	23	400	.0120
	CQ13A1PF224J3	23	600	.0396
	CQ09A1TC104J3	23	200	.0020
	CQ13A1TC104J3	23	200	.0020
	CQ09A1TE334J3	23	400	.0264
	CQ13A1TF154J3	23	600	.0275
CQ20	CQ20A1KG105K1	23	1,000	.500
	CQ20C1KJ684K1	23	2,000	1.36
	CQ20A1KL334K1	23	3,000	1.485
	CQ20C1KN154K1	23	5,000	2.375
	CQ20-1KR683K1	23	7,500	1.862
	CQ20-1KS393K1	23	10,000	1.950
	CQ20-1KT223K1	23	12,500	1.714
	CQ20-1KU153K1	23	15,000	1.688
CQ72	CQ72B1EG105K3	23	1,000	.5
	CQ72E1KG105K3	23	1,000	.5
	CQ72E1EN104K3	23	5,000	1.25
	CQ72D1ES104K3	23	10,000	5.0
	CQ72D1KS104K3	23	10,000	5.0
	CQ72D1ES105K3	23	10,000	50.0
	CQ72D1KT254K3	23	12,500	19.531
	CQ72D1ET105K3	23	12,500	78.125

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the currentversion before use.

APPENDIX

TABLE XXII. Examples of combined-type submissions 1/ - Continued.

Styles	Types to be submitted	Number of sample units to be submitted	DC voltage rating	Watt-second rating
CQR07	CQR07A1QA105J3M	82	50	.00125
	CQR07A1QB105J3M	41	100	.005
	CQR07A1QC684J3M	41	200	.0136
	CQR07A1QE474J3M	41	400	.0376
	CQR07A1QF224J3M	41	600	.0432
CQR09, CQR12, and CQR13	CQR09A1KC105J3M	41	200	.020
	CQR13A1KC105J3M	41	200	.020
	CQR09A1KE474J3M	41	400	.0376
	CQR13A1KF474J3M	41	600	.0846
	CQR09A1KG474J3M	41	1,000	.235
	CQR13A1KG474J3M	41	1,000	.235
CQR19	CQR19A1KD105J3M	41	300	.045
	CQR19A1KE105J3M	41	400	.080
	CQR19A1KF474J3M	82	600	.0846
CQR29, CQR32, and CQR33	CQR29A1MZ106J3M	41	30	.0045
	CQR33A1MA125J3M	41	50	.0015
	CQR29A1MB685J3M	41	100	.0340
	CQR33A1MC105J3M	41	200	.0200
	CQR29A1ME105J3M	41	400	.0800
	CQR33A1MF684J3M	41	600	.1224
	CQR29A1MG224J3M	41	1,000	.1100
	CQR33A1MG224J3M	41	1,000	.1100
CQR39, CQR42, and CQR43	CQR39A1KB105K3M	41	100	.0050
	CQR43A1KC105K3M	41	200	.0200
	CQR39A1KE474K3M	41	400	.0376
	CQR43A1KF474K3M	41	600	.0846
	CQR39A1KG474K3M	41	1,000	.2350
	CQR43A1KG474K3M	41	1,000	.2350
CQ05 and CQ10	CQ05A1KE105K3	23	400	.08
	CQ10A1KE105K3	23	400	.08
	CQ05A1KG474K3	23	1,000	.235
	CQ10A1KG474K3	23	1,000	.235
CQ11	CQ11A1KE474K3	23	400	.04
	CQ11A1KF684K3	23	600	.122

1/ This table is set up as a guide; for other combinations, reference is made to the text.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:58Z
Check the source to verify that this is the current version before use.

APPENDIX

30.2.1 Combined type retainer submission. The following details apply:

a. Sample size: As specified in table XXIII.

b. Sampling criteria: Retainers submitted may be divided between the largest and smallest sizes in the footed and spaded design as shown in table XXIII or in the designs in the largest and smallest case size required for complete CQ72 qualification.

c. Extent of qualification: Either submission of 30.2.1b will confer eligibility for complete qualification of CQ072 brackets.

TABLE XXIII. Example of combined sample submission.

Types to be submitted	Number of retainers to be submitted
CQ072FA1	14
CQ072SA1	14
CQ072FJ11	14
CQ072SJ11	14

30.3 Impregnant of filling compound. A minimum of .25 pound of each impregnant or filling compound used in the sample units for which qualification is sought shall be submitted.

40. DATA REQUIREMENTS

40.1 Test data. When examinations and tests are to be performed at a Government laboratory, prior to submission, all sample units shall be subjected to all of the examinations and tests indicated as nondestructive in table IX. Each submission shall be accompanied by the test data obtained from these examinations and tests. The performance of the destructive examinations and tests by the supplier on a duplicate set of sample units is encourage, although not required. All test data shall be submitted in duplicate.

40.2 Description of items. The supplier shall submit a detailed description of the materials and constructional features of the capacitors being submitted for inspection, including information as to whether they are liquid impregnated or liquid filled; the type and quantity of the impregnant or filling compound; the type, thickness, and number of layers of capacitor dielectric material and foil; the material, thickness, and applied finish of the case; and details on the end seal and terminal assembly.

40.3 Certification of materials. The supplier shall submit certification, in duplicate, that the materials used in his components are in accordance with the applicable specification requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the currentversion before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, AV, ME, MI
Navy - AS, OS, MC, SH
Air Force - 17, 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5910-1822)

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-C-19978F	2. DOCUMENT DATE (YYMMDD) 940331

3. DOCUMENT TITLE
CAPACITORS, FIXED, PLASTIC (OR PAPER-PLASTIC) DIELECTRIC, (HERMETICALLY SEALED IN METAL, CERAMIC, OR GLASS CASES), ESTABLISHED AND NON-ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME 645 LOG/LGME Gentile Station	b. TELEPHONE (Include Area Code) (1) Commercial 513-296-5517 (2) AUTOVON 986-5517
c. ADDRESS (Include Zip Code) 1060 Hamilton St. Dayton, OH 45444-5400	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:58Z
Check the source to verify that this is the current version before use.