MIL-W-19882A(SHIPS)
AMENDMENT - 1
31 MAY 1966

MILITARY SPECIFICATION

WINCHES, DRUM, POWER OPERATED, BATHYTHERMOGRAPH

This amendment forms a part of Military Specification MIL-W-19882A (SHIPS), dated 28 October 1960.

Page 1, paragraph 2.1: Under "MILITARY" specifications, add the following:

"MIL-S-901 - Shock Tests; H. I. (High Impact); Shipboard Machinery, Equipment and Systems, Requirements for."

Page 1, paragraph 3.1, line 2: After "test of" add "4.2,".

Page 2, paragraph 3.3.1, line 1: After "General requirements.-" add "The winch shall be designed to withstand grade A shock in accordance with Specification MIL-S-901."

Page 2, paragraph 3.3.1.3, heading: Delete and substitute "Weight and size.-".

Pages 2 and 3, paragraph 3.3.2.1: Delete and substitute:

"3.3.2.1 Clutch.- The winch drum shall be equipped with a friction type disc clutch having positive disengagement. The clutch shall drive the rated load at rated speed. When the drum is running free and the electric motor brake is set, the clutch shall be able to smoothly brake and stop the drum from speeds up to 1000 r.p.m. The clutch shall be able to hold without slip, a pull equal to 200 percent winch rated line pull when the wire rope is on the bare drum. The clutch shall be engaged by means of a hand lever. The lever shall be of a type that can be locked in all operating positions. The lock shall be of the hand grip release type. Adjustments to compensate for clutch wear shall be provided. The life of the clutch should not be adversely affected when operating as a brake."

FSC 3950

Source: https://assist.dla.mil -- Downloaded: 20261O-19T06:50Z
Check the source to verify that this is the current version before use.

Page 3, paragraph 3.3.3, line 5: Delete "spur,".

Page 3, paragraph 3.3.7.2, next to last line: Delete and substitute: "Insulation.- Class H."

Page 4, paragraph 3.3.10, heading: Delete and substitute: "Measuring device.-".

Page 4, paragraph 3.3.12, line 1: Delete "hand operated" and substitute "powered".

Page 4, paragraphs 3.3.13 through 3.3.13.3: Delete.

Page 4, paragraph 3.5: Add the following new sentence at the end of the paragraph: "The design life of the winch shall be 5,000 hours."

Page 5, paragraph 3.8.1, line 5 and paragraph 3.8.3, line 3: Delete "bureau" and substitute "command".

Page 5, paragraph 3.8.4: Add the following item:

"(e) Dimensioned location of the center of gravity of the winch."

Page 5, paragraph 3.9, line 2: Delete "type III" and substitute "class B".

Page 5, paragraphs 3.9.1 and 3.9.2: Delete.

Page 6, paragraph 3.10: Delete and substitute:

"3.10 Onboard repair parts.- One set of onboard repair parts shall be provided for each winch."

Page 6, paragraphs 3.11 and 3.12: Delete.

Page 6, paragraphs 4.2.1 through 4.2.1.2: Delete and substitute:

"4.2.1 Tests at place of manufacture.- Preproduction tests shall be conducted on one winch of each design by the contractor, at his own expense, at the place of manufacture. These tests may be witnessed by authorized representatives of the command or agency concerned."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:50Z
Check the source to verify that this is the current version before use.

Page 6, paragraph 4.2.4, last line: Add "and the winch overhauled".

Page 7, paragraph 4.4, last sentence: Delete and substiute: "Any sample winch containing one or more visual or dimensional defects shall not be offered for delivery and if the number of defective winches in any sample exceeds the acceptance number for that sample, this shall be cause for rejection of the lot represented by the sample."

Page 7, paragraph 4.5.1, third line: Delete "in each direction".

Page 7, paragraph 4.5.3: In third line, delete "200" and substitute "150" and in fourth line, delete "300" and substitute "200".

Page 7, paragraphs 4.5.4 and 4.5.5: Delete and substitute:

"4.5.4 Clutch.- Each sample winch shall be tested to determine the ability of the clutch to hold a pull equal to 200 percent winch rated load, to stop and hold 150 percent winch rated load, and to smoothly slow down and stop rated load between 60 and 2000 f.p.m."

"4.5.5 Rejection.- If any winch fails any test or any part is permanently distorted, this shall be cause for rejection of the entire lot.

Page 7: Delete "Notice" paragraph.

Preparing activity:
Navy - SH
(Project 3950-N068Sh)

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:50Z
Check the source to verify that this is the current version before use.