MILITARY SPECIFICATION

HOSE, SYNTHETIC RUBBER, WIRE REINFORCED, AND END FITTINGS, REUSABLE, FOR FLEXIBLE HOSE ASSEMBLIES, (DOUBLE-WIRE BRAID OR TWO-SPIRAL AND ONE-WIRE BRAID HIGH PRESSURE SIZES -4 THROUGH -32)

This specification is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers synthetic rubber hoses, reinforced with two braids of wire or two spiral and one wire braid in sizes -4 through -32 for high pressure hydraulic application.

1.2 Classification. End fittings for hose covered by this specification shall be sizes -4 through -32 as applicable and shall be of the following types:

Type A - SAE, 37-degree tube swivel to hose, straight, tube sizes 1/4 inch to 2 inches (see figure 1).
Type B - Gasket seal union, male half to hose, straight, tube sizes 1/8 inch to 2 inches (see figure 2).
Type BL - Gasket seal union, male half to hose, 90-degree elbow, tube sizes 1/8 inch to 2 inches (see figure 3).
Type C - O-seal union, male half to hose straight, tube sizes 1/4 inch to 2 inches (see figure 4).
Type CL - O-seal union, male half to hose, 90-degree elbow, tube sizes 1/4 inch to 2 inches (see figure 5).
Type D - 90-degree elbow, hose to hose, hose dash size -6 to -32 (see figure 6).
Type E - 250-pound flange to hose, straight, tube sizes 1/2 inch to 2 inches (see figure 7).
Type EL - 250-pound flange to hose, 90-degree elbow, tube sizes 1/2 inch to 2 inches (see figure 8).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4720
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 202640-19T19:25Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications. The following specifications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-C-390 - Copper Alloy Castings (Including Cast Bar).
QQ-N-281 - Nickel-Copper Alloy Bar, Rod, Plate, Sheet, Strip, Wire, Forgings, and Structural and Special Shaped Sections.
QQ-N-286 - Nickel-Copper-Aluminum Alloy, Wrought (UNS N05500).
QQ-N-288 - Nickel-Copper Alloy and Nickel-Copper-Silicon Alloy Castings.

MILITARY

MIL-T-1368 - Tube and Pipe, Nickel-Copper Alloy, Seamless and Welded.
MIL-L-2104 - Lubricating Oil, Internal Combustion Engine, Tactical Service.
MIL-T-16420 - Tube, Copper-Nickel Alloy, Seamless and Welded (Copper Alloy Numbers 715 and 706).
MIL-L-17331 - Lubricating Oil, Steam Turbine and Gear, Moderate Service.
MIL-F-20042 - Flanges, Pipe and Bulkhead, Bronze (Silver Brazing).
MIL-H-24135 - Hose, Synthetic Rubber, Wire Reinforced, and End Fittings, Reusable, for Flexible Hose Assemblies, General Specification for.

(Copies of specifications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Hose. Hose furnished under this specification shall conform to the requirements of MIL-H-24135 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:25Z
Check the source to verify that this is the current version before use.

3.2 Material.

3.2.1 Hose. Rubber compounds used shall be resistant to petroleum base oils and sea water and shall consist of synthetic rubber or a blend of synthetic rubbers and shall meet the requirements of MIL-H-24135 and as specified herein.

3.2.2 Fittings. Material for fittings shall be as shown on figures 1 through 8.

3.3 Reinforcement. Reinforcement shall consist of two-wire braids or two spiral and one-wire braid applied in such a manner as to meet all the requirements of this specification.

3.4 Dimensions and pressures. Hose dimensions and pressures shall be in accordance with table I.

TABLE I. Dash number, performance characteristics, and dimensions.

Hose size (dash no.)	Pressure (lb/in^2)		Hose dimensions (inches)						Min bend radius (inches)	Approx wt/ft (lbs/ft)
			Id tube		Od cover		Od reinf			
	Working (max)	Burst (min)	min	max	min	max	min	max		
-4	5,000	20,000	0.242	0.273	0.657	0.719	0.477	0.523	4	0.39
-6	4,000	16,000	.367	.398	.813	.875	.633	.679	5	.44
-8	3,500	14,000	.485	.531	.938	1.000	.750	.812	7	.64
-10	2,750	11,000	.610	.656	1.063	1.125	.875	.938	8	.65
-12	2,250	9,000	.735	.781	1.219	1.281	1.031	1.093	9.5	.82
-16	2,000	8,000	.985	1.040	1.516	1.609	1.344	1.406	12	1.00
-20	1,625	6,500	1.235	1.297	1.938	2.062	1.779	1.797	16.5	1.95
-24	1,250	5,000	1.485	1.547	2.188	2.312	1.969	2.047	20	2.02
-32	1,125	4,500	1.985	2.047	2.688	2.812	2.453	2.547	25	2.98

3.5 Fitting types and sizes. Fitting types and sizes shall be as shown on figures 1 through 8.

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions shall be in accordance with MIL-H-24135 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T19:25Z
Check the source to verify that this is the current version before use.

4.2 Qualification samples for testing.

4.2.1 Hose. Qualification testing of hose shall consist of hose samples as specified in table II. Samples shall be not less than 15 inches in length and shall be fitted with qualified end fittings.

TABLE II. Numbers of hose samples for qualification testing.

Hose size (dash no.)	Number of hose samples to be provided
-8	4
-32	5

4.2.2 End fittings. Qualification testing of end fittings only shall consist of 18 end fittings of the same type as specified in table III. End fitting samples shall be installed on nine qualified hose samples in the sizes listed in table II.

TABLE III. Numbers of end fitting samples for qualification testing.

End fitting size (hose dash no.)	Number of end fitting samples to be provided
-8	8
-32	10

4.2.3 Hose and end fittings combined. When a single contractor of both hose and fittings qualifies both hose and fittings, or a hose contractor and a fitting contractor qualifies the hose and fittings in a combined qualification test, the samples shall be provided as specified in table IV.

Source: https://assist.dla.mil -- Downloaded: 202640-19T19:25Z
Check the source to verify that this is the current version before use.

TABLE IV. Number of samples for combined qualification testing.

One approved source					
Hose size (dash no.)	No. of hose samples to be provided		End fitting (hose dash no.)	No. of end fittings to be provided	
	Qualifier[2/]	Approved[1/] source		Qualifier[2/]	Approved[1/] source
-8	2	2	-8	4	4
-32	3	2	-32	5	5

Two or more approved sources						
Hose size (dash no.)	Number of samples to be provided by			End fitting size (dash no.)	Number of end fittings to be provided by		
	Qualifier[2/]	Approved[1/] source no. 1	Approved[1/] source no. 2		Qualifier[2/]	Approved[1/] source no. 1	Approved[1/] source no. 2
-8	2	1	1	-8	4	2	2
-32	3	1	1	-32	5	3	2

Hose samples shall be not less than 15 inches in length and shall be coupled on one end with the fitting being submitted for qualification and on the other end with previously qualified end fittings.

1/ Approved source - Previously qualified hose and fittings, or hose or fitting.
2/ Qualifier - Hose and fittings, or hose or fitting to be qualified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:25Z
Check the source to verify that this is the current version before use.

4.2.4 Sequence of tests on sample hose assemblies shall be as specified in table V.

TABLE V. Sequence of qualification tests on sample assemblies.

	Sample numbers								
	Size (dash no.) -8				Size (dash no.) -32				
Test sequence	1	2	3	4	5	6	7	8	9
Proof pressure (see 4.6.1)1/	X	X	X	X	X	X	X	X	X
Stability test (see 4.6.2)1/	X	X	X	X	X	X	X	X	X
Aging test (see 4.6.3)1/		X	X	X		X	X	X	X
Hydraulic fluid circulation (see 4.6.4)1/		X				X			
Impulse test (see 4.6.5)1/				X				X	X
Burst test (see 4.6.6)1/	X				X				
Cold temperature flexing (see 4.6.8)1/			X				X		

1/ See MIL-H-24135.

4.3 The test fluid shall be petroleum base oil in accordance with MIL-L-17331 or MIL-L-2104 for the aging, hydraulic fluid circulation, and impulse tests.

4.4 The peak pressure for the dynamic impulse test shall be 150 percent of maximum working pressure in accordance with table I.

5. PACKAGING

(The packaging requirements specified herein apply only for direct Government acquisition.)

5.1 The packaging requirements shall be in accordance with MIL-H-24135.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:25Z
Check the source to verify that this is the current version before use.

6. NOTES


6.1 Intended use. Hose and fittings to this specification are intended for use in shipboard or shore to ship piping systems where pressures do not exceed the rated working pressure and temperatures do not exceed minus 40 to 200°F.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Type of end fittings for hoses (see 1.2).

Preparing activity:
Navy - SH
(Project 4720-N530-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:25Z
Check the source to verify that this is the current version before use.



SH 1320204


Tube size (nom)	Rubber hose (dash no.)	T thread CL-3	A (max)	C (see note 2)	G (see note 2)	M ref
1/4	-4	7/16-20 UNF	2.75	0.563	1.00	0.37
5/16	-4	1/2-20 UNF	2.75	.625	1.00	.40
3/8	-4	9/16-18 UNF	3.00	.688	1.25	.40
3/8	-6	9/16-18 UNF	3.00	.688	1.25	.40
1/2	-6	3/4-16 UNF	3.25	.875	1.25	.44
1/2	-8	3/4-16 UNF	3.50	.875	1.50	.44
5/8	-8	7/8-14 UNF	3.50	1.00	1.50	.52
3/4	-8	1-1/16-12 UNF	3.50	1.25	1.50	.57
5/8	-10	7/8-14 UNF	3.50	1.00	1.50	.52
3/4	-12	1-1/16-12 UN	4.00	1.25	1.75	.57
7/8	-12	1-3/16-12 UN	4.00	1.375	1.75	.58
1	-12	1-5/16-12 UN	4.00	1.50	1.75	.60
1	-16	1-5/16-12 UN	4.50	1.50	2.25	.60
1-1/4	-16	1-5/8-12 UN	4.75	2.00	2.25	.64
1-1/4	-20	1-5/8-12 UN	5.25	2.00	2.75	.64
1-1/2	-20	1-7/8-12 UN	5.25	2.25	2.75	.74
1-1/2	-24	1-7/8-12 UN	5.75	2.25	3.00	.74
2	-32	2-1/2-12 UN	6.75	2.875	3.50	.93

NOTES:

1. Dimensions are in inches.
2. Fitting assembly materials for swivel nut, hose nipple and socket shall conform to QQ-N-281, class A or B, form 1, condition cold drawn or QQ-N-286, form 1 or form 2, condition cold drawn or hot finished. Tolerance for the hex dimension shall be determined from the material specification, QQ-N-281 or QQ-N-286.
3. Socket (body) alternative material shall conform to QQ-N-288, composition B.
4. Socket shall be one-piece design.

FIGURE 1. Type A, 37-degree tube swivel to hose, straight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:25Z
Check the source to verify that this is the current version before use.



SH 1320205


Tube size (nom)	Rubber hose (dash no.)	T thread CL-3	A (max)	B (see note 2)	C (see note 2)	E ± 0.005	F ± 0.005	I (ref)	M (ref)
1/8	-4	7/8-12 N	3.00	0.938	1.00	0.406	0.594	1/16	0.81
1/4	-6	1-1/8-12 UNF	3.25	1.25	1.25	.406	.641	1/16	.88
3/8	-6	1-1/4-12 UNF	3.25	1.375	1.25	.547	.797	1/16	.88
3/8	-8	1-1/4-12 UNF	3.50	1.375	1.50	.547	.797	1/16	.88
3/8	-12	1-1/4-12 UNF	3.75	1.375	1.75	.547	.797	1/16	.88
1/2	-12	1-1/2-12 UNF	4.00	1.625	1.75	.672	1.000	1/16	.94
1/2	-16	1-1/2-12 UNF	4.25	1.625	2.25	.672	1.000	1/16	.94
3/4	-16	1-3/4-12 UN	4.50	1.875	2.25	.875	1.188	5/64	1.00
1	-16	2-1/8-12 UN	4.75	2.25	2.25	1.094	1.375	5/64	1.12
1	-20	2-1/8-12 UN	5.25	2.25	2.75	1.094	1.375	5/64	1.12
1-1/4	-16	2-5/8-12 UN	5.00	2.75	2.25	1.344	1.750	3/32	1.25
1-1/4	-20	2-5/8-12 UN	5.50	2.75	2.75	1.344	1.750	3/32	1.25
1-1/4	-24	2-5/8-12 UN	5.25	2.75	3.00	1.344	1.750	3/32	1.25
1-1/2	-32	2-7/8-12 UN	6.00	3.00	3.50	1.656	2.094	7/64	1.31
2	-32	3-5/8-12 UN	8.00	3.75	3.50	1.938	2.375	1/8	1.38

NOTES:

1. Dimensions are in inches.
2. Fitting assembly materials shall conform to QQ-N-281, class A or B, form 1, condition cold drawn or QQ-N-286, form 1 or form 2, condition cold drawn or hot finished. Tolerance for the hex dimension shall be determined from the material specification, QQ-N-281 or QQ-N-286.
3. Socket (body) alternative material shall conform to QQ-N-288, composition B.
4. This fitting is for replacement purposes only and is not to be used in new construction.

FIGURE 2. Type B, gasket seal union, male half to hose, straight.

Source: https://assist.dla.mil -- Downloaded: 202610-19T19:25Z
Check the source to verify that this is the currentversion before use.



SH 1320206


Tube size (nom)	Rubber hose (dash no.)	T thread CL-3	A (max)	B (see note 2)	C (see note 2)	H (max)	E ± 0.005	F ± 0.005	I (ref)	M (ref)	R rad (min)
1/8	-4	7/8-12 N	3.55	0.938	1.00	2.00	0.406	0.534	1/16	0.81	0.38
1/4	-6	1-1/8-12 UNF	3.55	1.25	1.25	2.25	.406	.641	1/16	.88	.50
3/8	-8	1/14-12 UNF	3.81	1.375	1.50	2.50	.547	.797	1/16	.88	.75
1/2	-12	1-1/2-12 UNF	4.75	1.625	1.75	3.25	.672	1.000	1/16	.94	1.25
3/4	-16	1-3/4-12 UN	5.75	1.875	2.25	3.75	.875	1.188	5/64	1.00	1.50
1	-20	2-1/8-12 UN	6.75	2.25	2.75	4.25	1.094	1.375	5/64	1.12	1.75
1-1/4	-24	2-5/8-12 UN	7.00	2.75	3.00	5.00	1.344	1.750	3/32	1.25	2.00
1-1/2	-32	2-7/8-12 UN	8.00	3.00	3.50	5.75	1.656	2.094	7/64	1.31	2.50
2	-32	3-5/8-12 UN	8.25	3.75	3.50	6.00	1.938	2.375	1/8	1.38	2.50

NOTES:

1. Dimensions are in inches.
2. For hose sizes -4 through -12, the fitting assembly materials shall conform to QQ-N-281, class A or B, form 1, condition cold drawn or QQ-N-286, form 1, condition cold drawn or hot finished. Tolerance for the hex dimension shall be determined from the material specification, QQ-N-281 or QQ-N-286.
3. For hose sizes -16 through -32, the fitting assembly material shall conform to MIL-T-16420, composition 70-30, grade 2, type I, class 6000.
4. Socket (body) alternative material shall conform to QQ-N-288, composition B.
5. The 90 degree tube elbow, for fitting sizes 1/8 through 3/4 inch shall conform to MIL-T-1368, class A; for fitting sizes 1 inch through 2 inches to MIL-T-16420, composition 70-30, grade 2, type I, class 700 special or class 1650 special.
6. This fitting is for replacement purposes only and is not to be used in new construction.

FIGURE 3. Type BL, gasket seal union, male half to hose, 90 degree elbow.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:25Z
Check the source to verify that this is the current version before use.



SH 1320207


Tube size (nom)	Hose end size	T thread CL-3A	A (max)	B (see note 2)	C (see note 2)	M (ref)
1/4	-6	1-3/16-12 UN	3.25	1.25	1.25	0.62
3/8	-6	1-3/8-12 UNF	3.25	1.44	1.25	.62
3/8	-8	1-3/8-12 UNF	3.50	1.44	1.50	.62
1/2	-12	1-3/4-12 UN	4.00	1.81	1.75	.62
3/4	-16	2-12 UN	4.50	2.12	2.25	.62
1	-16	2-5/16-12 NS	4.75	2.38	2.25	.75
1	-20	2-5/16-12 NS	5.25	2.38	2.75	.75
1-1/4	-16	2-3/4-12 UN	5.00	2.88	2.25	.75
1-1/4	-20	2-3/4-12 UN	5.50	2.88	2.75	.75
1-1/4	-24	2-3/4-12 UN	5.25	2.88	3.00	.75
1-1/2	-32	3-1/16-12 NS	6.00	3.12	3.50	.88
2	-32	3-3/4-12 UN	6.00	3.88	3.50	.88

NOTES:

1. Dimensions are in inches.
2. Fitting assembly materials shall conform to QQ-N-281, class A or B, form 1, condition cold drawn or QQ-N-286, form 1, condition cold drawn or hot finished. Tolerance for the hex dimension shall be determined from the material specification, QQ-N-281 or QQ-N-286.
3. Socket (body) alternative material shall conform to QQ-N-288, composition B.

FIGURE 4. Type C, O-ring seal union.

Source: https://assist.dla.mil -- Downloaded: 202640-19T19:25Z
Check the source to verify that this is the current version before use.



SH 1320208


Tube size (nom)	Hose end size (dash no.)	T thread CL-3	A (max)	B (see note 2)	C (see note 2)	H (max)	M (ref)	R rad (min)
1/4	-6	1-13/16-12 UN	3.55	1.25	1.25	2.25	0.62	0.50
3/8	-8	1-3/8-12 UNF	3.81	1.44	1.50	2.50	.62	.75
1/2	-12	1-3/4-12 UN	4.75	1.81	1.75	3.25	.62	1.25
3/4	-16	2-12 UN	5.75	2.12	2.25	3.75	.62	1.50
1	-20	2-5/16-12 NS	6.75	2.38	2.75	4.25	.75	1.75
1-1/4	-24	2-3/4-12 UN	7.00	2.88	3.00	5.00	.75	2.00
1-1/2	-32	3-1/16-12 NS	8.00	3.12	3.50	5.75	.88	2.50
2	-32	3-3/4-12 UN	8.25	3.88	3.50	6.00	.88	2.50

NOTES:

1. Dimensions are in inches.
2. For hose sizes -6 through -12, the fitting assembly materials shall conform to QQ-N-281, class A or B, form 1, condition cold drawn or QQ-N-286, form 1, condition cold drawn or hot finished. Tolerance for the hex dimension shall be determined from the material specification, QQ-N-281 or QQ-N-286.
3. For hose sizes -16 through -32, the fitting assembly material shall conform to MIL-T-16420, composition 70-30, grade 2, type I, class 6000.
4. Socket (body) alternative material shall conform to QQ-N-288, composition B.
5. The 90-degree tube elbow, for fitting sizes 1/8 through 3/4 inch shall conform to MIL-T-1368, class A; for fitting sizes 1 inch through 2 inches to MIL-T-16420, composition 70-30, grade 2, type I, class 700 special or class 1650 special.

FIGURE 5. Type CL, O-ring seal union, male half to hose, 90-degree elbow.

Source: https://assist.dla.mil -- Downloaded: 202610-19T19:25Z
Check the source to verify that this is the current version before use.



SH 1320209


Rubber hose (dash no.)	A (max)	B (see note 2)	C (see note 2)	R rad (min)
-6	3.55	0.69	1.25	0.50
-8	3.81	.90	1.50	.75
-12	4.75	1.06	1.75	1.25
-16	5.75	1.38	2.00	1.50
-20	6.75	1.62	2.75	1.75
-24	7.00	1.88	3.00	2.00
-32	8.00	2.50	3.50	2.50

NOTES:

1. Dimensions are in inches.
2. For hose sizes -6 through -12, the fitting assembly materials shall conform to QQ-N-281, class A or B, form 1, condition cold drawn or QQ-N-286, form 1, condition cold drawn or hot finished. Tolerance for the hex dimension shall be determined from the material specification, QQ-N-281 or QQ-N-286.
3. For hose sizes -16 through -32, the fitting assembly materials shall conform to MIL-T-16420, composition 70-30, grade 2, type I, class 6000.
4. Socket (body) alternative material shall conform to QQ-N-288, composition B.
5. The 90-degree tube elbow, for fitting sizes 1/8 through 3/4 inch shall conform to MIL-T-1368, class A; for fitting sizes 1 inch through 2 inches to MIL-T-16420, composition 70-30, grade 2, type I, class 700 special or class 1650 special.

FIGURE 6. Type D, 90-degree elbow, hose to hose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:25Z
Check the source to verify that this is the current version before use.



SH 1320210


Hose size (dash no.)	Nps	Number of bolt holes	A (max)	C (see note 2)	G (see note 2)	J ± 0.062	K ± 0.005	L (nom)	M (nom)	N ± 0.016	S ± 0.005
-12	1/2	3	3.92	1.12	1.50	3.56	1.50	2.44	0.56	0.69	0.71
-16	3/4	4	4.34	1.38	1.75	3.81	1.84	2.69	.56	.69	.92
-20	1	4	4.81	1.62	2.25	4.25	2.12	3.12	.56	.75	1.18
-24	1-1/4	4	4.97	2.12	2.50	4.50	2.74	3.38	.56	.81	1.53
-32	1-1/2	6	5.33	2.25	3.00	5.06	2.74	3.94	.56	.81	1.77
-32	2	6	5.33	2.69	3.00	5.06	3.28	4.44	.68	.81	1.77

NOTES:

1. Dimensions are in inches.
2. Fitting assembly materials for hose nipple and socket shall conform to QQ-N-281, class A or B, form 1, condition cold drawn or QQ-N-286, form 1, condition cold drawn or hot finished. Tolerance for the hex dimension shall be determined from the material specification, QQ-N-281 or QQ-N-286.
3. The flange shall conform to QQ-C-390, alloy number C90300.
4. Socket (body) alternative material shall conform to QQ-N-288, composition B.
5. The flange shall be designed to swivel freely through 360 degrees and to mate with 250-pound plain flange to MIL-F-20042.

FIGURE 7. Type E, 250-pound flange to hose, straight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:25Z
Check the source to verify that this is the current version before use.



SH 1320211

Hose size (dash no.)	Nps	Number of bolt holes	A (max)	C (see note 2)	H (max)	J ± 0.062	K ± 0.005	L (nom)	M (nom)	N ± 0.016	R (nom)	S ± 0.005
-12	1/2	3	4.52	1.50	2.19	3.56	1.50	2.44	0.56	0.69	1.25	0.71
-16	3/4	4	5.25	1.75	2.49	3.81	1.84	2.69	.56	.69	1.50	.92
-20	1	4	6.10	2.25	2.69	4.25	2.12	3.12	.56	.75	1.75	1.18
-24	1-1/4	4	6.32	2.50	3.13	4.50	2.74	3.38	.56	.81	2.00	1.53
-32	1-1/2	6	7.38	3.00	3.35	5.06	2.74	3.94	.56	.81	2.50	1.77
-32	2	6	7.38	3.00	3.35	5.56	3.28	4.44	.68	.81	2.50	1.77

NOTES:

1. Dimensions are in inches.
2. Fitting assembly materials for flange, shoulder, hose nipple and socket shall conform to QQ-N-281, class A or B, form 1, condition cold drawn or QQ-N-286, form 1 or form 2, condition cold drawn or hot finished. Tolerance for the hex dimension shall be determined from the material specification, QQ-N-281 or QQ-N-286.
3. The 90-degree tube elbow for 1/2-inch fitting size shall conform to MIL-T-1368, class A; for fitting sizes 3/4 inch through 2 inches to MIL-T-16420, composition 70-30, grade 2, type I, class 700 special or 1650 special.
4. The flange shall conform to QQ-C-390, alloy number C90300.
5. Socket (body) alternative material shall conform to QQ-N-288, composition B.
6. The flange shall be designed to swivel freely through 360 degrees and to mate with 250-pound plain flange to MIL-F-20042.
7. Socket shall be one-piece design.

FIGURE 8. Type EL, 250-pound flange to hose, 90-degree elbow.

Source: https://assist.dla.mil -- Downloaded: 202640-19T19:25Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: *In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (DO NOT STAPLE), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.*

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. *Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.*

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 5523)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 5523)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362

Source: https://assist.dla.mil -- Downloaded: 202640-19T19:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-24135/1 (SH)	Hose, Synthetic Rubber, Wire Reinforced, And End Fittings, Reusable, For Flexible Hose Assemblies

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-19T19:25Z
Check the source to verify that this is the current version before use.