A-A-1926A
January 15, 1988
SUPERSEDING
A-A-1926
March 15, 1982

COMMERCIAL ITEM DESCRIPTION

CLOSER, DOOR

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification FF-H-121.

This commercial item description covers mechanical devices for automatically closing and controlling hinged or pivoted doors by means of metal springs and liquid or air controlled checks.

Salient characteristics:

Design. Product design shall conform to the requirements of ANSI/BHMA A156.4 'American National Standard For Door Controls - Closers'. All dimensions and threads shall be in US units and all surfaces intended for mating accessories or attachments shall dimensioned to be compatible with standard domestically (US) dimensioned components.

Type and grade. Type and grade shall be in accordance with the identifying type numbers shown in ANSI/BHMA A156.4 as specified.

Sizes. Size shall be in accordance with Table A1 of Appendix A of ANSI/BHMA A156.4 for the applicable type of closer, as specified. The term "size" relates to the closer's capacity to control various door widths and is measured in terms of closing force when tested.

Hand. Door closers shall be designed for right hand or left hand operation or reversible as specified.

Options. When specified, closers shall incorporate optional features PT 4A, PT 4B, PT 4C, PT 4D, PT 4E, PT 4F, PT 4G and PT 4H, PT 8A, PT 8B, PT 8C, PT 8D, PT 8E, PT 8F, PT 8G, PT 8H, PT 8J and PT 8K. When conflicting or incompatible optional features are specified, it shall be the supplier's responsibility to obtain clarification from the contracting officer.

Plunger access. Certain door closers such as tubular pneumatic closers are sometimes designed so that one end of the tube will permit access to the plunger for servicing, this feature is not required unless otherwise specified in the contract or purchase order.

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:18Z
Check the source to verify that this is the current version before use.

Finish. Closer finish may be any finish identified in appendix A of ANSI/BHMA A156.4 unless otherwise specified.

Fasteners. All fasteners required for installation shall be included with the closers (wood screws and machine screws). Hardware furnished shall be of suitable size. When specified, through bolts shall be furnished.

Installation and adjusting tools. Any tools necessary for adjusting valves and spring power or special installation tools required other than common hand tools shall be furnished with each closer unless otherwise specified.

Instructions. Instructions for mounting shall be furnished with each closer. When specified, template information for preparation of doors or frames shall be furnished.

Workmanship. The closers furnished shall be free from imperfections which may impair durability or serviceability.

Quality Assurance Provisions. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Sampling.

Lot. All closers of the same type, grade and size presented for acceptance at one time shall be considered a lot for purposes of inspection.

Sampling for quality conformance examination and testing. A random sample of closers shall be selected from each lot in accordance with Military Standard MIL-STD-105 `Sampling Procedures And Tables For Inspection By Attributes'.

Visual examination. Samples shall be selected in accordance with MIL-STD-105, general inspection level II, AQL 4.0 expressed in terms of percent defective. The sample closers shall be visually examined to verify compliance with this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:18Z
Check the source to verify that this is the current version before use.

Tests per ANSI/BHMA A156.4. Samples shall be selected in accordance with MIL-STD-105, special inspection level S-1, AQL 2.5 expressed in terms of percent defective. The sample closers shall be tested in accordance with ANSI/BHMA A156.4.

Certification. Listing in the current Builders Hardware Manufacturers Association, Inc., Directory Of Certified Door Closers or other listing service which provides equivalent testing and follow-up service shall be considered proof of conformance with ANSI/BHMA A156.4 test requirements. Labeling, listing and follow-up service procedures are specified in the BHMA directory. The Government may refuse to accept such listing as evidence of conformance if closers furnished are subsequently found not to conform with requirements.

Examination for preparation for delivery. A random sample of unit, intermediate and shipping containers (as applicable) shall be selected from each lot and examined for conformance with the preservation, packaging, packing, labeling and marking required in the contract or order. Samples shall be selected in accordance with MIL-STD-105, Inspection level II, AQL 6.5 expressed in terms of defects per hundred unit.

Preservation,packaging,packing,labeling,and marking (Civil Agencies). The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Packaging (DOD). The packaging shall be in accordance with ASTM Standard D3951 `Commercial Packaging, Practice for'.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:18Z
Check the source to verify that this is the current version before use.

Notes:

Ordering activities should specify:
1) Type (see ANSI/BHMA A156.4 paragraph 11.14).
2) Grade (see ANSI/BHMA A156.4 Appendix A, paragraph A8).
3) Size (see table A1 of ANSI/BHMA A156.4.).
4) Finish if suppliers standard finish is not acceptable (see ANSI/BHMA A156.4, Appendix A, paragraph A5).
5) Hand (right hand, left hand or reversible).
6) Options (see paragraphs 3.8, 3.12 and Appendix A paragraph A7 of ANSI/BHMA A156.4), (care should be taken that multiple options are compatible, verify with supplier).
7) Plunger access feature on tubular pneumatic closers if considered necessary (repairs may not be economically prudent, making this feature unwarranted).
8) Through bolts if standard wood screws or machine screws are not acceptable.
9) Template information if required.

The COMMERCIAL ITEM CERTIFICATION CLAUSE is not required when this commercial item description is used for procurement.

ANSI/BHMA standards and directories are available from the Builders Hardware Manufacturers Association, Inc., 60 East 42nd Street, New York, NY 10165 or the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

Copies of Military Standard 105 are available from the Naval Publications and Forms Center, 5801 Tabor Ave., Philadelphia, PA 19120.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

The standards referenced in this document shall be the issues in effect on the date of the invitation for bids or request for quotation and shall be used to determine compliance with these requirements. In the event that there is a conflict between this document and a standard referenced herein, this document shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:18Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Assignee Activity:
DLA - IS

Review Activities:

DLA - IS
Navy - YD
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:

VA - OSS

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.