A-A-50050
May 10 1983

COMMERCIAL ITEM DESCRIPTION

MOLDING MACHINES, MEAT - FISH

The General Services Administration has authorized the use of this Commercial Item Description in preference to Type II, class 1 and 2, Type III, and Type IV of Military Specification MIL-M-40163. (See supersession data for the specific items this document replaces.)

Salient characteristics.

The molding machines shall be of the following types and classes.

Type I - Bench mounted

The type I meat molding machines shall be electric motor operated, self-contained, bench mounted, with automatic paper feed.

Class 1 - 1200 Patties per hour

The class 1 molding machine shall meet the following requirements:

Production rate - 1200 patties per hour (min.)
Hopper capacity - 20 pounds
Mold plate for 3 oz., 4 inch diameter patty
Electrical characteristics - 120 V, 60 Hz, 1 Ph, equipped with 6 foot UL approved, 3 wire power supply cord with grounding plug, and 1/2 HP motor.
Maximum dimensions - 36 inches long by 13 inches wide by 20 inches high

Class 2 - 2100 Patties per hour

The class 2 molding shall meet the following requirements:

Production rate - 2100 patties per hour (min.)
Hopper capacity - 40 pounds
Mold plate for 3 oz., 4 inch diameter patty
Electrical characteristics - 120 V, 60 Hz, 1 Ph, equipped with 6 foot UL approved, 3 wire power supply cord with grounding plug, and 1/2 HP motor.
Maximum dimensions - 24 inches long by 36 inches wide by 33 inches high

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Type II - Meat molding machine attachment (see ordering data).

The type II molding machine shall be designed for attachment to a meat grinder or chopper. The molding machines shall mold ground meat from the grinder in a strip backed with paper, adjustable to automatically cut the strip into loaves of 1/2, or 1-1/2 pounds at the rate of 2400 through 3600 per hour.

Electrical characteristics - 120 V, 60 Hz, 1 Ph, equipped with a 10 foot UL approved, 3 wire power supply cord with grounding plug.

Alternate electrical characteristics. Electrical characteristics for the type II molding machine shall be 50 Hz, VAC (or 110/220 VAC), 1 Ph, when alternately specified by procurement documents.
Maximum dimensions - 10 inches long by 22 inches wide by 14 inches high

Type III meat molding machine shall be electrical motor operated, self-contained, floor mounted with automatic counter/stacker, automatic paper feed and automatic conveyor.

Production rate - 3600 patties per hour (min.)
Hopper capacity - 200 pounds
Mold plate for 3 oz., 4 inch diameter patty
Automatic counter/stacker and conveyor - The automatic counter/stacker shall have an automatic paper feed unit that inserts paper between each patty and be capable of stacking from 2 to 16 patties on the automatic conveyor. The automatic conveyor shall be capable of automatically moving one or more stacks of patties away from the molding machine.
Cabinet - stainless steel
Electrical characteristics - 230 V, 60 Hz, 1 Ph, equipped with 6 foot UL approved, 3 wire power supply cord with grounding plug.
Maximum dimensions - 35 inches long by 90 inches wide by 61 inches high

Standard compliance. Except for the type II alternate electrical characteristics, the machines shall comply with Underwriters Laboratories Standard No. UL 73 and the National Sanitation Foundation Standard No. 8.

Identification plate. In addition to marking and identification required by UL 73, the identification plate shall include contract number and national stock number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Certification.

The contractor shall certify that the product offered meets the salient characteristics of the description and conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Packaging.

A. Commercial packaging. Each molding machine shall be packaged in accordance with commercial practice.

B. Commercial packing. Each molding machine shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

C. Export packaging. Each molding machine shall be disassembled to the extent determined by the supplier to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be packaged in a domestic fiberboard box constructed and closed in accordance with PPP-B-636. The machine and parts shall be cleaned, preserved, cushioned and immobilized to afford protection against corrosion, deterioration and physical damage during shipment and storage.

D. Export packing. Types I, II and III molding machines shall be export packed as hereinafter specified.

Type I. Each complete type I molding machine shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601, or nailed wood box conforming to class 1, style 2 or 4, type 2 load of PPP-B-621. The contents of each box shall be blocked and braced to prevent movement while the box is in transit. Each shipping container shall be closed and strapped in accordance with appendix of PPP-B-601 or PPP-B-621, as applicable.

Type II. Each type II molding machine shall be packed in a snug-fitting fiberboard box, constructed, closed and reinforced in accordance with style RSC, grade V3c, V3s and V4s of PPP-B-636. Each machine shall be immobilized within the box. For distribution to Navy and Air Force, reinforcement shall be restricted to non-metallic strapping in accordance with the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Type III. Each complete molding machine shall be packed in one or more boxes as determined by the supplier. The box shall be a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601, or nailed wood box conforming to class 1, style 2 or 4, grade B, type 2 load of PPP-B-621. The contents of each box shall be blocked and braced to prevent movement while the box is in transit. The machine shall be blocked in a manner to provide approximately 1-inch clearance between the legs and the bottom of the box. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

E. Marking of interior boxes and shipping containers (commercial and export). Commercial marking for interior boxes and shipping containers is acceptable provided the following information is included:

National stock number	Date of packaging (month/year)
Item description	Contract number
Quantity, unit of issue	Name, address and zip code of contractor 1/

1/ Interior boxes do not require this information.

When a molding machine is shipped in two or more containers, set markings shall be applicable. The set markings shall be placed on the surfaces containing identification markings and located in the lower right hand corner. A 2-inch black disc shall be placed above these numbers on each container. For example:

SET 1	SET 2
PK 1 of 3	PK 1 of 3
PK 2 of 3	PK 2 of 3
PK 3 of 3	PK 3 of 3

Source of information for nongovernment documents.

Underwriters Laboratories, Inc.
333 Pfingsten Road
Northbrook, IL 60062

National Sanitation Foundation
NSF Building
Ann Arbor, MI 48105

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department,
1616 P Street, N.W., Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

Supersession data.

The types and classes of molding machines covered by this Commercial Item Description replace the types and classes covered by MIL-M-40163 as indicated below:

CID - A-A-50050	MIL-M-40163
Type I, class 1	Type II, class 1
Type I, class 2	Type II, class 2
Type II	Type III
Type III	

Ordering data type II molding machine.

Procurement documents shall specify the manufacturer and model number of the meat grinder or chopper to which the type II molding machine is to be connected to assure compatibility. In addition, procurement documents shall specify alternate electrical characteristics when applicable.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD, TS
Navy - MC, SA
Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0732

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.