A-A-51493
20 June 1986

COMMERCIAL ITEM DESCRIPTION

BIN, STORAGE

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers a plastic storage bin. The storage bin shall have a molded slot on the front for an identification card. The storage bin shall be used for storing supplies in a military medical facility.

Salient characteristics:

The bin shall be fabricated of high-density plastic and have a molded slot on the front vertical surface for an identification card and shall be designed with a sloping front hopper for easy access.

The bin shall have a smooth finish with exterior corners and edges rounded and have the following overall dimensions:

Length:	13-1/4 inches (34.39 cm)
Width:	11-3/8 inches (28.89 cm)
Height:	6 inches (15.24 cm)

The bin shall be designed with a reinforcement rim around the top wall, two side walls, extending forward down an open slope on both sides to a front hopper ledge. This slope shall be 20 degrees from vertical. The rim shall be 3/8 inch high and capable of accommodating a noncomponent sliding lid. When the lid is in place and closed, it shall be contained within the rim vertically and horizontally, overlapping the entire bin opening, except it shall be allowed to slide forward on a horizontal ledge, off the hopper ledge and continue sliding forward and be removed from the bin. A template of the lid to be accommodated shall have two surfaces, a top surface and a forward surface sloping downward, having the following dimensions:

Thickness:	0.065 inch (0.165 cm)
Width:	11-1/16 inches (28.10 cm)
Top length:	11-5/16 inches (37.33 cm)
Sloping length:	2-11/16 inches (6.83 cm)
Angle of slope:	20 degrees

This template shall be capable of being removed only by sliding it forward.

AMSC N/A FSC 7125

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:56Z
Check the source to verify that this is the current version before use.

The card slot shall be capable of holding a card 3-1/4 inches wide by 1 inch high. The slot shall be capable of containing the bottom edge and two side edges of the card, but shall not interfere with or be covered by a drop flange added to the lid template which drops 3/16 inch below the hopper ledge.

The front hopper shall have an interior wall which slopes downward toward the rear of the bin at an angle from vertical of 30 degrees (±10 degrees). This sloping wall shall extend from the hopper ledge to the bin floor. The hopper ledge shall be approximately 3 inches high and extend from side to side and shall be joined with the reinforcement rim.

The design of the bin shall incorporate sufficient bracing to enable the bin to support 50 pounds of content weight and, alternatively, 50 pounds of stack weight in accordance with test requirements specified herein. In addition, the bin shall be resilient and be capable of withstanding a tension force of 20 pounds, pulling the midsection of the top side edges together.

Workmanship. The storage bin shall be free from defects which detract from its appearance or impair its serviceability.

Unit. Each (EA). One storage bin, as specified, constitutes one unit.

Quality Assurance Provisions.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contact or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Records. Records of examination and test performed by or for the contractor shall be maintained by the contractor and made available to the Government upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:56Z
Check the source to verify that this is the current version before use.

Tests. Tests shall be conducted to determine compliance with specification requirements. Where feasible, the same sample shall be used for determining two or more test characteristics.

Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and as specified herein. The unit of product for test purposes shall be one (1) storage bin.

TABLE I. Sampling for examination and tests.

	Inspection level	AQL (defects per 100 units)
For visual examination		
Major defects	II	1.0
Total defects (Major and and minor combined)	II	2.5
For dimensional detracts	II	1.0
For tests	II	1.0

Examination. The box shall be examined for major defects in appearance of molding (thin spots on wall surfaces, unfilled ridges, bubbles, and inappropriate relief at edges and corners).

Tests. Tests shall be conducted to determine compliance with this specification in accordance with table II.

Table II. Tests

Test	Test description
A.	Using a template as described herein or Lewis Systems Part No. C041, test that the bin is capable of receiving the lid. Capturing elements of the bin shall have, at least, 0.005 inch clearance in the vertical direction. The top shall slide freely and easily and shall not be allowed to disengage except by sliding the top forward. NOTE: This test shall be conducted before and after tests B, C, and D.
B.	Support the bin by its top rim. Place a cushioning pad inside the bin which covers the entire bottom. Load the bin with 50 pounds of pellets. Examine the bin for damage. Remove the test load and the cushion. Examine the bin for damage. There shall be no evidence of damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:56Z
Check the source to verify that this is the current version before use.

C. Place the test unit on a flat and level surface. Place a second unit (not being tested) on top of the test unit. Load 47 to 48 pounds on the second unit, allowing the second unit to transfer its load weight on to the test unit. Examine the test unit for damage. Remove the test load and second unit. Examine the test unit for damage. There shall be no evidence of damage.

D. Apply a 20 pound tension force between two opposite sides (sides with longest lengths). The locations of force contact shall be on top outside of the bin, within 1/4 inch of the top, on the centerline between the front and back of the bin. Maintain the application of this force for 5 minutes. Examine the bin for cracks and/or other damage excluding deformation. There shall be no evidence of damage. Repeat test A above.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements.

Federal Food, Drug and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances, and regulations.

Recovered materials. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580 to the maximum extent practical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:56Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

NOTE: The following National Stock Number is covered by this document:

7125-01-139-9545

Ordering data. Intermediate/exterior package quantities and labeling and marking must be specified in the contract and/or order.

MILITARY INTERESTS:

Custodians:

Army-MD
Navy-MS
Air Force-03

PREPARING ACTIVITY:

DoD-MB

Agent:

DLA-DM

CIVIL AGENCY COORDINATING ACTIVITIES:

VA-OSS
PHS

PGC H1031

Project No. 7125-0116

Location: CID/BIN-STORAGE/H12

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:56Z
Check the source to verify that this is the current version before use.