MIL-C-45359B
17 February 1988
SUPERSEDING
MIL-C-45359A
20 December 1967

MILITARY SPECIFICATION

# COIL, STARTING: ENGINE IGNITION, WITH FILTER, 24 VOLT DC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers waterproof, 24 volt (V) (nominal rating) direct current (dc) starting coils for use on ignition systems incorporating direct coupled magnetos used on internal combustion engines for military vehicles.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2920
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS
FEDERAL

| | |
|---|---|
| QQ-S-571 | - Solder; Tin Alloy, Tin-Lead Alloy, and Lead Alloy. |

MILITARY

| | |
|---|---|
| MIL-C-11693 | - Capacitors, Feed Through, Radio-Interference Reduction, AC and DC (Hermetically Sealed in Metal Cases) Established and Non-Established Reliability, General Specification For. |
| MIL-F-13927 | - Fungus Resistance Test; Automotive Components. |
| MIL-C-46168 | - Coating, Aliphatic Polyurethane, Chemical Agent Resistant. |
| MIL-C-53039 | - Coating, Aliphatic Polyurethane, Single Component, Chemical Agent Resistant. |

STANDARDS
FEDERAL

| | |
|---|---|
| FED-STD-H28 | - Screw-Thread Standards for Federal Services. |
| FED-STD-595 | - Colors. |

MILITARY

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-130 | - Identification Marking of US Military Property. |
| MIL-STD-193 | - Painting Procedures and Marking for Vehicles, Construction Equipment and Material Handling Equipment. |
| MIL-STD-202 | - Test Methods for Electronic and Electrical Component Parts. |
| MIL-STD-1184 | - Electrical Components for Automotive Vehicles; Waterproofness Tests. |
| MIL-STD-45662 | - Calibration Systems Requirements. |
| MS51355 | - Coil, Starting-Engine Ignition, with Filter, 24 Volt dc. |

2.1.2 Drawing. The drawing forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be that in effect on the date of the solicitation.

DRAWINGS
ARMY

| | |
|---|---|
| 7727531 | - Gap, Sparking. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards and drawings required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B117 - Salt Spray (Fog) Testing, Method of.

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. Coils furnished under this specification shall be products which are authorized by the qualifying activity for listing on the applicable qualified products list (QPL) at the time set for opening of bids (see 4.4 and 6.3).

3.2 Materials. Materials shall be as specified herein and in referenced specifications and drawings. Materials shall be uniform and free of defects and imperfections that might affect the serviceability and appearance of the finished product (see 4.7.1).

3.2.1 Dissimilar metals. Except where necessary to complete an electrical circuit, contact between dissimilar metals, which would encourage galvanic action shall be avoided. Separation of dissimilar metals shall be accomplished by providing insulation between mating surfaces (see 4.7.1).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

3.2.2 Recycled, virgin and reclaimed materials. There are no requirements for the exclusive use of virgin materials. The use of recycled or reclaimed (recovered) materials is acceptable provided that all other requirements of this specification are met (see 6.4.1).

3.3 Design and construction. The coils shall conform to MS51355 or other applicable standards or drawings as specified (see 4.7.1, 4.7.2 and 6.2).

3.3.1 Interchangeability. To provide for interchangeability, coils fabricated in accordance with this specification shall have external dimensions that fall within the envelope outline of the applicable drawing or military standard. Electrical connectors, mounting dimensions and location shall also conform to the detail requirements of the applicable document (see 4.7.2).

3.3.2 Standard parts. Military standard parts shall be incorporated wherever applicable. Commercial standard parts may be used provided they are interchangeable with military standard parts without modification, and the equivalent military standard part is identified by the manufacturer (see 4.7.1).

3.3.3 Weight. The weight of the coil shall not exceed 30 ounces (see 4.7.1).

3.3.4 Threaded parts. All screw threads shall conform to FED-STD-H28. The form, number per inch, and class of threads shall be as specified on applicable standards or drawings (see 4.7.1 and 4.7.2).

3.3.5 Locking devices. Lock washers, self-locking nuts, safety wires, or other approved locking devices shall be incorporated where specified or where required to prevent loosening of components (see 4.7.1).

3.3.6 Solder. Solder employed in making electrical connections shall be a resin core type conforming to QQ-S-571 (see 4.7.1).

3.3.7 Capacitors. If used, feed through capacitors for radio interference suppression shall be in accordance with the applicable requirements of MIL-C-11693 (see 4.7.1).

3.3.8 Polarity. The coil shall operate with a negatively grounded circuit (see 4.7.1).

3.4 Performance.

3.4.1 Electrical.

3.4.1.1 Output voltage. When tested as specified in 4.7.3.1, the output voltage shall be not less than the values specified in table I.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

TABLE I. Minimum output voltage.

| Input voltage (V dc) | Magneto shaft speed (rpm) | Output voltage | |
|---|---|---|---|
| | | +73 ± 18°F<br>-65 ± 5°F<br>(kV) | +160 ± 10°F<br>(kV) |
| 18 | 35 | 9.0 | 8.0 |
| 18 | 100 | 9.0 | 8.0 |
| 28.5 | 35 | 10.0 | 9.0 |
| 28.5 | 100 | 10.0 | 9.0 |

3.4.1.2 Endurance. When tested as specified in 4.7.3.2, the coil shall evidence no damage or malfunction and shall subsequently meet the requirements of 3.4.1.1.

3.4.1.3 Dielectric strength. When tested as specified in 4.7.3.3, the coil shall evidence no burning, charring, smoking, rupture or other damage to the insulation and shall subsequently meet the requirements of 3.4.1.1.

3.4.1.4 Shunting resistance. When tested as specified in 4.7.3.4, the coil in conjunction with an associated magneto shall maintain an output voltage of not less than 5000 V when operating at a magneto shaft speed of 100 revolutions per minute (rpm) with an input of 28.5 V dc, and a resistance of 250,000 ohms in a circuit having a total capacitance load of 150 plus or minus (±) 10 micro-microfarads.

3.4.2 Environmental.

3.4.2.1 Vibration. When tested as specified in 4.7.4.1, the coil shall evidence no breakage, loosened or distorted parts or other physical damage and shall subsequently meet the requirements of 3.4.1.1.

3.4.2.2 Waterproofness. When tested as specified in 4.7.4.2, the coil shall evidence no leakage or damage which would impair electrical performance.

3.4.2.3 Shock. When tested as specified in 4.7.4.3, the coil shall evidence no breakage, loosened or distorted parts or other physical damage and shall subsequently meet the requirements of 3.4.1.1.

3.4.2.4 Fungus resistance. When tested as specified in 4.7.4.4, the coil shall evidence no microbial growth adversely affecting performance and shall subsequently meet the requirements of 3.4.1.3 and 3.4.1.1.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

3.4.2.5 Corrosion resistance. When tested as specified in 4.7.4.5, the coil shall evidence no corrosion affecting performance and shall subsequently meet the requirements of 3.4.1.3 and 3.4.1.1.

3.5 Finish. Unless otherwise specified (see 6.2), surface treatment and painting of the housing and cover shall be in accordance with MIL-STD-193. Topcoat paint shall conform to MIL-C-46168 or MIL-C-53039. Color shall be black gloss enamel conforming to color chip 17038 of FED-STD-595 (see 4.7.2).

3.6 Identification marking. Identification marking shall be in accordance with MIL-STD-130 and as a minimum shall include the following (see 4.7.2):

Coil, starting 24 V dc
Current rating
Army part number
National stock number
Manufacturer's identification
US

3.7 Workmanship. Workmanship shall be such as to assure a product free of rust, burrs, scratches, chips, sharp edges, loose or defective connectors, cracked insulation or faulty soldering (see 4.7.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform or witness any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection equipment. Unless otherwise specified in the contract (see 6.2), the contractor is responsible for the provision and maintenance of all inspection equipment necessary to assure that supplies and services conform to contract requirements. Unless otherwise specified in table II, inspection equipment must be capable of repetitive measurements to an accuracy of 10 percent (%) of the measurement tolerance. Calibration of inspection equipment shall be in accordance with MIL-STD-45662.

TABLE II. Measuring instrument tolerance.

| Instrument | Accuracy - Maximum |
|---|---|
| Voltmeter dc | ± 0.25% |
| Electrostatic voltmeter | ± 1.0% |
| Oscilloscope | ± 3.0% |

4.2 Classification of inspections:

a. Qualification inspection (see 4.4).
b. Quality conformance inspections (see 4.5).
   1. Examination (see 4.5.2).
   2. Tests (see 4.5.3).
c. Control tests (see 4.6).

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be conducted under the following conditions:

a. Air temperature 73 ± 18 degrees Fahrenheit (°F)
b. Barometric pressure 28.5 + 2 inches mercury
   - 3
c. Relative humidity 50 ± 30%

4.3.1 Laboratory test conditions. Tests shall be conducted under general laboratory conditions which are free of dust, drafts and fumes. Mounting shall be in the manner and with devices for securing the coil as in intended use. Unless otherwise specified herein or in applicable specifications, test specimens shall be thermally stabilized for 1 hour before being subjected to the test.

4.3.2 Special test equipment. In addition to the standard measuring equipment, (see table II and applicable test specifications), test equipment shall include a test chamber capable of maintaining specified air temperatures over the range from minus (-) 65°F to plus (+) 165°F. Air movement in the high temperature chamber shall be held to a minimum to prevent a temperature gradient within the chamber and any cooling resulting from excess air motion.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

4.4 Qualification inspection. For the purpose of qualification (see 3.1) the prospective supplier shall submit four coils. These specimens, properly marked with identifying information, shall be representative of the units proposed to be furnished to the Government in connection with future procurement. Qualification testing shall be conducted by the Government at a place designated by the Government. The coils shall be inspected as specified in table III and tested in the order listed in table IV.

TABLE III. Classification of inspections.

| Title | Requirement | Inspection | Qualification | Quality conformance | | Control |
|---|---|---|---|---|---|---|
| | | | | Examination | Tests | |
| Materials and construction | 3.2, 3.2.1<br>3.3, 3.3.2 thru 3.3.8 | 4.7.1 | X | | | |
| Defects (see 4.5.2 and table V) | 3.3, 3.3.1<br>3.3.4, 3.5 thru 3.7 | 4.7.2 | X | X | | |
| Output voltage | 3.4.1.1 | 4.7.3.1 | X | | X | |
| Endurance | 3.4.1.2 | 4.7.3.2 | X | | | |
| Dielectric strength | 3.4.1.3 | 4.7.3.3 | X | | X | X |
| Shunting resistance | 3.4.1.4 | 4.7.3.4 | X | | | X |
| Vibration | 3.4.2.1 | 4.7.4.1 | X | | | |
| Waterproofness | 3.4.2.2 | 4.7.4.2 | X | | | |
| Shock | 3.4.2.3 | 4.7.4.3 | X | | | |
| Fungus resistance | 3.4.2.4 | 4.7.4.4 | X | | | |
| Corrosion resistance | 3.4.2.5 | 4.7.4.5 | X | | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

TABLE IV. Order of qualification testing.

| Specimen number | Test | Title |
|---|---|---|
| 1 | 4.7.3.1<br>4.7.3.2<br>4.7.3.1<br>4.7.3.4 | Output voltage<br>Endurance<br>Output voltage<br>Shunting resistance |
| 2 | 4.7.3.1<br>4.7.4.1<br>4.7.4.3<br>4.7.3.1<br>4.7.4.5<br>4.7.3.3<br>4.7.3.1 | Output voltage<br>Vibration<br>Shock<br>Output voltage<br>Corrosion resistance<br>Dielectric strength<br>Output voltage |
| 3 | 4.7.3.1<br>4.7.4.4<br>4.7.3.3<br>4.7.3.1 | Output voltage<br>Fungus resistance<br>Dielectric strength<br>Output voltage |
| 4 | 4.7.3.1<br>4.7.3.4<br>4.7.4.2<br>4.7.3.3<br>4.7.3.1 | Output voltage<br>Shunting resistance<br>Waterproofness<br>Dielectric strength<br>Output voltage |

4.4.1 Failure. Failure of any qualification sample to pass any of the inspections specified herein may be cause, at the option of the Government, for refusal to conduct additional inspections until the faults revealed by the inspection have been corrected.

4.5 Quality conformance inspections.

4.5.1 Sampling.

4.5.1.1 Lot formation. An inspection lot shall consist of all coils from an identifiable production period, from one manufacturer, submitted at one time for acceptance.

4.5.1.2 Sampling for examination. Samples for quality conformance examination shall be selected in accordance with general inspection level II of MIL-STD-105.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

4.5.1.3 Sampling for test. Samples for tests shall be selected in accordance with level S-3 of MIL-STD-105 from each lot that has passed the examination specified in 4.5.2.2.

4.5.2 Examination.

4.5.2.1 Acceptable quality level. Each coil selected in accordance with 4.5.1.2 shall be examined to determine conformance to the following acceptable quality levels (AQL).

| Classification | AQL |
|---|---|
| Major | 1.0 |
| Minor | 2.5 |

4.5.2.2 Classification of defects. For examination purposes, defects shall be classified as listed in table V.

TABLE V. Classification of defects.

| Category | Defect | Method of examination |
|---|---|---|
| Critical | None | |
| Major | AQL 1.0% Defective | |
| 101 | Nonconformance to dimensions which affect interchangeability (see 3.3, 3.3.1 and 3.3.4). | SIE 1/ |
| 102 | Faulty workmanship affecting performance (see 3.7). | Visual |
| Minor | AQL 2.5% Defective | |
| 201 | Nonconformance to dimensions which do not affect interchangeability (see 3.3, 3.3.1 and 3.3.4). | SIE |
| 202 | Improper finish (see 3.5). | Visual |
| 203 | Improper marking (see 3.6). | Visual |
| 204 | Faulty workmanship affecting appearance (see 3.7). | Visual |

1/ SIE = Standard Inspection Equipment.

4.5.3 Tests. Samples selected in accordance with 4.5.1.3 shall be subjected to the quality conformance tests specified in table III, in the order specified therein, and shall conform to an AQL of 6.5% on the basis of % defective.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

4.6 Control tests. Control tests shall be conducted on 2 coils from each lot of 500 units produced consecutively, except that not more than 4 nor less than 2 coils shall be selected in any 30-day period. The control test samples shall be selected from a lot which has passed the examinations specified in 4.5.2, and the quality conformance tests specified in 4.5.3, and shall be subjected to the control tests in table III with the shunting resistance test, 4.7.3.4, conducted first.

4.6.1 Failure. Failure of any coil to pass any of the specified control tests shall be cause for the Government to refuse acceptance of the production quantity represented, until action taken by the contractor to correct defects and prevent recurrence has been approved by the Government.

4.7 Methods of inspection.

4.7.1 Materials and construction. Conformance to 3.2, 3.2.1, 3.3, 3.3.2 through 3.3.8 shall be determined by inspection of contractor records providing proof or certification that design, construction, processing, and materials conform to requirements. Applicable records shall include drawings, specifications, design data, receiving inspection records, processing and quality control standards, vendor catalogs and certifications, industry standards, test reports, and rating data.

4.7.2 Defects. Conformance to 3.3, 3.3.1, 3.3.4, and 3.5 through 3.7 shall be determined by examination for the defects listed in table V. Examination shall be visual or by measurement with standard inspection equipment.

4.7.3 Electrical.

4.7.3.1 Output voltage. To determine conformance to 3.4.1.1, the coil shall be conditioned for 4 hours at an ambient air temperature of 73 $\pm$ 18°F. The coil shall be energized with an input voltage of 18.0 $\pm$ 0.5 V dc and coil terminal (booster and filter circuit terminal) shall be connected to a magneto with which the coil is intended to be used. One magneto secondary lead having voltage compatible with the polarity of the coil shall be connected through a type 1B3GT rectifier to a capacitor of 0.001 microfarads. The voltage across the capacitor shall be measured with an electrostatic voltmeter. Alternate suitable voltage measuring methods may be substituted. Total capacitance of the secondary circuit including the measuring apparatus shall be 150 $\pm$ 10 micro-microfarads. The other secondary leads shall be connected to a standard sparking gap set to an opening of 3 millimeters conforming to Drawing 7727531. Connections shall be made with suitable high-tension cable. The total capacitance of each such secondary circuit to ground including leads and any external capacitor shall be 150 $\pm$ 10 micro-microfarads. The magneto shall be operated at 35 and 100 rpm and the output voltage at each speed recorded. Subsequently, the test shall be repeated at an input voltage of 28.5 $\pm$ 0.5 V dc. The tests shall be repeated except that the ambient air temperature shall be +160 $\pm$ 10°F and -65 $\pm$ 5°F.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

4.7.3.2 Endurance. To determine conformance to 3.4.1.2, the coil with input lead connected to a 28.5 ± 0.5 V dc power source and output lead (booster and filter circuit terminal) connected to an associated magneto shall be energized and subjected to the following endurance test. With the magneto operating at 100 rpm, the coil shall be cycled for 250 hours at the rate of 2 minutes on time and 4 minutes off time. The coil shall subsequently be tested as specified in 4.7.3.1.

4.7.3.3 Dielectric strength. To determine conformance to 3.4.1.3, the coil shall be subjected to a potential of 600 V root mean square, 60 cycles per second applied for 1 minute between each output terminal and the case. The coil shall subsequently be tested as specified in 4.7.3.1.

4.7.3.4 Shunting resistance. To determine conformance to 3.4.1.4, the coil shall be connected as specified in 4.7.3.1 with the addition of a 250,000 ohm, 20 kilovolt (kV) fixed resistor connected from magneto output to ground. The magneto shall be operated at a shaft speed of 100 rpm, with an input voltage of 28.5 ± 0.5 V dc at an ambient air temperature of 73 ± 18°F. The output voltage shall be measured and recorded.

4.7.4 Environmental.

4.7.4.1 Vibration. To determine conformance to 3.4.2.1, the coil shall be mounted as in intended use, assuring that the mounting is free from resonances over the test frequency range. The specimen shall be subjected to a simple harmonic motion having an amplitude of 0.03 inch (0.06 inch maximum total excursion), the frequency being varied uniformly between the approximate limits of 10 and 55 hertz (Hz). The entire frequency range, from 10 to 55 Hz and return to 10 Hz, shall be traversed in approximately 1 minute. This motion shall be applied for a period of 1 hour in each of 3 mutually perpendicular directions (total of 3 hours). This test shall be conducted under electrical load conditions.

4.7.4.2 Waterproofness. To determine conformance to 3.4.2.2, the coil shall be tested in accordance with method 100, procedure 1 of MIL-STD-1184 using type II, class 2 requirements.

4.7.4.3 Shock. To determine conformance to 3.4.2.3, the coil shall be tested in accordance with method 213 of MIL-STD-202 using test condition H (75 gravity units) and sawtooth waveform.

4.7.4.4 Fungus resistance. To determine conformance to 3.4.2.4, the coil shall be subjected to the fungus resistance test as specified in method B of MIL-F-13927 using class 1 requirements, except that the duration of the test shall be for 90 continuous days. Subsequently, the coil shall be subjected to the tests specified in 4.7.3.3 and 4.7.3.1.

4.7.4.5 Corrosion resistance. To determine conformance to 3.4.2.5, the coil shall be tested in accordance with salt spray testing of ASTM B117, except that the duration of the test shall be 200 hours. Subsequently, the coil shall be subjected to the tests specified in 4.7.3.3 and 4.7.3.1 at room temperature.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking for the desired level shall be in accordance with the applicable packaging requirements specified by the contracting authority (see 6.2).

6. NOTES

6.1 Intended use. The coils covered by this specification are intended to provide additional starting current for the direct coupling type magneto of military vehicular internal combustion engines. The coil increases the magneto output at low cranking speeds, resulting in an intensified spark and easier starting.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Military part number.
c. Other applicable standards or drawings if required (see 3.3).
d. If finish shall be other than as specified (see 3.5).
e. If responsibility for inspection shall be other than as specified (see 4.1).
f. If responsibility for inspection equipment shall be other than as specified (see 4.1.2).
g. If inspection conditions shall be other than as specified (see 4.3).
h. Selection of applicable level and packaging requirements (see 5.1).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time set for opening of bids, qualified for inclusion in the applicable QPL whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualificaton in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. The activity responsible for the QPL is the Commanding General, US Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000 and information pertaining to qualification of products may be obtained from that activity (see 3.1).

6.3.1 Retention of qualification. Certification shall be requested every 2 years from each manufacturer listed on the QPL to retain listing on the QPL. This certification shall be forwarded to the preparing activity and shall be signed by a responsible official of management attesting that the listed product still meets the requirements of the current issue of the specification, is available from the listed plant, and can be produced under the same conditions as originally qualified; that is, same process, materials, construction, design, manufacturer's part number or designation. Failure to provide certification shall be cause for removal from the QPL.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

6.4 Definitions.

6.4.1 Recovered materials. "Recovered materials" means materials that have been collected or recovered from solid waste (see 6.4.2).

6.4.2 Solid waste. "Solid waste" means (a) any garbage, refuse, or sludge from a waste treatment plant, water supply treatment plant, or air pollution control facility; and (b) other discarded material, including solid, liquid, semisolid, or contained gaseous material resulting from industrial, commercial, mining, and agricultural operations, and from community activities. It does not include solid or dissolved material in domestic sewage, or solid or dissolved material in irrigation return flows or industrial discharges which are point sources subject to permits under section 402 of the Clean Water Act, (33 U.S.C. 1342 et seq.), or source, special nuclear, or byproduct material as defined by the Atomic Energy Act of 1954 (42 U.S.C. 2011 et seq.) (Source: Federal Acquistion Regulations, section 23.402).

6.5 Subject term (key word) listing.

Engine ignition starting coil, 24 V dc with filter
Ignition coil, engine starting, 24 V dc with filter
Starting coil, engine ignition, 24 V dc with filter

6.6 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - AT

User activities:
Army - ME
Navy - MC
DLA - CS

Preparing activity:
Army - AT

(Project 2920-0425)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

*OFFICIAL BUSINESS*
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Tank-Automotive Command
ATTN: AMSTA-GDS
Warren, MI 48397-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| | |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ USER |
| | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)*: _____ |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |
| | |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:47Z
Check the source to verify that this is the current version before use.