MILITARY SPECIFICATION

ENGINE, GASOLINE: 4-CYLINDER,
IN-LINE, LIQUID-COOLED, 65 HP, M151-2

This amendment forms a part of Military Specification MIL-E-45332C(AT), dated 30 June 1975.

PAGE 1

2.1, under "SPECIFICATIONS, Federal", delete:
"VV-G-001690 - Gasoline, Automotive."

2.1, under "SPECIFICATIONS, Federal", add:
"P-C-437 - Cleaning Compound, High Pressure (Steam) Cleaner."

2.1, under "SPECIFICATIONS, Military", delete:
"MIL-L-10295 - Lubrication Oil, Internal Combustion Engine, Sub-zero.
MIL-E-13856 - Electrical Components for Automotive Vehicles; Waterproofness Tests.
MIL-C-52412 - Cleaning Compound, High Pressure Cleaner, Steam."

PAGE 2

2.1, under "SPECIFICATIONS, Military", add:
"MIL-STD-46167 - Lubricating Oil, Internal Combustion Engine, Arctic."

2.1, under "STANDARDS, Military", add:
"MIL-STD-1184 - Electrical Components for Automotive Vehicles; Waterproofness Tests.
MS35909 - Spark Plug, Shielded, 14mm, 1-1/4 Inch Well (Other Than Aircraft)."

PAGE 3

3.2, line 2, delete "VV-G-001690" and substitute: "MIL-G-46015."

3.2.1, subparagraph (a), line 1, delete: "and transmission torus cover."

FSC 2805

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:44Z
Check the source to verify that this is the current version before use.

PAGE 5

3.2.6, line 3, delete: "or blocked in the full open position".

3.2.8, line 1, delete "VV-G-001690", and substitute: "MIL-G-46015".

PAGE 7

TABLE I, delete "Run-in schedule - see Table I" and substitute: "Production break-in run - see 3.4 and Table II".

PAGE 13

3.3.1, line 3, delete "MIL-E-13856" and substitute: "MIL-STD-1184".

3.3.3, line 5, delete.

3.3.4, line 3, delete "MIL-L-10295" and substitute: "MIL-L-467167".

PAGE 14

3.4, subparagraph (f), delete and substitute:

"f. The minimum coolant temperature shall be 140°F during break-in run. This temperature shall be recorded immediately before the coolant pump and immediately after the coolant outlet (thermostat) connection."

3.4, delete the last sentence and substitute:

"The valve lash shall be adjusted with the engine hot and idling immediately after period 3. In addition, all adjustments including, but not limited to, dwell, timing and valve lash required to satisfy this performance specification shall be performed during period 7."

PAGE 15

3.5.2, delete the last sentence and substitute:

"Rated horsepower shall be demonstrated as required in table I for the 500 hour endurance test, and at the completion of the production break-in run and the 50-hour control test."

3.5.3, delete the last sentence and substitute:

"Rated torque shall be demonstrated as required in table I for the 500-hour endurance test, and at the completion of the 50-hour control test."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:44Z
Check the source to verify that this is the current version before use.

PAGE 16

3.6.4, delete the sentence and substitute:

"The engine shall be cold soaked until its fuel, coolant and oil temperature are within ± 5°F of an ambient air temperature of minus 65°F. The engine shall be started in an ambient temperature of minus 65°F with the aid of the vehicle winterization kit, drawing 8712420."

PAGE 17

3.7, line 2, delete "MIL-C-52412", and substitute: "P-C-437".

PAGE 18

3.8, add: "Spark plugs conforming to MS35909-1 shall be used during the production control test. The vent lines shall be disconnected from the ignitor and coupled together through a junction block prior to the start of the test. The ignitor shall be vented to the atmosphere during the entire control test. After completion of the control test, the vent lines shall be connected to the ignitor."

Add new paragraph:

"3.8.1.1 Required adjustments and checks. During the 50-hour control test the following checks and adjustments shall be made:

"a. Initial checks (after break-in run):

(1) Check timing at 550 rpm and record in test log.
(2) Check dwell angle and record in test log.
(3) Check valve lash and record in test log.
(4) Check idle for 650 rpm and record in test log.

b. 25-Hour check point:

(1) Check timing at 550 rpm, set as required and record in test log.
(2) Check dwell angle, set as required and record in test log.
(3) Check valve lash, set as required and record in test log.
(4) Check spark plugs, clean and adjust or replace as required and record in test log.
(5) Check idle for 650 rpm, set as required and record in test log.

c. 50-Hour check point (prior to power check run): Repeat entire 25-hour check."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:44Z
Check the source to verify that this is the current version before use.

PAGE 19

3.11.2, delete the last sentence and substitute:

"The name plate shall conform to MIL-P-514 and shall contain the following minimum information, unless otherwise shown on applicable drawings:"

PAGE 23

4.4.1, delete last sentence.

Add new paragraph:

"4.4.1.1 Control testing. The 50-hour control test shall be conducted as specified in 3.8 through 3.8.5, and Table IV."

PAGE 27

6.4, in the corrected BHP equation, under the radical sign, delete "±" and substitute: "+".

Custodian:
Army - AT

Preparing activity:
Army - AT

Project No. 2805-A531

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:44Z
Check the source to verify that this is the current version before use.