MILITARY SPECIFICATION

LIGHT, WARNING, VEHICULAR: ROTATING UNIT, 14 AND 28 VOLT DC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers 14- and 28-volt (V) direct current (dc) rotating warning lights, referred to herein as "warning lights", for use on emergency, security, utility, or maintenance vehicles (see 6.1).

1.2 Classification. Warning lights covered by this specification shall be of the following types and classes, as specified (see 6.2):

Type I - 14 V dc.

Class 1 - Amber dome.
Class 2 - Blue dome.
Class 3 - Red dome.

Type II - 28 V dc.

Class 1 - Amber dome.
Class 2 - Blue dome.
Class 3 - Red dome.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 6220
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

STANDARDS
MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-202	- Test Methods for Electronic and Electrical Component Parts.
MIL-STD-454	- Standard General Requirements for Electronic Equipment.
MIL-STD-461	- Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.
MIL-STD-462	- Electromagnetic Interference Characteristics, Measurement of.
MIL-STD-810	- Environmental Test Methods and Engineering Guidelines.
MIL-STD-45662	- Calibration Systems Requirements.
MS51317	- Light, Warning, Vehicular, Rotating, DC.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE J575	- Tests for Motor Vehicle Lighting Devices and Components.
SAE J576	- Plastic Materials for Use in Optical Parts such as Lenses and Reflectors of Motor Vehicle Lighting Devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

SAE J578 - Color Specification for Electric Signal Lighting Devices.

SAE J845 - 360 Degree Warning Lamp for Authorized Emergency, Maintenance and Service Vehicles.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. Unless otherwise specified (see 6.2), the contractor shall furnish warning lights which shall be subjected to first article inspection (see 4.4). First article inspection samples, properly marked with identifying information, shall be representative of the units to be furnished to the Government. All subsequent warning lights delivered to the Government shall conform to these samples in all of their pertinent physical and performance attributes.

3.2 Materials. Materials shall be as specified herein and in referenced specifications and standards. Materials shall be free of defects which adversely affect performance of the finished product (see 4.8.1 and 6.3).

3.2.1 Dome material. The plastic used in fabricating domes shall meet the color and performance requirements specified herein and shall meet the requirements of SAE J576 (see 4.8.1).

3.2.2 Skirt material. The skirt material shall be metal or plastic and shall meet the performance requirements specified herein (see 4.8.1).

3.2.3 Dissimilar metals. Except where necessary to complete an electrical circuit, contact between dissimilar metals which would encourage galvanic action shall be avoided. Separation of dissimilar metals shall be accomplished by providing insulation between mating surfaces (see 4.8.1).

3.3 Design and construction. Warning lights shall be designed and constructed in accordance with MS51317. The warning lights shall utilize two or more sealed beam lamps and shall be wired such that failure of one lamp will not affect the other functions of the warning light (see 4.8.2).

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:43Z
Check the source to verify that this is the current version before use.

3.3.1 Installation instructions. Each warning light shall be furnished with complete instructions covering the installation of the warning light. A wiring diagram showing all of the electrical connections to be made shall be included in the installation instructions (see 4.8.2).

3.3.2 Soldering. Soldering shall be in accordance with requirement 5 of MIL-STD-454 (see 4.8.1).

3.3.3 Color. The color of the warning light's dome (per applicable class of MS51317) shall be as specified by SAE J578 and table I (see 4.8.3).

TABLE I. Color of warning light domes.

Class	Color
1	Yellow
2	Signal Blue
3	Red

3.4 Performance.

3.4.1 Operation. When supplied with the voltage specified in table II, warning lights shall meet the flashing rate and current requirements of table II (see 4.8.4.1).

TABLE II. Operation requirements.

Type	Voltage (V dc)	Flashing rate (flashes/minute)	Maximum direct current (amperes)
I	14 ± 0.5	90 ± 30	10.5
II	28 ± 0.5	90 ± 30	5.5

3.4.2 Candlepower. The warning lights shall meet the photometric requirements of SAE J845 for the classes and colors specified in table III (see 4.8.4.2).

TABLE III. Photometric requirements.

Class	Class per SAE J845	Color
1	1	Yellow
2	2	Signal Blue
3	1	Red

3.4.3 Endurance. Warning lights shall exhibit no electrical or mechanical malfunction, except lamp failure, and shall meet the requirements of 3.4.1 after being operated for 500 hours (see 4.8.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.4.4 Environmental.

3.4.4.1 High temperature. The warning light shall meet the high temperature requirements of SAE J845 (see 4.8.4.4.1).

3.4.4.2 Low temperature. The warning light shall meet the low temperature requirements of SAE J845 (see 4.8.4.4.2).

3.4.4.3 Vibration. Warning lights shall show no evidence of disintegration of component materials or assemblies and shall meet the requirements of 3.4.1 after being subjected to vibration in each direction of the three major axes. The frequency range shall be 10 to 30 hertz (Hz) and the amplitude shall be as specified in MIL-STD-202, method 201 (see 4.8.4.4.3).

3.4.4.4 Shock. Warning lights shall show no evidence of disintegration of component materials or assemblies and shall meet the requirements of 3.4.1 after being subjected to induced shocks of sawtooth waveform along each of the three mutually perpendicular axes with a peak value of 25 gravity units (g). Lamp filament failure shall not constitute failure of the warning light (see 4.8.4.4.4).

3.4.4.5 Salt fog. Warning lights shall meet the requirements of 3.4.1 and shall evidence no interior or exterior corrosion after exposure to a salt fog atmosphere (see 4.8.4.4.5).

3.4.4.6 Water spray. Warning lights shall meet the requirements of SAE J575 for water spray (see 4.8.4.4.6).

3.4.4.7 Electromagnetic interference. Warning lights shall meet the requirements of MIL-STD-461 for class A3 equipment, methods CE03 and RE02 (see 4.8.4.4.7).

3.4.4.8 Weather resistance. Warning lights shall meet the requirements of 3.3.3 and 3.4.2 and shall show no evidence of cracking or crazing after exposure to solar radiation in accordance with MIL-STD-810, method 505, procedure II for 56 cycles with no deviation of the spectral distribution for thermal effects allowed (see 4.8.4.4.8).

3.4.4.9 Heat aging. Warning lights shall meet the requirements of 3.3.3 and 3.4.2 and shall show no evidence of cracking, warping or crazing after exposure to ambient temperatures of not less than 200 degrees Fahrenheit (°F) [93 degrees Celsius (°C)] for not less than 240 hours (see 4.8.4.4.9).

3.4.4.10 Dust. Warning lights shall meet the requirements of SAE J575 for dust exposure (see 4.8.4.4.10).

3.5 Identification and marking. The following information shall be permanently and legibly marked on each warning light in accordance with MIL-STD-130 (see 4.8.2):

MS part number
Voltage rating
Manufacturer's identification

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. Workmanship shall be such quality as to assure that warning lights furnished under this specification are free of defects that compromise, limit, or reduce performance or intended use. Warning lights shall be free of burrs, rust, scratches, sharp edges, loose components, chips, and unnecessary oil or foreign materials (see 4.8.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform or witness any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply wih all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Inspection equipment. Unless otherwise specified in the contract (see 6.2), the contractor is responsible for the provision and maintenance of all inspection equipment necessary to assure that supplies and services conform to contract requirements. Inspection equipment must be capable of repetitive measurements to an accuracy of 10 percent of the measurement tolerance. Calibration of inspection equipment shall be in accordance with MIL-STD-45662.

4.2 Classification of inspection:

a. First article inspection (see 4.4).
b. Quality conformance inspections (see 4.5).
    1. Examination (see 4.5.2).
    2. Tests (see 4.5.3).
c. Control tests (see 4.6).

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be conducted under the following conditions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

a. Air temperature 73 ± 18°F (23 ± 10°C)
b. Barometric pressure 28.5 $^{+2}_{-3}$ inches (in) mercury (Hg)
[725 $^{+50}_{-75}$ millimeters (mm) Hg]
c. Relative humidity 50 ± 30 percent

4.4 First article inspection. Unless otherwise specified (see 6.2), the Government shall select three complete warning lights (with three additional sealed beam lights) produced under the production contract (see 6.2) for first article inspection. First article samples shall be inspected as specified in table IV, in the order listed in table V. Approval of the first article sample by the Government shall not relieve the contractor of his obligation to supply warning lights that are fully representative of those inspected as a first article sample. Any changes or deviation of the production units from the first article sample shall be subject to the approval of the contracting officer.

4.4.1 First article inspection failure. Test item deficiencies during, or as a result of, the first article test shall be cause for rejection of the items until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiency. Any deficiency found during, or as a result of, the first article test shall be evidence that all items already produced prior to completion of the first article test are similarly deficient unless contrary evidence satisfactory to the contracting officer is furnished by the contractor. Such deficiencies on all items shall be corrected by the contractor. The Government shall not accept products until first article testing is completed to the satisfaction of the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of inspections.

Title	Requirement	Inspection	First article	Quality conformance		Control
				Examination	Test	
Materials and construction	3.2, 3.2.1, 3.2.2, 3.2.3, and 3.3.2	4.8.1	X			
Defects	3.3, 3.3.1, 3.5, and 3.6	4.8.2	X	X		
Color	3.3.3	4.8.3	X			X
Operation	3.4.1	4.8.4.1	X		X	X
Candlepower	3.4.2	4.8.4.2	X			X
Endurance	3.4.3	4.8.4.3	X			
High temperature	3.4.4.1	4.8.4.4.1	X			
Low temperature	3.4.4.2	4.8.4.4.2	X			
Vibration	3.4.4.3	4.8.4.4.3	X			
Shock	3.4.4.4	4.8.4.4.4	X			
Salt fog	3.4.4.5	4.8.4.4.5	X			X
Water spray	3.4.4.6	4.8.4.4.6	X			X
Electromagnetic interference	3.4.4.7	4.8.4.4.7	X			
Weather resistance	3.4.4.8	4.8.4.4.8	X			
Heat aging	3.4.4.9	4.8.4.4.9	X			
Dust	3.4.4.10	4.8.4.4.10	X			X

TABLE V. First article test sequence.

Sample number		
1	2	3
4.8.4.1	4.8.4.1	4.8.4.1
4.8.3	4.8.4.4.3	4.8.4.4.7
4.8.4.4.1	4.8.4.1	4.8.4.4.8
4.8.4.4.2	4.8.4.4.6	4.8.4.4.9
4.8.4.2	4.8.4.4.5	4.8.4.4.10
4.8.4.1	4.8.4.1	
4.8.4.3		
4.8.4.4.4		
4.8.4.1		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection.

4.5.1 Sampling.

4.5.1.1 Lot formation. An inspection lot shall consist of all the warning lights of one type and part number, from an identifiable production period, from one manufacturer, submitted at one time for acceptance.

4.5.1.2 Sampling for examination. Samples for quality conformance examination shall be selected in accordance with general inspection level II of MIL-STD-105.

4.5.1.3 Sampling for test. Samples for tests shall be selected in accordance with level S-3 of MIL-STD-105.

4.5.2 Examination.

4.5.2.1 Acceptable quality level. Each sample selected in accordance with 4.5.1.2 shall be examined to determine conformance to the following acceptable quality levels (AQL) on the basis of percent defective.

Classification	AQL
Major	1.0
Minor	2.5

4.5.2.2 Classification of defects. For examination purposes, defects shall be classified as listed in table VI.

TABLE VI. Classification of defects.

Category	Defect	Method of examination
Critical	None	
Major	AQL 1.0% Defective	
101	Assembly, incomplete (see 3.3).	Visual
102	Dimensions affecting interchangeability, out of tolerance (see 3.3).	SIE 1/
103	Installation instructions, missing (see 3.3.1).	Visual
104	Identification marking, improper (see 3.5).	Visual
105	Faulty workmanship affecting performance (see 3.6).	Visual
Minor	AQL 2.5% Defective	
201	Dimensions not affecting interchangeability, out of tolerance (see 3.3).	SIE 1/
202	Faulty workmanship affecting appearance (see 3.6).	Visual

1/ SIE = Standard Inspection Equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

4.5.3 Test. Samples selected in accordance with 4.5.1.3 shall be subjected to the quality conformance test specified in table IV and shall conform to an AQL of 2.5.

4.6 Control tests. Control tests shall be conducted on one warning light from each lot of 500 units consecutively produced, except that not more than three tests shall be performed in a 30-day period. The warning lights shall be subjected to the tests specified in table IV, in the following order: 4.8.4.1, 4.8.3, 4.8.4.2, 4.8.4.4.5, 4.8.4.4.6, and 4.8.4.4.10.

4.7 Failure. Failure of any warning light to pass any of the specified quality conformance or control tests shall be cause for the Government to refuse acceptance of the production quantity represented, until action taken by the contractor to correct defects and prevent recurrence has been approved by the Government.

4.8 Methods of inspection.

4.8.1 Materials and construction. Conformance to 3.2, 3.2.1, 3.2.2, 3.2.3, and 3.3.2 shall be determined by inspection of contractor records providing proof or certification that design, construction, processing, and materials conform to requirements. Applicable records shall include drawings, specifications, design data, receiving inspection records, processing and quality control standards, vendor catalogs and certifications, industry standards, test reports, and rating data.

4.8.2 Defects. Conformance to 3.3, 3.3.1, 3.5, and 3.6 shall be determined by examination for the defects listed in table VI. Examination shall be visual, tactile, or by measurement with standard inspection equipment.

4.8.3 Color. To determine conformance to 3.3.3, the domes shall be tested in accordance with SAE J578.

4.8.4 Performance.

4.8.4.1 Operation. To determine conformance to 3.4.1, the warning light shall be connected to a power source and operated at the voltage specified in table II for 30 $\pm$ 5 minutes. The flashing rate and current consumption shall be measured and recorded at the beginning of the test and at 5 minute intervals throughout the test. The flashing rate shall be determined by multiplying the revolutions per minute (rpm) of the warning light lamps by the number of lamps in the light.

4.8.4.2 Candlepower. To determine conformance to 3.4.2, the warning light shall be subjected to photometry testing in accordance with SAE J575.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

4.8.4.3 Endurance. To determine conformance to 3.4.3, the warning light shall be connected to a power source of the applicable voltage specified in table II and subjected to the following cycle: 25 minutes on, 5 minutes off, for a total of 500 hours of on-time. If a lamp burns out, the lamp shall be replaced and the test continued. During the test, the warning light shall be examined for electrical and mechanical malfunction. After the test, the warning light shall be tested as specified in 4.8.4.1, except that the duration of the test shall be 5 minutes.

4.8.4.4 Environmental.

4.8.4.4.1 High temperature. To determine conformance to 3.4.4.1, the warning light shall be subjected to the high temperature flash rate test specified in SAE J845.

4.8.4.4.2 Low temperature. To determine conformance to 3.4.4.2, the warning light shall be subjected to the low temperature flash rate test specified in SAE J845.

4.8.4.4.3 Vibration. To determine conformance to 3.4.4.3, the warning light shall be mounted as in intended use and shall be tested in accordance with MIL-STD-202, method 201. Motion shall be applied for 1 hour in the direction of each of the three major axes for a total of 3 hours. The warning light shall be operated for the last 10 minutes of each hour.

4.8.4.4.4 Shock. To determine conformance to 3.4.4.4, the warning light shall be mounted as in intended use and shall be tested in accordance with method 516.3, procedure I of MIL-STD-810. The shock pulse shape shall be in accordance with figure 516.3-4 of MIL-STD-810. The pulse shall have an amplitude of 25 g and a duration of 11 milliseconds (ms). Three shocks in each direction shall be applied along each of the three mutually perpendicular axes for a total of 18 shocks. Subsequently, the warning lights shall be tested in accordance with 4.8.4.1, except that the duration of the test shall be 5 minutes.

4.8.4.4.5 Salt fog. To determine conformance to 3.4.4.5, the warning light shall be mounted as in intended use and shall be tested in accordance with method 509.2, procedure I of MIL-STD-810, except that the exposure period shall be 96 hours. Subsequently, the warning light shall be tested in accordance with 4.8.4.1, except that the duration of the test shall be 5 minutes.

4.8.4.4.6 Water spray. To determine conformance to 3.4.4.6, the warning light shall be subjected to the water spray test specified in SAE J575. Subsequently, the warning light shall be tested in accordance with 4.8.4.1, except that the duration of the test shall be 5 minutes.

4.8.4.4.7 Electromagnetic interference. To determine conformance to 3.4.4.7, the warning light shall be tested in accordance with methods CE03 and RE02 of MIL-STD-462.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

4.8.4.4.8 Weather resistance. To determine conformance to 3.4.4.8, the warning light shall be mounted as it is in the vehicle. The toggle bolts (see MS51317) used to mount the warning light shall be torqued to at least 6 pound feet (lb ft). The warning light shall then be tested in accordance with MIL-STD-810, method 505, procedure II for 56 cycles. No deviation of spectral distribution for thermal effects shall be allowed. Subsequently, the warning light shall pass the tests of 4.8.3 and 4.8.4.2.

4.8.4.4.9 Heat aging. To determine conformance to 3.4.4.9, the warning light shall be mounted as specified in 4.8.4.4.8. The warning light shall then be subjected to an ambient temperature of not less than 200°F (93°C) for not more than 240 hours. Subsequently, the warning light shall pass the tests of 4.8.3 and 4.8.4.2.

4.8.4.4.10 Dust. To determine conformance to 3.4.4.10, the warning light shall be subjected to the dust test specified in SAE J575. Subsequently, the warning light shall be tested in accordance with 4.8.4.1, except that the duration of the test shall be 5 minutes.

5. PACKAGING

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking for the desired level shall be in accordance with the applicable packaging standard or packaging data sheet specified by the contracting authority (see 6.2).

6. NOTES

6.1 Intended use. The warning lights covered by this specification are intended for use on emergency, security, utility, or maintenance vehicles having 14- or 28-V dc electrical systems (see 1.1).

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type, class, and military standard title, number, and date (see 1.2 and 3.3).
c. If first article samples are not required (see 3.1).
d. If responsibility for inspection shall be other than as specified (see 4.1).
e. If responsibility for inspection equipment shall be other than as specified (see 4.1.2).
f. If inspection conditions shall be other than as specified (see 4.3).
g. If first article inspection is not required (see 4.4).
h. Selection of applicable level and packaging standard or packaging data sheet (see 5.1).

6.3 Recycled materials. The use of recycled materials which meet the requirements of the applicable material specifications without jeopardizing the intended use of the item shall be encouraged (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

6.4 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.5 Subject term (key word) listing.

Rotating Vehicular Warning Light
Vehicular Warning Light
Warning Light

Custodians:
Army - AT
Navy - YD
Air Force - 99

Review activities:
Army - ME
DLA - GS
Air Force - 82

User activities:
Navy - MC, SH

Preparing activity:
Army - AT

(Project 6220-0337)

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Tank-Automotive Command
ATTN: DRSTA-GSS
Warren, MI 48080

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.