NOT MEASUREMENT SENSITIVE

MIL-S-45324L
12 December 1990
SUPERSEDING
MIL-S-45324K
28 September 1984

MILITARY SPECIFICATION

SCOOTERS, MOTOR: GASOLINE ENGINE DRIVEN, THREE- AND FOUR-WHEEL, COMMERCIAL

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers gasoline engine driven three-wheeled scooters intended for both local streets and roads and on-station operation, and four-wheeled scooters restricted to on-station operation (see 6.1 for details on intended use). Vehicles procured under this specification are commercial items which are warranted by the manufacturer as specified in acquisition documents.

1.2 Classification. Scooters shall be one of the following styles, as specified (see 6.2):

Style A - Scooter, 1,000 pound flatbed, with panel sides and tailgate.
Style B - Scooter, with enclosed lockable package compartment.
Style C - Scooter, with integral van body.
Style D - Scooter, with integral van body and rear passenger seats.
Style E - Scooter, refuse collection.
Style F - Scooter, 2,000 pound flatbed.
Style G - Scooter, 1,500 pound flatbed, wide tread, with panel sides and tailgate.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

1.2.1 Model. The model of the scooter shall be determined by the intended usage and by the number of wheels, as specified (see 6.2):

Model 1 - On-road, 3-wheel
Model 2 - On-station, 4-wheel
Model 3 - On-station, 3-wheel.

1.2.2 Class. The class of the scooter shall be determined by the cab enclosure, as specified (see 6.2):

Class I - Integral cab and body
Class II - Enclosed driver's cab, separate from body
Class III - Open driver's area.

* 1.2.3 Combinations. The combinations of style, model, and class ordered under this specification shall be limited to those shown in table I.

TABLE I. Combinations.

Scooter style	Models available			Classes available		
A	1	2	3	-	II	III
B	1	2	3	-	II	III
C	1	2	-	I	-	-
D	-	2	-	I	-	-
E	1	-	-	-	II	III
F	-	2	3	-	II	III
G	-	-	3	-	II	III

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS
FEDERAL
W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting and Starting.

STANDARDS
FEDERAL
FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-461	- Electromagnetic Interference Characteristics Requirements for Equipment.
MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking, and Data Plate Standards.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

* DEPARTMENT OF DEFENSE
Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should reference the code of Federal Regulations, 49 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Certification and Test Procedures for New Motorcycles; Emission Regulations and Appendices.
EPA Noise Emission Regulations for Motorcycles.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)
Standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

(Application for copies of OSHA publications should reference the Code of Federal Regulations 29 CFR, Part 1910, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

SAE, INC.
SAE Standards and Recommended Practices.

J245	- Engine Rating Code - Spark Ignition.
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
J588	- Turn Signal Lamps.
J589	- Turn Signal Switch.
J607	- Small Spark Ignition Engine Test Code.
J695	- Turning Ability and Off Tracking.
J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

* (Application for copies of Tire and Rim Association publications should be addressed to The Tire and Rim Association, Inc., 175 Montrose West Ave., Copley, OH 44321.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.6, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. All items shall be as represented and rated in the chassis manufacturer's technical data book. Special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity, prior to delivery of the items. The model furnished shall be not older than the manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Treatment and painting. The vehicle shall be treated and painted in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate service (see 6.2), the exterior color shall be in accordance with MIL-STD-1223.

* 3.1.1.2 Marking and data plates. As specified by the procuring activity for the appropriate military service (see 6.2), identification marking and data plates shall be in accordance with MIL-STD-1223. When specified (see 6.2), concealed markings shall be furnished.

* 3.1.1.3 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with the truck requirements of FED-STD-297. When specified (see 6.2), the vehicle shall be rustproofed in accordance with the truck tropical rustproofing requirements of FED-STD-297.

3.1.1.4 Pintle assembly. When specified (see 6.2), a pintle assembly with associated reinforcements and safety chain attachment devices shall be installed on the rear of model 2 or model 3 vehicles. The pintle assembly shall be of the fixed type, five-ton capacity, with locking pin and chain, Holland Hitch Model T60AL. The pintle assembly shall be installed on the chassis or reinforced bumper with reinforcements to transfer pintle loads directly to the frame. The rearmost part of the pintle shall be not more than four inches forward of the rearmost part of the vehicle. The pintle hook mounted height measured from ground level to the centerline of the pintle hook on the loaded vehicle shall be in the range of 12 to 18 inches. Two trailer chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment shall provide an ultimate strength not less than the gross vehicle weight of the vehicle furnished. The pintle hook shall be secured with a minimum of four 0.500 inch bolts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.1.1.5 Trailer lighting receptacle. When specified (see 6.2), on pintle-equipped vehicles, a trailer lighting receptacle shall be installed at the rear of the vehicle adjacent to the pintle assembly. The lighting receptacle shall be 12-volt and shall conform to SAE J560 with its conductors connected and color coded as specified therein.

3.1.1.6 Spark arrester. When specified (see 3.4.3.1), the vehicle shall be furnished with an exhaust system spark arrester.

3.2 General design.

3.2.1 Model 1 scooter design standards.

3.2.1.1 Federal Motor Vehicle Safety Standards. Model 1 scooters and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards applicable to motorcycles in effect on the date of manufacture.

3.2.1.2 Interior sound level. The interior sound level of model 1, class 1 and class 2 scooters shall conform to Federal Motor Carrier Safety Regulation 393.94, except when cloth cab doors are furnished (see 3.4.11.1).

3.2.1.3 Exterior noise level. The exterior noise level of model 1 scooters shall conform to the EPA Noise Emission Regulations for Motorcycles. Vehicles destined for California shall comply with the California Vehicle Code.

3.2.1.4 Air pollution control. Model 1 scooters shall comply with the EPA regulations governing Certification and Test Procedures for New Motorcycles; Emission Regulations and Appendices in effect on the date of manufacture.

3.2.2 Model 2 and model 3 scooter design standards.

3.2.2.1 OSHA standards. Model 2 and model 3 scooters shall comply with all vehicle requirements set forth in the OSHA standards, section 1910.178, for powered industrial trucks, type G designation.

3.2.3 Curb weight. The curb weight shall include the weight of the chassis; the body with all attachments, accessories, and equipment; and full complement of fuel, lubricants and coolant. Curb weight shall be not less than 900 pounds.

3.2.4 Total rated payload. The total rated payload shall be as specified in table II, distributed between the operator's location, the passenger's location, and the loadspace, as indicated in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

TABLE II. Total rated payload (in pounds).

Style	Model	Loadspace Payload	Operator	Passenger(s)	Total rated payload
A, B, C, E	1	1,000	175	-	1,175
A, B	2	1,000	175	175	1,350
C	2	825	175	175	1,175
D	2	300	175	700	1,175
* F	2	2,000	175	175	2,350
* F	3	2,000	175	-	2,175
G	3	1,500	175	175	1,850

3.2.5 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings must be submitted to the engineering office of the procuring activity.

3.2.6 Vehicle dimensions. The vehicle dimensions shall be as specified in table III.

TABLE III. Dimensions (inches).

Feature	Model 1	Model 2	Model 3		
	All styles	All styles	Style A	Style F	Style G
Wheelbase (minimum)	78	84	78	84	78
Wheel tread (minimum)	41	41	41	41	45
Overall length (maximum)	127	120 1/	112	132	125
Overall width (minimum)	47	47	47	47	54
Overall height, class I and class II (maximum)	71	71	71	71	72
Overall height, class III (maximum excluding mirrors)	47	48	47	47	50

1/ NOTE: Overall length for style F shall not exceed 140 inches.

3.2.7 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.8 Asbestos. Asbestos materials shall not be used in any form in any part of the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.3 Performance. Vehicle performance shall be rated with the vehicle loaded with the specified payload and operating at maximum engine governed speed. Road surfaces shall be smooth, dry, and hard.

3.3.1 Maximum geared speed. Unless a pintle assembly is required (see 3.1.1.3), the maximum geared speed at engine governed speed shall be within 5 percent of the speed listed in table IV as standard for the body style and model specified. When specified (see 6.2), the optional geared speed specified in table IV shall be provided by use of an optional rear axle ratio. When a pintle assembly is required (see 3.1.1.3), the maximum geared speed shall not exceed 24 miles per hour (mph).

* TABLE IV. Maximum speeds (nominal).

Style	Model	Standard geared speed (mph)	Optional geared speed (mph)
A thru C	1	39	29
A thru C	2	22	-
D	2	22	-
A	3	22	18
E	1	29	18
F	2	18	-
F	3	18	-
G	3	23	-

3.3.2 Gradeability. High speed gradeability requirements shall be met with the transmission in the highest gear; low speed gradeability shall be achieved in first gear. Based on the required maximum geared speed (see 3.3.1), the scooter shall ascend the continuous grades specified in table V, when loaded with the payload specified in table V.

TABLE V. Gradeability.

Maximum geared speed (mph)	Payload (pounds)	Percent grade (high speed)	Percent grade (low speed)
18	1,000	9	25
22 or 23	1,500	8	20
29	1,000	7	20
39	1,000	4	12

3.3.3 Drawbar pull. When a pintle is required (see 3.1.1.4), the scooter shall be capable of developing a continuous first gear drawbar pull of 750 pounds. When an auxiliary transmission (see 3.4.4.3) is specified for pintle-equipped style G scooters, the drawbar pull shall be not less than 1,000 pounds.

* 3.3.4 Turning clearance. The scooter shall turn within a vehicle clearance circle (conforming to SAE J695) of not more than 25 feet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.3.5 Service brake performance. The service brakes on model 1 scooters shall conform to Federal Motor Vehicle Safety Standard No. 122. For model 2 and model 3 scooters, the service brakes shall stop and hold the vehicle loaded with total rated payload on a 25 percent grade, and shall stop the fully loaded scooter within a distance of 30 feet from a speed of 18 mph on smooth, dry, level, hard-surfaced road.

3.3.6 Parking brake performance. The parking brakes of model 1 scooters shall conform to Federal Motor Vehicle Safety Standard No. 122. The parking brakes of model 2 and model 3 scooters shall hold the vehicle, loaded with total rated payload, on grades of not less than 20 percent.

3.3.7 Cold starting performance. The scooter shall be capable of starting and operating after a 48-hour exposure to a minus 10 degree Fahrenheit (°F) ambient temperature.

3.3.8 Waterproofness. The scooter shall be capable of being driven at speeds up to maximum geared speed through puddles and standing water on paved surfaces without leakage into the cab and without entry of water into the electrical system, wheel bearings, steering column bearings or other lubricated areas. The frequency of adjustment required to maintain bearings watertight shall be not greater than the manufacturer's recommended lubrication frequency.

3.4 Chassis. Model 1 and model 3 scooters shall be of the three wheel type with single front and two rear wheels. Model 2 scooters shall be of the four wheel type. Front wheel steering and rear wheel driving shall be provided.

* 3.4.1 Engine. The engine shall be a two, three or four cylinder, air- or water-cooled, four-stroke cycle, gasoline engine. The engine shall develop not less than 18 horsepower at a governed speed not greater than 3600 revolutions per minute (rpm) when operated on unleaded fuel with a research octane rating of 91. The rated net torque output of the engine shall be not less than 28 pound-feet. Engine net torque and horsepower ratings shall be determined in accordance with SAE J245, SAE J607 or SAE J1349.

3.4.1.1 Oil filter. A full-flow type oil filter shall be furnished.

3.4.1.2 Governor. An engine governor shall be furnished, set and sealed to limit the engine speed to the engine manufacturer's maximum recommended operating speed.

3.4.2 Fuel system. The fuel system shall be equipped with an easily accessible in-line fuel filter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.4.2.1 Air cleaner. An air cleaner shall be furnished.

3.4.2.2 Fuel tank. The fuel capacity shall be not less than 5.5 gallons.

3.4.3 Exhaust system. For model 1 scooters, the exhaust system shall limit noise levels to those specified in 3.2.1.2 and 3.2.1.3. For model 2 and model 3 scooters, the manufacturer's standard exhaust system, including a muffler, shall be furnished.

3.4.3.1 Spark arrester. When specified (see 6.2), a spark arrester shall be furnished.

3.4.4 Drive train.

* 3.4.4.1 Clutch. A single-plate dry clutch not less than 6.5 inches in diameter shall be provided. The clutch torque capacity shall exceed the maximum delivered engine torque. The clutch lining shall be asbestos free.

3.4.4.2 Transmission. Unless otherwise specified (see 3.4.4.3), the scooter shall be equipped with a 3- or 4-speed manual transmission.

3.4.4.3 Auxiliary transmission. When specified (see 6.2), style G scooters shall be equipped with an auxiliary transmission to provide 6 forward speeds.

3.4.5 Electrical system. A 12-volt electrical system shall be provided.

3.4.5.1 Ignition system. A battery type ignition system shall be provided. An alternator of not less than 35 amperes rated capacity shall be furnished.

3.4.5.2 Starter. An electrical starting system shall be furnished.

3.4.5.3 Battery. The battery shall be a 12-volt maintenance-free type, having the maintenance-free characteristics listed in W-B-131. The battery capacity shall be sufficient to provide the cold cranking amperes required by the cold starting performance requirements of 3.3.7.

3.4.5.4 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. When specified (see 6.2), for vehicles operating in critical communications areas, electromagnetic radiation shall be suppressed in accordance with the requirements of MIL-STD-461 for class IIIC equipment.

* 3.4.6 Frame. The frame shall be constructed of tubular, box or channel sections, using integral welded or riveted construction.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.4.6.1 Bumpers. Except for styles E and G, the manufacturer's standard rear bumper shall be furnished. When specified (see 6.2), for model 2 and model 3 vehicles, the manufacturer's standard or optional front bumper shall be furnished and attached to the frame.

3.4.7 Suspension. The suspension system shall include springs or rubber shear mounts and shock absorber(s) on the front wheel(s) and multiple leaf springs and shock absorbers on the rear wheels. Suspension components shall have a rated capacity at least equal to the load imposed on each member, measured at the ground, with the scooter loaded with its total rated payload (see table II).

3.4.8 Steering. The steering control shall be of the automotive steering wheel type. The steering column shall be mounted in ball, roller, or needle bearings.

3.4.9 Wheels, rims, tires, and tubes. The scooter shall be equipped with single wheels. Rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished.

3.4.9.1 Tires. Tires shall be pneumatic, tube or tubeless type with highway tread. Tires shall have a rated capacity at least equal to the load imposed on each tire, measured at the ground, with the scooter loaded with its total rated payload (see table II). Tire size on style G scooters shall be not less than 18 x 9.50-8 on the rear and 8.00-6 on the front.

3.4.9.2 Spare tire mounting bracket. When specified (see 6.2), for all scooter styles except style G, a spare tire mounting bracket shall be attached to the scooter.

3.4.9.3 Spare wheel assembly. When specified (see 6.2), a spare wheel with mounted tire shall be installed on the spare tire mounting bracket. Wheel, rim and tire size, and ply rating shall be the same as those on the vehicle.

* 3.4.10 Service brakes. Service brakes shall be of the hydraulic type. Except for style G, each wheel shall be equipped with brakes. Brake construction for model 1 scooters shall conform to Federal Motor Vehicle Safety Standard No. 122. Brake housings shall be protected from entry of sand, dirt, and water. Brake construction for model 2 and model 3 scooters shall be the manufacturer's standard for the scooter furnished. Brake linings shall be of nonasbestos material.

3.4.10.1 Parking brakes. A hand-operated or a foot operated with a hand release mechanical parking brake conforming to 3.3.6 shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.4.11 Cab. An enclosed cab, integral with the body, shall be provided on class I scooters. An enclosed cab, separate from the body, shall be furnished on class II scooters. The requirements of 3.4.11.1 through 3.4.11.5 shall apply to both class I and class II scooters. No cab or windshield is required on class III scooters.

* 3.4.11.1 Cab construction. The enclosed cab shall be of rigid construction. A windshield of laminated safety glass and a rear window of laminated or tempered safety glass shall be furnished which will provide an adequate field of vision to the seated driver. Side closures shall be lockable steel or aluminum doors on class I and class II scooters, except when specified (see 6.2), weatherproof cloth doors shall be provided on class II scooters. Steel or aluminum doors shall have windows of laminated or tempered safety glass and cloth doors shall have soft clear plastic windows.

3.4.11.2 Windshield wiper. The manufacturer's standard or optional electric windshield wiper shall be furnished on class I and class II scooters.

3.4.11.3 Heater and defroster. Unless otherwise specified (see 6.2), the manufacturer's standard or optional hot air heating and defrosting system shall be furnished on all class I and class II scooters except style G.

3.4.11.4 Cab area seating. Model 1 and model 3 scooters shall have a single or two place seat provided with a backrest, hip restraint, and vinyl clad padded construction. Model 2 scooters shall be furnished with a full width two-place bench seat with similar provisions.

3.4.11.5 Seat belts. Seat belts shall be provided on model 1 scooters. Unless otherwise specified (see 6.2), seat belts shall be provided on model 2 and model 3 scooters.

3.4.12 Instruments.

3.4.12.1 Speedometer. A speedometer with odometer shall be furnished.

3.4.12.2 Engine hour meter. When specified (see 6.2), an engine hour meter having a totalizing mechanism of not less than 9,999 hours shall be furnished to register accurately the number of hours of engine operating time. The meter shall be of rugged construction to ensure continuous trouble-free performance under severe operating conditions. The engine hour meter shall be mounted on the cab instrument panel, or within the normal field of view of the operator.

3.4.12.3 Ammeter. An ammeter or charging indicator shall be furnished.

3.4.12.4 Oil pressure indicator. When available as the manufacturer's standard or optional equipment, an oil pressure gage or indicator shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

3.4.12.5 Fuel gage. A fuel gage shall be provided.

3.4.13 Lighting equipment.

* 3.4.13.1 Headlight(s), tail lights and stoplights. The scooter shall be equipped with sealed beam headlight(s), and a tail light, stoplight, or combination stoplight and tail light. Lamps and reflective devices for model 1 scooters shall conform to Federal Motor Vehicle Safety Standard No. 108. The stoplight(s) shall override the four-way emergency flasher.

3.4.13.2 Turn signals. For model 1 scooters and, when specified (see 6.2), model 2 and model 3 scooters, turn signals shall be furnished. Turn signal lamps shall conform to SAE J588. The turn signal switch shall be mounted on the left side of the steering column and shall conform to class B of SAE J589. Single lens directional signals shall be furnished at the front and rear of the scooter, and a flashing indicator shall be provided.

3.4.14 Accessories.

3.4.14.1 Horn. All scooter styles except style G shall be equipped with the manufacturer's standard horn.

3.4.14.2 Rearview mirrors. Adjustable rearview mirrors shall be provided on the right and left sides of the scooter. The mirrors shall furnish the driver with an adequate view to the rear.

3.5 Vehicle styles.

* 3.5.1 Style A (1,000 pound flatbed, with panel sides and tailgate). Style A scooters shall be equipped with a steel flatbed platform with steel sides and a swingdown tailgate. The interior dimensions of the compartment shall be not less than 43 inches in width, 50 inches in length, and 12 inches in depth. The platform bed may be composed of 2 levels. The bed shall be provided with panels of not less than 16-gage reinforced steel at the front, rear and sides, with the rear section serving as a tailgate.

* 3.5.1.1 Tarpaulin cover. When specified (see 6.2), the manufacturer's standard weatherproof tarpaulin cover (with tiedowns) shall be furnished to cover the complete bed and cargo.

3.5.2 Style B (enclosed lockable package compartment). Style B scooter shall be provided with an enclosed rigid-construction package compartment to the rear of the cab. The covered floor area of the package compartment shall be not less than 1,500 square inches. The box type cover shall be of rigid construction with a hinged opening equipped with a handle and lock. Inside height under the cover, measured from the floor, shall be not less than 18 inches. When the cover size is shorter than the total bed length, a bulkhead shall be provided to close off the lockable compartment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

* 3.5.3 Style C (integral van body). Style C scooter shall be provided with a fully enclosed cab integral with a fully enclosed cargo compartment, all of rigid construction. Side windows shall be provided. A lockable door with window shall be provided at the rear of the scooter. Windshield shall be of laminated safety glass. Side and rear windows shall be of laminated or tempered safety glass. The capacity of the cargo area shall be not less than 60 cubic feet.

3.5.4 Style D (integral van body with seats). Style D scooter shall be identical to the style C integral van body scooter, except that individual, fold-up, padded personnel seats with backrests and hip restraints shall be provided for three passengers in the rear. The rear personnel seats shall be positioned longitudinally and shall face inward. The seating positions shall be staggered to permit adequate leg room. Seat belts shall be provided at each position.

* 3.5.5 Style E (refuse collection). Style E scooter shall be provided with a hydraulically operated refuse hopper to the rear. The hopper shall be of not less than 1.6 cubic yards capacity. The hopper shall be capable of dumping refuse into a receptacle which has an upper edge not less than 43 inches above the ground. Full hydraulic dumping with hydraulic dump cylinder(s) and a hydraulic control valve shall be provided. Power for hydraulic operations shall be provided by an electrically driven hydraulic pump, by engine drive belts or by direct shaft drive from the engine.

3.5.6 Style F (2,000 pound flatbed). Style F scooter shall be provided with a diamond-tread steel flatbed to the rear of the driver's seat. The flatbed shall be not less than 46 inches in width and 70 inches in length. The flatbed shall have a payload capacity of not less than 2,000 pounds.

* 3.5.6.1 Tarpaulin cover. When specified (see 6.2), the manufacturer's standard or optional weatherproof tarpaulin cover (with tiedowns) shall be furnished to cover the complete bed and cargo.

3.5.7 Style G (1,500 pound flatbed, wide tread, with panel sides and tailgate). Style G scooter shall be equipped with a steel flatbed platform with steel sides and swingdown tailgate. The interior dimensions of the compartment shall be not less than 52 inches in width, 46 inches in length, and 12 inches in depth. The platform bed shall consist of a single level.

* 3.5.7.1 Tarpaulin cover. When specified (see 6.2), the manufacturer's standard or optional weatherproof tarpaulin cover (with tiedowns) shall be furnished to cover the complete bed and cargo.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government, the contractor shall service and adjust the vehicle for operational use including at least the following: alinement of light(s); adjustment of the engine, electrical and brake system; filling and charging

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

of the battery; filling of the cooling system for liquid-cooled engines with ethylene glycol type antifreeze and water in equal parts by volume; inflation of all tires; complete lubrication of chassis and engine with the grades of lubricants recommended for the ambient air temperature at the delivery point. When the vehicle is crated for shipment, all liquids shall be drained.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. *QUALITY ASSURANCE PROVISIONS*

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examination and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle. The first vehicle of each style and model covered by the contract and produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

4.3.1 Road test. The first production vehicle shall be examined and road tested with rated payload by the contractor to assure that the vehicle will operate in accordance with contractual requirements. Operational tests shall be conducted to determine conformance of the vehicle to 3.3 through 3.3.7. Conformance to the gradeability requirements of 3.3.2 may be demonstrated on one grade at one speed, in any gear range, with calculations furnished to show performance in the gear range and at the speed and grade specified. Certified engineering calculations shall be furnished. Cold starting verification (3.3.7) shall be by manufacturer's certification.

4.3.2 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.3 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under the contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. Model 1 scooters are intended for nontactical use by the Government in transporting personnel and cargo on local streets and roads and for on-station usage over improved roads. Model 2 and model 3 scooters are intended for nontactical use only within the confines of military installations, over improved roads, with limited and low speed traffic where licensing of vehicles for roadway use would not otherwise be required. The use of model 2 and model 3 scooters on the roads at large military installations with heavy traffic is not intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Body style, model, and class of vehicle required (see 1.2, 1.2.1, and 1.2.2).
* (c) Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
* (d) Identification of appropriate service for painting and marking (see 3.1.1.1 and 3.1.1.2).
(e) Concealed marking, if required (see 3.1.1.2).
(f) Rustproofing, if required (see 3.1.1.3).
* (g) Tropical rustproofing, if required (see 3.1.1.3).
(h) Pintle assembly, if required (see 3.1.1.4).
(i) Trailer lighting receptacle, if required (see 3.1.1.5).
(j) Optional geared speed, if required (see 3.3.1).
(k) Spark arrester, if required (see 3.4.3.1).
(l) An auxiliary transmission for style G, if required (see 3.4.4.3).
(m) Electromagnetic radiation suppression per MIL-STD-461 for class IIIC equipment, if required (see 3.4.5.4).
(n) Front bumper provisions, if required (see 3.4.6.1).
(o) Spare tire mounting bracket, if required (see 3.4.9.2).
(p) Spare tire and rim, if required (see 3.4.9.3).
(q) Cloth doors, if required (see 3.4.11.1).
(r) If heater/defroster is not required (see 3.4.11.3).
(s) If seat belts are not required on models 2 and 3 (see 3.4.11.5).
(t) Engine hour meter, if required (see 3.4.12.2).
(u) Turn signals, if required (see 3.4.13.2).
(v) Tarpaulin cover, if required for styles A, F, or G (see 3.5.1.1, 3.5.6.1, or 3.5.7.1).

6.3 Classification change. This specification covers vehicles previously procured under both MIL-S-45324 (3- or 4-wheel motor scooters) and MIL-T-62275(AT) (4-wheel airfield or facility maintenance cargo trucks). The corresponding types from these specifications are shown in table VI.

TABLE VI. Corresponding types.

Past issue	Current issue		
Type	Style	Model	Class
I	B	1	III
II	B	1	II
III	C	1	I
IV	E	1	II
V	-	-	-
VI	D	2	I
VII	F	2	II
MIL-S-62275	A	2	II

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

* 6.4 Subject term (key word) listing.

Flatbed
Integral van body
Lockable package compartment
On-road
On-station
Refuse collection
Tailgate.

6.5 Identification of changes. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodians:
Army - AT
Navy - YD

Reviewer interest:
Army - AT
Navy - YD

Preparing Activity:
Army - AT

Project No. 2340-0034

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Tank-Automotive Command
ATTN: AMSTA-GDS
Warren, MI 48397-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:43Z
Check the source to verify that this is the current version before use.