MIL-S-45337C
12 June 1985
SUPERSEDING
MIL-S-45337B
13 June 1966

MILITARY SPECIFICATION

SPOTLIGHT: 24 VOLT DIRECT CURRENT

This specification is approved for use by US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers four spotlight assemblies for use on military vehicles.

1.2 Classification. The spotlight assemblies shall be furnished in the following types and classes as specified (see 6.2):

Type I	- Waterproof
Type II	- Splash resistant
Class A	- With mounting bracket
Class B	- Without mounting bracket

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-GSS, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

FSC 6220

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS
FEDERAL

QQ-S-571	- Solder: Tin Alloy, Tin Lead Alloy, and Lead-Tin Alloy; and Lead Alloy.
TT-E-485	- Enamel, Semi-Gloss, Rust-Inhibiting.
TT-E-529	- Enamel, Alkyd, Semi-Gloss.
PPP-B-601	- Box, Wood, Cleated - Plywood.
PPP-B-636	- Box, Shipping, Fiberboard.

MILITARY

MIL-M-14	- Molding Plastics and Molded Plastics Parts, Thermosetting.
MIL-P-116	- Preservation, Methods of.
MIL-P-997	- Plastic-Material, Laminated, Thermosetting, Electrical-Insulating: Sheets, Glass Cloth, Silicone Resin.
MIL-S-8660	- Silicone Compound.
MIL-C-13486	- Cable, Special Purpose Electrical: Low Tension, Heavy-Duty Single-Conductor and Multiconductor.
MIL-A-13881	- Anti-Seize Compound, Mica-Base (for Threaded Fittings).
MIL-F-13927	- Fungus Resistance Test; Automotive Components.
MIL-P-15037	- Plastic Sheet, Laminated Thermosetting, Glass-Cloth Melamine-Resin.

STANDARDS
FEDERAL

FED-STD-595	- Colors.
DOD-STD-1866	- Soldering Process, General Non-Electrical.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-147	- Palletized and Containerized Unit Loads 40 Inch x 48 Inch Pallets, Skids, Runners or Pallet Type Base.
MIL-STD-202	- Test Methods for Electronic and Electrical Component Parts.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing, with Appropriate Test Methods.
MIL-STD-45662	- Calibration System Requirements.
MS 51307	- Spotlight; 24 Volt DC.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

NATIONAL BUREAU OF STANDARDS

Handbook H28	- Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D.C. 20401)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951	- Standard Practice for Commercial Packaging.

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA, 19103.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

...ments to the government. Fold on lines on reverse side, staple in corner, and send to ... ... are invited to submit com...

3. REQUIREMENTS

3.1 First article. Unless otherwise specified (see 6.2), the contractor shall furnish spotlights which shall be subjected to first article inspection (see 4.4). First article inspection samples, properly marked with identifying information shall be representative of the unit to be furnished to the Government. All subsequent spotlights delivered to the Government shall conform to these samples in all of their pertinent physical and performance attributes.

3.2 Materials. Materials shall be as specified herein, on applicable standards or drawings, and in applicable specifications (see 4.6.1).

3.2.1 Use of dissimilar metals. Except where necessary to complete an electrical circuit, contact between dissimilar metals, which would encourage galvanic action, shall be avoided. Where such contact is not necessary to complete an electrical circuit, but is otherwise unavoidable, parts shall be insulated (see 4.6.1).

3.2.2 Metals. Metals shall be of corrosion resistant type or shall be treated to resist corrosion (see 4.6.1).

3.2.3 Nonmetals. For external parts of sealed components and all parts of unsealed components insulating and sealing compound shall conform to MIL-S-8660 (see 4.6.1).

3.2.4 Plastic material. Plastic material shall conform to MIL-M-14 for molded material and MIL-P-997 or MIL-P-15037 for laminated material (see 4.6.1).

3.2.5 Solder. Solder employed in making electrical connections shall be a rosin core type conforming to compositions SN50, SN60, SN70 of QQ-S-571 (see 4.6.1).

3.3 Design and construction. The spotlight and its mounting brackets shall be constructed to the requirements, form, and dimensions of the part numbers shown on MS 51307 in accordance with table I (see 4.5.2 and 4.6.2).

TABLE I. Part number application.

Type	Class	
	A	B
I	MS 51307-1	MS 51307-3
II	MS 51307-2	MS 51307-4

3.3.1 Standard parts. Military standard parts shall be incorporated wherever possible. Commercial standard parts may be used provided they are functionally and mechanically interchangeable with military standard parts without modification (see 4.6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

3.3.1.1 Soldering. Soldering shall meet the requirements of DOD-STD-1866 (see 4.6.1).

3.3.2 Threaded parts. All screw threads shall conform to Handbook H28 (see 2.2). The form, number per inch, and class of threads shall be as specified on applicable standards or drawings. All threads, except electrical conducting parts and self locking nuts, shall be coated with anti-seize compound conforming to MIL-A-13881 (see 4.6.1).

3.3.3 Locking devices. Lockwashers, self locking nuts, or other approved locking devices shall be incorporated where specified or where required to prevent loosening of components (see 4.6.3).

3.3.4 Polarity. The spotlight shall operate in a circuit having either the negative or positive battery terminal ground (see 4.6.3).

3.3.5 Housing. The spotlight housing shall be of sufficient size and mechanical strength to withstand handling, transit, storage, and installation without causing malfunction or distortion of parts (see 4.6.3).

3.3.6 Connectors. The spotlight shall be provided with electrical connectors of the type and style specified on MS 51307 (see 4.6.3).

3.3.7 Switch. The spotlight shall be provided with an "ON-OFF" switch placed in a position where it can be operated without requiring the operator to remove his fingers from the handle (see 4.6.3).

3.3.8 Cable. All cable shall conform to MIL-C-13486 (see 4.6.3).

3.3.9 Mounting bracket. Class A spotlights shall be furnished with the mounting bracket specified in MS 51307 (see 4.6.3).

3.4 Performance characteristics.

3.4.1 Beam pattern. When tested as specified in 4.6.4, the spotlight shall produce a beam with a minimum intensity of 70 000 candle power at 60 feet, measured on the lamp axis.

3.4.2 Spotlight head rotation. When operated as specified in 4.6.5, the minimum horizontal spotlight head rotation shall be 160 degrees (°) left of the center of rotation.

3.4.3 Beam alinement. When tested as specified in 4.6.6, the backlash between the handle and the spotlight head shall cause no more than plus or minus 2 1/2 angular degrees movement of the spotlight head.

3.4.4 Endurance. After testing as specified in 4.6.7, the spotlight shall evidence no damage or malfunction and shall subsequently meet the requirements of 3.4.2 and 3.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

The following military specification and specification sheets of

3.5 Environmental requirements.

3.5.1 Vibration resistance. When tested as specified in 4.6.8, there shall be no mechanical or electrical malfunction and the spotlight shall subsequently meet the requirements of 3.4.2 and 3.4.3.

3.5.2 Shock resistance. When tested as specified in 4.6.9, there shall be no mechanical or electrical malfunction and the spotlight shall subsequently meet the requirements of 3.4.2 and 3.4.3.

3.5.3 Corrosion resistance. When tested as specified in 4.6.10, the spotlight shall evidence no corrosion that will affect operation and shall subsequently meet the requirements of 3.4.2 and 3.4.3.

3.5.4 Waterproofness.

3.5.4.1 Type I. When tested as specified in 4.6.10.1, type I spotlights shall evidence no leakage and shall subsequently meet the requirements of 3.4.2 and 3.4.3.

3.5.4.2 Type II. When tested as specified in 4.6.10.2, type II spotlights shall drain and shall subsequently meet the requirements of 3.4.1, 3.4.2 and 3.4.3.

3.5.5 Fungus resistance. When tested as specified in 4.6.11, the spotlight shall evidence no fungus growth that will affect operation and shall subsequently meet the requirements of 3.4.2 and 3.4.3.

3.5.6 Dust resistance. When tested as specified in 4.6.12, the spotlight shall evidence no damage that will affect operation and shall subsequently meet the requirements of 3.4.2 and 3.4.3.

3.5.7 Low temperature operation. When tested as specified in 4.6.13.1, the spotlight shall conform to the requirements of 3.4.2. There shall be no evidence of any noticeable damage.

3.5.8 High temperature operation. When tested as specified in 4.6.13.2, the spotlight shall conform to the requirements of 3.4.2. There shall be no evidence of any noticeable damage.

3.6 Painting. Unless otherwise specified by the procuring activity (see 6.2), the exterior surfaces of the spotlight housing and cover shall be painted with an olive drab semigloss enamel conforming to TT-E-485 or TT-E-529. Color shall conform to color X 24087 of FED-STD-595 (see 4.5.2, 4.6.1, and 4.6.2).

3.7 Marking. The spotlight shall be marked in accordance with MIL-STD-130 and as specified on MS 51307. Marking shall include the following minimum information, in the order shown (see 4.5.2 and 4.6.2):

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

24 Volt
US
Federal stock number
Military stock number
Manufacturer identification

3.8 Installation. Each spotlight shall be furnished with complete instructions covering its installation (see 4.5.2 and 4.6.2).

3.9 Workmanship. Workmanship shall be of a quality which will assure a product free of burrs, scratches, rust, chips, sharp edges, loose or defective connectors, cracked insulation, faulty soldering or other defects which will affect serviceability or appearance. Lenses shall be free from all visable defects, such as scratches, paint, bubbles and dirt (see 4.5.2 and 4.6.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform or witness any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection equipment. Unless otherwise specified in the contract (see 6.2), the supplier is responsible for the provision and maintenance of all inspection equipment necessary to assure that supplies and services conform to contract requirements. Commercial, modified commercial, or supplier designed inspection equipment or measuring set-ups must be capable of repetitive measurements to an accuracy of 10 percent of the measurement tolerance. Calibration of inspection equipment shall be in accordance with MIL-STD-45662.

4.2 Classification of inspection:

a. First article inspection (see 4.4).
b. Quality conformance inspections (see 4.5).
    1. Examination (see 4.5.2).
    2. Acceptance tests (see 4.5.3).
    3. Control tests (see 4.5.3.2).

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be conducted under the following conditions:

a. Air temperature 23 ± 10 degrees Celsius (°C)
b. Barometric pressure 725 + 50 millimeter (mm) mercury (Hg)
    - 75
c. Relative humidity 50 ± 30 percent

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

4.4 First article inspection. Unless otherwise specified, the Government shall select three spotlight assemblies produced under the production contract (see 6.2) for first article inspection. First article samples shall be inspected as specified in table II. Approval of the first article sample by the Government shall not relieve the contractor of his obligation to supply spotlight assemblies that are fully representative of those inspected as a first article sample. Any changes or deviation of the production units from the first article sample shall be subject to the approval of the contracting officer.

4.4.1 First article inspection failure. Test item deficiencies during, or as a result of, the first article test, shall be cause for rejection of the items until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiency. Any deficiency found during, or as a result of the first article test, shall be prima facie evidence that all items already produced prior to completion of the first article test are similarly deficient unless evidence satisfactory to the contracting officer is furnished by the contractor that they are not similarly deficient. Such deficiencies on all items shall be corrected by the contractor at no cost to the Government. The Government shall not final accept products until first article testing is completed to the satisfaction of the Government.

TABLE II. Classification of inspections.

Title	Requirement	Inspection	First article	Quality conformance		
				Examination	Acceptance (100%)	Control
Materials and construction	3.2 thru 3.2.5 and 3.3.1 thru 3.3.2, 3.3.8 and 3.6	4.6.1	X		X	
Defects (see table III)	3.3, 3.6, 3.7 and 3.9	4.6.2	X	X	X	
Features	3.3 - 3.3.9	4.6.3	X			X
Beam pattern	3.4.1	4.6.4	X		X	
Spotlight head rotation	3.4.2	4.6.5	X		X	
Beam alinement	3.4.3	4.6.6	X		X	
Endurance	3.4.4	4.6.7	X			X
Vibration resistance	3.5.1	4.6.8	X			X
Shock resistance	3.5.2	4.6.9	X			X
Corrosion resistance	3.5.3	4.6.10	X			X
Type I	3.5.4.1	4.6.10.1	X			X
Type II	3.5.4.2	4.6.10.2	X			X
Fungus resistance	3.5.5	4.6.11	X			X
Dust resistance	3.5.6	4.6.12	X			X
Low temperature	3.5.7	4.6.13.1	X			X
High temperature	3.5.8	4.6.13.2	X			X

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:45Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection.

4.5.1 Sampling.

4.5.1.1 Lot formation. An inspection lot shall consist of all the spotlight assemblies of one type and part number, from an identifiable production period, from one manufacturer, submitted at one time for acceptance.

4.5.1.2 Sampling for examination. Samples for quality conformance examination shall be selected in accordance with general inspection level II of MIL-STD-105.

4.5.1.3 Sampling for control tests. Samples for control tests shall be selected in accordance with general inspection level II of MIL-STD-105.

4.5.2 Quality conformance examinations.

4.5.2.1 Acceptable quality level. Each sample selected in accordance with 4.5.1.2 shall be examined to determine conformance to the following acceptable quality levels (AQL) on the basis of percent defective.

Classification	AQL
Major	1.0
Minor	2.5

4.5.2.2 Classification of defects. For examination purposes, defects shall be classified as listed in table III.

TABLE III. Classification of defects.

Category	Defect	Method of examination
Critical	None	
Major	AQL 1.0% Defective	
101	Dimensions affecting interchangeability not within tolerance (see 3.3).	SIE 1/
102	Improper marking (see 3.7).	Visual
103	Faulty workmanship affecting function (see 3.9).	Visual
Minor	AQL 2.5% Defective	
201	Dimensions not affecting interchangeability not within tolerance (see 3.3).	SIE 1/
202	Faulty workmanship affecting appearance (see 3.9).	Visual
203	Unsatisfactory or damaged paint (see 3.6).	Visual
204	Installation instructions inadequate or missing (see 3.8).	Visual

1/ SIE = Standard Inspection Equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

4.5.3 Quality conformance tests.

4.5.3.1 Acceptance tests (100 percent). Each spotlight assembly shall be subjected to the acceptance tests specified in table II.

4.5.3.2 Control tests. Samples selected in accordance with 4.5.1.3 shall be subjected to the control tests specified in table II.

4.5.3.3 Failure. Failure of any spotlight assembly to pass any of the specified tests shall be cause for the Government to refuse acceptance of the production quantity represented, until action taken by the contractor to correct defects and prevent recurrence has been approved by the Government.

4.6 Methods of inspection.

4.6.1 Materials and construction. To determine conformance to 3.2 through 3.2.5, 3.3.1 through 3.3.2, 3.3.8 and 3.6, inspection and material certification records shall be maintained by the contractor. Records shall be subject to review by the Government and shall include date, part, or characteristic identification, inspection results, and disposition of lot (accepted or rejected). Corrective action taken on noted defects shall be subject to approval by the Government.

4.6.2 Defects. Conformance to 3.3, 3.6, 3.7 and 3.9 shall be determined by examination for the defects listed in table III. Examination shall be visual, tactile, or by measurement with standard inspection equipment.

4.6.3 Features. Conformance to 3.3 through 3.3.9, shall be determined by exercising the spotlight and by qualitative observation sufficient to demonstrate that specified characteristics and features are present and functional.

4.6.4 Beam pattern. To determine conformance, the spotlight shall be mounted in an operating position in a darkened room, connected to a 28 volt (V) direct current (dc) power source, and the switch turned to the "on" position. The beam produced shall then conform to the requirements specified in 3.4.1.

4.6.5 Spotlight head rotation. When operated by means of the handle provided, the minimum horizontal spotlight head rotation shall be as specified in 3.4.2.

4.6.6 Beam alinement. To determine conformance to 3.4.3, the spotlight shall be operated as specified and the beam aligned by means of the handle on a spot 25 feet from the light source. The handle position shall be fixed mechanically, the spotlight head moved by hand, and the degree of backlash thereby determined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

4.6.7 Endurance. To determine conformance to 3.4.4, the spotlight shall be subjected to 1000 cycles of operation at rated voltage. One cycle shall consist of turning the switch to the "on" position, rotating the handle to the full right position, rotating the handle to the full left position, returning to the center of rotation, and turning the switch to the "off" position. The 1000 sycles of operation shall be conducted at an ambient air temperature of 77 ± 15 degrees Fahrenheit (°F).

4.6.8 Vibration resistance test. After mounting to simulate actual mounting in use, the spotlight shall be subjected to the vibration resistance tests specified in method 201 of MIL-STD-202 for 1 hour in each direction of the three major axes of the spotlight. Filament breakage in lamp shall not constitute failure. After the test, the spotlight shall be examined to determine conformance to 3.5.1.

4.6.9 Shock resistance. The spotlight, with the lamp removed, shall be mounted to simulate actual mounting in use and subjected to the shock resistance test specified in method 205, test condition B, of MIL-STD-202. Shocks shall be applied twice in each direction of the three major axes. After the test, the lamp shall be replaced and the spotlight shall be examined to determine conformance to 3.5.2.

4.6.10 Corrosion resistance. The spotlight shall be subjected to the salt spray test specified in method 101 of MIL-STD-202, except that the duration of the test shall be 200 hours. After the test, the spotlight shall be examined to determine conformance to 3.5.3.

4.6.11 Water proofness.

4.6.11.1 Type I. To determine conformance to 3.5.4.1, type I spotlight shall be submerged in a salt water solution containing 5 percent Sodium Chloride by weight at an ambient temperature of 77 ± 15°F and subjected to 6 pounds per square inch (psi) internal pressure for 30 minutes and subsequently to 6 psi internal vacuum for 30 minutes. Bubbles which are the result of entrapped air on the various exterior parts of the spotlight shall not be considered leakage after the test.

4.6.11.2 Type II. To determine conformance to 3.5.4.2, type II spotlights shall be mounted as specified with all drain holes open and shall be subjected to a precipitation of 0.1 inch of water per minute, delivered at an angle of 45° from the horizontal from a nozzle with a solid cone spray for a period of 12 hours after the test.

4.6.12 Fungus resistance. The spotlight shall be subjected to the class 2, method B, fungus resistance test of MIL-F-13927. Specimens shall be incubated for continuous 90 days. After the test, the spotlight shall be examined to determine conformance to 3.5.5.

4.6.13 Dust resistance. To determine conformance to 3.5.6, the spotlight shall be subjected to procedure I, method 510.2, sand and dust resistance test of MIL-STD-810, except that the test shall be conducted at an ambient air temperature of 77 ± 15°F only and the test period shall be 24 hours. The spotlight shall be mounted in the dust chamber as in intended use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

4.6.14 Extreme temperature.

4.6.14.1 Low temperature. To determine conformance to 3.5.7.1, the spotlight shall be subjected to a temperature of minus 65 ± 5°F for 24 hours. The spotlight shall then be energized for a period of 3 to 5 minutes after which it shall be subject to the test specified in 4.6.4.

4.6.14.2 High temperature. To determine conformance to 3.5.8, the spotlight shall be subjected to a temperature of plus 160 ± 5°F for 24 hours. The spotlight shall then be energized for a period of 3 to 5 minutes, after which it shall be subjected to the test specified in 4.6.4.

5. PREPARATION FOR DELIVERY

5.1 Preservation. Preservation shall be Level A or commercial as specified (see 6.2).

5.1.1 Level A. Unless otherwise specified (see 6.2), each spotlight shall be preserved in accordance with the methods of MIL-P-116 designated herein insuring compliance with the applicable requirements of that specification.

5.1.1.1 Type I. Type I spotlights shall be preserved in accordance with MIL-P-116, method III, in container conforming to PPP-B-636, class domestic, and closure shall be in accordance with the closure requirements of the box specification.

5.1.1.2 Type II. Type II spotlights shall be preserved in accordance with MIL-P-116, method IC-1, in containers conforming to PPP-B-636, class domestic, and closure shall be in accordance with the closure requirement.

5.1.2 Commercial. The commercial preservation of spotlights shall be in accordance with ASTM D 3951.

5.2 Packing. Packing shall be Level A, B or commercial.

5.2.1 Level A. The spotlights shall be packed in a shipping container conforming to PPP-B-601, overseas type. Blocking, bracing, cushioning and anchoring shall conform to the requirements of MIL-STD-1186. The container shall be closed and strapped in accordance with the appendix of the box specification.

5.2.2 Level B. The spotlights shall be packed in a shipping container conforming to PPP-B-636, class weather-resistant, variety DW, grades V11c, V13c or V15c, style optional. The container shall be closed in accordance with the closure requirements of the box specification.

5.2.3 Commercial. The preserved spotlights shall be packed in accordance with the requirements of ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

5.3 Palletization. When specified (see 6.2), unitized loads, commensurate with the level of packing specified in the contract or order, shall be palletized in accordance with MIL-STD-147. Palletized loads shall be uniform in size and quantities to the greatest extent possible. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order (see 6.2), each unit pack, intermediate and exterior container and unitized load shall be marked in accordance with the requirements of MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The spotlight assemblies covered by this specification are intended for use on military vehicles using 24 volt lamps.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type and class to be furnished (see 1.2).
c. If first article samples are not required (see 3.1).
d. Applicable military standard drawing and date, and part number (see 3.3 and 3.6).
e. If responsibility for inspection shall be other than as specified (see 4.1).
f. If responsibility for inspection equipment shall be other than as specified (see 4.1.1).
g. If inspection conditions shall be other than as specified (see 4.3).
h. If first article inspection is not required (see 4.4).
i. Required levels of preservation and packing (see 5.1 and 5.2).
j. If palletization is required (see 5.3).

6.3 Recycled materials. The use of recycled materials which meet the requirements of the applicable material specifications without jeopardizing the intended use of the item shall be encouraged (see 3.2).

Custodian:
Army - AT
Navy - MC
Air Force - 99

Review activity:
Air Force - 82

Preparing activity:
Army - AT

(Project No. 6220-0323)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

NAVAL SHIP ENGINEERING CENTER

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:45Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commanding Officer
US Army Tank-Automotive Command
ATTN: AMSTA-GSS
Warren, MI 48397-5000

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:45Z
Check the source to verify that this is the current version before use.