
REVIEW INTEREST: DCSC, 69
USER INTEREST: YD, ATAC

FED. SUP CLASS
2805




SIDES OF RING GROOVES MUST RUN TRUE WITH PISTON PIN BORE WITHIN .002 T.I.R.


RING LANDS MAY LOCALLY SHOW EFFECT OF CAM GRINDING SKIRT.

PISTON SKIRT IS GR
.0015 - .0025 I
MAX. DIA. A

CANCELED AFTER 1 APRIL 1982
NO SUPERSEDING STANDARD.

JIGGING BOSSES OR NOTCHES PERMISSIBLE AS QUALIFIED.





3/32 REINFORCEMENT TO OVERLAP CAST RELIEF AND TAPER PARALLEL WITH INSIDE OF SKIRT

WT. OF FIN. PISTON 1937 ± 4 GRAMS.

APPROVED [illegible] REVISED (A) 15 DEC 1965 (B) 1 APRIL 1982

This Military Standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

(A) ENTIRE STANDARD REVISED

P.A. MO (ERDL) Other Cust A.F. - 69 NAVY - YD	TITLE PISTON, INTERNAL COMBUSTION ENGINE: 4-5/8" x 5-15/16"	PART NO. MS 13885-1 MILITARY STANDARD MS 13885
PROCUREMENT SPECIFICATION MIL-E-11275	SUPERSEDES:	SHEET 1 OF 5

DD FORM SEP 67 672-1 (Coordinated)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:30Z
Check the source to verify that this is the current version before use.