FSC: N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

USER ACTIVITIES: ARMY - MD, OM
NAVY - MS

REVIEWER ACTIVITIES: ARMY - ME
NAVY - OS
AIR FORCE - 03


FED. SUP CLASS
6640



MS36510-1



MS36510-2
MS36510-3



MS36510-4
MS36510-5

PART NUMBER	RPM RANGE	DIMENSIONS LENGTH	DIA.
MS36510-1	200-300		16
MS36510-2	2		
MS36510-3			
MS			

CANCELLED

CANCELLED AFTER 29 AUG 1990

NO SUPERSEDING STANDARD

MATERIAL: ...may be stain- ...ave a vinyl mat

DESIGN: Th... ...ate or rheostat speed controls and spa... ...operate on 120 V/60Hz. The electrical wir... ...the requirements of the Underwriters Laboratory, Code ... ...e rpm range as cited in the table is taken in water at am... ...erature.

MS36510-3 shall be the same as -2 except it shall have a heating element that will operate from slightly above ambient to 510°C.

MS36510-4 shall have 6 motors coupled together to give synchronous speeds for mixing up to 6-1000 mL beakers.

MS36510-5 shall be the same as -4 except it shall have a heating element that will operate from slightly above ambient to 371°C.

NOTES: 1. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.

Ⓐ CANCELLATION

APPROVED 30 APR 1982 REVISED Ⓐ 29 AUG 1990

P.A. EA	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust MS 99		STIRRER, MAGNETIC, LABORATORY	MS36510
Procurement Specifications NONE	SUPERSEDES:		SHEET 1 OF 1

DD FORM 1 MAY 73 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Project Number 6640-1843-02

CANCELLATION DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:42Z
Check the source to verify that this is the current version before use.