FED. SUP CLASS
5305



(B)

	NOMINAL SIZE	.086	.112	.138	.164	.190	.250	.3125	.375	.500
	THREADS PER INCH (UNC-3A)	56	40	32	32	24	20	18	16	13
J	SOCKET WIDTH ACROSS FLATS NOM	.035	.050	.062	.078	.094	.125	.156	.188	.250
P	POINT DIAMETER MAX	.057	.075	.092	.109	.127	.156	.203	.250	.344
	MIN	.053	.070	.087	.103	.120	.149	.195	.241	.334
Q	POINT LENGTH MAX	.024	.030	.038	.043	.049	.067	.082	.099	.130
	MIN	.020	.026	.032	.037	.041	.059	.074	.089	.120

L LENGTH	TOL	DASH NUMBER								
.125	±.010	1*	9*	18*						
.188		2*	10*	19*	29*	39*				
.250		3*	11*	20*	30*	40*	49*	61*		
.312			12*	21*	31*	41*	50*	62*	73*	
.375				22*	32*	42*	51*	63*	74*	84*
.500				23*	33*	43*	52*	64*	75*	85*
.625							53*	65*	76*	86*
.750	±.020						54*	66*	77*	87*
1.000							55*	67*	78*	88*

* Indicates manufacturer's non-stock production items.

NOTES:

1. MATERIAL: Corrosion-Resisting Steel, 300 Series, in accordance with procurement specification.
2. PROTECTIVE COATING: Passivated in accordance with QQ-P-35.
3. THREADS: The threads shall be in accordance with MIL-S-7742.
4. MAGNETIC PERMEABILITY: These setscrews have a magnetic permeability of 2.0 max (air = 1.0) for a field strength of H = 200 oersteds, when using a magnetic indicator per MIL-I-17214.
5. DIMENSIONS: All dimensions are in inches, unless otherwise specified.
6. PART NUMBER: The MS part number consists of the MS number, plus the dash number. Example: MS51045-1.
7. Referenced documents shall be of the issue in effect on date of invitations for bid.
8. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

INTERCHANGEABILITY

(B) Screws covered by the dash numbers given in MS51046 are cancelled after 6 March 1964 and superseded by the screws covered on MS51045 having the same dash numbers. Cancelled screws may be used until existing stocks are depleted. Use only MS51045 screws for new design.

REVIEWER: AV, IS, MI, ME
USER: AT, CL, MC, ME, OS, SH, YD

APPROVED 7 MAY 1958 REVISED (A) 6 MAR 1964 (B) 29 DEC 1972

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC	TITLE	MILITARY STANDARD
Other Cust 82	SETSCREW - HEXAGON SOCKET, HALF-DOG POINT, CORROSION-RESISTING STEEL, PASSIVATED, UNC-3A	MS 51045
PROCUREMENT SPECIFICATION FF-S-200	SUPERSEDES MS51046	SHEET 1 OF 1

DD FORM 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:56Z
Check the source to verify that this is the current version before use.