JJJ-S-351H
October 20, 1981
SUPERSEDING
Fed. Spec. JJJ-S-351G
July 12, 1974

FEDERAL SPECIFICATION

SYRUP

This specification was approved by the U.S. Department of Agriculture, for use by all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for syrup for use by all Federal agencies.

1.2 Classification. Syrup shall be of the following types (and classes for type VIII only), (see 6.1):

Type I	-	Syrup sugarcane (fancy-sulfured)
Type II	-	Syrup, blended, sugar (sucrose) and refiners'
Type III	-	Syrup, blended, corn and refiners'
Type V	-	Syrup, blended, sugar and maple
Type VI	-	Syrup, blended, corn and sugar syrup (sucrose)
Type VII	-	Syrup, blended, invert and sugar syrup (sucrose)
Type VIII	-	Syrup, imitation maple
Class 1	-	Thin
Class 2	-	Thick

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-C-29	-	Canned Subsistence Items, Packaging and Packing of
PPP-C-460	-	Glass Containers, Filled and Closed, Packaging and Packing of
PPP-I-350	-	Individual Servings of Subsistence; Packaging and Packing of

FSC 8925

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

Federal Standard:

FED-STD-123 - Marking for Domestic Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications, standards, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, New York, Washington, Philadelphia, Atlanta, Chicago, Kansas City, MO, Fort Worth, Houston, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal specifications, standards, and commercial item desciptions, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-L-35078 - Loads, Unit: Preparation of Nonperishable Subsistence Items; General Specification For

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-668 - Sanitary Standards for Food Plants

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

Laws and Regulations:

US Department of Health and Human Services

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder

21 CFR 110 - Current Good Manufacturing Practices in Manufacturing, Processing, Packaging or Holding of Human Food

The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance of thereof.)

US Department of Agriculture

US Standards for Grades of Sugarcane Syrup
US Standards for Grades of Refiners Syrup
US Standards for Grades of Maple Syrup
US Standards for Condition of Food Containers

(Application for copies should be addressed to the Information Division, Agricultural Marketing Service, US Department of Agriculture, Washington, DC 20250.)

US Army Natick Research and Development Laboratories

Food Technology, Vol XI, No. 9 (1957) - "Hedonic Scale Method of Measuring Food Preferences"

Analytical Letters 8(3), 215-224 (1975) - "A Versatile System for Sugar Analysis via Liquid Chromatography"

(Application for copies should be addressed to the US Army Natick Research and Development Laboratories, ATTN: DRDNA-YB, Natick, MA 01760.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Association of Official Analytical Chemists

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington VA 22209.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:45Z
Check the source to verify that this is the currentversion before use.

3. REQUIREMENTS

3.1 Bid sample approval (type VIII only). When specified (see 6.1), representative samples consisting of 3 containers of at least 16 ounces each of the product which the contractor proposes to furnish, shall be submitted to the contracting officer for approval prior to the bid opening, and shall be tested to the extent necessary to properly evaluate the bids. One of the tests shall be for palatability in accordance with 4.5.2. These samples shall serve as the standard reference as concerns palatability, only, for the procured item.

3.2 Material. All of the material shall be clean, sound, wholesome, and free from any foreign odors, flavors, or extraneous matter.

3.2.1 Corn syrup. Corn syrup shall be a purified concentrated solution of nutritive saccharides obtained from starch and having a dextrose equivalent of 40 or more. Corn syrup shall contain at least 70 percent solids.

3.2.1.1 High fructose corn syrup. High fructose corn syrup shall contain at least 41 percent fructose on a dry weight basis when tested as specified in 4.5.1. High fructose corn syrup shall contain at least 70 percent solids.

3.2.2 Flavoring. Flavoring shall be pure vanilla extract or imitation vanilla or a combination thereof. Maple flavor, when used, shall be imitation or pure maple flavor, or any combination thereof.

3.3 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

3.4 Finished product.

3.4.1 Type I, syrup sugarcane (fancy-sulfured). Type I syrup shall be formulated from the juice of the sugarcane or by the solution of sugarcane concentrate without the removal of any of the sugar. The product shall have a Brix solids content of not less than 74 percent or Baume test (Bureau of Standards Baume scale for sugar solution) of not less than 39.5 degrees (modulus 145). Total sugars (sucrose plus reducing sugars) shall constitute at least 88 percent of the solids and sulfated ash shall constitute not more than 4.5 percent of the solids. The product shall contain not more than 100 parts of total sulfites, calculated as total sulfur dioxide per million parts of Brix solids, and shall possess a color no darker than US Color Standard No. 2, as specified in US Standards for Grades of Sugarcane Syrup.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:45Z
Check the source to verify that this is the current version before use.

3.4.2 Type II, syrup, blended sugar (sucrose) and refiners'. Type II syrup shall be formulated from not more than 50 percent (solids basis) of fancy grade refiners' syrup (or its constituents), blended with granulated sugar syrup. The product shall contain a Brix solids content of not less than 70 percent, or Baume test (Bureau of Standards Baume scale for sugar solutions) of not less than 37.6 degrees (Modulus 145), and not more than 1.2 percent of ash. If the refiners' syrup is made from Hawaiian raw sugar, the product shall contain not more than 2.0 percent of ash. Part of the sucrose may be inverted by means of invertase or other suitable inverting agent.

3.4.3 Type III, syrup, blended, corn and refiners'. Type III syrup shall be formulated from not less than 10 nor more than 20 percent (solids basis) of fancy grade refiners' syrup, blended with corn syrup. The product shall contain not less than 72 percent Brix solids or Baume test (Bureau of Standards Baume scale for sugar solutions) of not less than 38.5 degrees (Modulus 145) and not more than 1.0 percent of ash. If the refiners' syrup is made from Hawaiian raw sugar, the product shall contain not more than 1.6 percent of ash.

3.4.4 Type V, syrup, blended, sugar and maple. Type V syrup shall be formulated from not less than 15 percent maple sap syrup or maple sugar syrup of at least 66 percent Brix solids and the balance granulated sugar syrup. The finished product shall contain not less than 66 percent Brix solids or Baume test (Bureau of Standards Baume scale for sugar solutions) of not less than 35.5 degrees (Modulus 145).

3.4.5 Type VI, syrup, blended, corn and sugar syrup (sucrose). Type VI syrup shall be formulated from 85 percent corn syrup (solids basis) and the balance sugar syrup (solids basis). The product shall contain not less than 75 percent Brix solids or Baume test (Bureau of Standards Baume scale for sugar solutions) of not less than 40.0 degree (Modulus 145) and not more than 0.5 percent of ash. The product shall contain no added coloring and shall be made with or without flavoring, vanillin U.S.P. grade, or ethyl vanillin flavoring or any combination of two or more such flavoring ingredients.

3.4.6 Type VII, syrup, blended, invert and sugar syrup (sucrose). Type VII syrup shall be formulated from equal parts of invert sugar and sugar syrup (solids basis). The product shall contain not less than 76 percent Brix solids or Baume test (Bureau of Standards Baume scale for sugar solutions) of not less than 40.5 degrees (Modulus 145) and not more than 0.2 percent ash.

3.4.7 Type VIII, syrup, imitation maple.

3.4.7.1 Class 1, thin. Class 1, thin-type imitation maple syrup shall be a colored and flavored blend conforming to either formula A or B:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

Formula	Proportion by weight	
A	Sucrose 1/ 80 parts	Corn syrup (solids basis) 2/ 20 parts
B	High fructose corn syrup (solids basis) 70 parts	30 parts

1/ Sugar syrup may be substituted on a solids basis for all or part of the sucrose.

2/ Corn syrup with a D.E. between 40 and 52 shall be used.

The finished syrup shall possess a characteristic maple flavor similar to US Grade A table maple syrup and shall be clean, clear, free from fermentation, and free from any objectionable flavor, odor, or sediment. It shall be colored to simulate US Grade A table maple syrup. The color shall not be lighter than light amber or darker than medium amber, as represented by the color standards of the US Department of Agriculture. The finished syrup shall be not less than 70 percent Brix solids or 37.6 degree Baume (Bureau of Standards Baume scale for sugar solutions, Modulus 145).

3.4.7.2 Class 2, thick. Class 2, thick-type imitation maple syrup shall conform to 3.4.7.1, except for formulation and percent Brix solids or degree Baume. Thick type syrup shall conform to either formula A or B.

Formula	Proportion by weight	
A	Sucrose 1/ 20 parts	Corn syrup (solids basis) 80 parts
B	High fructose corn 2/ syrup (solids basis) 20 parts	80 parts

1/ Sugar syrup may be substituted on a solids basis for all or part of the sucrose. Formula A product shall contain not less than 18 percent sucrose, on a moisture free basis.

2/ Formula B shall contain at least 7.0 percent fructose, on a moisture free basis.

The finished syrup shall be not less than 72 percent Brix solids or 38.5 degrees Baume and a maximum of 75 percent Brix solids or 40.0 degrees Baume (Bureau of Standards Baume scale for sugar solutions, Modulus 145).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.4.7.3 Palatability (type VIII only). Delivery samples shall be compared with the approved bid sample (see 4.5.2) (when required) and shall be equal to or better than that sample.

3.4.8 Processing. All syrup formulae specified herein shall be heat processed (pasteurized) according to good commercial practice. Either hot fill or pasteurization in the container is acceptable. If hot fill is used, the can shall be inverted after closure to sanitize the lid. (Note: Heating the syrup to a center temperature of not less than 180°F for five minutes has been found adequate.)

3.5 Workmanship. The product shall be prepared in accordance with Part 110 of the Code of Federal Regulations, Title 21, Current Good Manufacturing Practice in Manufacturing, Processing, Packing, or Holding of Human Food. In addition, for military agencies, the product shall be processed in establishments meeting the requirements of MIL-STD-668.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Plant qualification. The product shall be unacceptable if produced and stored in plants which do not meet the requirements specified in 3.5.

4.3 Bid sample approval (type VIII only). Bid sample shall be tested along with reference standards as prescribed in 4.5.2.1. A minimum of 20 responses shall be obtained for each bid sample. Reference standards shall be served in each bid session and each shall be randomly assigned to an equal number of test subjects. Any bid sample which has a mean rating lower, at the 5 percent level of significance, than that of the reference samples shall be rejected. Approved samples shall be held to serve as reference standards for testing of deliveries as specified in 3.4.7.3.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

4.4.1.1 Ingredient examination. Conformance of ingredients to identity requirements (as applicable) of 3.2 and 3.4 as concerns source, grade, type, or percent solids shall be ascertained by examination of pertinent labels, invoices or other valid documents. In addition, each ingredient shall be examined organoleptically, as necessary, to determine conformance to condition requirements of 3.2. The sample unit shall be approximately 1 pound derived from a primary container or if the primary container yields an insufficient sample, a number of primary containers shall be drawn to provide a sufficient sample. Five sample units shall be examined. In the event a lot consists of less than five containers, a sample unit shall be extracted from each container in the lot. Ingredients which do not conform to the above referenced requirements shall be unacceptable and use of such shall be cause for rejection of the involved product.

4.4.1.2 Testing of corn syrup and maple sap or maple sugar syrup. Testing shall be as shown in table I. A test failure shall indicate an unacceptable ingredient and use of such shall be cause for rejection of the involved finished product. In lieu of testing, labels and invoices may be examined to verify conformance to test requirements of components.

TABLE I. Component tests

Component	Sample unit	Lot size expressed in	Inspection level	Characteristic	Results reported	Test ref and reqmt para
Corn syrup	1 pint composite 1/	Pounds	S-2	Reducing sugars	Nearest percent anhydrous dextrose	3.2.1 and 4.5.1
Maple sap syrup or maple sugar syrup	1 pint composite 1/	Pounds	S-1	Brix solids	Nearest percent	3.4.4 and 4.5.1

1/ The sample unit shall be derived from the number of primary containers indicated by the inspection level.

4.4.2 In-process inspection. Any nonconformance revealed by the in-process examination in 4.4.2.1 and 4.4.2.2, whether by examination of records or by actual inspection shall be cause for rejection of the involved lot of material or the finished product made therefrom, as applicable.

4.4.2.1 In-process examination of formulation. Unless otherwise specified (see 6.1), examination shall be performed for types II, III, V, VI, VII and VIII (classes 1 and 2) products to the extent necessary to determine conformance to formulation requirements. Formulation records shall be maintained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

4.4.2.2 In-process examination of heat processing. Examination shall be made to determine compliance with the requirements of 3.4.8. Time and temperature records shall be maintained.

4.4.3 End item inspection.

4.4.3.1 Net contents examination. The cans or bottles of syrup shall be examined for the net contents defects listed in table II. The lot size shall be expressed in units of cans or bottles. The sample unit shall be one filled and closed can or bottle. The inspection level shall be S-3 and the acceptable quality level (AQL) shall be 2.5 percent defective. In addition, the lot shall be rejected if the average net contents of the sample units examined is less than the specfied net contents.

TABLE II. Net contents defects 1/ 2/

Category	Defect
Minor	
201	Net weight or net volume more than 5 percent under required weight or net volume (container required to have 16 or less avoirdupois or fluid ounces).
202	Net weight or net volume more than 2 percent under required weight or net volume (container required to have more than 16 avoirdupois or fluid ounces).

1/ For volume determination, condition product to 65-75°F. Devices for determining weight or volume shall be calibrated in no larger than 1/10 ounce increments.

2/ Not applicable to individual servings which shall be covered by applicable table of examination of PPP-I-350.

4.4.3.2 Product examination. The syrup shall be examined for the defects listed in table III. The lot size shall be expressed in units of filled and closed cans, bottles, or ten individual serving containers. The sample unit shall be one can, one bottle, or ten individual serving containers. The inspection level shall be S-3 and the AQL shall be 1.0 major and 2.5 minor defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

TABLE III. Product defects 1/

Category		Defect
Major	Minor	
101		Sedimentation or suspension of extraneous material in type VIII product. 2/
102		Palatability of type VIII product not equal to or better than bid sample.
103		Objectionable odor or flavor (types I through III and V through VII. Also applicable to type VIII product when bid sample is not specified).
	201	Color of product not as specified (applicable to types I, and VIII). 3/
104		Flavor of type VIII product not as specified (when bid sample is not required).

1/ Presence of foreign material, e.g., paint, splinters, visual mold, pieces of glass or metal, rust, dirt, infestation, or other foreign material shall be cause for rejection of the lot. For product packaged in glass containers, examine neck and lip of container and adjacent contact area with product. If chipped glass is noted, sieve contents of container to determine if glass is present in product.

2/ Transfer sample unit packaged in can or individual serving containers to suitable size glass container prior to visual examination. Finely divided particles of suspended material that do not materially affect appearance or edibility of product shall not be considered a defect.

3/ Interpretation of color and grade requirements shall be in accordance with US Standards for Grades of Sugarcane Syrup, US Standards for Grades of Refiners' Syrup (except ash requirements when Hawaiian raw sugar is used), and US Standards for Grades of Maple Syrup in effect on date of invitation for bids or request for proposal.

4.4.4 End item testing. The finished product shall be tested to determine compliance with the analytical requirements of 3.4 as applicable to the type and class of syrup being procured. Test characteristics and method of reporting results shall be as detailed in table IV. Procedures for tests shall be as referenced in 4.5.1. The sample for testing shall be a quart composite of syrup derived from the number of primary containers indicted by inspection level S-2. Lot size shall be expressed in units of primary containers. Any test failure shall be cause for rejection of the involved lot of finished product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

TABLE IV. Reporting of test results

Type	Test characteristics	Results reported
I	Brix solids or Baume	Nearest percent or Nearest 0.1 degree
	Total sugars (sucrose and reducing)	Nearest percent
	Sulfated ash	Nearest 0.1 percent of Brix solids
	Total sulfites	Nearest ppm as SO_2 of Brix solids
II	Brix solids or Baume	Nearest percent or nearest 0.1 degree
	Ash	Nearest 0.1 percent
III	Brix solids or Baume	Nearest percent or Nearest 0.1 degree
	Ash	Nearest 0.1 percent
V	Brix solids or Baume	Nearest percent or Nearest 0.1 degree
VI	Brix solids or Baume	Nearest percent or Nearest 0.1 degree
	Ash	Nearest 0.1 percent
VII	Brix solids or Baume	Nearest percent or Nearest 0.1 degree
	Ash	Nearest 0.1 percent
VIII	Brix solids or Baume	Nearest percent or Nearest 0.1 degree
	Sucrose	Nearest percent
	Fructose	Nearest percent

4.4.5 Packaging inspection.

4.4.5.1 Packaging of cans inspection. Inspection of the preservation, packing, and labeling of cans shall be in accordance with the quality assurance provisions of PPP-C-29.

4.4.5.2 Packaging of glass bottles inspection. Inspection of the preservation, packing, and labeling of glass bottles shall be in accordance with the quality assurance provisions of PPP-G-460.

4.4.5.3 Packaging of individual servings inspection. Inspection of the preservation, packing, and labeling of individual servings shall be in accordance with the quality assurance provisions of PPP-I-350.

4.4.5.4 Unit load examination. Examination of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Chemical analysis. Unless otherwise specified, chemical analyses, if required by the purchaser, shall be made in accordance with the issue of Official Methods of Analysis of the Association of Official Analytical Chemists in effect on the date of the invitation for bids or request for proposal or in accordance with methods that give equivalent results.

Test	Source	Method
Soluble Solids by Refractometer	Chapter: Sugars and Sugar Products Section: Solids	By means of Refractometer Official
Reducing sugars as dextrose	Chapter: Sugars and Sugar Products Section: Sugars, Syrups, and Molasses	Lane-Eynon General Volumetric
Sulfated Ash	Chapter: Sugars and Sugar Products Section: Sugars, Syrups, and Molasses	Sulfated Ash, Official
Ash	Chapter: Sugars and Sugar Products Section: Sugars, Syrups, and Molasses	Ash, Official
Sucrose	Chapter: Sugars and Sugar Products Section: Sugars, Syrups and Molasses	Sucrose Chemical Method
Total sulfites	Chapter: Preservatives and Artificial Sweeteners Section: Sulfurous Acid	Monier-Williams Method, Official
Fructose	Analytical Letters 8(3), 215-224 (1975) (See 2.1)	Sugar Analysis via Liquid Chromatography

4.5.2 Palatability test (type VIII only). Tests for palatability, as required, shall be performed in accordance with 4.5.2.1 and 4.5.2.2 for the establishment of reference standards; and when specified (see 6.1), 4.3 for bid sample approval.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

4.5.2.1 Procedure. Approximately 1-ounce portions shall be served at a temperature of 95 to 105°F in coded glasses to a consumer type panel. The panel members shall rate each sample on a 9 point hedonic scale* graduated in successive degrees of like and dislike. The samples shall be presented successively with a minimum interval of 45 seconds between samples, in controlled orders, so that each sample is served an equal number of times in each temporal position. Each subject shall rate from two to six samples at a test session but all subjects shall rate the same number of samples in a given session. The subjects shall test without interference from each other or from outsiders.

*For further details see "Hedonic Scale Method of Measuring Food Preferences," reprinted from Food Technology, 1957, Vol. XI, No. 9, supplement pages 9-14.

1	2	3	4	5	6	7	8	9
Dislike extremely	Dislike very much	Dislike moderately	Dislike slightly	Neither like nor dislike	Like slightly	Like moderately	Like very much	Like extremely

4.5.2.2 Selection of reference standards. Samples complying with the requirements of this specification will be tested at the same sessions by a consumer panel yielding not less than 40 ratings per sample. Tests will be conducted according to 4.5.2.1. Samples which are acceptable and can be used for reference standards shall be those that are not different from the highest ranking sample at the 5 percent level of significance. Reference samples shall be stored in closed containers and held at a temperature of approxmately 40°F. The reference standards for any given test session shall be selected randomly from among the available reference standards.

5. PACKAGING

5.1 Preservation. The product shall be unit packed in accordance with 5.1.1, 5.1.2 or 5.1.3 as specified (see 6.1). Net weight or net volume shall be as specified (see 6.1). The following minus tolerances from net weight or volume will be allowed in any one container, provided the average net weight or volume of the container inspected in table II is not less than the net weight or volume specified: 5 percent for containers required to have a net weight of 1-pound or less; 2 percent for containers required to have a net weight of more than 1-pound.

5.1.1 Cans, level A and C. The product shall be unit packed in cans in accordance with the level A or C requirements of PPP-C-29, as specified (see 6.1).

5.1.2 Glass bottles, level C. One pint, 1 quart, 24 fluid ounces or 36 fluid ounces of the product shall be unit packed in a glass bottle to afford adequate protection against deterioration during shipment from the supply source to the first receiving activity. The contractor may use his standard practice when it meets these requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:45Z
Check the source to verify that this is the current version before use.

5.1.3 Individual servings, level B or C. The product shall be unit packed in accordance with level B or C requirements of PPP-I-350, as specified (see 6.1) for imitation maple syrup.

5.2 Packing. The product shall be packed in accordance with 5.2.1, 5.2.2 or 5.2.3, as applicable.

5.2.1 Cans, level A, B, or C. The product in cans shall be packed in accordance with the level A, B, or C requirement of PPP-C-29, as specified (see 6.1).

5.2.2 Glass bottles, level B or C. The product in glass bottles shall be packed in accordance with level B or C requirements of PPP-G-460, as specified (see 6.1).

5.2.3 Individual servings, level B or C. Individual servings shall be packed in accordance with level B or C requirements of PPP-I-350, as specified (see 6.1) for imitation maple syrup.

5.3 Unit loads. When specified (see 6.1), syrup packed as specified in 5.2 shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified.

5.4 Labeling and marking.

5.4.1 Cans. Cans shall be labeled in accordance with PPP-C-29.

5.4.2 Glass containers and individual servings. Any labeling complying with the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder shall be acceptable.

5.4.3 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129 or FED-STD-123, as applicable.

5.4.4 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

~~(a) Title, number, and date of this specification.~~

(b) Type required and class if type VIII is specified (see 1.2).
(c) If bid samples (type VIII only) are required (see 3.1).
(d) When formulation examination is not required by civil agencies (see 4.4.2.1).
(e) When palatability tests are to be performed for bid samples (see 4.5.2).
(f) Method of preservation to be used and net weight or volume required (see 5.1).
(g) Preservation and packing levels (see 5.1 and 5.2).
(h) Type and class of unit load when unit loading is specified (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

6.2 Destination inspection (civil agencies). When the finished product has been inspected and passed at point other than destination, the contract should require that the product be inspected at destination for condition and quantity only.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 50

Review Activities

Army - MD
Navy - MC, MS
DLA - SS

CIVIL AGENCY COORDINATING ACTIVITIES:

HHS-HSM
USDA-FQA
VA-OSS

PREPARING ACTIVITY:

Army - GL

Project No. 8925-0121

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.