JJJ-V-002169A(Army-GL)
August 8, 1985
SUPERSEDING
JJJ-V-002169(Army-GL)
24 June, 1983

INTERIM FEDERAL SPECIFICATION

POTATOES, DICED IN BUTTER SAUCE, THERMOSTABILIZED, TRAY PACK

This interim Federal specification was developed by U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers potatoes in butter sauce, thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

TT-C-495	- Coatings, Exterior, for Tinned Food Cans
PPP-B-636	- Boxes, Shipping, Fiberboard

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal standard-ization documents, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Nonperishable Subsistence Items; General Specifications for

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermo-stabilized Foods for the Armed Forces

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

U.S. Department of Health and Human Services

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Applications for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Department of Agriculture (USDA)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

Regulations Governing Inspection and Certification of Processed Fruits and Vegetables, Processed Products Thereof, and Certain Other Processed Food Products

(Applications for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, D.C. 20250.)

U.S. Standards for Grades of Butter

(Applications for copies should be addressed to the Director, Dairy Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Environmental Protection Agency (EPA)

National Interim Primary Drinking Water Regulations

(Applications for copies should be addressed to the Office of Drinking Water WH 550, Environmental Protection Agency, Washington, DC 20406.)

2.2 Other publications. The following documents, form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Academy of Sciences

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

Association of Official Analytical Chemists (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Potatoes, fresh. The potatoes shall be fresh, firm and of a white flesh variety suitable for canning. The maximum specific gravity for the potatoes shall be 1.075 with a reducing sugar content of not more than 2.0 percent on a dry weight basis.

3.2.2 Butter, lightly salted. The lightly salted butter shall be U.S. Grade A or better, conforming to the U.S. Standards for Grades of Butter.

3.2.3 Calcium chloride. The calcium chloride shall meet the requirements of the Food Chemicals Codex.

3.2.4 Calcium disodium EDTA. The calcium disodium EDTA ingredient shall meet the requirements of the Food Chemicals Codex.

3.2.5 Salt. The salt shall be non-iodized, white, refined sodium chloride with or without anti-caking agents.

3.2.6 Sugar. The sugar shall be white, refined sucrose, granulated cane or beet sugar, or a combination thereof. It shall meet the bacterial requirements of MIL-STD-900.

3.2.7 Starch, waxy maize, modified. The starch shall be white, odorless, finely pulverized modified waxy maize food starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range of 140° to 170°F, and a typical viscosity (be fully hydrated) at common retort temperatures. It shall resist breakdown at low pH, under shear stress and conditions of cold storage. The starch shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.8 Lecithin. Lecithin shall comply with the Food Chemicals Codex.

3.2.9 Sodium bisulfite. Sodium bisulfite shall comply with the Food Chemicals Codex.

3.2.10 Water. Water used for formulation and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.3 Preparation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.3.1 Preparation of potatoes. The fresh potatoes shall be thoroughly cleaned to remove dark and extraneous material, peeled, trimmed, and thoroughly washed. The washed potatoes shall be mechanically diced with dicer settings at approximately 3/4 by 3/4 by 3/4 inch. The potato dices shall be handled in a manner that will prevent browning and other discoloration. Sodium bisulfite may be used provided that sulfur dioxide concentration in the finished product conforms with 3.6.1. The potato dices shall be blanched in 190° -200°F water for three minutes, cooled immediately in cold water to less than 100°F, and drained. When dehydro-frozen potato dices are used, they shall be fully rehydrated prior to filling into the tray pack cans. Following blanching or rehydration (as applicable), the potatoes shall be handled in a manner to prevent discoloration. The potato dices shall be filled within two hours after blanching (fresh potatoes) or rehydration (dehydro-frozen potatoes).

3.3.2 Sauce. The sauce shall be prepared as follows:

Ingredient	Percent by weight
Water	76.783
Butter	15.000
Starch, waxy maize, modified	5.000
Lecithin	0.250
Sugar	1.500
Salt	1.250
Calcium chloride	0.200
Calcium disodium EDTA	0.017

a. A thin slurry shall be made using the starch and part of the water.

b. The remainder of the ingredients shall be heated to 180° - 190°F.

c. The slurry shall be added and the final mixture heated to 180° - 190°F and held at this temperature range for five minutes.

d. The volume of the final mixture shall be adjusted with water to compensate for evaporation loss during heating and holding.

e. The sauce shall be filled into the tray pack cans within four hours after cooking. The temperature of the prepared sauce shall be held at 150° - 180°F until filling into the tray cans.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product so as to conform to the following requirements:

a. Sufficient weight of diced potatoes shall be placed into each tray pack can to meet the drained weight requirements of 3.6 and the can immediately filled with sauce to not less than 106 ounces of product.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T12:45Z
Check the source to verify that this is the currentversion before use.

b. The temperature of the sauce at time of filling shall be not less than 150°F.

c. The can shall be hermetically sealed (under a vacuum of not less than 10 inches of mercury).

d. The filled and sealed tray pack can shall be in the retort process within one hour of being filled.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting at 240°F or less until a sterilization value (F_o) of not less than 5.6 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material, such as, but not limited to dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor, such as, but not limited to burnt, scorched, stale, sour, rancid, musty, moldy or sulfurous.

c. There shall be no color foreign to the product.

d. The salt content of the finished product shall be not greater than 1.0 percent nor less than 0.5 percent.

e. No individual can shall weigh less than 104 ounces.

f. The average net weight shall be not less than 106 ounces.

g. No individual can shall have a drained weight of potatoes more than 72 ounces or less than 66 ounces.

h. Potatoes shall be firm but not mushy, hard or fibrous.

i. Potatoes shall be distinct dices and have a white to off-white color.

j. The sauce shall be glossy, moderately thick and smooth.

k. The sauce shall be pale off-white to yellow color.

l. The sulfur dioxide level in the finished product shall not exceed 100 ppm when tested in accordance with 4.6.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods, and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this specification.

4.3 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.4 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be evident by examination of pertinent labels, markings, U.S. Grade certificates, certificates of analyses or other such valid documents acceptable to the inspection agency. In addition, prior to use, each ingredient shall be examined organoleptically, as necessary, to determine conformance to the condition requirements. Any nonconformance to an identity, condition or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

4.5 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.6 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.6.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 empty tray pack cans and lids and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 106 ounces or if the net weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.6.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated for at least 15 minutes in 140° to 150°F water, opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection. 1/

Lot size (cans)	Sample size (No. of cans)	Cumulative sample	Acceptance number	Rejection number
0-3200	8		0	2
	8	16	1	2
3201-35000	13		0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be acceptable.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:45Z
Check the source to verify that this is the current version before use.

TABLE II. Product inspection 1/ 2/

Category	Defect
Major	
101	Washed drained weight of potatoes in a can less than 66 ounces. 3/
102	Washed drained weight of potatoes in a can more than 72 ounces. 3/
103	Potatoes hard, fibrous, and/or mushy.
104	Potatoes not distinct dices.
105	Potatoes not a white to off-white color.
106	Sauce not smooth, glossy and moderately thick.
107	Sauce not a pale off-white to yellow color.

1/ The presence of any foreign material (e.g. glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale, etc.) or foreign color shall be cause for rejection of the lot. (To be determined by USDA inspection operation employee.)

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability or overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an AMS agent.)

3/ Procedure for the determination of washed drained weight. The contents of the tray pack can shall be poured into a 12-inch diameter U.S. Standard 1/4 inch sieve such as to distribute the product evenly in the sieve. The sieve and contents shall be immersed in 150° ± 10°F water, and the sieve shall be agitated with a vigorous swirling motion for 1 minute taking care to separate the product into individual dice. The sieve and contents shall be removed from the water and then reimmersed momentarily twice in succession. The sieve shall be tilted to an approximate 45 degree angle and allowed to drain 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.

4.6.3 Salt and sulfur dioxide content testing. Nine tray pack cans shall be selected from the lot and distributed as follows:

- Three for laboratory analysis.
- Three for submission to the contractor.
- Three for retention by an AMS agent as a reserve sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

The three tray packs for laboratory analyses shall individually be tested for salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists and sulfur dioxide content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter 20: Food Additives; Subchapter: Chemical Preservatives; Method: Total Sulfurous Acid, except that preparation of the samples shall be as follows. The three unopened cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened, and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The lot shall be rejected if the salt content in any individual tray pack is greater than 1.0 percent or less than 0.5 percent or the sulfur dioxide content in any individual tray pack is greater than 100 ppm. Results shall be reported to the nearest 0.1 percent. Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the salt or sulfur dioxide content requirements. When the reserve samples are analyzed, the analyses shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.7 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows: Major: (1) National stock number, item description, contract number or date of pack markings missing, incorrect, or illegible; (2) Reinforcement with nonmetallic strapping or tape is not used. Minor: (1) Other required markings missing, incorrect, or illegible; (2) Interior packing with fiberboard liner or pads not as specified; (3) Height of box liner less than inside depth dimension of box by more than 1/8 inch or extends above top edge of box; (4) Length or width of pads less than box dimensions by more than 1/8 inch; (5) Arrangement or number of cans not as specified.

4.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 106 ounces of food product, sealed and thermoprocessed as specified in 3.4, 3.5, and 3.6. The base plate of the can shall be electrolytic chromium-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating conforming to type I of TT-C-495.

5.1.2 Level C. The product shall be packaged as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pads shall be full length and width less approximately 1/8 inch in each dimension. The box liner and pads shall be fabricated of grade V3c fiberboard. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping for type II, class F loads.

5.2.2 Level B packing. Four cans of product, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pads shall be full length and width less approximately 1/4 inch in each dimension and be fabricated of class domestic fiberboard.

5.3 Unit load. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497. In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.7 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT

a. To heat in water: Submerge unopened can in boiling water. Simmer gently 20 to 25 minutes. Avoid overheating to the point where internal pressure is evident (can shows evidence of bulging). Remove from water and open lid for serving. CAUTION: Use care when opening as pressure may have been generated within the can.

b. To heat in oven: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 35 to 40 minutes until contents reach an internal temperature of 165°F. WARNING: Do not place closed can in oven as heating will cause the can to burst.

YIELD

Approximately 18 servings of 2/3 cup each.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary markings in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:45Z
Check the source to verify that this is the currentversion before use.

d. Level of packaging and packing required (see 5.1 and 5.2).
e. Type and class of unit load when required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/ MCO 4030.33A/DLAR 4145.7.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all procurement documents regarding arrangements for selection, inspection, and approval of the first article.

Preparing activity:

Army - GL

Project No. 8940-A510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
JJJ-V-002169A(Army-GL)	Potatoes, Diced in Butter Sauce, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

storage and handling practices, has a national or regional distribution from