JJJ-V-002180A(Army-GL)
August 8, 1985
SUPERSEDING
JJJ-V-002180(Army-GL)
June 27, 1983

INTERIM FEDERAL SPECIFICATION

POTATOES, SWEET, GLAZED, THERMOSTABILIZED, TRAY PACK

This interim Federal specification was developed by the U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers glazed sweet potatoes thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

TT-C-495 - Coatings, Exterior, For Tinned Food Cans
PPP-B-636 - Boxes, Shipping, Fiberboard

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bi-monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

operation. Filling shall be completed within one hour after product

(Single copies of this specification, and other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Fransico, CA; Los Angeles , CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal standardization documents, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-L-1497 - Labeling of Metal Cans for Subsistence items
MIL-L-35078 - Loads, Unit: Preparation of Nonperishable Subsistence Items, General Specification for

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermo-stabilized Foods for the Armed Forces

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

U.S. Department of Health and Human Services

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Department of Agriculture (USDA)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

U.S. Standards for Grades of Butter

(Application for copies should be addressed to Director, Dairy Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Regulations Governing Inspection and Certification of Processed Fruits and Vegetables, Processed Products Thereof and Certain Other Processed Food Products.

U.S. Standards for Grades of Canned Sweet Potatoes

U.S. Standards for Grades of Frozen Concentrated Orange Juice.

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Environmental Protection Agency (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Association of Official Analytical Chemists (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

National Academy of Sciences

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, Washington, DC 20418.)

Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Potatoes, sweet, fresh. The sweet potatoes shall be a soft-flesh type that is freshly dug (uncured), firm, fairly well colored, free from freezing injury, internal discoloration and damage and of a variety suitable for canning. If freshly dug sweet potatoes are not available, properly cured and stored sweet potatoes may be used provided the cured sweet potatoes are mature, firm, fairly well colored, free from chilling injury, freezing injury, internal discoloration and damage and have been stored at 55° to 60°F and 85 percent to 90 percent relative humidity for not more than four months.

3.2.2 Water. Water used for formulation, blanching and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.2.3 Sugar, brown, light. The brown sugar shall be partially refined cane or beet sugar. It shall be light brown in color and shall have a sweet molasses-like flavor.

3.2.4 Butter, lightly salted. The lightly salted butter shall comply with the U.S. Grade A or better requirements of the U.S. Standards for Grades of Butter.

3.2.5 Starch, waxy maize, modified. The starch shall be white, odorless, finely pulverized, modified waxy maize starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range of 140°-170°F and a typical viscosity (be fully hydrated) at common retort temperatures. It shall resist breakdown at low pH, under shear stress, and conditions of cold storage. The starch shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.6 Orange juice concentrate, frozen. Frozen orange juice concentrate shall comply with the U.S. Grade A requirements of the U.S. Standards for Grades of Frozen Concentrated Orange Juice.

3.2.7 Salt. Salt shall be non-iodized, white, refined sodium chloride with or without anti-caking agents.

3.2.8 Sodium bisulfite. Sodium bisulfite shall comply with the Food Chemicals Codex.

3.3 Preparation and processing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.3.1 Sweet potato preparation. The sweet potatoes shall be washed thoroughly and sorted to remove foreign material and diseased or otherwise damaged potatoes. The sweet potatoes shall be peeled, snipped, scrubbed and trimmed to remove parts not suitable for canning. Peeling may be accomplished by mechanical abrasion, steam peeling, lye peeling or a combination of these methods. After trimming, the potatoes shall be mechanically diced with dicer settings of approximately 1 1/4 by 3/4 by 1/2 inches. The peeled and cut sweet potatoes shall be handled in such a manner that will prevent browning or other discoloration. Sodium bisulfite may be used provided that sulfur dioxide concentration in the finished product conforms with 3.6.j. The cut potatoes shall be blanched in 170° to 180°F water for 1 to 3 minutes. The blanched potatoes shall be placed in trays, covered with hot syrup and the trays sealed within 2 hours after blanching.

3.3.2 Syrup preparation. The syrup shall be formulated as follows:

Ingredients	Percent by weight
Water	48.0
Sugar, light brown	37.0
Butter, lightly salted	7.0
Starch, waxy maize, modified	3.8
Orange juice concentrate	3.0
Salt	1.2
	100.0

Approximately 80 percent of the water shall be combined with the brown sugar, butter, orange juice and salt in a processing vessel, and heated to approximately 140°-145°F. A starch slurry shall be prepared using the remaining water and the starch. The starch slurry shall be added slowly with constant agitation to the sugar mixture and the final mixture heated to 200°-205°F and held for approximately 5 minutes at this temperature. Prior to filling, the volume of the final mixture shall be adjusted with water to compensate for evaporation loss during preparation. Each batch of prepared syrup shall be completely filled into the tray cans within one (1) hour following syrup preparation.

3.4 Tray pack filling and sealing. Each tray pack can shall be filled with product so as to conform to the following requirements:

a. Not less than 72 ounces of cut blanched sweet potatoes shall be placed in each tray pack can (see 5.1.1) and the can immediately filled with syrup to not less than 110 ounces of product.

b. The temperature of the syrup at time of filling shall be not less than 150°F.

c. Each can shall be hermetically sealed (under vacuum of not less than 10 inches of mercury) immediately after filling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting at a maximum retort temperature of 240°F or below until a sterilization value (F_o) of not less than 6.0 has been achieved.

3.6 Finished product. The finished product shall comply with the following requirements:

a. There shall be no foreign material, such as but not limited to dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor, such as but not limited to burnt, scorched, stale, sour, rancid, musty or moldy.

c. There shall be no color foreign to the product.

d. No individual can shall contain less than 72 ounces drained weight of sweet potatoes.

e. The average net weight shall be not less than 110 ounces drained.

f. No individual can shall weigh less than 108 ounces.

g. The salt content of the finished product shall not exceed 1.0 percent.

h. The syrup shall be moderately thick, tan-yellow, translucent and shall not be lumpy or watery.

i. The sweet potatoes shall meet the requirements of U.S. Grade A, golden, pieces, cuts, or cut canned sweet potatoes.

j. The sulfur dioxide level in the finished product shall not exceed 100 ppm when tested in accordance with 4.6.3.

3.6.1 Palatability. The finished product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods", and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this specification.

4.3 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.4 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified, or qualified in this specification or other applicable purchase document.

4.4.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be evident by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses or other such valid documents acceptable to the inspection agency. In addition, prior to use, each ingredient shall be examined organoleptically, as necessary, to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5 In-processing examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing and packing requirements. Any nonconformance revealed by actual examination or by review or records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.6 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.6.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing by 30) from

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

the weight of each tray pack in the sample. The results shall be reported to the nearest 1.0 ounce. If the average net weight is less than 110 ounces or if the net weight of any individual can is less than 108 ounces, the lot shall be rejected.

4.6.2 Product inspection. The sample size shall be as indicated by the double random sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray packs shall be heated at least 15 minutes in 140°to 150°F water, opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (No. of cans)	Cumulative sample	Acceptance number	Rejection number
0-3200	8	---	0	2
	8	16	1	2
3201-35000	13	---	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product inspection 1/ 2/ 3/

Category	Defect
Major	
151	Drained weight of sweet potatoes less than 72 ounces. 4/
152	Syrup not tan-yellow in color.
153	Syrup lumpy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

TABLE II. Product inspection 1/ 2/ 3/ (cont'd)

Category	Defect
Major	
154	Syrup not translucent.
155	Syrup not moderately thick.

1/ The presence of any foreign material, (e.g., glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale, etc.), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved pre-production sample (see 6.1) in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall only be performed when deemed necessary by the AMS agent.)

3/ The product not meeting grade shall be cause for rejection of the lot.

4/ To determine drained weight, the free liquid in the can shall be poured off and the remaining contents shall be poured into a flat bottom container. A minimum of three times the tray pack can's volume of 190° to 212°F water shall be added to the container so as to cover the contents. The contents and water shall be agitated so as to remove sauce without breaking up the sweet potato pieces. The contents shall then be poured into a U.S. Standard No. 1/4-inch sieve in a manner that will distribute the product over the sieve without breaking the potato pieces. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at an approximate 45 degree angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weights shall be reported to the nearest 0.1 ounce.

4.6.3 Salt and sulfur dioxidecontent testing. Nine tray packs shall be selected from the lot and distributed as follows:

- Three for laboratory analysis.
- Three for submission to the contractor.
- Three for retention by the AMS agent as a reserve sample.

The three tray packs for laboratory analysis shall be individually tested for salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, and for sulfur dioxide content in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter 20: Food additives; Subchapter chemical preservatives; Method: Total sulfurous acid except that preparation of the sample shall be as follows:

The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The lot shall be rejected if the salt content in any individual can is greater than 1.0 percent. Results shall be reported to the nearest 0.1 percent. The lot shall be rejected if the sulfur dioxide content in any individual can is greater than 100 ppm. Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analyses indicated that the involved lot will be rejected because of noncompliance with the salt or sulfur dioxide requirements. When the reserve samples are analyzed, their analyses for salt or sulfur dioxide shall be considered final. Unused reserve samples shall be returned to the contractor for inclusion in the same or subsequent lots.

4.7 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that the inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable), in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows: Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible; (2) Reinforcement with nonmetallic strapping or tape is not used. Minor: (1) Other required markings missing, incorrect or illegible; (2) Interior packing with fiberboard liner or pads not as specified; (3) Height of box liner less than inside depth dimension of box by more than 1/8 inch or extends above top edge of box; (4) Length or width of pads less than box dimensions by more than 1/8 inch; (5) Arrangement or number of cans not as specified.

4.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 110 ounces of the food product, sealed, and thermoprocessed as specified in 3.4, 3.5 and 3.6. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify the compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.2 Level C. The product shall be packaged as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (0+ inch, -1/8 inch). The pads shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of grade V3c fiberboard. The pads shall be placed between the cans and on the top and bottom of the stacked cans. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497. In addition, the name of product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.7 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

Tray cans may be heated prior to serving or served at ambient temperature without heating. When heated, the following heating directions shall apply:

TO HEAT

a. To heat in water: Submerge unopened can in boiling water. Simmer gently 35 minutes. Avoid overheating to the point where internal pressure is evident (can showing evidence of bulging). Remove from water and open lid for serving.

CAUTION: Use care when opening as pressure may have been generated within the can.

b. To heat in oven: Either punch several holes in lid of tray can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 30 to 40 minutes until contents reach an internal temperature of 165°F.

WARNING: Do not place closed can in oven as heating will increase internal pressure which will cause the can to burst.

YIELD

18 servings of approximately 2/3 cup each

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary marking in capital letters larger than other markings shall be included: CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of packaging and packing required (see 5.1 and 5.2).
e. Type and class of unit load when unit loading is required (see 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Preparing activity:

Army - GL

Project No. 8940-A495

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
JJJ-V-002180A(Army-GL)	Potatoes, Sweet, Glazed, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.