KKK-C-650E
July 15, 1985
SUPERSEDING
KKK-C-650D
January 31, 1974

FEDERAL SPECIFICATION

CREEPER, MECHANIC'S (AUTOMOTIVE)

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two types of wood body mechanic creepers.

1.2 Classification.

1.2.1 Types. Creepers furnished under this specification shall be of the following types, as specified (see 6.2 and 6.4):

Type I	- Four swivel-type casters and a padded headrest.
Type II	- Four or six swivel-type casters and an adjustable, padded head and shoulder rest.

2. APPLICABLE DOCUMENTS

2.1 Government publications. The issues of the following documents, in effect on date of invitation for bids or solicitation for offers, form a part of this specification to the extent specified herein.

Federal Specifications

PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall

Federal Standards

FED-STD-H28	- Screw-Thread Standards for Federal Services
FED-STD-123	- Marking for Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026Feb20 12:43Z
Check the source to verify that this is the current version before use.

(Single copies of this specification, and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes, are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications

MIL-P-116 - Preservation, Methods of

Military Standards

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulation:

Occupational Health and Safety Administration (OSHA) 29 CFR 1910.241-247 General Industrial Safety and Health Standards.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Americal Plywood Association

US Product Standard PS 1-83 - Construction and Industrial Plywood

(Application for copies should be addressed to the American Plywood Association, P.O. Box 11700, Tacoma, WA 98411.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM)

ASTM D3951-82 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Hardwood Lumber Association (NHLA)

NHLA Standard - Rules for the Measurement and Inspection of Hardwood and Cypress Lumber

(Application for copies should be addressed to the National Hardwood Lumber Association, P.O. Box 34518, Memphis, TN 38184-0518.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS.

3.1 First article. When specified (see 6.2), the contractor shall furnish one or more creepers for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. Creepers shall be new and of the manufacturer's latest design which shall meet the requirements specified herein. The design shall provide for safe equilibrium and ease of maneuverability when the creepers are used on a shop-floor surface. The design shall also combine strength to withstand rough usage and handling during normal service, with lightness in weight for portability. The design, selection, and construction of hardwood components shall be at the option of the manufacturer as necessary to meet the requirements of this specification. Manufacturers shall use the National Hardwood Lumber Association (NHLA) standard referenced in 2.2 for selection of quality grades of hardwoods. Hardwoods shall be selected only from those so identified by the NHLA.

3.2.1 Occupational safety standards. The product shall comply with OSHA standards set forth in 29 CFR 1910.241-247 that are applicable to mechanic's creepers.

3.2.2 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

3.2.3 Interchangeability. All parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a particular type or model may be replaced, interchanged, and adjusted without modification of the replacement parts or any other parts of the unit. When practical, all parts shall be permanently and legibly marked in accordance with MIL-STD-130.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.2.4 Load capacities. The creepers shall be capable of withstanding, without more than 0.125 inch permanent set or deformation in any direction, structural failure, or damage the following load requirements;

(a) A concentrated load of at least 500 pounds applied over a 9 by 10 inch area centrally located from the casters.
(b) An impact load of at least 200 pounds allowed to free-fall at least 18 inches. (The load shall be distributed over the plywood platform, excluding frame rails and headrest.)
(c) For type I only, the headrest shall be capable of supporting a load of at least 100 pounds over 50 percent of the headrest area.
(d) For Type II only, the head and shoulder rest shall be capable of supporting a load of at least 200 pounts over 100 percent of the rest area in both the raised and lowered position.
(e) The creeper casters shall operate freely with no damage, sticking, binding, loosening, or wearing in excess of 0.062 inch after 50 cycles of a back and forth movement with the creeper uniformly loaded with 200 pounds. One cycle shall consist of one back and forth movement during which all casters turn 180 degrees.

3.3 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the producing industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.4 Construction. All parts used in fabrication of the creepers shall be new and free of defects. In no event shall patching processes be used for reclaiming defective parts. All part surfaces shall be clean and free of extraneous materials. External surfaces shall be smooth and free of sharp edges. Construction shall result in creepers that are safe, rugged, sturdy, and indicative of quality equipment produced by manufacturers normally involved in producing these items.

3.4.1 Platforms. Wood platforms shall be of contiguous, slatted, or plywood panel type of construction. Plywood shall be exterior type, grade A/B or better, meeting the requirements of US Product Standard PS 1-83. Where a wood frame is used, frame members shall be of sound hardwood, surfaced on all four sides, and not less than 0.75 inch thick. Moisture content of all hardwood members shall not exceed 18 percent (oven dry weight). Frame members shall be connected by through type, plated, oval head stove bolts, nuts, and lockwashers. Slats shall be supported and secured to withstand the load requirements specified in 3.2.4. Plywood panels shall be no less than 5/16 inch thick, four ply, sound fir or hardwood plywood, reinforced with hardwood cross-ribs and hardwood side rails as necessary to meet the load requirements of this specification. The rails shall be not less than 1.75 inches wide for the full length of the platform. The edges of plywood components shall be sealed with a waterproof coating. The clearance between bolts and bolt holes in the wood members shall be sufficient to prevent splitting and cracking of the wood at the holes. The top surfaces of the platform shall be free of sharp protrusions of bolt heads, screw heads, nuts, or other

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

fastening devices. Shallow, oval head bolts are permissable above the surface only in the side rails and frame members.

3.4.1.1 Dimensions. Type I creepers shall be not less than 35 inches in overall length, not less than 14.5 inches in overall width, and not greater than 3.75 inches high to the top of the platform and frame members (excluding headrest). Type II creepers shall be not less than 41.75 inches in overall length, not less than 15.25 inches in overall width, and not greater than 3.75 inches high to the top of the platform and frame members (excluding headrest). Clearance between the floor surface and the bottom of the platform and frame members shall be not less than 0.5 inch.

3.4.2 Casters. Creepers shall be furnished with swivel casters of the type that the wheel is canted approximately 45 degrees to the floor. The rims of the wheels shall be either convexed or beveled to match the angle of the cant with the floor. The wheels for Type I creepers shall be not less than 2.25 inches in diameter. The wheels for Type II creepers shall be not less than 2.75 inches in diameter for the four outer casters and not less than 2.25 inches in diameter for the center casters when supplied (see 1.2). Bearing surface and swivel action shall be provided by a steel shaft in combination with a separate steel ball thrust-bearing or by a hemispherically machined steel shaft end. Casters shall be of sufficient height to provide not less than 0.5 inch clearance between creeper cross-ribs and the floor when the creeper is loaded with 200 pounds, distributed uniformly. The casters shall provide free movement of the creeper in any direction. Caster wheels shall be metal alloy or nylon (or ABS plastic) capable of withstanding the load and wear resistant requirements specified in 3.2.4. Exterior surfaces of the casters shall be free of rough edges and burrs and shall have a smooth finish. All metallic surfaces of the casters except surfaces of the bearing components shall be given a protective plating in accordance with best commercial practice. Caster bearings shall be lubricated by the supplier. Casters shall be mounted so that the centerline of the perpendicular shaft is not more than 5.25 inches from the ends of side rails or frame. When six casters are used, one shall be mounted on centerline, halfway between the two end casters of each side rail. The casters shall be secured to the creeper by through type, plated, oval head stove bolts, nuts, and lockwashers. No sharp protrusions shall be allowed above the top surface of the frame members, platform, or side rails (see 3.4.1).

3.4.3 Headrest, type I. The headrest shall be located on the top surface at one end of the main body of the creeper. It shall be mounted so that the length is centered on, and perpendicular to, the longitudinal centerline of the main body. The headrest shall not extend beyond the platform. Including padding, the headrest shall be at least ten inches long, three inches wide, and three inches thick. The padding shall be foam rubber or other resilient material, with an oil-grease-proof cover which shall be turned under the headrest or provided with a finishing strip.

3.4.4 Head and shoulder rest, type II. The head and shoulder rest shall be located on the top surface at one end of the main body of the creeper. The rest shall be mounted and hinged so that the length is centered on, and perpendicular to, the longitudinal centerline of the main body. It shall not extend beyond the platform. The head and shoulder rest length shall be at least 14 inches long from its hinged point, including the padded headrest, and as wide as the headrest padding. The padded headrest itself shall be at least ten inches long, three

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

inches wide, and three inches thick. The padding shall consist of foam rubber or other resilient material, with an oil-grease-proof cover which shall be turned under the headrest or provided with a finishing strip. The head and shoulder rest shall be provided with at least four height adjustments with a total raised height of at least six inches between framework and total height.

3.4.5 Metallic parts. Metallic parts, unless inherently corrosion resistant, shall be plated with a protective finish that shall provide protection against corrosion.

3.4.6 Fastening devices. All screws, pins, bolts, rivets, and similar parts shall be standard commercial products. These fastening devices, when required, shall be installed with means for preventing loss of tightness and adjustment. The methods for preventing loss of tightness or adjustment shall be in accordance with accepted engineering standards and practice. All such parts when subject to removal or adjustment shall not be swaged, peened, staked, or otherwise deformed.

3.5 Product identification.

3.5.1 Civil agencies. Creepers shall be marked in a plain and permanent manner with the manufacturer's name or trademark in such a way that the source of manufacture can be readily identified.

3.5.2 Military. Creepers shall be marked for identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2), shall include the National Stock Number.

3.6 Surface finishes and painting.

3.6.1 Surface finishes. Before painting, wood surfaces shall be smooth, free of sharp edges and splinters, and with a fully sanded surface finish that is equivalent to standard commercial lumber finishes. All metal surfaces shall be smooth and free of sharp edges and burrs.

3.6.2 Painting. Creepers shall be coated with a clear varnish, lacquer, or polyurethane finish that shall be equal to the best commercial practice prevalant in the producing industry. At least one coat of sealer (primer) and one finish coat shall be applied.

3.7 Workmanship. Standards of workmanship shall assure that the creepers shall have the stability, strength, safety, and efficient operating characteristics found in the best commercial units and as specified in Section 3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Unless otherwise specified (see 6.2), quality conformance inspection shall be applied to production items offered for acceptance under the contract. Unless otherwise specified (see 6.2), quality conformance inspection shall consist of (a) through (c) below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

(a) Product examination (see 4.5).
(b) Impact load test (see 4.6.2).
(c) Packaging inspection (see 4.7).

4.4.1 Sampling. Unless otherwise specified (see 6.2), quality conformance inspection shall be applied to production items offered for acceptance on the contract or purchase order. As a minimum, quality conformance inspection and test shall consist of (a) through (c) below. Sampling shall be conducted in accordance with MIL-STD-105 using single sampling for normal inspection at the Inspection Levels and Acceptable Quality Levels (AQL) specified below:

(a) Product examination. Production items shall be examined to determine compliance with the characteristics specified in 4.5. Acceptance shall be based on an AQL of 2.5 defects per hundred units for major defects and 6.5 defects per hundred units for minor defects at Inspection Level II.
(b) Uniform impact load test. Sampling for test (see 4.6.2) shall be conducted in accordance with Special Inspection Level S-4. Failure of any item to pass this test shall be cause for rejection of the lot which the sample represents.
(c) Inspection of preparation for delivery. Sampling for packaging inspection (see 4.7) shall be conducted in accordance with Special Inspection Level S-4. Acceptance shall be based on an AQL of 4.0 percent defective.

4.5 Product examination. The creepers shall be examined to determine compliance with the requirements of Section 3 and the contract. As a minimum, the following characteristics shall be examined:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

(a) First article inspection (see 4.4)

CHARACTERISTICS	DEFECT CLASSIFICATION		REQUIREMENT PARAGRAPH
	MAJOR	MINOR	
Design	X		3.2
Threads	X		3.2.2
Interchangeability	X		3.2.3
Materials	X		3.3
Reclaimed materials when applicable	X		3.3.1
Construction	X		3.4
Platforms	X		3.4.1
Dimensions	X		3.4.1.1
Casters	X		3.4.2
Headrest (Type I)	X		3.4.3
Head and shoulder rest (Type II)	X		3.4.4
Metallic parts	X		3.4.5
Fastening devices	X		3.4.6
Product identification			3.5
Civil agencies		X	3.5.1
Military		X	3.5.2
Finishes and painting			3.6
Surface finishes	X		3.6.1
Painting	X		3.6.2
Workmanship	X		3.7

A certificate of conformance may be provided to satisfy the examination requirements when more than a visual or dimensional verification would be necessary.

4.5.1 Evidence of compliance with OSHA standards. Evidence of compliance with applicable safety and health requirements shall be reviewed (see 3.2.1 and 6.3).

4.6 Tests.

4.6.1 Concentrated load test. With the creeper in normal operating position, a load of 500 pounds shall be applied over a 9 by 10 inch area at a location between the centerlines of the casters. There shall be no structural failure, damage, or excessive permanent set or deformation (see 3.2.4).

4.6.2 Uniform impact load test. Center the creeper platform, with the creeper in normal operating position, under a 200 pound sandbag suspended not less than 18 inches above the creeper platform. The longitudinal axis of the sandbag shall be horizontal and parallel to, and over the approximate center of, the platform. Release the sandbag instantaneously, allowing it to fall freely onto the creeper platform. There shall be no structural failure, damage, or excessive permanent set or deformation (see 3.2.4).

4.6.3 Caster and clearance test. Uniformly load the creeper platform with 200 pounds and move the creeper with an air cylinder or similar device so that all casters turn 180° on each cycle of a back and forth movement (one cycle) for at least 50 cycles. Clearance between the creeper cross ties and the floor shall be not less than 0.5 inch. All casters shall operate freely with no damage, sticking, or binding. All casters shall remain secure with no evidence of looseness or wear exceeding 0.062 inch (see 3.2.4 and 3.4.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

4.6.4 Headrest load test (Type I only). Apply a load of 100 pounds over 50 percent of the rest area for at least three minutes and then remove the load. There shall be no structural failure, damage, or permanent set or deformation exceeding 0.125 inch (see 3.2.4).

4.6.5 Head and shoulder rest load test (Type II only). Apply a load of 200 pounds over 100 percent of the rest area for at least three minutes in both the raised and lowered positions and then remove the load. There shall be no structural failure, damage, or permanent set or deformation exceeding 0.125 inch (see 3.2.4).

4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the preparation for delivery requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation. Preservation shall be Level A or Commercial. Unless otherwise specified (see 6.2), Commercial preservation shall be provided. When military (Level A) preservation is required, it shall be so specified in the contract. Commercial preservation shall consist of standard commercial practices for protecting the product from environmental damage.

5.1.1 Level A.

5.1.1.1 Cleaning and drying. Cleaning and drying shall be in accordance with any applicable process and procedure of MIL-P-116.

5.1.1.2 Unit packaging. Unit packaging shall conform to method III of MIL-P-116 with each creeper packaged in a fiberboard box conforming to PPP-B-636, class domestic.

5.1.2 Commercial. Unit packaging shall afford adequate protection against damage during multiple shipments, handling, and storage. The supplier may use his standard practice when it meets these requirements.

5.2 Packing. Packing shall be Level A, Level B, or Commercial. Unless otherwise specified (see 6.2), Commercial packing shall be provided. When military (Levels A and B) packing is required, it shall be so specified in the contract.

5.2.1 Level A. Creepers packaged as specified in 5.1.1.2 shall be packed in an exterior shipping container conforming to PPP-B-601, overseas type, or PPP-B-621, class 2. The gross weight of each shipping container shall not exceed the weight limitations of the applicable box specification. As far as practicable, containers shall be uniform in size and contain like quantities. Blocking and bracing shall be in accordance with MIL-STD-1186.

5.2.2 Level B. Creepers packaged as specified in 5.1.1.2 shall be packed as specified in 5.2.1 except that the shipping containers shall conform to PPP-B-601, domestic type, PPP-B-621, class 1, or PPP-B-640, class 1 or 2.

5.2.3 Commercial. Creepers packaged as specified in 5.1.2 shall be packed in a manner to affort adequate protection against damage during shipment from the supply source to the first receiving activity. Shipping containers shall comply with rules and regulations applicable to the mode of transportation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

5.3 Marking. Millitary marking shall be Level A, Level B, or Industrial. Unless otherwise specified (see 6.2), Industrial marking shall be provided. When military (Levels A and B) or civil agency marking is required, it shall be so specified in the contract.

5.3.1 Civil agencies. Marking shall be as specified in FED-STD-123.

5.3.2 Military agencies. Level A and Level B marking shall be as specified in MIL-STD-129. Industrial marking shall be as specified in ASTM D3951-82.

6. NOTES

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) First article when required (see 3.1).
(d) Product identification if different (see 3.5).
(e) First article inspection if different (see 4.3).
(f) Quality conformance inspection if different (see 4.4).
(g) Sampling if different (see 4.4.1).
(h) Level of preservaton, packing, and marking if different (see 5.1, 5.2, and 5.3).

6.3 OSHA standards. Products which meet all requirements of this specification comply with the OSHA standards published prior to the date of this specification and identified in Section 3 (see 3.2.1).

6.4 Militaty use. Military (DoD) procurement should be limited to only the Type I (non-adjustable headrest) creeper. Past standardization actions have resulted in DoD concurrance that the Type II creeper (adjustable headrest) be considered non-standard.

MILITARY INTERESTS:

Custodians
Army - AL
Navy - YD

User Activity
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
Army - AL

DoD Project 4910-0591

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research
and Development Center
ATTN: SMCAR-ETS (R)
Rock Island, IL 61299-7300

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
KKK-C-650E	Creeper, Mechanic's (Automotive)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.