MIL-C-60297(MU)
AMENDMENT 2
24 March 1972
SUPERSEDING
AMENDMENT 1
3 November 1970

MILITARY SPECIFICATION

COUNTER, TIME INTERVAL: 10547200

This amendment forms a part of Military Specification MIL-C-60297(MU), dated 18 June 1970.

* Page 3, paragraph 3.8: Delete and substitute the following:

"3.8 Performance.- The assembly shall be operable when supply voltages are applied as follows:

21.0 ± 0.5 VDC applied to Pin L of Socket 25J1
7.0 ± 0.5 VDC applied to Pin E of Socket 25J1."

* Paragraph 3.8.1.3: Delete "25J2" and substitute "25J1". Make this same change wherever 25J2 is specified.

* Paragraph 3.9.a" After the word "with" add the following: Connector 10540745 on".

* Paragraph 3.9.b: Delete and substitute the following: "Connector MS 24049-3 from the counter interface with Connector MS 24050-3 on the display panel."

Page 10, paragraph 4.6.5.1: Delete "27 VDC" and substitute "21 VDC"; delete "9 VDC" and substitute "7 VDC."

Page 14, Figure 1: Delete "27V" and "9V" and substitute "21 VDC" and "7 VDC".

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A353

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.