MILITARY SPECIFICATION

CASE, CARTRIDGE, 105MM, M148A1B1

This amendment forms a part of Military Specification MIL-C-63292 (AR) dated 8 February 1980 and is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

4.3.1:

Change "254*" to "262".

Delete the following sentence in its entirety: "*All samples must meet the requirements for thermal treatment and high stress expansion test as performed in the uncoated state."

PAGE 6

Table I - First Article Inspection:

Cartridge Case - Prior to Coating: Delete the following:

"Macro examination	4	3.8.2	4.5.5
Tension Test (Info Only)	4	3.3	4.5.4"

Cartridge Case - After Coating:

Change "254" to "262"

Add:	"Tension Test (Info Only)	4	3.3	4.5.4
	Macro Examination	4	3.8.2	4.5.5"

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.

PAGE 8

4.4.2.1:

Delete Major Defects 101, 103, 104, 105, 106 and 107 in their entirety.

Major Defect 117, change "Gage" to "Visual"

PAGE 9

4.4.2.1: Minor Defect 208, change "3.8" to "3.8.4 and 3.8.5".

PAGE 10

4.4.2.2:

Major Defect 105, after 100%" add "(a)".

Add the following Major Defects:

"118	Thermal treatment			100%	(a)	3.3.1 4.5.1
119	Hardness	4	(b)			3.3 4.5.3
120	Macro examination	4	(b)			3.8.2 4.5.5"

Add "Note (b). Reject on one defect
Note (c). Sample used for the hardness test shall be used in the tension test (See 4.5.4)"

PAGE 11

4.4.2.2:

Minor Defect 207, change "3.8" to "3.8.4 and 3.8.5".

Add the following defect:

"Special				
301	Tension test (Information Only)	(c)	3.3	4.5.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.

PAGE 12

4.4.2.3:

Major Defect, delete "None defined."

Add Major Defect 101:

"101	Cracks and other metal defects (cartridge cases) just prior to packing into carton	100%	3.8.1	Visual"

PAGE 15

4.5.4: Delete this paragraph in its entirety and substitute:

Tension test (Information Only). Four cartridge cases from each lot shall be subjected to this test. The test specimens shall be taken from each cartridge case in accordance with the standard position and size of the tensile specimen chart described in Figure 1. The yield strength, tensile strength and elongation shall be determined in accordance with the procedures prescribed by ASTM-E8. The results shall be recorded for information only."

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 1315-A525

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.