MILITARY SPECIFICATION

TAPE, FAN FOLDED

This amendment forms a part of Military Specification MIL-T-60164(MU), dated 29 May 1967.

Paragraph 3.2.2 Lamination: Delete paragraph.

Paragraph 3.3.1 Flame resistance: Delete "850 degrees" and substitute "750 degrees".

Paragraph 3.3.2 Solubility: Delete "alchols".

Paragraph 3.3.6 Opacity: Delete "95%" and substitute "90%".

Paragraph 3.3.7 Internal tear resistance: Delete and substitute:

"Internal tear resistance.- Tape shall have a minimum internal tear resistance of 60 grams, machine direction; 65 grams cross direction."

Paragraph 3.7.2 Folding endurance: Delete "1500 double folds" and substitute "750 double folds".

Add the following paragraphs in proper sequence:

4.1.1 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) Type I tapes manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.1.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.1.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:13Z
Check the source to verify that this is the current version before use.

and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

Paragraph 4.5.2.1, Flame resistance: Delete "850°" and substitute "750°".

Paragraph 4.5.2.5, Opacity: Delete "5%" and substitute "10%".

Paragraph 4.5.8, Folding endurance: Delete "1500" and substitute "750".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A102

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:13Z
Check the source to verify that this is the current version before use.