MILITARY SPECIFICATION

CASE, MEDICAL LABORATORY EQUIPMENT SET

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for a nylon carrying case suitable for holding three intermediate rigid containers for the subassemblies of the NSN 6545-00-926-1483 Medical Equipment Set, Medical Laboratory, Combat, Individual. The case is also designed for use with the NSN 8465-00-782-3248 Rucksack, Nylon, Olive Drab 106, Water-Repellent, 4 pockets, with adjustable waist belt.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

V-F-106	Fastener, Slide, Interlocking
V-T-285	Thread, Polyester
QQ-Z-325	Zinc Coating, Electrodeposited, Requirements For
PPP-B-585	Box, Wood, Wirebound
PPP-B-601	Box, Wood, Cleated Plywood
PPP-B-621	Box, Wood, Nailed and Lock Corner
PPP-B-636	Boxes, Shipping, Fiberboard

Military

MIL-E-480	Enamel, Baking, Phenol-or-Urea-Formaldehyde
MIL-F-495	Finish, Chemical, Black, for Copper Alloys
MIL-B-543	Buckle, Tongueless and Web Strap
MIL-W-4088	Webbing, Textile, Woven Nylon
MIL-S-5626	Steel, Chrome-Molybdenum (4140), Bars, Rods, and Forging Stock (For Aircraft Application)
MIL-S-6029	Steel, Chrome-Nickel-Molybdenum (8740), Bars, Rods, and Forging Stock (For Aircraft Application)

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:59Z
Check the source to verify that this is the current version before use.

Military (Cont'd)

MIL-E-20652	Eyelet, Metallic, and Eyelet Washers, Metallic, General Specification For
MIL-E-20652/1	Eyelets, Metallic, Rolled Flange Type; and Eyelet Washer.
MIL-F-21840	Fastener Tapes, Hook and Pile, Synthetic, General Specification For
MIL-W-27265	Webbing, Textile, Woven Nylon, Impregnated
MIL-C-43128	Cloth, Plain Weave, Nylon, Water Repellent, OG-106

STANDARDS

Federal

FED-STD-151	Metal, Test Methods
FED-STD-751	Stitch, Seam and Stitching

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWING

DEFENSE PERSONNEL SUPPORT CENTER

24053	Case, Medical Laboratory Equipment Set

(Copies of specifications, standards, and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

THE COLOR ASSOCIATION OF THE UNITED STATES, INC.

United States Army Color Card of Standard Shades for Slide Fastener Tapes.

Department of Defense Standard Color Card of Official Standardized Shades for Sewing Threads
1968

(Application for copies of each should be addressed to the Color Association of the United States, Inc., 200 Madison Avenue, New York, N.Y. 10016.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:59Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Except where otherwise specified, materials shall conform to the applicable portions of the specifications, standards, and drawing specified herein, and as described in 3.2 and shall be capable of meeting the requirements specified therein. In addition, the metals shall conform to the chemical requirements of their applicable specifications when tested as specified in section 4. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and entirely suitable for the purpose intended.

3.1.1 Cloth, nylon. The nylon cloth shall be olive green No. 106, water repellent, conforming to MIL-C-43128.

3.1.2 Webbing, nylon. The nylon webbing shall conform to Class 2 of MIL-W-4088 as follows:

3/4 inch width shall be Type Ia.

1-23/32 inch width shall be Type VIII.

3.1.2.1 Color and finish. The nylon webbing shall be dyed olive drab number 7 to match the standard shade, and shall be resin impregnated conforming to class R of MIL-W-27265. The resin impregnated webbing shall conform to the applicable requirements of MIL-W-27265.

3.1.3 Thread polyester. The thread for all stitching shall conform to type I, class I, sub-class A, Size F, of V-T-285. The thread shall be dyed olive drab shade S-1, C.I. 66022, except the colorfastness requirements and test methods shall be limited to weathering only.

3.1.4 Fasteners, hook and pile. The hook and pile fasteners shall be Type II, Class 1 of MIL-F-21840. Color shall be green, OG 106; width shall be 5/8 inch.

3.1.5 Buckle, nonslip. The nonslip buckle shall conform to type V, class 3, size 3/4 inch of MIL-B-543.

3.1.6 Eyelets and washers. Eyelets shall be M20652/1 - BBE117 and washers shall be M20652/1 - BBW101 of MIL-E-20652.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:59Z
Check the source to verify that this is the current version before use.

3.1.7 Fasteners, slide. Except as specified herein, the slide fasteners shall conform to V-F-106, type 1, style 6, size MHS except that the zipper tape shall be 1 inch wide instead of the 3/4 inch tape specified. Metal parts shall be brass with a black chemical finish conforming to MIL-F-495. The slider shall be equipped with a wire stirrup pull equipped with a thong. The length of the chain shall be as required to effect a smooth and secure closure of the case opening.

3.1.7.1 Tape. The slide fastener tapes shall be vat dyed olive drab shade S, conforming to U.S. Army Color Card of Standard Shades for Slide Fastener Tapes, and shall be water repellent and mildew resistant, in accordance with V-F-106. Mildew resistance shall be obtained by using copper-8-quinolinolate only.

3.1.7.1.1 Water repellence. The finished tape shall be tested for water resistance as specified in V-F-106.

3.1.7.2 Salt spray resistance. The slide fasteners shall meet the salt spray resistance requirements specified in V-F-106.

3.1.7.3 Webbing for thongs. Webbing for thongs shall conform to the requirements of V-F-106 for thongs (cotton webbing) except that mildew resistance shall be obtained by using copper-8-quinolinolate only.

3.1.8 Adapter. The 500 pound, quick fit, adapter shall be reversible and in accordance with Drawing. Steel shall be type 4140 of MIL-S-5626, or type 8740 of MIL-S-6049. Finish shall be zinc plate in accordance with Type III, class 2 of QQ-Z-325, followed by bake enameling. The enamel shall conform to type I or II of MIL-E-480. The color shall be black.

3.1.9 Stitching sealant. Exterior stitching shall be sealed by the application of one of the two sealants listed in 6.2, or equal, in accordance with the manufacturer's directions.

3.2 Construction. The construction of the case shall conform to the requirements specified herein and to those shown on Defense Personnel Support Center Drawing 24053.

3.2.1 Stitching, machine. All stitching shall conform to FED-STD-751 as follows:

For all stitching except overedge stitching; type 301, 8 to 10 stitches per inch.

For overedge stitching (single operation optional); type 503 or 504, 8 to 10 stitches per inch.

For closing seams and overedge stitching (simultaneous operation optional); type 301 in combination with 503, 504 or 502, 8 to 10 stitches per inch.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:59Z
Check the source to verify that this is the current version before use.

All edges of closing seams shall be overstitched. There shall be no lubrication of the thread by any means prior to or during sewing. Any of the operations requiring box, box with cross stitch, K stitching, straight line tacking or any other design of stitching cited in this specification may be performed with an automatic stitching machine provided the requirements for stitch pattern, stitches per inch, size, and types, of thread are met; and at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching.

3.2.1.1 Type 301 stitching. Thread breaks in stitching shall be overstitched not less than 1 inch at each break. Stitching shall be backstitched not less than 1 inch at the ends, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching, and the lock will be imbedded in the materials sewed.

3.2.1.2 Overedge stitching. Thread breaks in overedge stitching shall be overstitched not less than 3/4 inch at each break. Thread tension shall be maintained so that there will be no loose stitching.

3.2.2 Eyelets and washers. Eyelets shall be securely clinched to the washers, without cutting the material.

3.2.3 Fusing of nylon webbing. All ends of nylon webbing shall be fused after cutting, including bias cuts.

3.3 Marking for identification. Each case shall be legibly and permanently marked with black waterproof ink or paint in accordance with the drawing.

3.4 Workmanship. Workmanship shall be first class throughout. Complete cases shall be well made and free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURNACE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:59Z
Check the source to verify that this is the current version before use.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the cloth, fasteners, hardware, tape, and webbing, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Quality conformance inspection. The examinations and tests required to assure conformance of those items or lots of items to be offered for acceptance are classified as specified in tables I and I (see 4.2.1 and 4.2.2) and 4.2.3.

4.2.1 Sampling for examination.

4.2.1.1 Sampling for visual defects. Sampling for visual defects shall be conducted in accordance with MIL-STD-105. The inspection levels and acceptable quality levels shall be as indicated in table I. Unit of product for examination purposes shall be one case.

Table I. Sampling for Visual Defects

	Inspection level	AQL (defects per 100 units)
Major	II	2.5
Total (Major and Minor combined)	II	6.5

4.2.2 Examination. The case shall be examined for defects including, but not limited to, those listed in Table II.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:59Z
Check the source to verify that this is the current version before use.

Table II. Classification of Defects

Major	
101	Any component missing.
102	Any required operation omitted or improperly performed.
103	Any hole, cut, tear, mend, patch, or unauthorized splice.
104	Needle chews that may develop into hole.
105	One or more spots or stains of an obviously permanent nature.
106	Seam type other than specified.
107	Stitch type other than specified.
108	Less than 8 stitches per inch.
109	Webbing with frayed or scalloped edges.
110	Hardware components broken or malformed.
111	Burrs or sharp edges on hardware.
112	Finish omitted on hardware.
113	Markings omitted, incorrect, or illegible.
Minor	
201	One or more removable spots or stains clearly noticeable.
202	Any part of case pleated, twisted, or caught in any unrelated row of stitching.
203	Thread ends not trimmed.
204	Broken or skipped stitch not amounting to an open seam.
205	Thread breaks not backstitched for 1 inch.
206	Finish on hardware not uniform.
207	Color of markings not uniform.

4.2.3 Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, Inspection Level S-2, Acceptable Quality Level 4.0. Unit of product shall be one case.

4.2.3.1 Sampling for chemical testing of metals. Four ounces of each lot of each metal used in the construction of the cases shall be selected for the chemical analysis as specified in 4.3.1.

4.3 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.3.1 Chemical analysis of metals. The samples selected in accordance with 4.2.3.1 shall be analyzed in conformance with methods 111 or 112 of FED-STD-151. In case of dispute, method 111 shall be used for referee analysis.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:59Z
Check the source to verify that this is the current version before use.

4.4 Examination of preparation for delivery. An examination shall be made to determine whether the packaging, packing and marking comply with the requiremets of section 5. Defects shall be scored as specified in table III. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

Table III. Examination of preparation for delivery

Examine	Defect
Containers	Not as specified.
Contents	Not as specified.
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Component missing or damaged.
Workmanship	Bulging or distortion of containers.

4.4.1 Examination of closure and reinforcement for containers. When shipping containers are required to comply with PPP-B-636, examination for defects in closure and reinforcement shall be in accordance with the appendix to that specification.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.1).

5.1.1 Unit of issue. Each case, as specified, constitutes one unit of issue.

5.1.2 Level A.

5.1.2.1 Unit package. Each case with slide fastener closed shall be neatly folded and packaged in a clear snug fitting polyethylene bag having a minimum thickness of not less than 0.004 inch. A 1/4 inch diameter hole shall be made in the bag to allow excess air to escape and the closure of bag shall be effected by heat sealing.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:59Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.1).

5.2.1 Level A. Forty units shall be packaged in a snug fitting exterior container constructed in accordance with PPP-B-636, type CF, class weather-resistant. The box shall conform to the special requirements as specified in PPP-B-636. Closure strapping and waterproofing shall be as specified in the appendix of the box specification.

5.2.2 Level B. Forty units shall be packed in a snug fitting exterior container constructed in accordance with PPP-B-636, type CF, class domestic. Closure of the box shall be as specified in PPP-B-636 utilizing method I or II.

5.2.3 Level C. The subject commodity shall be packed in substantial commemercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.2.4 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure delivery to destination.

5.3 Marking.

5.3.1 Unit package. Each unit package shall be marked in accordance with MIL-STD-129. Marking shall include the contract or purchase order number and name of contractor. Marking may be printed on the bag or on a label placed within the bag in such a manner so as to permit ready identification.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:59Z
Check the source to verify that this is the current version before use.

6.2 Stitching sealants. The two sealants referenced in 3.1.9 are:

Bostik No. 7058
Bostik Chemical Group, USM Corp.
Middleton, Mass. 01949

Tite Seal
Eureka Tent Corp.
625 Conklin Hwy.
Binghamton, NY 13902

6.3 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet military requirements.

6.4 This specification is intended to cover the following item appearing in the Federal Supply Catalog:

NSN	Item Identification
6545-00-926-8935	CASE, MEDICAL LABORATORY EQUIPMENT SET

6.5 Supersession Data. This specification includes the requirements of Defense Medical Purchase Description No. 2, dated 29 May 1968.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6545-0016

Review activities:
Army - MD
Navy - MS
Air Force - 03

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 202640-21T09:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise improve use of the document. DoD contractors, government activities, or manufacturers' vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-37106

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:59Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, Pa. 19101

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

U.S. MAIL

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:59Z
Check the source to verify that this is the current version before use.