MIL-F-37135
21 March 1975

MILITARY SPECIFICATION

FLURAZEPAM HYDROCHLORIDE CAPSULES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers Flurazepam Hydrochloride Capsules, 30 mg, 500s. (See 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-C-186	Containers, Packaging and Packing for Drugs, Chemicals, and Pharmaceuticals. (See 6.4).

STANDARDS

Federal

Int. Fed. Std. No. 00285	Capsules (for Medicinal Purposes).

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 6505

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:02Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

U.S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE,
FOOD AND DRUG ADMINISTRATION

Federal Food, Drug, and Cosmetic Act and
Regulations Promulgated Thereunder.

(Application for copies should be addressed to the Food and Drug Administration, Washington, D. C. 20204.)

U.S. PHARMACOPEIAL CONVENTION, INC.

Pharmacopeia of the United States.

(Application for copies should be addressed to the Mack Publishing Company, Easton, Pa. 18042.)

3. REQUIREMENTS

3.1 Material. Shall be Flurazepam Hydrochloride Capsules and shall be in accordance with all applicable requirements of Interim Federal Standard No. 00285, and as specified herein:

S2. Classification. Shall be type I or type II.

S5.4 The following additional requirements are added to this paragraph:

Shall contain 30 mg of Flurazepam Hydrochloride per capsule within the designated assay limits.

3.1.1 Assay. Capsules shall assay to contain not less than 90.0 percent and not more than 110.0 percent of the required amount of Flurazepam Hydrochloride, when determined as described in 4.3.1.1.

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:02Z
Check the source to verify that this is the current version before use.

3.1.2 Identification. Capsules shall comply with the requirements of 4.3.1.2.

3.2 Active ingredient. The Flurazepam Hydrochloride used in the manufacture of the finished capsules shall comply with the following requirements:

3.2.1 Description. Shall be an off-white to yellow, crystalline powder.

3.2.2 pH. A 5 percent solution in purified water shall have a pH between 1.3 and 2.0 at 25° C when determined potentiometrically using the USP method.

3.2.3 Identity. Shall comply with the identity tests specified in 4.3.2.

3.2.4 Infrared absorption. The infrared absorption spectrum of a potassium bromide dispersion of the sample at a concentration of about 1 mg sample per 300 mg KBr shall compare qualitatively with that of a similar preparation of Flurazepam Hydrochloride reference powder similarly measured.

3.2.5 Ultraviolet absorption. Shall comply with the requirements of 4.3.2.2.

3.2.6 Melting range. Shall melt between 208°C and 218°C when determined using the USP Class I a method.

3.2.7 Loss on Drying. Shall not exceed 1.5 percent when a 1 gram sample is dried at 105°C. for four hours.

3.2.8 Residue on Ignition. Shall be not more than 0.1 percent when determined using the USP method.

3.2.9 Heavy Metals. Shall contain not more than 20 p.p.m. heavy metals when determined using USP Method II.

3.2.10 Related compounds. Shall contain not more than 0.1 percent of each of the following impurities when determined as specified in 4.3.2.3:

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:02Z
Check the source to verify that this is the current version before use.

2-Chloro-10-(2-diethylaminoethyl)-9-acridanone hydrochloride

5-Chloro-2-(2-diethylaminoethylamino)-2' -fluorobenzophenone hydrochloride

7-Chloro-5-(2-fluorophenyl)-1,3-dihydro-2H-1, 4-benzodiazepin-2-one

3-Amino-6-chloro-1-(2-diethylaminoethyl)-4-(2-fluorophenyl) carbostyril

In addition, shall contain not more than 0.1 percent of any one unknown impurity. The sum total of all impurities shall not exceed 0.5 percent.

3.2.11 Organically Bound Fluorine. Shall contain not less than 3.91 and not more than 4.33 percent organically bound fluorine when determined as specified in 4.3.2.4.

3.2.12 Free Fluoride. Shall contain not more than 0.05 percent free fluoride when determined as specified in 4.3.2.5.

3.2.13 Assay. Sahll assay not less than 99.0 and not more than 101.0 percent (dry basis) when determined as specified in 4.3.2.6.

3.3 Other ingredients. All other ingredients shall comply with S5.2 of Int. Fed. Std. No. 00285.

3.4 Potency Period. The potency period (expiration dating period) shall be 48 months.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-21T10:02Z
Check the source to verify that this is the currentversion before use.

4.1.1 Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of 4 years after delivery of the supplies to which such records relate.

4.1.2 No company supplying any ingredient(s) to the contractor will be considered an acceptable facility for the performance of any inspection requirements specified herein.

4.2 Sampling. Sampling shall be conducted in accordance with Int. Fed. Std. No. 00285.

4.2.1 If (i) the quality assurance representative submits samples to the laboratory at the Defense Personnel Support Center, or (ii) the bidder (or offeror) is required by the terms of the Schedule or otherwise to submit samples to said laboratory, a quantity of 500 mg. of Flurazepam Hydrochloride Reference powder* accompanied by a certificate of analysis listing all test results, shall be submitted with the finished product to the Technical and Quality Assurance Division, Directorate of Medical Materiel, Defense Personnel Support Center, Attention: Quality Assurance Branch, 2800 South 20th Street, Philadelphia, Pa. 19101.

*As a minimum, the reference sample shall meet the requirements of 3.2.

4.3 Tests.

4.3.1 Filled capsules.

4.3.1.1 Assay.

Reagents

Acidified Methanol: Carefully mix 28 ml of concentrated sulfuric acid with sufficient anhydrous methanol to make 1 liter of solution (approximately 1.0N with respect to sulfuric acid).

Reference Solution

Quantitatively and stepwise prepare a reference solution containing approximately 10 mcg of Flurazepam Hydrochloride reference powder per ml in acidified methanol.

Source: https://assist.dla.mil -- Downloaded: 20260-21T10:02Z
Check the source to verify that this is the current version before use.

Procedure.

Weigh the contents of not less than 20 capsules and determine the average weight per capsule. Mix the combined contents and transfer an accurately weighed portion of the powder, equivalent to about 100 mg of Flurazepam Hydrochloride, into a 100-ml volumetric flask. Add about 50 ml of acidified methanol and shake the flask mechanically for about 5 minutes. Dilute to volume with acidified methanol and filter through filter paper. Dilute 10.0 ml of the second solution to 100 ml using the same solvent. Concomittantly determine the absorbances of the sample and reference solutions relative to an acidified methanol blank in 1 cm cells, at approximately 239 mu using a suitable spectrophotometer. Calculate the percent of the required amount.

4.3.1.2 Identification.

Add 5 ml of a citric acid: acetic acid: acetic anhydride solution (1 g:10 ml: 90 ml) to about 50 mg of the capsule fill in test tube. Mix well and heat in a boiling water bath for 3 minutes: a cherry red color develops.

4.3.2 Active ingredient.

4.3.2.1 Identity.

Add 3 ml of a citric acid: acetic anhydride solution (1 g:10 ml:90 ml) to about 10 mg of sample in a small test tube. Heat in a boiling water bath for 3 minutes: a cherry-red color develops.

Add 1 ml of diluted nitric acid to about 2 of a 5 percent aqueous solution. Add 5 drops of silver nitrate T.S.: a white precipitate forms.

4.3.2.2 Ultraviolet absorption.

The ultraviolet absorption of a sample solution containing approximately 10 mcg Flurazepam Hydrochloride per ml in Acidified Methanol (see 4.3.1.1) shall exhibit a maximum at 239 ± 2 mu and the absorptivity shall be not less than 57.5 and not more than 61.5. The ultraviolet absorption of a sample solution containing approximately 20 mcg Flurazepam Hydrochloride per ml in Acidified Methanol shall exhibit a maximum at 284 ± 2 mu and the absorptivity shall be not less than 25.0 and not more 28.0.

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:02Z
Check the source to verify that this is the current version before use.

4.3.2.3 Related Compounds.

System I

Standards. Prepare reference standard solutions of the following substances at concentrations of 0.1 mg per ml (standard solution I) and 0.05 mg per ml (standard solution II) in methanol.

5-Chloro-2-(2-diethylaminoethylamino)-2'-fluorobenzophenone hydrochloride

7-Chloro-5-(2-fluorophenyl)-1,3-dihydro 2H-1,4-benzodiazepin-2-one

3-Amino-6-chloro-1-(2-diethylaminoethyl)-4-(2-fluorophenyl)carbostyril

Solvent System

Ethyl ether: diethylamine (150:4)

Absorbant

Silica Gel GF

Sample

Dissolve 1 gram of sample in 10 ml of methanol (Sample Solution I). Dilute 10 ml of Sample Solution I to 100 ml with methanol (Sample Solution II). Dilute 1.0 ml of Sample Solution II to 10 ml with methanol (Sample Solution III). Dilute 5 ml of Sample Solution III to 10 ml with methanol (Sample Solution IV). Sample solutions III and IV are used to estimate the unknown impurities.

Procedure.

Saturate a paper-lined tank (ca 9 x 27 x 30 cm) by wetting the entire paper surface with the developing solvent. Discard the solvent. Add fresh solvent. Apply 10 ul of Sample Solution I, 10 ul of Sample Solution III, 10 ul of each standard solution to a prepared thin layer plate. Insert the plate into the developing tank. Develop the chromatogram until the solvent front has moved about 16 cm. Remove the plate and air dry for not more than 5 minutes. Discard the solvent, add fresh solvent, insert the plate for a second development, for about 16 cm. Air dry the plate and view under shortwave ultraviolet light. Estimate the percent impurities.

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:02Z
Check the source to verify that this is the current version before use.

System II

Standard

Dissolve 10 mg of 2-Chloro-10-(2-diethylaminoethyl)-9-acridanone hydrochloride reference in 200 mg of methanol.

Solvent system:

Methylene chloride:ethyl ether"methanol"concentrated ammonia (60:90: 2:0.75) (Prepare fresh).

Absorbant

Silica Gel GF

Procedure

Apply 10 ul of the sample and 10 ul of the standard solutions to a prepared thin layer plate. Insert the plate into a paper lined developing tank which has been allowed to equilibrate by wetting the paper with developing solvent and allowing it to stand for about 30 minutes before use. Develop the chromatogram until the solvent front has moved about 16 cm. Remove the plate and view under shortwave ultraviolet light. Estimate the percent impurities.

4.3.2.4 Organically Bound Fluorine.

Reagents

Ethylene Glycol Dimethyl Ether (1, 2-dimethoxyethane): High purity, fluoride free, b.p. 83° - 85°C.

Sodium Hydroxide: Certified, A.C.S. grade

2-Propanol: A.C.S. reagent grade

Sodium-biphenyl: 15 ml vials (Southwestern Analytical Chemicals), or equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:02Z
Check the source to verify that this is the current version before use.

Sodium Fluride: Primary standard or analytical reagent grade.

Glacial Acetic Acid: A.C.S. reagent grade

59% 2-Propanol: Prepare an aqueous solution (v/v)

Sodium Chloride: Analytical reagent grade

Sodium Citrate: Analytical reagent grade

Hydrogen Peroxide (30%): Reagent grade

Acetate Buffer Solution (ABS): Transfer 110 g of sodium chloride, and 1 g of sodium citrate to a 2-liter volumetric flask. Add 600 - 800 ml of purified water and dissolve by shaking. Carefully add 150 g of sodium hydroxide, to the flask and dissolve by shaking. Cool to room temperature and cautiously add 450 ml of glacial acetic acid, while stirring. Cool to room temperature and add 600 ml of 2-propanol. Dilute to volume with water. The pH of this solution should be 5.0 to 5.5.

Apparatus

Fluoride Specific Ion Electrode: Orion Model #94-09, or equivalent.

pH meter: Orion Digital Model #801, or Corning Model 12, or equivalent.

Reference Electrode (modified): Sargent Calomel Model #S-30084-15 (glass sleeve), or equivalent. To prepare, mix 70 ml of saturated potassium chloride solution (freshly prepared to pre-cooled to at least 90 C) with 30 ml of 2-propanol. Fill the electrode with the clear supernatant solution and allow the electrode to remain in the 2-propanol-saturated potassium chloride solution (30:70) for a minimum of two hours before using (preferably overnight). Refill the electrode with freshly prepared solution each time before using.

All glassware and/or plastic lab-ware should be clean and free from trace amounts of fluoride. The use of plastic lab-ware is strongly recommended, although it is not an absolute necessity, for solution containment during potential measurements.

Standard Preparation

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:02Z
Check the source to verify that this is the current version before use.

Stock Solution

Weigh accurately exactly 2.211 g of sodium fluoride, which has been previously dried for 24 hours at 100 - 110 C, into a 1-liter volumetric flask. Dissolve in about 200 ml of purified water. Add 1.0 ml of 0.1M soidum hydroxide and dilute to volume with water (F = 1 mg/ml). Store this solution in a closed plastic container.

Working Standard Solutions

Pipet 10 ml of Stock Solution into a 100-ml volumetric flask and dilute to volume with ABS (Solution I). Dilute 20.0 ml of Solution I to 250 ml with ABS (Solution II). Pipet exactly 10, 15, 20 and 25 ml of Solution II into separate 100-ml volumetric flasks. Pipet, also, into each flask 15 ml of the reagent blank and dilute to volume with ABS. These Working Standard Solutions should be freshly prepared for each analysis (conc.: F = 0.08, 0.12, 0.16, and 0.20 mg/100 ml, respectively).

Reagent Blank

Pipet 25 ml of ethylene glycol dimethyl ether into a 500-ml round-bottom flask and treat in the same manner as the sample. After refluxing is completed, allow the solution to cool to room temperature, and then quantitatively transfer it to a 250-ml volumetric flask with 59% 2-propanol. Dilute to volume with the same solvent.

Sample Preparation (Perform in duplicate.)

Weight accurately about 485 mg of sample into a 250-ml volumetric flask. Add about 200 ml of ethylene glycol dimethyl ether and a few glass beads to the flask. Cover the flask with a small beaker and heat on a hot plate, maintaining a flask volume of 200 ml by replacing the ethylene glycol dimethyl ether lost by heating. Heat until the sample is completely dissolved. Cool the flask to room temperature and dilute to volume with the same solvent (Sample Solution).

Pipet 25 ml of Sample Solution into a 500-ml round-bottom reflux flask. Add, from a vial, 15 ml of sodium-biphenyl reagent through a longstem funnel to prevent splattering. Swirl the flask gently and cover with a small beaker. Allow the flask to stand to room temperature for about 5 to 10 minutes. Cautiously pipet 50.0 ml of 2-propanol into the flask with swirling. Pipet 10 ml of 30% hydrogen peroxide and 4 ml of IM sodium hydroxide into the flask. Connect the flask to a water cooled condenser (previously cleaned with water and 2-propanol and dried). Reflux the sample until the hydrogen peroxide is completely destroyed (about 1 hour) using a preheated hot plate set for

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:02Z
Check the source to verify that this is the current version before use.

medium heat (about 250°C). (The hydrogen peroxide is destroyed when bubbles cease to form and slight bumping occurs.) Allow the sample to cool to room temperature and rinse the condenser with 10-15 ml of 59% 2-propanol. Quantitatively transfer the sample to a 250-ml volumetric flask and dilute to volume with 59% 2-propanol. Dilute 15.0 ml of this sample solution to 100 ml with ABS (Working Sample Solution). NOTE: This last dilution is for the sample solution only.

Procedure.

Transfer the Working Standard Solutions and the Working Sample Solutions to separate 150-ml beakers containing teflon coated stirring bars. Measure the potential, in millivolts, by immersing the fluoride specific and modified reference electrodes into each solution, stirring until equilibrium is attained (about 1 to 2 minutes). After each measurement, rinse the electrodes with water and wipe the electrodes dry, being careful not to scratch the crystal in the specific ion electrode. Measure the standards first, progressing from lower to higher concentrations.

Plot the fluoride concentration (mg/100 ml) against the potential (millivolts) for each standard solution on semilogarithmic paper (1 cycle x 70 divisions). Read the fluoride concentration (C) in the measured sample solution directly from the graph.

4.3.2.5 Free Fluoride.

Apparatus. Same as for 4.3.2.4 except for reference -lectrode. Unmodified Sargent Calomel Model #S-30084-15 (gloss sleeve), or the equivalent may be used.

Standard Preparation

Use the Fluoride Stock Solution and Acetate Buffer Solution (ABS) as prepared for the Fluorine determination in 4.3.2.4.

Method I

Standard Solution

Dilute exactly 10.0 ml of Stock Solution to 100 ml with ABS (Solution I). Dilute exactly 10.0 ml of Solution I to 250 ml with ABS (Solution II). Dilute exactly 5.0 ml of Solution II to 200 ml with ABS (Working Standard, F = 0.02 mg/200 ml).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:02Z
Check the source to verify that this is the current version before use.

Procedure

Weigh accurately about 200 mg of sample into a 200-ml volumetric flask. Dissolve the sample in 150 - 180 ml of ABS with shaking. Dilute to volume with ABS and mix well.

Transfer the Working Standard to a 250-ml beaker containing a stirring bar. Immerse the fluoride specific and reference electrodes into the solution and measure and record the potential (millivolts) while the solution is stirring. Rinse the electrodes with water and wipe dry, being very careful not to scratch the crystal of the fluoride specific electrode. Transfer the sample solution to a 250-ml beaker and treat as the standard. If the sample solution potential is more positive than that of the standard solution, the sample contains less than 0.01% free fluoride (negligible). If the potential is less positive, perform Method II to determine total free fluoride in the sample.

Method II

Standard Solution

Dilute exactly 5.0 ml of Stock Solution to 250 ml with ABS (Solution I). Pipet 5, 15, 25, and 50 ml of Solution I into separate 100-ml volumetric flasks and dilute to volume with ABS (Working Standards, F = 0.1, 0.3, 0.5, and 1.0 mg/100 ml, respectively.)

Procedure

Weigh accurately about 1 g of sample into a 100-ml volumetric flask. Add about 70 - 80 ml of ABS and dissolve the sample by shaking. Dilute to volume with ABS. Measure the potentials of the Working Standard Solutions and the sample solution as previously described.

Calculation

Plot fluoride concentration (mg/100 ml) against potential (millivolts) for each Working Standard (Method II) on semi-logarithmic paper (1 cycle x 70 divisions). Read the fluoride concentration of the sample solution (C) from the graph.

4.3.2.6

Assay (Dry Basis)

Weigh accurately about 0.6 g of sample into a 250-ml beaker. Dissolve the sample in 80 ml of glacial acetic acid and add 20 ml of mercuric acetate T.S. Titrate potentiometrically with 0.1N perchloric acid in glacial acetic acid using a glass-calomel electrode system. Each milliliter of 0.1N perchloric acid is equivalent to 23.04 mg of flurazepam hydrochloride.

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:02Z
Check the source to verify that this is the current version before use.

4.4 Examination of preparation for delivery. An examination shall be made to determine whether the packaging, packing, and marking comply with the requirements of section 5. Defects shall be scored as specified in table I. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 and the acceptable quality level shall be 4.0 defects per hundred units.

Table I. Examination of preparation for delivery

Examination	Defect
Containers	Not as specified.
Quantity	Quantity in interior packages and shipping containers not as specified.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, tape improperly applied, or containers distored.
Markings	Omitted, incorrect, illegible, improper size, location, sequence, or method of application.

NOTE: The above examination is only applicable to the unit, intermediate and exterior containers.

5. PREPARATION FOR DELIVERY

5.1 Shall be in accordance with all applicable requirements of Interim Federal Specification PPP-C-186 and as specified herein:

5.1.1 Immediate containers. Shall comply with the following: Shall be a commercially available immediate container considered acceptable by the Food and Drug Administration (FDA) for the product contained therein and shall be of such compatibility that neither the contents nor the container are altered in any way by each other.

5.2 Labeling. Labeling shall be in accordance with the requirements of the Federal Food, Drug and Cosmetic Act, and shall include the information required below:

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:02Z
Check the source to verify that this is the current version before use.

5.2.1 Immediate container. Each immediate container label shall bear the following information:

(a) label information in accordance with commercial practice.

(b) the expiration date.

5.2.2 Unit packages. Each unit package label shall bear the following:

(a) labeling information in accordance with commercial practice.

(b) the National Stock Number.

NOTE: The National Stock Number shall not be preceded by any prefix.

Strip labeling may be used.

Label adhesion test shall not apply.

If a unit package is not supplied, the National Stock Number shall appear on the immediate container label.

5.3 Packaging and packing.

5.3.1 Unit of issue. One bottle containing 500 capsules, as specified, constitutes one unit of issue.

5.3.2 Unit package. At the option of the contractor, each unit may be packaged as specified in 5.2.5 of PPP-C-186.

5.3.3 Procedure code. Procedure code No. 6 applies to PPP-C-186. Liner and pack are not required in the intermediate package.

5.4 Marking.

5.4.1 Intermediate package. Each intermediate package shall be marked in accordance with 5.5.3 of PPP-C-186. Type I Shelf life marking shall fied in MIL-STD-129 shall also be shown. Marking shall include the legend:

"STORE AT CONTROLLED ROOM TEMPERATURE (59° - 86° F.)"

5.4.2 Exterior container. Exterior container shall be marked in accordance with 5.5.4 of PPP-C-186. Type I Shelf life marking as specified in MIL-STD-129 shall also be shown. Marking shall include the legend:

"STORE AT CONTROLLED ROOM TEMPERATURE (59° - 86° F.)"

Source: https://assist.dla.mil -- Downloaded: 202640-21T10:02Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) the National Stock No.
(c) Selection of applicable levels of packaging and packing (see 5.3).

6.2 This specification covers the following item:

National Stock Number	Item Identification
6505-00-400-7294	FLURAZEPAM HYDROCHLORIDE CAPSULES, 30 mg, 500s

6.3 This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types which are normally procured to meet Military requirements.

6.4 All reference to PPP-C-186 refers to Interim Federal Specification PPP-C-00186B which is mandatory for use until superceded by a revision.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6505-1321

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:02Z
Check the source to verify that this is the current version before use.