METRIC

MIL-T-24649/11(SH)
10 June 1994

# MILITARY SPECIFICATION SHEET

## TELEPHONE, HARDWARE, SOUND POWERED IC/TRC REEL, CASUALITY COMMUNICATION

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-T-24649

**REQUIREMENTS:**

| | |
|---|---|
| Dripproof (see 3.3.6) | not required |
| Splashproof (see 3.3.7) | not required |
| Watertight (see 3.3.8) | not required |
| Insulation resistance (see 3.3.9) | not required |
| Talk demonstration (see 3.3.10) | not required |
| Identification plate (see 3.4.3) | not required |
| Information plate (see 3.4.4) | not required |
| Station plate (see 3.4.5) | not required |
| Switches (see 3.4.6) | not required |
| Terminal boards (see 3.4.7) | not required |
| Wire (see 3.4.8) | not required |
| Wire terminals (see 3.4.9) | not required |


Construction

1. All dimensions unless otherwise specified are in mm. Tolerances, unless otherwise specified shall be plus or minus 0.127 mm.
2. All sharp edges or corners exposed to touch shall be slightly rounded.
3. Screw threads for all threaded securing devices shall conform to FED-STD-H28. The thread shall be right handed, of the course thread series.
4 Threads in aluminum alloys shall not be used. Through bolts shall be used whenever practical. Inserts shall be provided where screws or bolts must be removed for maintenance.
5. Threads shall not be employed in plastic parts without the use of suitable threaded metallic inserts.
6. No deviation in details, dimensions, size and type as shown on the applicable standard will be permitted, unless approved by the Naval Sea Systems Command (NAVSEA)
7 All loose parts required for installation or operation shall be provided in a suitable cloth or plastic bag and packaged with the assembly


Preparing activity:
Navy - SH
(Project 5935-N457-11)


DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:39Z
Check the source to verify that this is the current version before use.




FRONT VIEW





WIRING DIAGRAM


FIGURE 1 IC/Reel, casualty communication



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:39Z
Check the source to verify that this is the current version before use.




DETAIL "A"




DETAIL "B"

FIGURE 2 Details



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:39Z
Check the source to verify that this is the current version before use.