
INCH-POUND
MIL-C-55302/25D
31 October 1988
SUPERSEDING
MIL-C-55302/25C
24 March 1980

MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, 120, 150, 160, AND 180 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.075 SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-55302.



STYLE I (INTERNAL KEYING)

FIGURE 1. Connectors, receptacle, (.075 spacing).

(D) denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Dash 1/ number	Number of contacts	Type	A	B	C	D	E	Contact identification numbers
01 02 03 04	120	I II III IV	5.380 (136.65)	5.090 (129.29)	59	4.425 (112.40)	4.690 (119.13)	1 - 60 61 - 120
05 06 07 08	150	I II III IV	6.505 (165.23)	6.215 (157.86)	74	5.550 (140.97)	5.815 (147.70)	1 - 75 76 - 150
09 10 11 12	160	I II III IV	6.880 (174.75)	6.590 (167.39)	79	5.925 (150.50)	6.190 (157.23)	1 - 80 81 - 160
13 14 15 16	180	I II III IV	7.630 (193.80)	7.340 (186.44)	89	6.675 (169.55)	6.940 (176.28)	1 - 90 91 - 180

1/ Dash numbers 01 through 16 are for style 1 (internal keying) connectors.

FIGURE 1. Connectors, receptacle,(.075 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connectors, receptacle, (.075 spacing) - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.


Dash 1/ number	Number of contacts	Type	A	B	C	D	E	Contact identification numbers
17 18 19 20	120	I II III IV	5.380 (136.65)	5.090 (129.29)	59	4.425 (112.40)	4.690 (119.13)	1 - 60 61 - 120
21 22 23 24	150	I II III IV	6.505 (165.23)	6.215 (157.86)	74	5.550 (140.97)	5.815 (147.70)	1 - 75 76 - 150
25 26 27 28	160	I II III IV	6.880 (174.75)	6.590 (167.39)	79	5.925 (150.50)	6.190 (157.23)	1 - 80 81 - 160
29 30 31 32	180	I II III IV	7.630 (193.80)	7.340 (186.44)	89	6.675 (169.55)	6.940 (176.28)	1 - 90 91 - 180


1/ Dash numbers 17 through 32 are for style 2 (external keying) connectors.

FIGURE 1. Connectors, receptacle,(.075 spacing) - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.










RECOMMENDED PRINTED CIRCUIT BOARD LAYOUT.
(CONNECTOR SIDE)







RECOMMENDED PRINTED CIRCUIT BOARD
LAYOUT. (CONNECTOR SIDE)



RECOMMENDED PRINTED CIRCUIT BOARD
LAYOUT.

FIGURE 1. Connectors, receptacle, (.075 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.003	.08	.087	2.21
.004	.10	.096	2.44
.005	.13	.101	2.57
.006	.15	.108	2.74
.010	.25	.109	2.77
.012	.30	.113	2.87
.014	.36	.125	3.18
.015	.38	.130	3.30
.018	.46	.135	3.43
.019	.48	.136	3.45
.020	.51	.140	3.56
.022	.56	.171	4.34
.025	.64	.175	4.44
.027	.69	.176	4.47
.028	.71	.180	4.57
.030	.76	.185	4.70
.031	.79	.200	5.08
.032	.81	.235	5.97
.040	1.02	.242	6.15
.045	1.14	.248	6.30
.050	1.27	.250	6.35
.0625	1.588	.255	6.48
.063	1.60	.260	6.60
.065	1.65	.298	7.57
.067	1.70	.300	7.62
.073	1.85	.305	7.75
.075	1.90	.315	8.00
.080	2.03	.330	8.38
.081	2.06	.332	8.43
.083	2.11	.340	8.64
.085	2.16	.400	10.16

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 (.13 mm) on decimals and ±2° on angles.
4. These connectors mate with connectors specified in MIL-C-55302/23.
5. Use printed circuit boards with the type III receptacle.
6. Minimum pad length on printed circuit board.
7. Termination layout on .025 (.64 mm) modular grid.
8. Numbers indicating, every 5 cavities stamped on side. Numbers indicating end cavities and lines indicating every 5 cavities stamped on mating face.
9. Location indicators embossed on surface.

FIGURE 1. Connectors, receptacle,(.075 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Ⓓ Material:
Plating: Engagement area: Gold per MIL-C-55302 for .100 length, over nickel all over per MIL-C-55302.

Termination area: Tin lead over nickel per MIL-C-55302 for the following lengths:

.165 minimum length for type I.
.200 minimum length for type II.
.300 minimum length for type III.
.140 minimum length for type IV.

Contact identification: See figure 1.

Contact rating: 3.0 amperes maximum per contact, 2.25 amperes continuous per contact at 75°F.

Keying: See MIL-C-55302/31.

Oversized pin exclusion (sockets only): .0465 diameter pin.

Contact separation force: The connector shall meet the requirements of MIL-C-55302/29.

Wire size: Number 26 AWG maximum with type II, solder eyelet contact for wire termination.

Resistance to test probe damage: The connector shall meet the requirements of MIL-C-55302/30.

Mating and unmating: The maximum mating force in pounds shall be the number of contacts multiplied by .25 and the withdrawal force in pounds shall be a minimum of .025 times the number of contacts and shall not exceed the measured insertion force.

Contact resistance: The average contact resistance of all contacts measured shall not exceed .015 ohm, and no individual contact pair shall have a resistance exceeding .020 ohm.

Contact retention: 3 pounds minimum.

Dielectric withstanding voltage:
Sea level: 900 volts rms.
High altitude: 200 volts rms.

Replacement contacts: See MIL-C-55302/32.

Ⓓ Contact removal tool: See MIL-I-81969/01.

Part number: M55302/25- (dash number from figure 1).

Patent number 3,404,367. The Government has a royalty free license under this patent for the benefit of manufacturers of the item either for the Government or for use in equipment to be delivered to the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 17

Review activities:
Army - CR, AR, MI
Navy - SH, AS, OS
Air Force - 11, 99
DLA - ES

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3645-03)

☆U.S. GOVERNMENT PRINTING OFFICE: 1989 - 604-033/10958

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.